

Application for FCC Certificate
On Behalf of
Shanghai Viva Home Improvement Co., Ltd.

Ballast

Model No.	VEB82122	VEB82130	VEB82132	VEB82140
Serial No.	E2008121819	E2008121815	E2008121820	E2008121821

FCC ID : OGB821

Prepared For : Shanghai Viva Home Improvement Co., Ltd.
No. 888, Zhangcao Rd. Caojing, Jinshan,
Shanghai 201507, China

Prepared By : Audix Technology (Shanghai) Co., Ltd.
3F 34Bldg 680 Guiping Rd,
Caohejing Hi-Tech Park,
Shanghai 200233, China

Tel: +86-21-64955500
Fax: +86-21-64955491

Report No. : ACI-F08076
Date of Test : Dec 19, 2008
Date of Report : Dec 22, 2008

TABLE OF CONTENTS

	Page
1 SUMMARY OF STANDARDS AND RESULTS	4
1.1 Description of Standards and Results	4
2 GENERAL INFORMATION	5
2.1 Description of Equipment Under Test	5
2.2 Lamp	6
2.3 Description of Test Facility	6
2.4 Measurement Uncertainty	6
3 CONDUCTED EMISSION TEST	7
3.1 Test Equipment	7
3.2 Block Diagram of Test Setup	7
3.3 Conducted Emission Limits (FCC Part 18 Consumer Equipment)	7
3.4 Test Configuration	7
3.5 Operating Condition of EUT	8
3.6 Test Procedures	8
3.7 Test Results	8
4 MAGNETIC FIELD EMISSION TEST	13
4.1 Test Equipment	13
4.2 Block Diagram of Test Setup	13
4.3 Magnetic Field Emission Limit (FCC Part 18 305(b))	14
4.4 Test Configuration	14
4.5 Operating Condition of EUT	14
4.6 Test Procedures	14
4.7 Test Results	15
5 RADIATED EMISSION TEST	20
5.1 Test Equipment	20
5.2 Block Diagram of Test Setup	20
5.3 Radiated Emission Limit (FCC Part 18.305(c) Consumer Equipment)	21
5.4 Test Configuration	21
5.5 Operating Condition of EUT	21
5.6 Test Procedures	21
5.7 Test Results	22
6 DEVIATION TO TEST SPECIFICATIONS	27

TEST REPORT FOR FCC CERTIFICATE

Applicant : Shanghai Viva Home Improvement Co., Ltd.

Manufacturer : Shanghai Viva Home Improvement Co., Ltd.

EUT Description : Ballast

(A) Model No.	VEB82122	VEB82130	VEB82132	VEB82140
(B) Serial No.	E2008121819	E2008121815	E2008121820	E2008121821
(C) Power Supply	120V/60Hz			

Test Procedure Used:

*FCC RULES AND REGULATIONS PART 18 SUBPART C CLASS B OCTOBER 2008
AND MP-5/1986*

The device described above is tested by Audix Technology (Shanghai) Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 18 Subpart C (Class B) limits both radiated and conducted emissions.

The test results are contained in this test report and Audix Technology (Shanghai) Co., Ltd. is assumed full responsibility for the accuracy and completeness of these measurements. This report shows that the EUT (M/N: VEB82122, VEB82130, VEB82130, VEB82140; S/N: E2008121819, E2008121815, E2008121820, E2008121821) which was tested in 3m anechoic chamber on Dec 19, 2008 is technically compliance with the FCC official limits also.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of Audix Technology (Shanghai) Co., Ltd.

This report contains data that are not covered by the NVLAP accreditation.

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

Date of Test : Dec 19, 2008 Date of Report : Dec 22, 2008

Producer : Zeno Gu
ZENOGU / Assistant

Review : Sammy Chen
SAMMYCHEN / Assistant Manager

AUDIX[®] For and on behalf of
Audix Technology (Shanghai) Co., Ltd.

Signatory : Byron Kwo
Authorized Signature EMC BYRON KWO / Manager

1 SUMMARY OF STANDARDS AND RESULTS

1.1 Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Description / Test Item	Test Standard	Meets Limit	Results
EMISSION			
Conducted Disturbance at the Mains Terminals	FCC RULES AND REGULATIONS PART 18 SUBPART C OCTOBER 2008 AND MP-5/1986	18.307(c) Consumer Equipment	Pass
Magnetic Field Strength	FCC RULES AND REGULATIONS PART 18 SUBPART C OCTOBER 2008 AND MP-5/1986	18.305(b) Any type, Non-ISM Frequency	Pass
Radiated Emission	FCC RULES AND REGULATIONS PART 18 SUBPART C OCTOBER 2008 AND MP-5/1986	18.305(c) Consumer Equipment	Pass

2 GENERAL INFORMATION

2.1 Description of Equipment Under Test

Description : Ballast

Type of EUT : ☒ Production ☐ Pre-product ☐ Pro-type

Model No.	VEB82122	VEB82130	VEB82132	VEB82140
Serial No.	E2008121819	E2008121815	E2008121820	E2008121821
Lamp	22W Lamp	30W Lamp	32W Lamp	40W Lamp

N

Note 1 : VEB82122, VEB82130, VEB82132 and VEB82140 have same principle diagram and circuit board.

Note 2 : VEB82132 and VEB82140 are the same except for different lamp tube.

Applicant : Shanghai Viva Home Improvement Co., Ltd.
No. 888, Zhangcao Rd. Caojing, Jinshan,
Shanghai 201507, China

Manufacturer : Shanghai Viva Home Improvement Co., Ltd.
No. 888, Zhangcao Rd. Caojing, Jinshan,
Shanghai 201507, China

Model No	Apparent Power (VA)	Real Power (W)	Power Factor
VEB82122	40.00	20.00	0.52
VEB82130	59.00	27.00	0.47
VEB82132	70.00	34.00	0.49
VEB82140	84.00	44.00	0.52

2.2 Lamp

2.2.1 22W Lamp

Manufacturer : VIVA
Model Number : FC8T9 22W

2.2.2 30W Lamp

Manufacturer : VIVA
Model Number : FC9T9 30W

2.2.3 32W Lamp

Manufacturer : VIVA
Model Number : FC12T9 32W

2.2.4 40W Lamp

Manufacturer : VIVA
Model Number : FC40T9 40W

2.3 Description of Test Facility

Site Description (Semi-Anechoic Chamber) : Sept. 17, 1998 file on
July 26, 2006 Renewed
Federal Communications Commission
FCC Engineering Laboratory
7435 Oakland Mills Road
Columbia, MD 21046, USA

Name of Firm : Audix Technology (Shanghai) Co., Ltd.

Site Location : 3F 34Bldg 680 Guiping Rd,
Caohejing Hi-Tech Park,
Shanghai 200233, China

NVLAP Lab Code : 200371-0

2.4 Measurement Uncertainty

Conducted Emission Expanded Uncertainty: U = 1.26 dB
Radiated Emission Expanded Uncertainty : U = 3.02 dB

3 CONDUCTED EMISSION TEST


3.1 Test Equipment

The following test equipments are used during the conducted emission test in a shielded room:

Item	Type	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1.	Test Receiver	R&S	ESHS10	830223/007	Apr 02, 2008	Apr 02, 2009
2.	Line Impedance Stabilization Network (LISN)	FCC	KNW-407	8-1280-4	Apr 02, 2008	Apr 02, 2009
3.	50 Ω Coaxial Switch	Anritsu	MP59B	6200426389	Sep 19, 2008	Mar 19, 2009
4.	50 Ω Terminator	Anritsu	BNC	001	Apr 02, 2008	Apr 02, 2009
5.	Software	Audix	E3	SET00200 9804M592	--	--

3.2 Block Diagram of Test Setup

3.2.1 Conducted Disturbance Test Setup



3.3 Conducted Emission Limits (FCC Part 18 Consumer Equipment)

Frequency (MHz)	Maximum RF Line Voltage	
	(μ V)	dB(μ V)
0.45 ~ 2.51	250	48
2.51 ~ 3.0	3000	70
3.0 ~ 30	250	48
NOTE 1 – RF Line Voltage dB (μ V) = 20 log RF Line Voltage (μ V) NOTE 2 – The tighter limits shall apply at the boundary between two frequency ranges.		

3.4 Test Configuration

The EUT (listed in Sec.2.1) was installed as shown on Sec.3.2 to meet FCC requirement and operating in a manner that tends to maximize its emission level in a normal application.

3.5 Operating Condition of EUT

- 3.5.1 Setup the EUT as shown in Sec. 3.2.
- 3.5.2 Turn on the power of EUT.
- 3.5.3 The EUT will be operated normally.
- 3.5.4 Set the EUT on the lighting test mode, and then test.

3.6 Test Procedures

The EUT and lamp were connected to the power mains through a Line Impedance Stabilization Network (LISN). This provided a 50 ohm coupling impedance for the measuring equipment.

Both sides of AC line were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed or manipulated according to MP-5/1986 during conducted emission test.

The I.F bandwidth of Test Receiver ESHS10 was set at 10 kHz.

The frequency range from 450 kHz to 30 MHz for Lighting mode was checked.

The test modes were done on conducted test and the test results of the highest emissions are listed in Sec. 3.7.

3.7 Test Results

< PASS >

The frequency and amplitude of the highest conducted emission relative to the limit is reported. All emissions not reported below are too low against the prescribed limits.

Model No	Test Mode	Data Page
VEB82122	Lighting	P9
VEB82130		P10
VEB82132		P11
VEB82140		P12

NOTE 1 – Factor = Cable Loss + LISN Factor.

NOTE 2 – Emission Level = Meter Reading + Factor.

NOTE 3 – All readings are Quasi-Peak values. (QP)

NOTE 4 – The worst case is for VEB82132 model. The worst emission is detected at 0.483 MHz with corrected signal level of 46.58 dB (μV) (limit is 48.00 dB (μV)), when the VB of the EUT is connected to LISN.

EUT : Ballast Temperature : 21°C

Model No. : VEB82122 Humidity : 52%RH

Serial No. : E2008121819 Date of Test : Dec 19, 2008

Test Mode : Lighting

Test Line	Frequency (MHz)	Meter Reading dB(μV)	Factor (dB)	Emission Level dB(μV)	Limits dB(μV)	Margin (dB)	Remark
VA	0.467	44.04	0.70	44.74	48.00	3.26	QP
	0.643	41.52	0.62	42.14	48.00	5.86	
	0.797	39.17	0.61	39.78	48.00	8.22	
	1.428	34.39	0.64	35.03	48.00	12.97	
	12.683	35.46	0.87	36.33	48.00	11.67	
	25.682	34.17	1.17	35.34	48.00	12.66	
VB	0.471	45.96	0.60	46.56	48.00	1.44	QP
	0.567	41.94	0.66	42.60	48.00	5.40	
	0.900	40.35	0.61	40.96	48.00	7.04	
	6.755	32.86	0.83	33.69	48.00	14.31	
	12.683	42.20	0.97	43.17	48.00	4.83	
	25.149	35.68	1.24	36.92	48.00	11.08	

TEST ENGINEER: YONG XU

EUT : Ballast Temperature : 21°C

Model No. : VEB82130 Humidity : 52%RH

Serial No. : E2008121815 Date of Test : Dec 19, 2008

Test Mode : Lighting

Test Line	Frequency (MHz)	Meter Reading dB(μV)	Factor (dB)	Emission Level dB(μV)	Limits dB(μV)	Margin (dB)	Remark
VA	0.450	40.70	0.70	41.40	48.00	6.60	QP
	0.584	43.14	0.66	43.80	48.00	4.20	
	0.729	41.89	0.61	42.50	48.00	5.50	
	6.532	34.35	0.82	35.17	48.00	12.83	
	18.431	24.41	0.97	25.38	48.00	22.62	
	28.287	26.85	1.27	28.12	48.00	19.88	
VB	0.450	44.75	0.71	45.46	48.00	2.54	QP
	0.638	41.95	0.63	42.58	48.00	5.42	
	0.736	40.59	0.61	41.20	48.00	6.80	
	1.369	32.22	0.63	32.85	48.00	15.15	
	6.898	31.95	0.84	32.79	48.00	15.21	
	29.749	25.74	1.31	27.05	48.00	20.95	

TEST ENGINEER: YONG XU

EUT : Ballast Temperature : 21°C

Model No. : VEB82132 Humidity : 52%RH

Serial No. : E2008121820 Date of Test : Dec 19, 2008

Test Mode : Lighting

Test Line	Frequency (MHz)	Meter Reading dB(μV)	Factor (dB)	Emission Level dB(μV)	Limits dB(μV)	Margin (dB)	Remark
VA	0.528	44.83	0.69	45.52	48.00	2.48	QP
	0.609	45.60	0.64	46.24	48.00	1.76	
	1.056	39.85	0.61	40.46	48.00	7.54	
	1.446	36.72	0.64	37.36	48.00	10.64	
	4.707	30.30	0.73	31.03	48.00	16.97	
	29.254	23.28	1.29	24.57	48.00	23.43	
VB	0.483	45.88	0.70	46.58	48.00	1.42	QP
	0.604	44.92	0.64	45.56	48.00	2.44	
	0.679	45.03	0.61	45.64	48.00	2.36	
	1.330	39.44	0.63	40.07	48.00	7.93	
	4.457	33.59	0.72	34.31	48.00	13.69	
	29.749	22.24	1.31	23.55	48.00	24.45	

TEST ENGINEER: YONG XU

EUT : Ballast Temperature : 21°C

Model No. : VEB82140 Humidity : 52%RH

Serial No. : E2008121821 Date of Test : Dec 19, 2008

Test Mode : Lighting

Test Line	Frequency (MHz)	Meter Reading dB(μV)	Factor (dB)	Emission Level dB(μV)	Limits dB(μV)	Margin (dB)	Remark
VA	0.604	43.17	0.64	43.81	48.00	4.19	QP
	0.942	37.98	0.61	38.59	48.00	9.41	
	1.330	36.05	0.63	36.68	48.00	11.32	
	2.058	32.90	0.63	33.53	48.00	14.47	
	17.673	18.48	0.95	19.43	48.00	28.57	
	29.500	19.91	1.30	21.21	48.00	26.79	
VB	0.519	44.09	0.69	44.78	48.00	3.22	QP
	0.679	40.43	0.61	41.04	48.00	6.96	
	0.907	38.22	0.61	38.83	48.00	9.17	
	2.093	33.37	0.63	34.00	48.00	14.00	
	17.017	18.51	0.97	19.48	48.00	28.52	
	30.000	20.16	1.32	21.48	48.00	26.52	

TEST ENGINEER: YONG XU


4 MAGNETIC FIELD EMISSION TEST

4.1 Test Equipment

The following test equipment are used during the field strength test in a shielded room:

Item	Type	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1.	Loop Antenna	Schaffner	HLA6120	1193	Apr 06, 2008	Apr 06, 2009
2.	Test Receiver	R&S	ESHS10	844077/020	Feb 20, 2008	Feb 20, 2009
3.	50Ω Coaxial Switch	ANRITSU	MP59B	6200426390	Sep 18, 2008	Mar 18, 2009
4.	Software	Audix	E3	SET00200 9912M295-2	--	--

4.2 Block Diagram of Test Setup



4.3 Magnetic Field Emission Limit (FCC Part 18 305(b))

All emanations from Non-ISM frequency devices or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified below:

Frequency (MHz)	Distance (m)	Field Strength Limits ($\mu\text{V/m}$)	Converted Field Strength Limits By 3 Meters Measuring Distance dB ($\mu\text{V/m}$)
0.009~30	300	15	63.5
NOTE 1 - Distance refers to the distance in meters between the test antenna and the closed point of any part of the EUT.			
NOTE 2 - Audix Technology (Shanghai) Co., Ltd. only has a 3 meters Semi-anechoic Chamber to do the radiated disturbance test, therefore, Audix Shanghai used 3 meters measuring distance and converted limits to judge the EUT compliance with or not.			

4.4 Test Configuration

The FCC part 18 regulations test method must be used to find the maximum emission during Radiated Emission test.

The configuration of the EUT is same as used in conducted emission test. Please Refer to Section 3.4.

4.5 Operating Condition of EUT

- 4.5.1 Setup the EUT as shown on Section 4.2.
- 4.5.2 Turn on the power of all equipments.
- 4.5.3 Let the EUT work in test mode and test it.

4.6 Test Procedures

The EUT and lamp were placed on a table, which is 1.0 meter above ground. Measurements are performed at distance 3.0m with a 0.6m loop antenna as described in 2.2.4 of MP-5. The antenna shall be with the lower edge of the loop at height 2m above the floor.

The bandwidth setting on the test receiver (R&S Test Receiver ESHS10) is 200Hz from 9kHz to 150kHz and 10kHz from 150kHz to 30MHz. The EUT is tested in a semi-anechoic chamber.

All the test results are attached within Sec. 4.7.

4.7 Test Results

<PASS>

Refer to the following pages.

Model No	Test Mode	Data Page
VEB82122	Lighting	P16
VEB82130		P17
VEB82132		P18
VEB82140		P19

NOTE 1 – Factor = Antenna Factor + Cable Loss

NOTE 2 – All reading are Quasi-Peak Values.

NOTE 3 – The worst case is for VEB82130 model. The worst emission is detected at 0.026 MHz with corrected signal level of 54.95 dB (μV) (limit is 63.50 dB (μV)).

EUT : Ballast Temperature : 22°C

Model No. : VEB82122 Humidity : 60%RH

Serial No. : E2008121819 Date of Test : Dec 19, 2008

Test Mode : Lighting

Frequency (MHz)	Meter Reading dB(μV)	Factor (dB)	Emission Level dB(μV)	Limits dB(μV)	Margin (dB)	Remark
0.018	30.33	20.41	50.74	63.50	12.76	QP
0.023	29.67	20.55	50.22	63.50	13.28	
0.031	31.10	20.69	51.79	63.50	11.71	
0.154	29.53	20.25	49.78	63.50	13.72	
0.955	33.51	20.41	53.92	63.50	9.58	
1.198	33.58	20.28	53.86	63.50	9.64	

TEST ENGINEER: TOM SI

EUT : Ballast Temperature : 22°C

Model No. : VEB82130 Humidity : 60%RH

Serial No. : E2008121815 Date of Test : Dec 19, 2008

Test Mode : Lighting

Frequency (MHz)	Meter Reading dB(μV)	Factor (dB)	Emission Level dB(μV)	Limits dB(μV)	Margin (dB)	Remark
0.016	30.03	20.48	50.51	63.50	12.99	QP
0.026	34.30	20.65	54.95	63.50	8.55	
0.047	28.41	20.53	48.94	63.50	14.56	
0.154	29.30	20.25	49.55	63.50	13.95	
0.939	33.59	20.40	53.99	63.50	9.51	
1.218	31.59	20.27	51.86	63.50	11.64	

TEST ENGINEER: TOM SI

EUT : Ballast Temperature : 22°C

Model No. : VEB82132 Humidity : 60%RH

Serial No. : E2008121820 Date of Test : Dec 19, 2008

Test Mode : Lighting

Frequency (MHz)	Meter Reading dB(μV)	Factor (dB)	Emission Level dB(μV)	Limits dB(μV)	Margin (dB)	Remark
0.020	31.14	20.26	51.40	63.50	12.10	QP
0.049	24.32	20.39	44.71	63.50	18.79	
0.113	-20.03	20.03	0.00	63.50	63.50	
0.235	26.50	20.34	46.84	63.50	16.66	
1.050	23.36	20.45	43.81	63.50	19.69	
3.450	25.42	20.60	46.02	63.50	17.48	

TEST ENGINEER: TOM SI

EUT : Ballast Temperature : 22°C

Model No. : VEB82140 Humidity : 60%RH

Serial No. : E2008121821 Date of Test : Dec 19, 2008

Test Mode : Lighting

Frequency (MHz)	Meter Reading dB(μV)	Factor (dB)	Emission Level dB(μV)	Limits dB(μV)	Margin (dB)	Remark
0.014	26.96	20.47	47.43	63.50	16.07	QP
0.052	30.40	20.37	50.77	63.50	12.73	
0.355	20.98	20.24	41.22	63.50	22.28	
0.840	24.63	20.36	44.99	63.50	18.51	
2.350	18.12	20.47	38.59	63.50	24.91	
5.860	27.47	20.72	48.19	63.50	15.31	

TEST ENGINEER: TOM SI

5 RADIATED EMISSION TEST


5.1 Test Equipment

The following test equipments are used during the radiated emission test in a semi-anechoic chamber:

Item	Type	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1.	Test Receiver	R&S	ESVS10	844594/001	Mar 07, 2008	Mar 07, 2009
2.	Preamplifier	Agilent	8447D	2944A10548	Mar 19, 2008	Sep 19, 2008
3.	Preamplifier	HP	8449B	3008A00864	May 19, 2008	May 19, 2009
4.	Bi-log Antenna	TESEQ	CBL6112D	23193	May 14, 2008	May 14, 2009
5.	Spectrum	Agilent	E7405A	MY45106600	May 19, 2008	May 19, 2009
6.	Software	Audix	E3	SET00200 9912M295-2	--	--

5.2 Block Diagram of Test Setup

5.2.1 Radiated emission test setup



■ : 50 ohm Coaxial Switch

5.3 Radiated Emission Limit (FCC Part 18.305(c) Consumer Equipment)

Frequency (MHz)	Distance (m)	Field strength limits		Converted Field Strength Limits By 3 Meters Measuring Distance
		($\mu\text{V/m}$)	dB ($\mu\text{V/m}$)	dB ($\mu\text{V/m}$)
30 ~ 88	30	10	20.0	40.0
88 ~ 216	30	15	23.5	43.5
216 ~ 1000	30	20	26.0	46.0
NOTE 1 - The lower limit shall apply at the transition frequency. NOTE 2 - Measuring distance of 30 m is a primary requirement. However, 3 m (instead of 30 m) distance maybe allowed. In this case, the limits with measuring distance of 3 m shall be the above limit value increased $20\lg(30/3)=20\text{dB}$. NOTE 3 - 1 $\mu\text{V/m}$ is regarded as 0 dB $\mu\text{V/m}$.				

5.4 Test Configuration

The configuration of the EUT and peripherals are same as those used in conducted emission test.

Please refer to Sec.3.4.

5.5 Operating Condition of EUT

Same as conducted emission test which is listed in Sec.3.5, except for the test setup replaced by Sec.5.2.

5.6 Test Procedures

The EUT and lamp were placed on a turntable that is 1.0 meter above ground. The turntable rotated 360 degrees to determine the position of the maximum emission level. The EUT was set 3 meters away from the receiving antenna, which was mounted on an antenna tower. The antenna moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (Calibrated Bilog Antenna) was used as receiving antenna. Both horizontal and vertical polarizations of the antenna were set on measurement. In order to find the maximum emission, all of the interference cables were manipulated according to FCC MP-5: 1986 requirements during radiated emission test.

The bandwidth of Test Receiver R&S ESVS10 was set at 120 kHz.

The frequency range from 30 MHz to 1000 MHz was checked.

The test mode was done on radiated disturbance test and all the test results are listed in Sec.5.7.

5.7 Test Results

<PASS>

The frequency and amplitude of the highest radiated emission relative the limit is reported. All the emissions not reported below are too low against the FCC limit.

Model No	Test Mode	Data Page
VEB82122	Lighting	P23
VEB82130		P24
VEB82132		P25
VEB82140		P26

NOTE 1 – Emission Level = Antenna Factor + Cable Loss + Meter Reading.

NOTE 2 – The emission levels that are 20dB below the official limit are not reported.

NOTE 3 – 0° was the table front facing the antenna. Degree is calculated from 0° clockwise facing the antenna.

NOTE 4 – The worst case is for VEB82130 model. The worst emission at horizontal polarization was detected at 34.850 MHz with corrected signal level of 24.71 dB (μV/m) (limit is 40.00 dB (μV/m)), when the antenna was 1.00 m height and the turntable was at 240°. The worst emission at vertical polarization was detected at 35.800 MHz with corrected signal level of 37.30 dB (μV/m) (limit is 40.00 dB (μV/m)), when the antenna was 1.00 m height and the turntable was at 40°.

EUT : Ballast Temperature : 22°C

Model No. : VEB82122 Humidity : 60%RH

Serial No. : E2008121819 Date of Test : Dec 19, 2008

Test Mode : Lighting

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)
Horizontal	30.970	1.05	19.03	0.57	20.65	40.00	19.35
	95.960	1.69	10.70	0.85	13.24	43.50	30.26
	153.190	4.11	11.04	0.93	16.08	43.50	27.42
	279.290	2.20	13.52	1.42	17.14	46.00	28.86
	486.870	0.82	17.75	2.33	20.90	46.00	25.10
	578.050	-0.13	18.94	2.55	21.36	46.00	24.64
Vertical	35.820	18.22	16.45	0.64	35.31	40.00	4.69
	153.190	8.51	11.04	0.93	20.48	43.50	23.02
	281.230	8.28	13.57	1.44	23.29	46.00	22.71
	362.710	6.53	15.65	1.87	24.05	46.00	21.95
	492.690	1.61	17.80	2.35	21.76	46.00	24.24
	743.920	4.22	20.17	3.19	27.58	46.00	18.42

TEST ENGINEER: TOM SI

EUT : Ballast Temperature : 22°C

Model No. : VEB82130 Humidity : 60%RH

Serial No. : E2008121815 Date of Test : Dec 19, 2008

Test Mode : Lighting

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)
Horizontal	34.850	7.12	16.97	0.62	24.71	40.00	15.29
	120.210	2.78	12.98	0.88	16.64	43.50	26.86
	166.770	10.46	10.31	0.98	21.75	43.50	21.75
	280.260	3.21	13.55	1.44	18.20	46.00	27.80
	526.640	2.10	18.24	2.43	22.77	46.00	23.23
	671.170	1.79	19.57	2.95	24.31	46.00	21.69
Vertical	35.800	20.21	16.45	0.64	37.30	40.00	2.70
	119.240	6.98	12.97	0.88	20.83	43.50	22.67
	166.770	10.46	10.31	0.98	21.75	43.50	21.75
	257.950	7.78	13.06	1.31	22.15	46.00	23.85
	362.710	7.69	15.65	1.87	25.21	46.00	20.79
	743.920	2.92	20.17	3.19	26.28	46.00	19.72

TEST ENGINEER: TOM SI

EUT : Ballast Temperature : 22°C

Model No. : VEB82132 Humidity : 60%RH

Serial No. : E2008121820 Date of Test : Dec 19, 2008

Test Mode : Lighting

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)
Horizontal	30.970	1.36	19.03	0.57	20.96	40.00	19.04
	118.270	-0.39	12.91	0.88	13.40	43.50	30.10
	166.770	7.58	10.31	0.98	18.87	43.50	24.63
	279.290	3.42	13.52	1.42	18.36	46.00	27.64
	364.650	1.82	15.73	1.89	19.44	46.00	26.56
	765.260	0.19	20.36	3.25	23.80	46.00	22.20
Vertical	32.910	10.40	17.95	0.60	28.95	40.00	11.05
	43.580	12.59	11.88	0.72	25.19	40.00	14.81
	127.000	4.28	12.66	0.89	17.83	43.50	25.67
	281.230	11.12	13.57	1.44	26.13	46.00	19.87
	362.710	7.10	15.65	1.87	24.62	46.00	21.38
	743.920	3.89	20.17	3.19	27.25	46.00	18.75

TEST ENGINEER: TOM SI

EUT : Ballast Temperature : 22°C

Model No. : VEB82132 Humidity : 60%RH

Serial No. : E2008121821 Date of Test : Dec 19, 2008

Test Mode : Lighting

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)
Horizontal	37.760	3.97	15.20	0.66	19.83	40.00	20.17
	96.930	8.14	10.87	0.85	19.86	43.50	23.64
	161.920	11.45	10.46	0.97	22.88	43.50	20.62
	279.290	8.47	13.52	1.42	23.41	46.00	22.59
	526.640	0.72	18.24	2.43	21.39	46.00	24.61
	671.170	1.73	19.57	2.95	24.25	46.00	21.75
Vertical	36.790	18.15	15.80	0.65	34.60	40.00	5.40
	45.520	18.70	10.94	0.73	30.37	40.00	9.63
	108.570	12.62	12.17	0.86	25.65	43.50	17.85
	157.070	20.29	10.74	0.95	31.98	43.50	11.52
	279.290	12.88	13.52	1.42	27.82	46.00	18.18
	362.710	7.42	15.65	1.87	24.94	46.00	21.06

TEST ENGINEER: TOM SI

6 DEVIATION TO TEST SPECIFICATIONS

None