

APPLICATION FOR VERIFICATION
On Behalf of
AEI Protect-On Systems Limited

Self-Contained Access Control Reader
Model No.: AR-2808

FCC ID: OGJ-AR2808

Prepared for : AEI Protect-On Systems Limited
Address : Flat B, 4/F., Effort Industrial Building, 2-8 Kung Yip
Street, HongKong
Prepared by : Accurate Technology Co., Ltd.
Address : F1, Bldg. A&D, Changyuan New Material Port, Keyuan
Rd., Science & Industry Park, Nanshan District, Shenzhen
518057, P.R. China

Tel: +86-755-26503290
Fax: +86-755-26503396

Report No. : ATE20141501
Date of Test : Aug 04-12,2014
Date of Report : Aug 12,2014

TABLE OF CONTENTS

Description	Page
Test Report Declaration	
1. TEST RESULTS SUMMARY	4
2. GENERAL INFORMATION.....	5
2.1. Description of Device (EUT).....	5
2.2. Special Accessory and Auxiliary Equipment.....	5
2.3. Description of Test Facility	6
2.4. Measurement Uncertainty.....	6
3. POWER LINE CONDUCTED MEASUREMENT.....	7
3.1. For Power Line Conducted Emission.....	7
3.2. Power Line Conducted Emission Measurement Limits (Class B)	7
3.3. Power Line Conducted Emission Measurement Results.....	7
4. RADIATED EMISSION MEASUREMENT	8
4.1. For Radiated Emission Measurement	8
4.2. TEST CONFIGURATION.....	8
4.3. Block Diagram of Test Setup	9
4.4. Radiated Emission Limit	9
4.5. EUT Configuration on Measurement	9
4.6. Operating Condition of EUT	10
4.7. Test Procedure	10
4.8. Radiated Emission Noise Measurement Result.....	10
5. ANTENNA REQUIREMENT.....	14
5.1. The Requirement	14
5.2. Antenna Construction.....	14

Test Report Declaration

Applicant& address : AEI Protect-On Systems Limited
Flat B, 4/F., Effort Industrial Building, 2-8 Kung Yip Street,HongKong

Manufacturer& address : AEI Protect-On Systems Limited
Flat B, 4/F., Effort Industrial Building, 2-8 Kung Yip Street,HongKong

Product : Self-Contained Access Control Reader

Model No. : AR-2808

Trade name : /

Measurement Procedure Used:

FCC Rules and Regulations Part 15 Subpart C 15.207&15.209
FCC/ANSI C63.4-2009

The device described above is tested by Accurate Technology Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C limits both radiated and conducted emissions. The measurement results are contained in this test report and Accurate Technology Co., Ltd. is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of Accurate Technology Co., Ltd.

Date of Test : _____ Aug 04-12,2014
Date of Report : _____ Aug 12,2014

Prepared by : _____ 
(Eric, Engineer)

Approved & Authorized Signer : _____ 
(Sean, Manager)

1. TEST RESULTS SUMMARY

Test Items	Test Standard	Test Results
Power Line Conducted Emission	FCC Part 15.207	N/A
Radiated Emission	FCC Part 15.209	Pass

2. GENERAL INFORMATION

2.1. Description of Device (EUT)

The submitted sample is a Self-Contained Access Control Reader. The sample is powered by DC 12V.

		Self-Contained Access Control Reader
Frequency	:	125KHz
Number of Channels	:	1
Modulation Type	:	GFSK
Type of Antenna	:	Internal Antenna
Max antenna gain	:	0dBi
Power Supply	:	DC 12V

2.2. Special Accessory and Auxiliary Equipment

N/A

2.3. Description of Test Facility

EMC Lab : Accredited by TUV Rheinland Shenzhen, May 10, 2004

Listed by FCC

The Registration Number is 253065

Listed by FCC

The Registration Number is 752051

Listed by Industry Canada

The Registration Number is 5077A-1

Listed by Industry Canada

The Registration Number is 5077A-2

Accredited by China National Accreditation Committee for Laboratories

The Certificate Registration Number is L3193

Name of Firm : Accurate Technology Co., Ltd.

Site Location : F1, Bldg. A&D, Changyuan New Material Port, Keyuan Rd., Science & Industry Park, Nanshan District, Shenzhen 518057, P.R. China

2.4. Measurement Uncertainty

Conducted emission expanded uncertainty : $U=2.23\text{dB}$, $k=2$

Power disturbance expanded uncertainty : $U=2.92\text{dB}$, $k=2$

Radiated emission expanded uncertainty : $U=3.08\text{dB}$, $k=2$
(9kHz-30MHz)

Radiated emission expanded uncertainty : $U=4.42\text{dB}$, $k=2$
(30MHz-1000MHz)

Radiated emission expanded uncertainty : $U=4.06\text{dB}$, $k=2$
(Above 1GHz)

3. POWER LINE CONDUCTED MEASUREMENT

3.1. For Power Line Conducted Emission

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde & Schwarz	ESCS30	100307	Jan. 11, 2014	1 Year
2.	L.I.S.N.	Schwarzbeck	NLSK8126	8126431	Jan. 11, 2014	1 Year
3.	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100815	Jan. 11, 2014	1 Year
4.	50Ω Coaxial Switch	Anritsu Corp	MP59B	6200283933	Jan. 11, 2014	1 Year

Expanded Uncertainty: U= 2.23dB, k=2

3.2. Power Line Conducted Emission Measurement Limits (Class B)

Frequency MHz	Limits dB(µV)	
	Quasi-peak Level	Average Level
0.15—0.50	66—56*	56—46*
0.50—5.00	56	46
5.00—30.0	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

3.3. Power Line Conducted Emission Measurement Results

There are not any AC ports. Therefore, the test is not applicable and skipped.

4. RADIATED EMISSION MEASUREMENT

4.1. For Radiated Emission Measurement

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	E7405A	MY45115511	Jan. 11, 2014	1 Year
2.	Test Receiver	Rohde & Schwarz	ESCS30	100307	Jan. 11, 2014	1 Year
3.	Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Jan. 15, 2014	1 Year
4.	Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan. 15, 2014	1 Year
5.	Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Jan. 15, 2014	1 Year
6.	50 Coaxial Switch	Anritsu Corp	MP59B	6200506474	Jan. 11, 2014	1 Year
12.	Pre-Amplifier	Rohde & Schwarz	CBLU11835 40-01	3791	Jan. 11, 2014	1 Year


Expanded Uncertainty (9kHz-30MHz): U=3.08dB, k=2

Expanded Uncertainty (30MHz-1000MHz): U=4.42dB, k=2


Expanded Uncertainty (Above 1GHz): U=4.06dB, k=2

4.2. TEST CONFIGURATION

(A) Radiated Emission Test Set-Up, Frequency below 30MHz




(B) Radiated Emission Test Set-Up, Frequency 30-1000MHz



4.3. Block Diagram of Test Setup

4.3.1. Block diagram of connection between the EUT and simulators



4.4. Radiated Emission Limit

Frequency (MHz)	Field Strength Limitation		Field Strength Limitation at 3m Measurement Dist	
	(uV/m)	Dist	(uV/m)	(dBuV/m)
0.009 – 0.490	2400 / F(KHz)	300m	10000 * 2400/F(KHz)	20log 2400/F(KHz) + 80
0.490 – 1.705	24000 / F(KHz)	30m	100 * 24000/F(KHz)	20log 24000/F(KHz) + 40
1.705 – 30.00	30	30m	100* 30	20log 30 + 40
30.0 – 88.0	100	3m	100	20log 100
88.0 – 216.0	150	3m	150	20log 150
216.0 – 960.0	200	3m	200	20log 200
Above 960.0	500	3m	500	20log 500

Limit: $2400/125=19.2\mu\text{V}/\text{m}$ @ 300m

Distance Correction Factor = $40\log(\text{test distance}/\text{specific distance})$

4.5. EUT Configuration on Measurement

The equipment is installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

4.6.Operating Condition of EUT

- 4.6.1.Setup the EUT and simulator as shown as Section 4.2.
- 4.6.2.Turn on the power of all equipment.
- 4.6.3.Let the EUT work in test mode and measure it.

4.7.Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4: 2009 on radiated emission measurement.

From 9kHz to 30MHz at distance 3m The EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.

From 30MHz to 1000MHz at distance 3m The measuring antenna height varied between 1 and 4m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity. The measurements were performed for both vertical and horizontal antenna polarization.

The final measurement will be performed with an EMI Receiver set to Quasi Peak detector for the frequency bands 9kHz to 90kHz and 110 to 490 kHz where an average detector will be used according to Section 15.209(d)(2).

The final level, expressed in dBuV/m, is arrived at by taking the reading from the EMI receiver(Level dBuV) and adding the antenna correction factor and cable loss factor(Factor dB) to it. This result then has to be compared with the relevant FCC limit.The resolution bandwidth during the measurement is as follows:

9kHz – 150kHz: ResBW:200Hz
150kHz – 30MHz: ResBW:9kHz

The bandwidth of the EMI test receiver (R&S ESCS30) is set at 120kHz from 30MHz to 1000MHz.

4.8.Radiated Emission Noise Measurement Result

PASS.

From 9kHz to 30MHz

Frequency (MHz)	Quasi Peak (dB μ V/m)	Azimuth	Polarity (H/V)	Factors (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
0.125	68.14	153	H	-56.36	105.7	-37.56
2.02	40.55	36	H	-54.15	69.5	-28.95
14.25	35.22	205	H	-52.01	69.5	-34.28
0.125	72.14	185	V	-56.36	105.7	-33.56
3.68	42.74	352	V	-53.27	69.5	-26.76
17.35	36.24	15	V	-51.25	69.5	-33.26

Part 15 Section 15.31(f)(2) (9kHz-30MHz)

Limit at 3m=Limit at 300m-40*log(300(m)/3(m))

Limit at 3m=Limit at 30m-40*log(30(m)/3(m))

From 30MHz to 1000MHz



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: ricky #2134

Polarization: Vertical

Standard: FCC Class B 3M Radiated

Power Source: DC 12V

Test item: Radiation Test

Date: 14/08/08/

Temp.(C)/Hum.(%) 25 C / 55 %

Time: 8/40/07

EUT: Self-Contained Access Control Reader

Engineer Signature:


Mode: ON

Distance: 3m

Model: AR-2808

Manufacturer: AEI Protect-On

Note: Report No.:ATE20141501



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	33.2112	30.41	-17.25	13.16	40.00	-26.84	QP			
2	39.2991	30.82	-18.88	11.94	40.00	-28.06	QP			
3	45.5348	30.86	-19.51	11.35	40.00	-28.65	QP			

Job No.: ricky #2135

Polarization: Horizontal

Standard: FCC Class B 3M Radiated

Power Source: DC 12V

Test item: Radiation Test

Date: 14/08/08/

Temp.(C)/Hum.(%) 25 C / 55 %

Time: 8/40/24

EUT: Self-Contained Access Control Reader

Engineer Signature:


Mode: ON

Distance: 3m

Model: AR-2808

Manufacturer: AEI Protect-On

Note: Report No.:ATE20141501



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	31.9546	35.68	-17.07	18.61	40.00	-21.39	QP			
2	39.1616	31.81	-18.84	12.97	40.00	-27.03	QP			
3	68.1514	32.85	-21.29	11.56	40.00	-28.44	QP			

5. ANTENNA REQUIREMENT

5.1. The Requirement

According to Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

5.2. Antenna Construction

Device is equipped with unique antenna, which isn't displaced by other antenna. Therefore, the equipment complies with the antenna requirement of Section 15.203.

