

## 5 TEST CONDITIONS AND RESULTS


### 5.1 Conducted emission

For test instruments and accessories used see section 6 Part A 4.

#### 5.1.1 Description of the test location

Test location: Shielded Room S2

#### 5.1.2 Photo documentation of the test set-up





## 5.2 Radiated emission


For test instruments and accessories used see section 6 Part **SER 2, SER 3**.

### 5.2.1 Description of the test location

Test location: OATS 1  
Test location: Anechoic chamber 2  
Test distance: 3 m

### 5.2.2 Photo documentation of the test setup





### 5.2.3 Applicable standard

According to FCC Part 15B, Section 15.109 (a):

Except for Class A digital devices, the field strength of radiated emission from unintentional radiators at a distance of 3 m shall not exceed the given limit.

### 5.2.4 Description of Measurement

The radiated emissions from the EUT are measured in the frequency range of 30 MHz to 1000 MHz using a tuned receiver and appropriate broadband linearly polarized antennas. The setup of the EUT and the measurement procedure is in accordance to ANSI C63.4, Item 8 and 12. In the frequency range above 1 GHz a spectrum analyser is used. If the emission level in peak mode complies with the average limit, testing is stopped and peak values will be reported, otherwise, the emission is measured in average mode again and both are reported. The EUT is measured in RX continuous mode under normal conditions.

Instrument settings:

30 MHz – 1000 MHz:	RBW: 120 kHz	VBW: 3MHz	Detector: Peak
1000 MHz – 12.5 GHz	RBW: 1 MHz		