

Electromagnetic Emission

F C C M E A S U R E M E N T R E P O R T

CERTIFICATION OF COMPLIANCE

FCC Part 15 Certification Measurement

PRODUCT : LCD TV
MODEL/TYPE NO : DLN-26D3
FCC ID : OIODLN-26D3
APPLICANT : Erae Electronics Industry Co., Ltd.
#371-51, Kasan-Dong, Keumcheon-Ku, Seoul, 153-803, Korea
Attn.: Woon-Seok, Yu / Deputy General Manager
FCC CLASSIFICATION : Class B personal computers and peripherals
FCC RULE PART(S) : FCC Part 15 Subpart B
FCC PROCEDURE : Certification
TRADE NAME : DAEWOO, Erae
TEST REPORT No. : E05.0207.FCC.102N
DATES OF TEST : January 17 ~ February 05, 2005
DATES OF ISSUE : February 07, 2005
TEST LABORATORY : ETL Inc. (FCC Registration Number : 95422)
#584 Sangwhal-ri, Kanam-myon, Yoju-kun, Kyounggi-do,
469-885, Korea
Tel : (031) 885-0072 Fax : (031) 885-0074

This LCD TV, Model DLN-26D3 has been tested in accordance with the measurement procedures specified in ANSI C63.4-2001 at the ETL/EMC Test Laboratory and has been shown to be complied with the electromagnetic radiated emission limits specified in FCC Rule Part15 Subpart B:

I attest to the accuracy of data. All measurement herein was performed by me or was made under my supervision and is correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

The results of testing in this report apply to the product/system which was tested only. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.



Yo Han, Park / Chief Engineer



ETL Inc.

**#584 Sangwhal-ri, Kanam-myon, Yoju-kun,
Kyounggi-do, 469-885, Korea**

Table of Contents

FCC Measurement Report

- 1. Introduction**
- 2. Product Information**
- 3. Description of Tests**
- 4. Test Condition**
- 5. Test Results**
 - 5.1 Summary of Test Results**
 - 5.2 Conducted Emissions Measurement**
 - 5.3 Radiated Emissions Measurement**
- 6. Sample Calculation**
- 7. List of test Equipment for Measurement**

Appendix A. FCC ID Label and Location

Appendix B. Test Setup Photographs

Appendix C. External Photographs

Appendix D. Internal Photographs

Appendix E. Block Diagram

Appendix F. User Manual

Scope – *Measurement and determination of electromagnetic emission(EME) of radio frequency devices including intentional radiators and/or unintentional radiators for compliance with the technical rules and regulations of the U.S Federal Communications Commission(FCC)*

General Information

Applicant Name : Erae Electronics Industry Co., Ltd.
Address : #371-51, Kasan-Dong, Keumcheon-Ku, Seoul, 153-803, Korea
Attention : Woon-Seok, Yu / Deputy General Manager

- **EUT Type :** LCD TV
- **Model Number :** DLN-26D3
- **FCC ID :** OIODLN-26D3
- **S/N :** N/A
- **FCC Rule Part(s) :** FCC Part 15 Subpart B
- **Test Procedure :** ANSI C63.4-2001
- **FCC Classification :** Class B personal computers and peripherals
- **Dates of Tests :** January 17 ~ February 05, 2005
ETL Inc.
EMC Testing Lab (FCC Registration Number : 95422)
- **Place of Tests :** 584, Sangwhal-Ri, Kanam-Myun, Yaju-Kun,
Kyounggi-Do, Korea
Tel : (031) 885-0072 Fax : (031) 885-0074
- **Test Report No. :** E05.0207.FCC.102N

1. INTRODUCTION

The measurement test for radiated and conducted emission test were conducted at E-RAE Testing Laboratory Inc. facility located at 584, Sangwhal-ri, Ganam-myun, Youju-kun, Kyoungki-do, Korea. The site is constructed in conformance with the requirements of the ANSI C63.4-2001 and CISPR Publication 16. The ETL has site descriptions on file with the FCC for 3 and 10 meter site configurations. Detailed description of test facility was found to be in compliance with the requirements of Section 2.948 FCC Rules according to the ANSI C63.4-2001 and registered to the Federal Communications Commission(Registration Number : 95422).

The measurement procedure described in America national standard for method of measurement of radio-noise emission from low-voltage electrical and electronic equipment in the range of 9 kHz to 40 GHz (ANSI C.63.4-2001) was used in determining radiated and conducted emissions from the Erae Electronics Industry Co., Ltd. Model: DLN-26D3

2. PRODUCT INFORMATION

2.1 General Remark

The Equipment Under Test (EUT) is the Erae Electronics Industry Co., Ltd., LCD TV, Model: DLN-26D3, ELT-2622AN, ELT-2622BN & ELT-2600AP has a minor changes to the basic model.

Model Difference: Basic model name: DLN-26D3

Multi listing model name: ELT-2622AN, ELT-2622BN & ELT-2600AP

Technical Deviation: Models DLN-26D3, ELT-2622AN, ELT-2622BN & ELT-2600AP are same with basic model except for model name, brand name and front design.

2.2 Equipment Description

The Equipment Under Test (EUT) is the Erae Electronics Industry Co., Ltd., LCD TV, DLN-26D3

2.3 General Specification

● Chassis Type	: Plastic
● List of Each OSC. Or X-Tal. Freq. (>=1MHz)	: X-Tal: 18.432, 20.25, 13.50, 14.31818 MHz
● Aspect Ratio	: 15:9
● Screen Size (H x V)	: 566.4 x 339.84 mm
● Resolution	: 1280 x 1024
● Pixel pitch	: 0.4425 x 0.4425 mm
● Displayable Colors	: 16.7M
● Brightness	: 450cd/m ² (Typical)
● Contrast	: 500:1
● Viewing Angle	: 85 ° / 85 ° / 85 ° / 85 °
● Input signal	: NTSC, SD ~ HD, VGA ~ SXGA
● Tuner	: NTSC
● RGB Input	: D-Sub, DVID
● AC Input	: AC 100 – 240 V, 50/60 Hz, 2 A
● Power Consumption	: 140 W

3. DESCRIPTION OF TESTS

3.1 Conducted Emission Measurement

Conducted emissions measurements were made in accordance with § 12.2 in ANSI C63.4-2001 "measurement of information technology equipment ". The measurement were performed over the frequency range of 0.15 MHz to 30 MHz using a 50 /50uH LISN as the input transducer to a spectrum analyzer or a feld intensity meter. The measurements were made with the detector set for "Peak" amplitude within a bandwidth of 10 kHz or for "quasi-peak" within a bandwidth of 9 kHz.

- Procedure of Test

The line-conducted facility is located inside a shielded room 1 m X 1.5 m wooden table 80cm high is placed 40cm away from the vertical wall and more than 0.8 m away from the side wall of the shielded room. Grounds of two LISN are bonded to the reference horizontal ground plane. The EUT is powered from the LISN and the support equipment is powered from the other LISN. Powers of the LISN are filtered by a noise cut power line filters. All electrical cables are shielded by braided tinned steel tubing with inner ϕ 1.2cm. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and these supply lines will be connected to the LISN. Non-inductive bundling to a 1m length shortened all interconnecting cables more than 1m. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer or test receiver to determine the frequency producing the maximized emission from the EUT. The frequency producing the maximum level was reexamined using to set Quasi-Peak mode by manual, after scanned by automatic Peak mode from 0.15 to 30 MHz. The bandwidth of the spectrum analyzer was set to 9 kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission.

3. DESCRIPTION OF TESTS

3.2 Radiated Emission Measurement

Radiated emission measurements were in accordance with § 12.2 in ANSI C63.4-2001 "measurement of information technology equipment ". The measurements were performed over the frequency range of 30 MHz to 1 GHz using antenna as the input transducer to a spectrum analyzer or a field intensity meter. The measurements were made with the detector set for "Quasi-peak" within a bandwidth of 120 kHz.

- Procedure of Test

Preliminary measurements were made at 3 meter using broadband antennas, and spectrum analyzer to determined the frequency producing the maximized emission in shielded room. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth and height with respect to the antenna were noted for each frequency found. The spectrum was scanned from 30 to 1000 MHz using broadband antenna. For above 1 GHz, linearly polarized double ridge horn antennas were used. Final measurements were made open site at 3-meters. The test equipment was placed on a wooden turn-able table. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. Each frequency found during pre-scan measurements was re-examined by manual. The detector function was set to CISPR Quasi-peak mode and the bandwidth of the receiver was set to 120 kHz or 1MHz depending on the frequency of type of signal. The EUT, support equipment and interconnecting cables were re-configured to the set-up producing the max. Emission for the frequency and were placed on top of a 0.8-meter high non-metallic 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were re-arranged and manipulated to maximize each emission. The turntable containing the system was rotated; the antenna height was varied 1 to 4 meters and stopped at the azimuth or height producing the max emission. Each emission was maximized by: varying the mode of operation to the EUT and/or support equipment and changing the polarity of the antenna, whichever determined the worst-case emission. Photographs of the worst-case emission can be seen in Photographs of the worst-case emission test setup can be seen in Appendix B.

4. TEST CONDITION

4.1 Test Configuration

The device was configured for testing in a typical fashion (as a customer would normally use it). During the tests, the following conditions and configurations were used.

4.2 EUT operation

Operating Mode	The worst operating condition
Stand-by mode	X
640 * 480, 75 Hz, Full "H" pattern display & MP3 play mode	X
720 * 400, 70 Hz, Full "H" pattern display & MP3 play mode	X
800 * 600, 75 Hz, Full "H" pattern display & MP3 play mode	X
1024 * 768, 75 Hz, Full "H" pattern display & MP3 play mode	X
1280 * 1024, 60 Hz, Full "H" pattern display & MP3 play mode	

: Worst case investigated during the test.

4.3 Support Equipment Used

Following peripheral devices and interface cables were connected during the measurement:

EUT – LCD TV

FCC ID : OIODLN-26D3
Model Name : DLN-26D3
Serial No. : N/A
Manufacturer : Erae Electronics Industry Co., Ltd.
Power Supply Type : Switching
Power Cord : Non-Shielded, Detachable: 1.5 m
Data Cable : 1.8 m Shielded RGB, 1.8 m Shielded DVI-D, 1.2m Shielded RCA, 1.2m Shielded S-Video

Support unit 1 – Personal computer (DELL)

FCC ID : N/A (DoC)
Model Name : DHM
Serial No. : H9MB71S
Manufacturer : DELL
Power Supply Type : Switching
Power Cord : Non-Shielded, Detachable: 1.2 m
Data Port : RGB IN:1, Parallel:1, RS-232:1, PS/2: 2, USB: 4, RJ-45:1
: Audio in:1, Audio out:1, MIC IN:1

Support unit 2 –Keyboard (COMPAQ)

FCC ID	: N/A (DoC)
Model Name	: KB-9963
Serial No.	: B26960GBUKO13F
Manufacturer	: COMPAQ
Power Supply Type	: N/A
Power Cord	: N/A
Data Cable	: Shielded, 1.5m

Support unit 3 – Mouse (LOGITECH)

FCC ID	: DZL211029
Model Name	: M-S34
Serial No.	: LZC01002314
Manufacturer	: LOGITECH
Power Supply Type	: N/A
Power Cord	: N/A
Data Cable	: None-Shielded, 1.2m

Support unit 4 – USB Mouse (N/A)

FCC ID	: N/A
Model Name	: HL898W
Serial No.	: HL80811837
Manufacturer	: N/A
Power Supply Type	: N/A
Power Cord	: N/A
Data Cable	: Shielded, 1.2m

Support unit 5 – Serial Mouse (PETRA)

FCC ID	: JKGMUS5S01
Model Name	: MUS5S
Serial No.	: E183027
Manufacturer	: PETRA
Power Supply Type	: N/A
Power Cord	: N/A
Data Cable	: Shielded, 1.2m

Support unit 6 – DVD Box (ALPHACAST)

FCC ID	: N/A
Model Name	: DVDP-M100
Serial No.	: N/A
Manufacturer	: ALPHACAST
Power Supply Type	: DC 12 V of Adaptor
Power Cord	: Non-shielded, Detachable: 1.2 m
Data Cable	: Shielded, 1.2m

5. TEST RESULTS

5.1 Summary of Test Results

The measurement results were obtained with the EUT tested in the conditions described in this report. Detailed measurement data and plots showing the maximum emission of the EUT are reported.

Test Rule Parts	Measurement Required	Result
15.107	Conducted emissions measurement	Passed by 6.11 dB
15.109	Radiated emissions measurement	Passed by 3.70 dB

The data collected shows that the **Erae Electronics Industry Co., Ltd. / LCD TV / DLN-26D3** complies with technical requirements of above rules part 15.107 and 15.109 Class B.

5. TEST RESULTS

5.2 Conducted Emissions Measurement

EUT	LCD TV / DLN-26D3 (SN: N/A)
Limit apply to	FCC Part 15. 107(Class B)
Test Date	February 02, 2005
Operating Condition	Full "H" pattern display(1280 x 1024, 60Hz) & MP3 play mode
Environment Condition	Humidity Level: 37 %RH, Temperature: 20
Result	Passed by 6.11 dB

Conducted Emission Test Data

The following table shows the highest levels of conducted emissions on both polarizations of hot and neutral line.
Detector mode: CISPR Quasi-Peak mode (6dB Bandwidth : 9 kHz)

Frequency [MHz]	Reading [dB μ V]		Phase [*H/**V]	Limit [dB μ V]		Margin [dB]	
	Quasi-peak	Average		Quasi-peak	Average	Quasi-peak	Average
0.198	48.52	39.85	H	63.69	53.69	15.17	13.84
0.263	51.76	45.23	N	61.34	51.34	9.58	6.11
0.331	41.62	31.75	H	59.43	49.43	17.81	17.68
0.399	43.89	38.77	N	57.87	47.87	13.98	9.10
0.462	40.32	36.37	N	56.66	46.66	16.34	10.29
0.595	34.29	32.28	N	56.00	46.00	21.71	13.72
25.280	37.67	31.90	N	60.00	50.00	22.33	18.10

NOTES:

1. * H : HOT Line , **N : Neutral Line
2. Margin value = Limit – Reading
3. If the reading Quasi-Peak value is below the average limit, do not test average mode.



Test Engineer: H. S. Lee

5. TEST RESULTS


Line: HOT Line

ETL EMC Laboratory

Conducted Emission Test Result

EUT: DLN-26D3
 Manuf: Erea
 Op Cond:
 Operator:
 Test Spec: FCC Part 15 CLASS B
 Comment: HOT

Scan Settings		(3 Ranges)			Receiver Settings					
Transducer	No.	Start	Stop		Detector	M-Time	Atten	Preamp	OpRge	
		Start	Stop	Step	IF BW					
		150kHz	1000kHz	1000Hz	10kHz	PK+AV	10msec	Auto	OFF	60dB
		1000kHz	5MHz	2kHz	10kHz	PK+AV	10msec	Auto	OFF	60dB
		5MHz	30MHz	5kHz	10kHz	PK+AV	10msec	Auto	OFF	60dB
Prescan Measurement:		Detectors:	X PK / + AV							
		Meas Time:	see scan settings							
		Peaks:	8							
		Acc Margin:	10 dB							




5. TEST RESULTS**Line: Neutral Line**

ETL EMC Laboratory

Conducted Emission Test Result

EUT: DLN-26D3
 Manuf: Erea
 Op Cond:
 Operator:
 Test Spec: FCC Part 15 CLASS B
 Comment: NEUTRAL

Scan Settings		(3 Ranges)			Receiver Settings					
Frequencies		Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge
Start	Stop									
150kHz	1000kHz			1000Hz	10kHz	PK+AV	10msec	Auto	OFF	60dB
1000kHz	5MHz			2kHz	10kHz	PK+AV	10msec	Auto	OFF	60dB
5MHz	30MHz			5kHz	10kHz	PK+AV	10msec	Auto	OFF	60dB
Transducer	No.	Start	Stop			Name				
	1	9kHz	30MHz			Factor				
Prescan Measurement:		Detectors:	X	PK / + AV						
		Meas Time:		see scan settings						
		Peaks:		8						
		Acc Margin:		10 dB						



5. TEST RESULTS

5.3 Radiated Emissions Measurement

EUT	LCD TV / DLN-26D3 (SN: N/A)
Limit apply to	FCC Part 15. 109(Class B)
Test Date	February 02, 2005
Operating Condition	Full "H" pattern display(1280 x 1024, 60Hz) & MP3 play mode
Environment Condition	Humidity Level: 32 %RH, Temperature: 7
Result	Passed by 3.70 dB

Radiated Emission Test Data

The following table shows the highest levels of radiated emissions on both polarizations of horizontal and vertical. Detector mode: CISPR Quasi-Peak mode (6dB Bandwidth : 120 kHz)

Frequency [MHz]	Reading [dB μ V]	Polarization [*H/**V]	Ant.Factor [dB/m]	Cable Loss [dB]	Result [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
46.95	18.32	V	12.21	2.04	32.57	40.00	7.43
65.11	22.18	V	10.72	2.15	35.05	40.00	4.95
338.75	20.04	V	13.91	5.97	39.92	46.00	6.08
345.26	19.81	V	14.04	6.04	39.89	46.00	6.11
358.30	20.92	V	14.32	6.18	41.42	46.00	4.58
371.40	20.88	V	14.62	6.31	41.81	46.00	4.19
377.84	21.05	V	14.76	6.38	42.19	46.00	3.81
403.90	17.51	V	15.42	6.65	39.58	46.00	6.42
912.04	8.00	V	22.36	11.95	42.30	46.00	3.70

NOTES :* H : Horizontal polarization , ** V : Vertical polarization

1. Result = Reading + Antenna factor + Cable loss
2. Margin value = Limit - Result



Test Engineer: H. S. Lee

6. SAMPLE CALCULATION

Sample Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor.
The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF$$

where FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor

$$dB(\mu V/m) = 20 \log_{10} (\mu V / m) : \text{Equation 1}$$

$$dB\mu V = dBm + 107 : \text{Equation 2}$$

Example: @ 912.04 MHz

Class B Limit	= 46 dB $\mu V/m$
Reading	= 8.00 dB μV
Antenna Factor + Cable Loss	? 22.36 + 11.95 ? 34.30 dB $\mu V/m$
Total	= 42.30 dB $\mu V/m$
Margin	= 46.00 - 42.30 = 3.70 dB
	= 3.70 dB below Limit

7. List of Test Equipments for Measurements

Test Equipment		Model	Mfg.	Serial No.	Cal. Due Date
<input checked="" type="checkbox"/>	Spectrum Analyzer	E7402A	H.P	US39110107	05-10-18
<input checked="" type="checkbox"/>	Spectrum Analyzer	R3261A	Advantest	21720033	05-10-26
<input checked="" type="checkbox"/>	Receiver	ESVS 10	R & S	835165/001	05-04-12
<input checked="" type="checkbox"/>	EMI TEST Receiver	ESHS30	Rohde & Schwarz	0401901/002	05-10-18
<input type="checkbox"/>	Preamplifier	HP 8347A	HP	2834A00544	05-04-12
<input checked="" type="checkbox"/>	LISN	3825/2	EMCO	9006-1669	05-04-13
<input checked="" type="checkbox"/>	TriLog Antenna	VULB9160	Schwarz Beck	3082	05-07-27
<input type="checkbox"/>	LogBicon	VULB9165	Schwarz Beck	2023	05-07-06
<input type="checkbox"/>	Dipole Antenna	VHAP	Schwarz Beck	964	05-06-10
<input type="checkbox"/>	Dipole Antenna	VHAP	Schwarz Beck	965	05-07-09
<input type="checkbox"/>	Dipole Antenna	UHAP	Schwarz Beck	949	05-07-09
<input type="checkbox"/>	Dipole Antenna	UHAP	Schwarz Beck	950	05-06-10
<input type="checkbox"/>	Broad-band Horn Antenna	BBHA 9120D	Schwarz Beck	227	05-05-02
<input checked="" type="checkbox"/>	Turn-Table	DETT-03	Daeil EMC	-	N/A
<input checked="" type="checkbox"/>	Antenna Master	DEAM-03	Daeil EMC	-	N/A
<input type="checkbox"/>	Plotter	7440A	H.P	2725A 75722	N/A
<input checked="" type="checkbox"/>	Chamber	DTEC01	DAETONG	-	N/A
<input type="checkbox"/>	Thermo Hygrograph	3-3122	ISUZU	3312201	05-04-16
<input type="checkbox"/>	BaroMeter	-	Regulus	-	-