

Analysis Report

Report No.: 16080858HKG-001

The Equipment Under Test (EUT) is a portable 2.4GHz Transmitter (Controller Unit) for a RC stuffed elephant operating at the frequency range of 2425-2475MHz with the following occupied channels, 2425MHz, 2444MHz, 2451MHz and 2475MHz.

The EUT is powered by 2*1.5V AAA battery. After switching on the EUT and pressing the button, the stuffed elephant will produce sound.

Antenna Type: Internal integral antenna

Antenna Gain: 0dBi

Nominal rated field strength: 71.1dB μ V/m at 3m

Maximum allowed field strength of production tolerance: +/- 3dB

According to the KDB 447498:

Based on the Maximum allowed field strength of production tolerance was 74.1dB μ V/m at 3m in frequency 2.4GHz, thus;

The EIRP = $[(FS^2 * D) / 30] = 0.008mW$

Conducted power = Radiated Power (EIRP) – Antenna Gain

So;

Conducted Power = 0.008mW.

The SAR Exclusion Threshold Level:

= $3.0 * (\text{min. test separation distance, mm}) / \sqrt{\text{freq. in GHz}}$

= $3.0 * 5 / \sqrt{2.475} mW$

= 9.53 mW

Since the above conducted output power is well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.