

R.F Exposure/Safety Calculation for Mobile Access VE CELL-PCS System

The E.U.T. is wall or ceiling mounted. The typical distance between the E.U.T. and the general population is >20 cm for wall or ceiling mounted operation.

Calculation of Maximum Permissible Exposure (MPE)
Based on Section 1.1307(b)(1) Requirements

(a) FCC limit at 1960 MHz is: $1 \frac{mW}{cm^2}$

FCC limit at 881.5 MHz is: $f / 1500 = 0.588 \frac{mW}{cm^2}$

Using table 1 of Section 1.1310 limit for general population/uncontrolled exposures, the above level is an average over 30 minutes.

(b) The power density produced by the E.U.T. is

$$S = \frac{P_t G_t}{4\pi R^2}$$

P_t - Transmitted Peak Power (worst case)

G_t - Antenna Gain ,dBi

R - Distance from Transmitter

(c) Peak power density at worst case continuous transmission:

Modulation	Pt (mW)	Antenna type	G _T (dBi)	R (cm)	S _{AV} (mW/cm ²)	Spec (mW/cm ²)
CDMA	31.99	Integral	0	20	0.006	0.588
GSM	30.90	Integral	0	20	0.006	1.0
W-CDMA	45.71	Integral	0	20	0.009	1.0
CDMA	31.99	External	10	20	0.064	0.588
GSM	30.90	External	10	20	0.061	1.0
W-CDMA	45.71	External	10	20	0.091	1.0