

Table 1**FCC Part 90 Radiated Emissions Data - Site 2**

CLIENT: Nomadic Communications PTY Ltd.
 FCC ID: OKKNMX920
 DATE: 4 Jan 00
 BY: Chad M. Beattie
 JOB #: 5633X

Frequency	Polarity	Azimuth	Antenna	SA Level	AFc	E-Field	E-Field	Limit	Margin	Channel
MHz	H/V	Degree	Height m	(QP) dBuV	dB/m	dBuV/m	uV/m	uV/m	dB	
1792.03	V	135.00	1.0	71.7	-7.2	64.5	1673.7	16595.9	-19.9	L
1792.03	H	225.00	1.0	74.5	-7.2	67.3	2310.4	16595.9	-17.1	L
2688.04	V	270.00	1.0	65.7	-4.9	60.8	1092.7	16595.9	-23.6	L
2688.04	H	270.00	1.0	64.3	-4.9	59.4	930.0	16595.9	-25.0	L
3584.05	V	225.00	1.0	52.0	-3.7	48.3	258.7	16595.9	-36.1	L
3584.05	H	180.00	1.0	54.2	-3.7	50.5	333.3	16595.9	-33.9	L
4480.06	V	180.00	1.0	49.3	-2.8	46.5	211.5	16595.9	-37.9	L
4480.06	H	180.00	1.0	49.0	-2.8	46.2	203.6	16595.9	-38.2	L
5376.08	V	180.00	1.0	51.0	-2.1	48.9	279.6	16595.9	-35.5	L
5376.08	H	180.00	1.0	50.5	-2.1	48.4	263.9	16595.9	-36.0	L
6272.09	V	180.00	1.0	49.0	-0.5	48.5	266.1	16595.9	-35.9	L
6272.09	H	270.00	1.0	55.3	-0.5	54.8	551.6	16595.9	-29.6	L
7168.02	V	180.00	1.0	52.9	2.2	55.1	568.9	16595.9	-29.3	Amb
7168.02	H	180.00	1.0	53.8	2.2	56.0	631.0	16595.9	-28.4	Amb
8064.21	H	180.00	1.0	51.7	2.2	53.9	495.5	16595.9	-30.5	Amb
8064.21	V	180.00	1.0	52.1	2.2	54.3	518.8	16595.9	-30.1	Amb
8960.04	H	180.00	1.0	54.3	2.2	56.5	668.3	16595.9	-27.9	Amb
8960.04	V	180.00	1.0	53.8	2.2	56.0	631.0	16595.9	-28.4	Amb
1796.75	V	180.00	1.0	62.2	-7.2	55.0	562.3	16595.9	-29.4	M
1796.75	H	225.00	1.0	61.00	-7.2	53.8	489.7	16595.9	-30.6	M
2695.13	V	225.00	1.0	56.0	-4.9	51.1	358.1	16595.9	-33.3	M
2695.13	H	270.00	1.0	53.50	-4.9	48.6	268.6	16595.9	-35.8	M
3593.40	V	180.00	1.0	56.4	-3.7	52.7	429.9	16595.9	-31.7	M
3593.40	H	180.00	1.0	54.7	-3.7	51.0	353.5	16595.9	-33.4	M
4491.70	V	180.00	1.0	50.7	-2.8	47.9	248.0	16595.9	-36.5	M
4491.70	H	180.00	1.0	48.9	-2.8	46.1	201.6	16595.9	-38.3	M
5390.12	V	180.00	1.0	56.4	-2.1	54.3	521.2	16595.9	-30.1	Amb
5390.12	H	180.00	1.0	52.9	-2.1	50.8	348.4	16595.9	-33.6	Amb
6288.12	V	180.00	1.0	49.8	-0.4	49.4	293.9	16595.9	-35.0	Amb
6288.12	H	180.00	1.0	49.5	-0.4	49.1	284.0	16595.9	-35.3	Amb
7187.08	V	180.00	1.0	49.7	2.2	51.9	393.6	16595.9	-32.5	Amb
7187.08	H	180.00	1.0	50.7	2.2	52.9	441.6	16595.9	-31.5	Amb
8085.40	H	180.00	1.0	52.0	2.2	54.2	512.9	16595.9	-30.2	Amb
8085.40	V	180.00	1.0	52.6	2.2	54.8	549.5	16595.9	-29.6	Amb
8983.81	H	180.00	1.0	55.4	2.2	57.6	758.6	16595.9	-26.8	Amb
8983.81	V	180.00	1.0	55.2	2.2	57.4	741.3	16595.9	-27.0	Amb
1801.75	H	270.00	1.0	62.20	-7.2	55.0	564.0	16595.9	-29.4	H
1801.75	V	0.00	1.0	62.0	-7.2	54.8	551.1	16595.9	-29.6	H
2702.63	H	225.00	1.0	54.20	-4.9	49.3	291.5	16595.9	-35.1	H

2702.63	V	225.00	1.0	55.8	-4.9	50.9	350.4	16595.9	-33.5	H
3603.47	H	180.00	1.0	53.7	-3.7	50.0	315.5	16595.9	-34.4	H
3603.47	V	225.00	1.0	55.4	-3.7	51.7	383.7	16595.9	-32.7	H
4504.27	H	225.00	1.0	50.6	-2.8	47.8	245.5	16595.9	-36.6	H
4504.27	V	225.00	1.0	51.4	-2.8	48.6	269.1	16595.9	-35.8	H
5405.14	H	180.00	1.0	49.8	-2.0	47.8	244.1	16595.9	-36.6	Amb
5405.14	V	225.00	1.0	50.4	-2.0	48.4	261.6	16595.9	-36.0	Amb
6306.66	H	180.00	1.0	54.3	-0.4	53.9	497.6	16595.9	-30.5	Amb
6306.66	V	180.00	1.0	53.0	-0.4	52.6	428.5	16595.9	-31.8	Amb
7207.05	V	180.00	1.0	55.7	2.2	57.9	785.2	16595.9	-26.5	Amb
7207.05	H	180.00	1.0	53.7	2.2	55.9	623.7	16595.9	-28.5	Amb
8107.90	H	180.00	1.0	52.4	2.2	54.6	537.0	16595.9	-29.8	Amb
8107.90	V	180.00	1.0	53.6	2.2	55.8	616.6	16595.9	-28.6	Amb
9008.72	H	180.00	1.0	54.0	2.2	56.2	645.7	16595.9	-28.2	Amb
9008.72	V	180.00	1.0	56.7	2.2	58.9	881.0	16595.9	-25.5	Amb