

## Electromagnetic Emission

### F C C M E A S U R E M E N T R E P O R T

#### VERIFICATION OF COMPLIANCE

#### FCC Part 15 Certification Measurement

**PRODUCT** : 17" FLAT MONITOR  
**MODEL/TYPE NO** : E17AF  
**FCC ID** : OMNE17AF  
  
**APPLICANT** : IMRI Co., Ltd.  
: 270-2, Hunshin-Dong, Sangju-City, Kyungsangbuk-Do, Korea  
Attn. : Tae Moon, Choi / Q.A Dept, Deputy Manager  
  
**FCC CLASSIFICATION** : Part 15 Class B Unintentional Radiators  
Computing Device Peripheral(JBP)  
**FCC RULE PART(S)** : FCC Part 15 Subpart B  
**FCC PROCEDURE** : Certification  
**TRADE NAME** : IMRI  
**TEST REPORT No.** : E01.0811. FCC.328N  
**DATES OF TEST** : August 10, 2001  
**DATES OF ISSUE** : August 11, 2001  
  
**TEST LABORATORY** : ETL Inc ( FCC Registration Number : 95422)  
371-51, Gasan-Dong, Geumcheon-Gu, Seoul, Korea  
Tel : (031) 885-0072 Fax : (031) 885-0074

This 17" Flat CRT Monitor, Model E17AF has been tested in accordance with the measurement procedures specified in ANSI C63.4-1992 at the ETL/EMC Test Laboratory and has been shown to be complied with the electromagnetic radiated emission limits specified in FCC Rule Part15 Subpart B : Unintentional Radiators.

I attest to the accuracy of data. All measurement herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

The results of testing in this report apply to the product/system which was tested only. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.



Name : Kayoung Kim

Title : Chief Engineer & Lab.Manager

**E-RAE Testing Laboratory Inc.**  
371-51, Gasan-Dong, Geumcheon-Gu,  
Seoul, 153-023, Korea

## Table of Contents

### **ATTACHMENT A: COVER LETTER(S)**

#### **FCC Measurement Report**

- 1. Introduction**
- 2. Product Information**
- 3. Description of Tests**
- 4. Test Condition**
- 5. Test Results**
  - 5.1 Summary of Test Results**
  - 5.2 Conducted Emissions Measurement**
  - 5.3 Radiated Emissions Measurement**
- 6. Sample Calculations**
- 7. List of test Equipment used for Measurement**

**Appendix A. FCC ID Label and Location**

**Appendix B. Test Setup Photographs**

**Appendix C. External Photographs**

**Appendix D. Internal Photographs**

**Appendix E. Block Diagram**

**Appendix F. User Manual**

## FCC MEASUREMENT REPORT

**Scope** – *Measurement and determination of electromagnetic emission(EME) of radio frequency devices including intentional radiators and/or unintentional radiators for compliance with the technical rules and regulations of the U.S Federal Communications Commission(FCC)*

### General Information

**Applicant Name** : IMRI Co., Ltd.  
**Address** : 270-2, Hunshin-Dong, Sangju-City,  
Kyungsangbuk-Do, Korea  
**Attention** : Tae Moon, Choi / Q.A Dept, Deputy Manager

- **EUT Type :** 17" FLAT MONITOR
- **Model Number :** E17AF
- **FCC Identifier :** OMNE17AF
- **S/N :** N/A
- **FCC Rule Part(s) :** Part 15 Subpart B Unintentional Radiators
- **Test Procedure :** ANSI C63.4-1992
- **FCC Classification :** Part 15 Class B Unintentional Radiators  
Computing Device Peripheral(JBP)
- **Dates of Tests :** August 10, 2001
- **Place of Tests :** ETL Inc  
EMC Testing Lab (FCC Registration Number : 95422)  
584, Sangwhal-Ri, Kanam-Myun, Yoju-Kun,  
Kyounggi-Do, Korea  
Tel : (031) 885-0072 Fax : (031) 885-0074
- **Test Report No. :** E01.0811.FCC.328N

## 1. INTRODUCTION

---

The measurement test for radiated and conducted emission test were conducted at the open area test site of E-RAE Testing Laboratory Inc. facility located at 584, Sangwhal-ri, Ganam-myun, Youju-kun, Kyoungki-do, Korea. The site is constructed in conformance with the requirements of the ANSI C63.4-1992 and CISPR Publication 16. The ETL has site descriptions on file with the FCC for 3 and 10 meter site configurations. Detailed description of test facility was found to be in compliance with the requirements of Section 2.948 FCC Rules according to the ANSI C63.4-1992 and registered to the Federal Communications Commission(Registration Number : 95422 ).

The measurement procedure described in American National Standard for Method of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz (ANSI C.63.4-1992) was used in determining radiated and conducted emissions from the IMRI Co., Ltd.

Model : E17AF

## 2. PRODUCT INFORMATION

---

### 2.1 Equipment Description

The Equipment Under Test(EUT) is the IMRI Co., Ltd. 17" Flat CRT Monitor.

### 2.2 General Specification

|  |   |
|--|---|
| ● Chassis Type                               | : Plastic   |
| ● List of Each OSC. Or X-Tal. Freq. (>=1MHz) | : X-TAL – 12MHz<br>: WT62P1 - WELTREND<br>: TDA9109 - ST<br>: TDA9210 – ST                          |
| ● Chipset Brand & Part No.                   | : MTV030N08 – MYSON<br>: KA3842B – SAMSUNG<br>: TDA8172 - ST<br>: TDA9535 - ST                      |
| ● Number of Layers                           | : Main board – 1Layers, CRT board – 1 Layers<br>: Control board – 1Layers, LED Board – 1Layers      |
| ● Active Display Area(4:#Ratio)              | : Horizontal : 300mm ± 5mm<br>: Vertical : 225mm ± 5mm  |
| ● Scanning Frequency                         | : Horizontal : 30KHz to 70KHz<br>: Vertical : 50Hz to 160Hz   |
| ● Maximum Resolution                         | : Horizontal : 1280Dots<br>: Vertical : 1024Dots  |
| ● Input Video Signal                         | : Analogue 0.714 Vp-p Positive at 75  |
| ● Input Sync signal                          | : Separate Sync : TTL Level Positive / Negative<br>: Composite Sync : TTL Level Positive / Negative |
| ● Maximum Pixel Clock                        | : 110MHz (-3dB)   |
| ● Input Voltage                              | : 100V ~ 240V AC, 60/50Hz (PFC200V ~ 240V)  |
| ● Power Consumption                          | : 100Watts (Max)  |

### **3. DESCRIPTION OF TESTS**

---

#### **3.1 Conducted Emission Measurement**

Conducted emissions measurements were made in accordance with § 12.2 in ANSI C63.4-1992 "Measurement of Information Technology Equipment ". The measurement were performed over the frequency range of 0.15MHz to 30MHz using a 50 /50uH LISN as the input transducer to a Spectrum Analyzer or a Field Intensity Meter. The measurements were made with the detector set for "Peak" amplitude within a bandwidth of 10KHz or for "quasi-peak" within a bandwidth of 9KHz.

- Procedure of Test

The line-conducted facility is located inside a shielded room 1m X 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 1.5m away from the side wall of the shielded room. Two EMCO 3825/2 LISN are bonded to the shielded room. The EUT is powered from the EMCO LISN and the support equipment is powered from the another EMCO LISN. Power to the LISN are filtered by a noise cut power line filters. All electrical cables are shielded by braided tinned steel tubing with inner  $\phi$  1.2cm. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and these supply lines will be connected to the EMCO LISN. Non-inductive bundling to a 1m length shortened all interconnecting cables more than 1m. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the R3261A Spectrum Analyzer to determine the frequency producing the max. emission from the EUT. The frequency producing the max. level was reexamined using to set Quasi-Peak mode by manual, after scanned by automatic Peak mode from 0.15 to 30MHz. The bandwidth of the Spectrum Analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission.

### 3. DESCRIPTION OF TESTS

---

#### 3.2 Radiated Emission Measurement

Radiated emission measurements were in accordance with § 12.2 in ANSI C63.4-1992 "Measurement of Information Technology Equipment ". The measurements were performed over the frequency range of 30MHz to 1GHz using antenna as the input transducer to a Spectrum analyzer or a Field Intensity Meter. The measurements were made with the detector set for "Quasi-peak" within a bandwidth of 120KHz.

- Procedure of Test

Preliminary measurements were made at 3 meter using broadband antennas, and spectrum analyzer to determined the frequency producing the max. emission in shielded room. Appropriate precaution was taken to ensure that all emission from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth and height with respect to the antenna were noted for each frequency found. The spectrum was scanned from 30 to 1000MHz using SchwarzBeck Log-Bicon antenna. Above 1GHz, linearly polarized double ridge horn antennas were used. Final measurements were made open site at 10-meters. The test equipment was placed on a wooden turn-table. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. Each frequency found during pre-scan measurements was re-examined by manual. The detector function was set to CISPR Quasi-peak mode and the bandwidth of the receiver was set to 120kHz or 1MHz depending on the frequency of type of signal. The EUT, support equipment and interconnecting cables were re-configured to the set-up producing the max. emission for the frequency and were placed on top of a 0.8-meter high nonmetallic 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were re-arranged and manipulated to maximize each emission. The turntable containing the system was rotated; the antenna height was varied 1 to 4 meters and stopped at the azimuth or height producing the max. emission. Each emission was maximized by: varying the mode of operation to the EUT and/or support equipment and changing the polarity of the antenna, whichever determined the worst-case emission. Photographs of the worst-case emission can be seen in Photographs of the worst-case emission test setup can be seen in Appendix B.

## 4. TEST CONDITION

---

### 4.1 Test Configuration

The device was configured for testing in a typical fashion (as a customer would normally use it). During the tests, the following conditions and configurations were used.

### 4.2 EUT operation

The EUT was operated with "H" pattern display for the following operating conditions. The worst case emission was 1024x768 85Hz resolution.

| Resolution  | H/V Frequency     |                 |
|-------------|-------------------|-----------------|
| 640 X 480   | 43.269KHz / 85Hz  |                 |
| 800 X 600   | 46.875KHz / 75Hz  |                 |
| 1024 X 768  | 60KHz / 75Hz      |                 |
| 1024 X 768  | 68.677KHz / 85Hz  | Worst case mode |
| 1280 X 1024 | 63.98 kHz / 60 Hz |                 |

\* EMI TEST Pattern " H " Pattern Display

### 4.3 Support Equipment Used

Following peripheral devices and interface cables were connected during the measurement:

#### EUT – 17" MONITOR

|                   |  |
|-------------------|--|
| FCC ID            | : OMNE17AF                                     |
| Model Name        | : E17AF  |
| Serial No.        | : N/A  |
| Manufacturer      | : IMRI Co., Ltd.                               |
| Power Supply Type | : Switching                                    |
| Power Cord        | : Non-shielded, Detachable: 1.2m               |
| Data Cable        | : 1.5 m Shielded and ferrite core on RGB Cable |

#### Support Unit 1 - Personal computer (COMPAQ)

|                   |   |
|-------------------|---|
| FCC ID            | : N/A (DoC)   |
| Model Name        | : DESKPRO   |
| Serial No.        | : 7039JC8F0022  |
| Manufacturer      | : COMPAQ  |
| Power Supply Type | : Switching   |
| Power Cord        | : Non-Shielded, Detachable, 1.2m  |
| Port              | : Parallel: 1, USB: 2, Keyboard: 1, Mouse: 1, RS-232: 2, Video: 2, Speaker: 2, MIC: 1 |

#### Support Unit 2 - Keyboard (COMPAQ)

|                   |                  |
|-------------------|------------------|
| FCC ID            | : N/A(DOC)       |
| Model Name        | : KB-9963        |
| Serial No.        | : B26960FBUJV046 |
| Manufacturer      | : COMPAQ         |
| Power Supply Type | : N/A            |
| Power Cord        | : N/A            |

Data Cable : Shielded, 1.2m

#### 4. TEST CONDITION

---

Support Unit 3 - MOUSE (LOGITECH)

|                   |                   |
|-------------------|-------------------|
| FCC ID            | : JNZ201213       |
| Model Name        | : M-S48a          |
| Serial No.        | : F22420C5BJQ07ZG |
| Manufacturer      | : LOGITECH        |
| Power Supply Type | : N/A             |
| Power Cord        | : N/A             |
| Data Cable        | : Shielded, 1.2m  |

Support Unit 4 - SPEAKER (PC BANK)

|                   |                                     |
|-------------------|-------------------------------------|
| FCC ID            | : N/A                               |
| Model Name        | : N/A                               |
| Serial No.        | : N/A                               |
| Manufacturer      | : PC BANK                           |
| Power Supply Type | : Linear                            |
| Power Cord        | : Non-Shielded, Un-Detachable, 1.0m |
| Data Cable        | : Audio Cable, 0.5m                 |

Support Unit 5 – Serial Mouse (PETRA)

|                   |                     |
|-------------------|---------------------|
| FCC ID            | : JKGMUS5S01        |
| Model Name        | : MUS5S             |
| Serial No.        | : E183027           |
| Manufacturer      | : PETRA             |
| Power Supply Type | : N/A               |
| Power Cord        | : N/A               |
| Data Cable        | : Un-Shielded, 1.2m |

Support Unit 6 – Printer (H.P)

|                   |                                   |
|-------------------|-----------------------------------|
| FCC ID            | : B94C2164X                       |
| Model Name        | : C4562B                          |
| Serial No.        | : TH9411434G                      |
| Manufacturer      | : H.P                             |
| Power Supply Type | : DC24V From Adapter (C2182A/H.P) |
| Power Cord        | : Non-Shielded                    |
| Data Cable        | : Shielded, 1.5m                  |

## 5. TEST RESULTS

---

### 5.1 Summary of Test Results

This equipment, 17" flat CRT monitor, has various operating mode as described in the operating condition. The Conducted data and radiated emission test data were obtained in the worst case operating mode. The measurement results were obtained with the EUT tested in the conditions described in this report. Detailed measurement data and plots showing the maximum emission of the EUT are reported.

| Test Rule Parts | Measurement Required            | Result              |
|-----------------|---------------------------------|---------------------|
| 15.107 (e)      | Conducted Emissions Measurement | Passed by – 8.14 dB |
| 15.109(e)       | Radiated Emissions Measurement  | Passed by – 3.59 dB |

The data collected shows that the IMRI Co., Ltd. 17" MONITOR, E17AF complies with technical requirements of above rules part 15.107 and 15.109 Class B limits.

The equipment is not modified anything, mechanical or circuits to improve EMI status during a measurement. No EMI suppression device(s) was added and/or modified during testing.

## 5. TEST RESULTS

### 5.2 Conducted Emissions Measurement

|                       |   |
|-----------------------|---|
| EUT                   | 17" FLAT MONITOR / E17AF(SN:N/A)              |
| Limit apply to        | 15.107(e) : CISPR Pub.22(1997) Class B        |
| Test Date             | August 10, 2001                               |
| Operating Condition   | " H " Pattern display with 1024x768 85Hz mode |
| Environment Condition | Humidity Level : 41 %RH, Temperature : 23     |
| Result                | Passed by – 8.14 dB                           |

#### Conducted Emission Test Data

The following table shows the highest levels of conducted emissions on both polarization of live and neutral line.

Detector mode : CISPR Quasi-Peak mode ( 6dB Bandwidth : 9 KHz )

| Frequency<br>[MHz] | Reading<br>[dB $\mu$ V] |         | Phase<br>(*H/**N) | Limit<br>[dB $\mu$ V] |         | Margin<br>[dB] |         |
|--------------------|-------------------------|---------|-------------------|-----------------------|---------|----------------|---------|
|                    | Quasi-peak              | Average |                   | Quasi-peak            | Average | Q.Pk           | Average |
| 0.158              | 57.42                   | 16.75   | N                 | 65.56                 | 55.56   | 8.14           | 38.81   |
| 0.167              | 56.40                   | 20.15   | N                 | 65.10                 | 55.10   | 8.70           | 34.95   |
| 0.191              | 45.67                   | 36.97   | N                 | 63.99                 | 53.99   | 18.32          | 17.02   |
| 0.247              | 50.25                   | 30.50   | N                 | 61.85                 | 51.85   | 11.60          | 21.35   |
| 0.473              | 37.90                   | -       | H                 | 56.46                 | 46.46   | 18.56          | -       |
| 0.680              | 35.67                   | -       | N                 | 56.0                  | 46.0    | 20.33          | -       |
| 1.910              | 34.72                   | -       | N                 |                       |         | 21.28          | -       |
| 10.82              | 47.15                   | -       | N                 | 60.0                  | 50.0    | 12.85          | -       |
| 17.57              | 46.20                   | -       | N                 |                       |         | 13.80          | -       |
| 28.51              | 43.67                   | -       | N                 |                       |         | 16.13          | -       |

#### NOTES :



1. \* H : HOT Line , \*\*N : Neutral Line
2. Margin value = Limit – Reading
3. Measurement were performed at the EUT AC Power Inlet in the frequency band of 150kHz~30MHz.
4. If the Reading Quasi-Peak value is bellow the Average Limit, Do not test Average Mode.



Test Engineer : C. S. Kim



## 5. TEST RESULTS

### Line: HOT Line



## 5. TEST RESULTS

### Line: Neutral Line



## 5. TEST RESULTS

### 5.3 Radiated Emissions Measurement

|                       |   |
|-----------------------|---|
| EUT                   | 17" FLAT MONITOR / E17AF(SN:N/A)              |
| Limit apply to        | 15.109(e) : CISPR Pub.22(1997) Class B        |
| Test Date             | August 10, 2001                               |
| Operating Condition   | " H " Pattern display with 1024x768 85Hz mode |
| Environment Condition | Humidity Level : 41 %RH, Temperature : 23     |
| Result                | Passed by - 3.59dB                            |

### Radiated Emission Test Data

The following table shows the highest levels of radiated emissions on both polarization of horizontal and vertical.

Detector mode : CISPR Quasi-Peak mode ( 6dB Bandwidth : 120 kHz )

Measurement Distance : 10 meters

| Frequency [MHz] | Reading [dB $\mu$ V] | Polarization (*H/**V) | Ant. Factor [dB] | Cable Loss [dB] | Emission Level [dB $\mu$ V/m] | Limit [dB $\mu$ V/m] | Margin [dB] |
|-----------------|----------------------|-----------------------|------------------|-----------------|-------------------------------|----------------------|-------------|
| 47.31           | 11.66                | V                     | 13.02            | 1.70            | 26.38                         | 30.0                 | 3.62        |
| 113.57          | 5.53                 | V                     | 10.37            | 2.60            | 18.50                         | 30.0                 | 11.50       |
| 160.79          | 5.95                 | V                     | 12.80            | 3.20            | 21.95                         | 30.0                 | 8.05        |
| 170.33          | 8.09                 | V                     | 11.99            | 3.50            | 23.58                         | 30.0                 | 6.42        |
| 189.26          | 7.92                 | H                     | 10.88            | 3.70            | 22.50                         | 30.0                 | 7.50        |
| 198.74          | 7.15                 | H                     | 9.93             | 3.80            | 20.88                         | 30.0                 | 9.13        |
| 208.18          | 13.00                | H                     | 9.51             | 3.90            | 26.41                         | 30.0                 | 3.59        |
| 217.66          | 12.80                | H                     | 9.37             | 4.00            | 26.17                         | 30.0                 | 3.83        |
| 227.11          | 7.22                 | H                     | 10.00            | 4.00            | 21.22                         | 30.0                 | 8.78        |
| 255.49          | 7.78                 | H                     | 11.38            | 4.20            | 23.36                         | 37.0                 | 13.64       |
| 283.85          | 7.92                 | H                     | 12.21            | 4.50            | 24.63                         | 37.0                 | 12.38       |
| 350.13          | 1.85                 | H                     | 13.94            | 4.90            | 20.69                         | 37.0                 | 16.31       |

#### NOTES :

1. \* H : Horizontal polarization , \*\* V : Vertical polarization
2. Emission Level = Reading + Antenna factor + Cable loss
3. Margin value = Limit - Emission Level
4. The measurement was performed for the frequency range 30MHz ~ 1000MHz.



Test Engineer : C. S. Kim

## 6. SAMPLE CALCULATION

---

### Sample Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor.

The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF$$

where FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor

$$dB(\mu V/m) = 20 \log_{10} (\mu V / m) : \text{Equation 1}$$

$$dB\mu V = dBm + 107 : \text{Equation 2}$$

Example 1 : @ 0.158 MHz

$$\text{Class B Limit} = 1896 \mu V = 65.56 \text{ dBuV}$$

$$\text{Reading} = 57.42 \text{ dBuV}$$

$$\text{Convert to } \mu V = 743 \mu V$$

$$\text{Margin} = 57.42 - 65.56 = -8.14$$

= -8.14 dB below Limit

Example 2 : @208.18 MHz

$$\text{Class B Limit} = 31.7 \mu V = 30.0 \text{ dBuV/m}$$

$$\text{Reading} = 13.0 \text{ dBuV}$$

$$\text{Antenna Factor + Cable Loss} = 13.41 \text{ dB}$$

$$\text{Total} = 26.41 \text{ dBuV/m}$$

$$\text{Margin} = 26.41 - 30.0 = -3.59$$

= -3.59 dB below Limit

## 7. TEST EQUIPMENT LIST

---

### List of Test Equipments Used for Measurements

| Test Equipment                      |                        | Model      | Mfg.         | Serial No.  | Cal. Due Date |
|-------------------------------------|------------------------|------------|--------------|-------------|---------------|
| <input checked="" type="checkbox"/> | Spectrum Analyzer      | R3261A     | Advantest    | 21720033    | 01-10-08      |
| <input type="checkbox"/>            | Spectrum Analyzer      | ESA-L1500A | H.P          | US37360920  | 01-10-20      |
| <input checked="" type="checkbox"/> | Receiver               | ESVS 10    | R & S        | 835165/001  | 02-04-06      |
| <input checked="" type="checkbox"/> | Spectrum Analyzer      | R3265A     | Advantest    | 45060321    | 02-02-28      |
| <input checked="" type="checkbox"/> | Preamplifier           | HP8447D    | HP           | 2944A07626  | 02-01-10      |
| <input type="checkbox"/>            | Preamplifier           | HP 8347A   | HP           | 2834A00544  | 01-05-23      |
| <input checked="" type="checkbox"/> | TriLog Antenna         | VULB9160   | Schwarz Beck | 3082        | 02-05-08      |
| <input type="checkbox"/>            | LogBicon               | VULB9165   | Schwarz Beck | 2023        | 02-05-08      |
| <input type="checkbox"/>            | Dipole Antenna         | VHAP       | Schwarz Beck | 964         | 02-05-03      |
| <input type="checkbox"/>            | Dipole Antenna         | VHAP       | Schwarz Beck | 965         | 02-05-03      |
| <input type="checkbox"/>            | Dipole Antenna         | UHAP       | Schwarz Beck | 949         | 02-05-03      |
| <input type="checkbox"/>            | Dipole Antenna         | UHAP       | Schwarz Beck | 950         | 02-05-03      |
| <input type="checkbox"/>            | Double Ridged Horn     | 3115       | EMCO         | 9809-2334   | 01-09-20      |
| <input type="checkbox"/>            | Magnetic Loop Antenna  | 6502       | EMCO         | 9810-2111   | 01-12-11      |
| <input checked="" type="checkbox"/> | Turn-Table             | DETT-03    | Daeil EMC    | -           | N/A           |
| <input checked="" type="checkbox"/> | Antenna Master         | DEAM-03    | Daeil EMC    | -           | N/A           |
| <input checked="" type="checkbox"/> | Plotter                | 7440A      | H.P          | 2725A 75722 | N/A           |
| <input checked="" type="checkbox"/> | Chamber                | DTEC01     | DAETONG      | -           | N/A           |
| <input type="checkbox"/>            | Impedance Matching Pad | 6001.01.A  | SUNNER       | 3252        | 01-09-22      |
| <input checked="" type="checkbox"/> | Thermo Hygograph       | 3-3122     | ISUZU        | 3312201     | 01-12-20      |
| <input checked="" type="checkbox"/> | BaroMeter              | -          | Regulus      | -           | -             |