



FCC TEST REPORT

According to

FCC 47 CFR PART 22 SUBPART H AND PART 24 SUBPART E

Applicant	: MAXWEST TELECOM
Address	: 11037 warner ave #201 fountain valley, ca, 92708 USA
Manufacturer	: MAXWEST TELECOM
Address	: 11037 warner ave #201 fountain valley, ca, 92708 USA
Equipment	: MOBILE PHONE
Model No.	: ASTRO 4
Trade Name	: MAXWEST
FCC ID	: ONGASTRO4

I HEREBY CERTIFY THAT :

The measurements shown in this test report were made in accordance with the procedures given in **ANSI C63.4** The equipment was **passed** the test performed according to **FCC Rules and Regulations Part 15 Subpart C (2010)**.

The test was carried out on Oct 31, 2014 at **Cerpass Technology (Suzhou) Co.,Ltd**

- The test result refers exclusively to the test presented test model / sample.
- Without written approval of **Cerpass Technology Corp.** the test report shall not be reproduced except in full.
- The test report must not be used by the clients to claim product certification approval by **NVLAP** or any agency of the Government.



Table of Contents

1. Report of Measurements and Examinations	6
2. Test Configuration of Equipment under Test	7
2.1. Feature of Equipment under Test	7
2.2. Test Manner	8
2.3. Description of Test System	8
2.4. General Information of Test	9
2.5. Measurement Uncertainty	9
3. Test of Conducted Emission	10
3.1. Test Limit.....	10
3.2. Test Procedures.....	10
3.3. Typical Test Setup.....	11
3.4. Measurement Equipment	11
3.5. Test Result and Data	12
4. FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT	14
4.1. Test Limit.....	14
4.2. Test Procedures.....	14
4.3. Typical Test Setup.....	15
4.4. Measurement Equipment	16
4.5. Test Result and Data	17
5. Occupied Bandwidth.....	53
5.1. Test Limit.....	53
5.2. Test Procedures.....	53
5.3. Test Setup Layout	53
5.4. Measurement Equipment	53
5.5. Test Result and Data	54
6. Maximum Peak Output Power	66
6.1. Test Limit.....	66
6.2. Test Procedure	66
6.3. Test Setup Layout	66
6.4. Measurement Equipment	66
6.5. Test Result and Data	67
7. ERP & EIRP MEASUREMENT.....	79
7.1. Test Limit.....	79
7.2. Test Procedure	79
7.3. Test Setup Layout	80
7.4. Measurement Equipment	81
7.5. Test Result and Data	82
8. OUT OF BAND EMISSION AT ANTENNA TERMINALS.....	85
8.1. Test Limit.....	85
8.2. Test Procedure	85
8.3. Test Setup Layout	85
8.4. Measurement Equipment	85
8.5. Test Result and Data	86



9. FREQUENCY STABILITY V.S. TEMPERATURE MEASUREMENT	104
9.1. Test Limit.....	104
9.2. Test Procedure	104
9.3. Test Setup Layout.....	104
9.4. Measurement Equipment	104
9.5. Test Result and Data	105
10. FREQUENCY STABILITY V.S. VOLTAGE MEASUREMENT	108
10.1. Test Limit.....	108
10.2. Test Procedure	108
10.3. Test Setup Layout.....	108
10.4. Measurement Equipment	108
10.5. Test Result and Data	109



Document history

Attachment No.	Date	Description



FCC TEST REPORT

according to

FCC 47 CFR PART 22 SUBPART H AND PART 24 SUBPART E

Applicant	: MAXWEST TELECOM
Address	: 11037 warner ave #201 fountain valley, ca, 92708 USA
Manufacturer	: MAXWEST TELECOM
Address	: 11037 warner ave #201 fountain valley, ca, 92708 USA
Equipment	: MOBILE PHONE
Model No.	: ASTRO 4
Trade Name	: MAXWEST
FCC ID	: ONGASTRO4

I HEREBY CERTIFY THAT :

The measurements shown in this test report were made in accordance with the procedures given in **ANSI C63.4 – 2009** and the energy emitted by this equipment was **passed** **FCC Rule FCC PART 22 Subpart H and PART 24 Subpart E** in both radiated and conducted emission limits.

Testing was carried out on Oct 31, 2014 at **Cerpass Technology Corp.**

Signature

Miro Chueh/ Technical director



1. Report of Measurements and Examinations

FCC 47 CFR PART 22 SUBPART H AND PART 24 SUBPART E ANSI C63.4: 2003		
Test Parameter	Test Performed	Remark
Conducted Emission	YES	PASS
Field Strength of Spurious Radiation Measurement	YES	PASS
Occupied Bandwidth	YES	PASS
Maximum Peak Output Power	YES	PASS
ERP & EIRP Measurement	YES	PASS
Out of Band Emission at Antenna Terminals	YES	PASS
Frequency Stability V.S. Temperature Measurement	YES	PASS
Requency Stability V.S. Voltage Measurement	YES	PASS



2. Test Configuration of Equipment under Test

2.1. Feature of Equipment under Test

MOBILE PHONE	Model No:	ASTRO 4
Operation Frequency Range	WCDMA/HSUPA/HSDPA BAND5: 826.4 – 846.6 MHz WCDMA/HSUPA/HSDPA BAND2: 1852.4 – 1907.6 MHz	
Release version	HSDPA: Rel 5 HSUPA: Rel 6	



2.2. Test Manner

Test Manner	
a	During testing, the interface cables and equipment positions were varied according to 47 CFR, Part 2, PART 22 Subpart H and PART 24 Subpart E.
b	Adjust the EUT at the test mode and the test channel. Then test.
The test modes:	
The EUT had been tested under operating condition. After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz and power line conducted emissions below 30MHz, which worst case was in normal link mode only. EUT staying in continuous transmitting mode was programmed. WCDMA 850: Channel Low (CH4132), Channel Mid (CH4183) and Channel High (CH4233) were chosen for full testing. WCDMA1900: Channel Low (CH9262), Channel Mid (CH9400) and Channel High (CH9538) were chosen for full testing. HSUPA 850: Channel Low (CH4132), Channel Mid (CH4183) and Channel High (CH4233) were chosen for full testing. HSUPA 1900: Channel Low (CH9262), Channel Mid (CH9400) and Channel High (CH9538) were chosen for full testing. HSDPA 850: Channel Low (CH4132), Channel Mid (CH4183) and Channel High (CH4233) were chosen for full testing. HSDPA 1900: Channel Low (CH9262), Channel Mid (CH9400) and Channel High (CH9538) were chosen for full testing.	

2.3. Description of Test System

No.	Device	Manufacturer	Model No.	Description
1	N/A	N/A	N/A	N/A

**2.4. General Information of Test**

Test Site:	Cerpass Technology Corp.
Performand Location :	No.66,Tangzhuang Road, Suzhou Industrial Park, Jiangsu 215006, China
NVLAP LAB Code :	200814-0
FCC Registration Number :	916572, 331395
IC Registration Number :	7290A-1, 7290A-2
VCCI Registration Number :	T-1945 for Telecommunication Test C-2919 for Conducted emission test R-2670 for Radiated emission test below 1GHz G-227 for Radiated emission test above 1GHz

Laboratory accreditation

**2.5. Measurement Uncertainty**

Measurement Item	Measurement Frequency	Polarization	Uncertainty
Conducted Emission	9 kHz ~ 30 MHz	LINE/NEUTRAL	±2.71 dB
Radiated Emission	30 MHz ~ 25GHz	Vertical	±4.11 dB
		Horizontal	±4.10 dB
Occupied Bandwidth	---	---	±7500 Hz
Maximum Peak Output Power	---	---	±1.4 dB
Band Edges	---	---	±2.2 dB
Power Spectral Density	---	---	±2.2 dB



3. Test of Conducted Emission

3.1. Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz on the 120 VAC power and return leads of the EUT according to the methods defined in ANSI C63.4-2003 Section 3.1. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in section 2.2. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.


Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50

*Decreases with the logarithm of the frequency.

3.2. Test Procedures

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

3.3. Typical Test Setup




3.4. Measurement Equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date.
Test Receiver	R&S	ESCI	100565	2014.03.24	2015.03.23
AMN	R&S	ESH2-Z5	100182	2014.09.04	2015.09.03
Two-Line V-Network	R&S	ENV216	100325	2013.12.04	2014.12.03
ISN	FCC	FCC-TLISN-T2-02	20379	2014.03.24	2015.03.23
ISN	FCC	FCC-TLISN-T4-02	20380	2014.03.24	2015.03.23
ISN	FCC	FCC-TLISN-T8-02	20381	2014.03.24	2015.03.23
ISN	TESEQ	ISN ST08	30175	2014.03.24	2015.03.23
Current Probe	R&S	EZ-17	100303	2014.04.04	2015.04.03
Passive Voltage Probe	R&S	ESH2-Z3	100026	2014.03.24	2015.03.23
Pulse Limiter	R&S	ESH3-Z2	100529	2014.03.24	2015.03.23
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-004	2014.03.31	2015.03.30



3.5. Test Result and Data

Test Mode :	Normal Link		
AC Power :	AC 120V/60Hz	Phase :	LINE
Temperature :	24°C	Humidity :	42%
Pressure(mbar) :	1002	Date :	2014/10/12




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.2100	10.12	27.29	37.41	63.20	-25.79	QP
2	0.2100	10.12	19.27	29.39	53.20	-23.81	AVG
3	0.2819	10.14	25.50	35.64	60.76	-25.12	QP
4	0.2819	10.14	21.89	32.03	50.76	-18.73	AVG
5	0.5660	10.16	22.04	32.20	56.00	-23.80	QP
6	0.5660	10.16	21.25	31.41	46.00	-14.59	AVG
7	1.4819	10.16	20.66	30.82	56.00	-25.18	QP
8	1.4819	10.16	19.88	30.04	46.00	-15.96	AVG
9	2.1900	10.17	20.69	30.86	56.00	-25.14	QP
10	2.1900	10.17	16.30	26.47	46.00	-19.53	AVG
11	5.7140	10.25	27.99	38.24	60.00	-21.76	QP
12	5.7140	10.25	22.28	32.53	50.00	-17.47	AVG

Note: Measurement Level = Reading Level + Correct Factor



Test Mode :	Normal Link		
AC Power :	AC 120V/60Hz	Phase :	NEUTRAL
Temperature :	24°C	Humidity :	42%
Pressure(mbar) :	1002	Date :	2014/10/12



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.2100	10.13	27.91	38.04	63.20	-25.16	QP
2	0.2100	10.13	20.45	30.58	53.20	-22.62	AVG
3	0.2819	10.14	23.58	33.72	60.76	-27.04	QP
4	0.2819	10.14	19.66	29.80	50.76	-20.96	AVG
5	0.5660	10.15	21.15	31.30	56.00	-24.70	QP
6	0.5660	10.15	20.54	30.69	46.00	-15.31	AVG
7	1.0580	10.18	20.86	31.04	56.00	-24.96	QP
8	1.0580	10.18	20.31	30.49	46.00	-15.51	AVG
9	1.2700	10.18	22.32	32.50	56.00	-23.50	QP
10	1.2700	10.18	21.34	31.52	46.00	-14.48	AVG
11	5.7140	10.26	28.21	38.47	60.00	-21.53	QP
12	5.7140	10.26	22.06	32.32	50.00	-17.68	AVG

Note: Measurement Level = Reading Level + Correct Factor



4. FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT

4.1. Test Limit

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10\log(P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

4.2. Test Procedures

Final radiation measurements were made on a three-meter, Semi Anechoic Chamber. The EUT system was placed on a nonconductive turntable which is 0.8 meters height, top surface 1.0 x 1.5 meter. The spectrum was examined from 250 MHz to 2.5 GHz in order to cover the whole spectrum below 10th harmonic which could generate from the EUT. During the test, EUT was set to transmit continuously & Measurements spectrum range from 30 MHz to 26.5 GHz is investigated. For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, and then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements. A nonconductive material surrounded the EUT to supporting the EUT for standing on three orthogonal planes. At each condition, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters to find the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarization.

For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

Appropriate preamplifiers were used for improving sensitivity and precautions were taken to avoid

overloading or desensitizing the spectrum analyzer. No post – detector video filters were used in the test. The spectrum analyzer's 6 dB bandwidth was set to 1 MHz, and the analyzer was operated in the peak detection mode, for frequencies both below and up 1 GHz. The average levels were obtained by subtracting the duty cycle correction factor from the peak readings.

The following procedures were used to convert the emission levels measured in decibels



referenced to 1 microvolt (dBuV) into field intensity in micro volts pre meter (uV/m).

The actual field intensity in decibels referenced to 1 microvolt in to field intensity in micro volts per meter (dBuV/m). The actual field intensity in decibels referenced to 1 microvolt per meter (dBuV/m) is determined by algebraically adding the measured reading in dBuV, the antenna factor (dB), and cable loss (dB) and Subtracting the gain of preamplifier (dB) is auto calculate in spectrum analyzer.

$$(1) \text{ Amplitude (dBuV/m)} = \text{FI (dBuV)} + \text{AF (dB)} + \text{CL (dB)} - \text{Gain (dB)}$$

FI= Reading of the field intensity.

AF= Antenna factor.

CL= Cable loss.

P.S Amplitude is auto calculate in spectrum analyzer.


$$(2) \text{ Actual Amplitude (dBuV/m)} = \text{Amplitude (dBuV)} - \text{Dis (dB)}$$

The FCC specified emission limits were calculated according the EUT operating frequency and by following linear interpolation equations:

(a) For fundamental frequency : Transmitter Output < +30dBm

(b) For spurious frequency : Spurious emission limits = fundamental emission limit /10

4.3. Typical Test Setup



**4.4. Measurement Equipment**

Instrument	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date.
EMI Test Receiver	R&S	ESCI	100563	2014.02.10	2015.02.09
H64 Preamplifier	HP	8447F	3113A05582	2014.03.24	2015.03.23
Preamplifier	Agilent	8449B	3008A02342	2014.03.24	2015.03.23
Bilog Antenna	Sunol Science	JB1	A072414-2	2014.08.05	2015.08.04
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	9120D-619	2014.05.24	2015.05.23
Broad-Band Horn Antenna	Schwarzbeck	BBHA9170	9170-348	2013.11.04	2014.11.03
Spectrum Analyzer	R&S	FSP40	100324	2014.03.23	2015.03.24
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-002	2014.03.31	2015.03.30

**4.5. Test Result and Data****Radiated Spurious Emission Measurement Result / Under 1GHz:**

Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : WCDMA 850/ CH 4132

Frequency (MHz)	Antenna Polarization	Antenna Terminals level (dBm)	Substitution Antenna Gain (dBd)	Emission level (dBm)	Limit (dBm)	Margin (dB)
34.27	V	-15.36	-11.31	-26.67	-13.00	-13.67
117.31	V	-14.47	-13.53	-28.00	-13.00	-15.00
117.51	V	-15.56	-13.61	-29.17	-13.00	-16.17
125.87	V	-16.41	-14.45	-30.86	-13.00	-17.86
132.61	V	-16.42	-14.51	-30.93	-13.00	-17.93
826.21	V	-30.54	1.25	-29.29	-13.00	-16.29
73.91	H	-14.56	-16.34	-30.90	-13.00	-17.90
86.61	H	-14.64	-15.35	-29.99	-13.00	-16.99
114.34	H	-15.21	-14.37	-29.58	-13.00	-16.58
126.56	H	-14.47	-14.21	-28.68	-13.00	-15.68
316.84	H	-18.45	-9.34	-27.79	-13.00	-14.79
896.61	H	-24.19	-2.13	-26.32	-13.00	-13.32



Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : WCDMA 850/ CH 4183

Frequency	Antenna	Antenna	Substitution	Emission level	Limit	Margin
(MHz)	Polarization	Terminals level	Antenna Gain	(dBm)	(dBm)	(dB)
		(dBm)	(dBd)			
41.24	V	-16.34	-11.21	-27.55	-13.00	-14.55
114.54	V	-15.56	-13.56	-29.12	-13.00	-16.12
117.24	V	-14.43	-13.23	-27.66	-13.00	-14.66
135.25	V	-17.68	-14.43	-32.11	-13.00	-19.11
135.51	V	-15.54	-14.56	-30.10	-13.00	-17.10
836.51	V	-30.52	1.67	-28.85	-13.00	-15.85
73.61	H	-13.74	-16.52	-30.26	-13.00	-17.26
92.24	H	-15.41	-15.34	-30.75	-13.00	-17.75
116.51	H	-13.67	-14.31	-27.98	-13.00	-14.98
126.34	H	-14.51	-14.25	-28.76	-13.00	-15.76
319.81	H	-18.56	-9.45	-28.01	-13.00	-15.01
904.14	H	-23.62	-2.49	-26.11	-13.00	-13.11




Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : WCDMA 850/ CH 4233

Frequency	Antenna	Antenna	Substitution	Emission level	Limit	Margin
(MHz)	Polarization	Terminals level	Antenna Gain	(dBm)	(dBm)	(dB)
		(dBm)	(dBd)			
43.54	V	-14.42	-11.32	-25.74	-13.00	-12.74
115.67	V	-15.82	-13.52	-29.34	-13.00	-16.34
116.61	V	-13.62	-13.52	-27.14	-13.00	-14.14
134.18	V	-14.43	-14.25	-28.68	-13.00	-15.68
135.45	V	-15.52	-14.56	-30.08	-13.00	-17.08
836.67	V	-30.26	1.67	-28.59	-13.00	-15.59
78.51	H	-13.64	-16.58	-30.22	-13.00	-17.22
83.81	H	-12.69	-15.34	-28.03	-13.00	-15.03
115.42	H	-12.51	-14.34	-26.85	-13.00	-13.85
134.51	H	-13.59	-14.26	-27.85	-13.00	-14.85
315.46	H	-16.68	-9.58	-26.26	-13.00	-13.26
895.47	H	-27.69	-2.38	-30.07	-13.00	-17.07




Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : HSUPA 850/ CH 4132






Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : HSUPA 850 CH 4183





Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note: HSUPA 850/ CH 4233





Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : HSDPA 850 / CH 4132

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBd)	Emission level (dBm)	Limit (dBm)	Margin (dB)
35.43	V	-15.26	-11.29	-26.55	-13.00	-13.55
104.74	V	-15.37	-13.44	-28.81	-13.00	-15.81
114.61	V	-16.32	-13.78	-30.10	-13.00	-17.10
130.38	V	-15.69	-14.15	-29.84	-13.00	-16.84
135.72	V	-16.69	-14.47	-31.16	-13.00	-18.16
834.78	V	-28.49	1.87	-26.62	-13.00	-13.62
72.24	H	-14.39	-16.63	-31.02	-13.00	-18.02
85.71	H	-14.44	-15.27	-29.71	-13.00	-16.71
114.76	H	-15.62	-14.25	-29.87	-13.00	-16.87
125.51	H	-14.44	-14.15	-28.59	-13.00	-15.59
312.67	H	-20.79	-9.74	-30.53	-13.00	-17.53
894.64	H	-25.41	-2.44	-27.85	-13.00	-14.85



Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : HSDPA 850 / CH 4183

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBd)	Emission level (dBm)	Limit (dBm)	Margin (dB)
43.35	V	-15.41	-11.29	-26.70	-13.00	-13.70
105.65	V	-15.41	-13.44	-28.85	-13.00	-15.85
116.16	V	-14.49	-13.78	-28.27	-13.00	-15.27
125.88	V	-15.49	-14.15	-29.64	-13.00	-16.64
135.34	V	-13.52	-14.47	-27.99	-13.00	-14.99
826.11	V	-27.91	1.87	-26.04	-13.00	-13.04
72.48	H	-12.47	-16.63	-29.10	-13.00	-16.10
84.69	H	-14.51	-15.27	-29.78	-13.00	-16.78
105.37	H	-13.57	-14.25	-27.82	-13.00	-14.82
126.34	H	-15.81	-14.15	-29.96	-13.00	-16.96
324.45	H	-19.79	-9.74	-29.53	-13.00	-16.53
921.34	H	-24.04	-2.18	-26.22	-13.00	-13.22




Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : HSDPA 850 / CH 4233

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBd)	Emission level (dBm)	Limit (dBm)	Margin (dB)
42.34	V	-17.52	-11.29	-28.81	-13.00	-15.81
105.74	V	-16.62	-13.44	-30.06	-13.00	-17.06
127.04	V	-14.48	-13.78	-28.26	-13.00	-15.26
136.42	V	-16.57	-14.16	-30.73	-13.00	-17.73
135.75	V	-16.42	-14.47	-30.89	-13.00	-17.89
836.64	V	-29.69	1.87	-27.82	-13.00	-14.82
75.64	H	-12.32	-16.63	-28.95	-13.00	-15.95
85.46	H	-12.41	-15.27	-27.68	-13.00	-14.68
116.81	H	-13.38	-14.25	-27.63	-13.00	-14.63
125.48	H	-14.61	-14.15	-28.76	-13.00	-15.76
310.71	H	-18.39	-9.74	-28.13	-13.00	-15.13
901.49	H	-26.29	-2.44	-28.73	-13.00	-15.73




Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : WCDMA1900 /CH 9262






Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : WCDMA 1900/ CH 9400






Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : WCDMA 1900 /CH 9538






Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : HSUPA 1900/ CH 9262






Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : HSUPA 1900/ CH 9400





Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : HSUPA 1900/ CH 9538





Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : HSDPA 1900 / CH 9262

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBd)	Emission level (dBm)	Limit (dBm)	Margin (dB)
38.63	V	-16.87	-11.29	-28.16	-13.00	-15.16
105.84	V	-14.38	-13.44	-27.82	-13.00	-14.82
116.72	V	-13.49	-13.78	-27.27	-13.00	-14.27
135.24	V	-15.38	-14.15	-29.53	-13.00	-16.53
134.86	V	-14.52	-14.47	-28.99	-13.00	-15.99
825.51	V	-26.41	1.87	-24.54	-13.00	-11.54
75.61	H	-13.37	-16.63	-30.00	-13.00	-17.00
85.62	H	-12.63	-15.27	-27.90	-13.00	-14.90
105.85	H	-16.49	-14.25	-30.74	-13.00	-17.74
133.51	H	-14.48	-14.15	-28.63	-13.00	-15.63
311.49	H	-19.62	-9.74	-29.36	-13.00	-16.36
892.64	H	-23.57	-2.44	-26.01	-13.00	-13.01



Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : HSDPA 1900 / CH 9400

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBd)	Emission level (dBm)	Limit (dBm)	Margin (dB)
38.81	V	-15.42	-11.29	-26.71	-13.00	-13.71
106.24	V	-16.59	-11.47	-28.06	-13.00	-15.06
117.81	V	-15.58	-13.78	-29.36	-13.00	-16.36
125.27	V	-15.41	-14.15	-29.56	-13.00	-16.56
134.24	V	-15.63	-14.47	-30.10	-13.00	-17.10
824.24	V	-28.31	1.87	-26.44	-13.00	-13.44
72.52	H	-12.79	-16.63	-29.42	-13.00	-16.42
84.67	H	-13.87	-15.27	-29.14	-13.00	-16.14
116.67	H	-12.48	-14.25	-26.73	-13.00	-13.73
131.51	H	-14.47	-14.15	-28.62	-13.00	-15.62
310.67	H	-16.66	-9.74	-26.40	-13.00	-13.40
896.68	H	-23.61	-2.44	-26.05	-13.00	-13.05



Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : HSDPA 1900 / CH 9538

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBd)	Emission level (dBm)	Limit (dBm)	Margin (dB)
41.12	V	-16.57	-11.29	-27.86	-13.00	-14.86
105.64	V	-14.59	-11.47	-26.06	-13.00	-13.06
111.67	V	-15.72	-13.78	-29.50	-13.00	-16.50
125.82	V	-14.58	-14.15	-28.73	-13.00	-15.73
135.37	V	-15.68	-14.47	-30.15	-13.00	-17.15
836.67	V	-29.42	1.87	-27.55	-13.00	-14.55
79.67	H	-13.52	-16.63	-30.15	-13.00	-17.15
85.82	H	-13.47	-15.27	-28.74	-13.00	-15.74
105.95	H	-13.59	-14.25	-27.84	-13.00	-14.84
134.64	H	-14.66	-14.15	-28.81	-13.00	-15.81
315.82	H	-18.71	-9.74	-28.45	-13.00	-15.45
893.64	H	-24.25	-2.44	-26.69	-13.00	-13.69

**Above 1G:**


Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note :WCDMA 850 / CH 4132

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBd)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3192.25	V	-48.36	1.29	-47.07	-13.00	-34.07
3200.24	H	-50.39	1.31	-49.08	-13.00	-36.08

Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.




Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : WCDMA 850 /CH 4183



Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.



Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : WCDMA 850 / CH 4233



Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.



Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : HSUPA 850 / CH 4132

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBi)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3202.64	V	-50.16	1.29	-48.87	-13.00	-35.87
3203.34	H	-52.33	1.31	-51.02	-13.00	-38.02

Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.



Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : HSUPA 850 / CH 4183

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBi)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3201.64	V	-49.29	1.29	-48.00	-13.00	-35.00
3203.57	H	-53.53	1.31	-52.22	-13.00	-39.22

Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.



Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : HSUPA 850 / CH 4233

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBi)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3202.25	V	-50.28	1.29	-48.99	-13.00	-35.99
3204.51	H	-52.48	1.31	-51.17	-13.00	-38.17

Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.



Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : HSDPA 850 / CH 4132

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBi)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3202.54	V	-49.43	1.29	-48.14	-13.00	-35.14
3203.61	H	-50.51	1.31	-49.20	-13.00	-36.20

Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.



Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : HSDPA 850 / CH 4183

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBi)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3192.65	V	-49.79	1.29	-48.50	-13.00	-35.50
3203.67	H	-50.25	1.31	-48.94	-13.00	-35.94

Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.




Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : HSDPA 850 / CH 4233

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBi)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3203.41	V	-49.55	1.29	-48.26	-13.00	-35.26
3204.82	H	-51.26	1.31	-49.95	-13.00	-36.95

Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.




Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : WCDMA 1900 / CH 9262



Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.



Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : WCDMA1900 / CH9400



Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.



Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : WCDMA 1900 / CH 9538

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBi)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3196.92	V	-47.79	1.29	-46.50	-13.00	-33.50
3204.67	H	-50.29	1.31	-48.98	-13.00	-35.98

Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.



Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : HSUPA 1900 / CH 9262

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBi)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3202.34	V	-50.53	1.29	-49.24	-13.00	-36.24
3204.24	H	-54.41	1.31	-53.10	-13.00	-40.10

Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.



Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : HSUPA 1900 / CH 9400

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBi)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3198.61	V	-51.31	1.29	-50.02	-13.00	-37.02
3204.02	H	-52.52	1.31	-51.21	-13.00	-38.21

Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.



Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : HSUPA 1900 / CH 9538

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBi)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3191.53	V	-50.62	1.29	-49.33	-13.00	-36.33
3205.37	H	-53.52	1.31	-52.21	-13.00	-39.21

Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.



Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : HSDPA 1900 / CH 9262

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBi)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3199.61	V	-50.48	1.29	-49.19	-13.00	-36.19
3204.37	H	-50.62	1.31	-49.31	-13.00	-36.31

Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.



Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : HSDPA 1900 / CH 9400

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBi)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3199.75	V	-50.33	1.29	-49.04	-13.00	-36.04
3204.75	H	-51.63	1.31	-50.32	-13.00	-37.32

Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.



Engineer :Jing	Time : 2014-10-13
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : MOBILE PHONE	Note : HSDPA 1900 / CH 9538

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBi)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3192.24	V	-51.64	1.29	-50.35	-13.00	-37.35
3208.67	H	-52.49	1.31	-51.18	-13.00	-38.18

Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.



5. Occupied Bandwidth


5.1. Test Limit

According to §FCC 2.1049.

5.2. Test Procedures

The EUT's output RF connector was connected with a short cable to the spectrum analyzer, RBW was set to about 1% of emission BW, VBW is set to 3 times the RBW, -26dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.

5.3. Test Setup Layout



5.4. Measurement Equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	N9010A	Agilent	MY51350515	2014.09.29	2015.09.28
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-002	2014.03.31	2015.03.30




5.5. Test Result and Data

Test Item	Occupied Bandwidth
Test Mode	WCDMA 850
Test Date	2014-10-13


Channel No.	Frequency (MHz)	Measurement Level (kHz)
4132	826.4	4683
4183	836.6	4704
4233	846.6	4772

Channel 4132






Channel 4183



Channel 4233






Test Item	Occupied Bandwidth
Test Mode	WCDMA 1900
Test Date	2014-10-13


Channel No.	Frequency (MHz)	Measurement Level (kHz)
9262	1852.4	4773
9400	1880.0	4715
9538	1907.6	4747

Channel 9262






Channel 9400



Channel 9538






Test Item	Occupied Bandwidth
Test Mode	HSUPA 850
Test Date	2014-10-14


Channel No.	Frequency (MHz)	Measurement Level (kHz)
4132	826.4	4706
4183	836.6	4717
4233	846.6	4766

Channel 4132






Channel 4183



Channel 4233






Test Item	Occupied Bandwidth
Test Mode	HSUPA 1900
Test Date	2014-10-14


Channel No.	Frequency (MHz)	Measurement Level (kHz)
9262	1852.4	4750
9400	1880.0	4702
9538	1907.6	4744

Channel 9262






Channel 9400



Channel 9538






Test Item	Occupied Bandwidth
Test Mode	HSDPA 850
Test Date	2014-10-14


Channel No.	Frequency (MHz)	Measurement Level (kHz)
4132	826.4	4693
4183	836.6	4725
4233	846.6	4722

Channel 4132






Channel 4183



Channel 4233






Test Item	Occupied Bandwidth
Test Mode	HSDPA 1900
Test Date	2014-10-14


Channel No.	Frequency (MHz)	Measurement Level (kHz)
9262	1852.4	4719
9400	1880.0	4705
9538	1907.6	4720

Channel 9262






Channel 9400



Channel 9538





6. Maximum Peak Output Power


6.1. Test Limit

According to FCC §2.1046.

6.2. Test Procedure

- Place the EUT on a bench and set it in transmitting mode.
- Connect a low loss RF cable from the antenna port to a spectrum analyzer and CMU200 by a Directional Couple.
- EUT Communicate with CMU200, then selects a channel for testing.
- Add a correction factor to the display of spectrum, and then test.

6.3. Test Setup Layout



6.4. Measurement Equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	N9010A	Agilent	MY51350515	2014.09.29	2015.09.28
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-002	2014.03.31	2015.03.30
Universal Radio Communication Tester	R&S	CMU200	108823	2014.01.09	2015.01.08




6.5. Test Result and Data

Test Item	Maximum Peak Output Power
Test Mode	WCDMA 850
Test Date	2014-10-31


Channel No.	Frequency (MHz)	Average Power (dBm)	Peak Power (dBm)
4132	826.4	21.037	22.522
4183	836.6	20.759	22.375
4233	846.6	20.867	22.241

Channel 4132






Channel 4183



Channel 4233






Test Item	Maximum Peak Output Power
Test Mode	WCDMA 1900
Test Date	2014-10-31


Channel No.	Frequency (MHz)	Average Power (dBm)	Peak Power (dBm)
9262	1852.4	18.794	20.314
9400	1880.0	18.937	20.170
9538	1907.6	18.134	19.605

Channel 9262






Channel 9400



Channel 9538






Test Item	Maximum Peak Output Power
Test Mode	HSUPA 850
Test Date	2014-10-31


Channel No.	Frequency (MHz)	Average Power (dBm)	Peak Power (dBm)
4132	826.4	20.974	22.481
4183	836.6	20.768	22.323
4233	846.6	20.867	22.200

Channel 4132






Channel 4183



Channel 4233






Test Item	Maximum Peak Output Power
Test Mode	HSUPA 1900
Test Date	2014-10-31


Channel No.	Frequency (MHz)	Average Power (dBm)	Peak Power (dBm)
9262	1852.4	18.761	20.329
9400	1880.0	18.971	20.164
9538	1907.6	18.074	19.529

Channel 9262






Channel 9400



Channel 9538






Test Item	Maximum Peak Output Power
Test Mode	HSDPA 850
Test Date	2014-10-31


Channel No.	Frequency (MHz)	Average Power (dBm)	Peak Power (dBm)
4132	826.4	21.067	22.507
4183	836.6	20.718	22.336
4233	846.6	19.817	22.219

Channel 4132






Channel 4183



Channel 4233






Test Item	Maximum Peak Output Power
Test Mode	HSDPA 1900
Test Date	2014-10-31


Channel No.	Frequency (MHz)	Average Power (dBm)	Peak Power (dBm)
9262	1852.4	18.697	20.148
9400	1880.0	18.537	20.071
9538	1907.6	18.067	19.588

Channel 9262






Channel 9400



Channel 9538





7. ERP & EIRP MEASUREMENT

7.1. Test Limit

According to FCC §2.1046

FCC 22.913(a): The Effective Radiated Power (ERP) of mobile transmitters must not exceed 7 Watts.

FCC 24.232(b): The equivalent Isotropic Radiated Power (EIRP) must not exceed 2 Watts.

7.2. Test Procedure

The EUT was placed on a non-conductive turntable using a non-conductive support. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and EMI spectrum analyzer.

During the measurement of the EUT, the resolution bandwidth was set to 3MHz and the average bandwidth was set to 3MHz. The highest emission was recorded with the rotation of the turntable and the lowering of the test antenna. The reading was recorded and the field strength (E in dBuV/m) was calculated.

ERP in frequency band 824-849MHz, and EIRP in frequency band 1850 –1910MHz were measured using a substitution method. The EUT was replaced by half-wave dipole (824-849MHz) or horn antenna (1850-1910MHz) connected to a signal generator. The spectrum analyzer reading was recorded and ERP/EIRP was calculated as follows:


$$\text{ERP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBd)} - \text{Cable (dB)}$$

$$\text{EIRP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBi)} - \text{Cable (dB)}$$




7.3. Test Setup Layout

Below 1 GHz




Above 1 GHz





For Substituted Method Test Set-UP



7.4. Measurement Equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	N9010A	Agilent	MY51350515	2014.09.29	2015.09.28
H64 Amplifier	HP	8447F	3113A05582	2014.03.24	2015.03.23
Preamplifier	Agilent	8449B	ED-HE-EMI-077	2014.03.24	2015.03.23
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	9120D-619	2014.05.24	2015.05.23
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	9120D-618	2014.05.24	2015.05.23
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-002	2014.03.31	2015.03.30



7.5. Test Result and Data

WCDMA 850 TEST DATA

Channel	Frequency (MHz)	Antenna Pol.	Reading level (Peak) (dB)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
4132	826.4	V	22.58	1.01	23.59	38.5	-14.91
	826.4	H	21.77	0.96	22.73	38.5	-15.77
4183	836.6	V	21.49	1.77	23.26	38.5	-15.24
	836.6	H	21.38	1.46	22.84	38.5	-15.66
4233	846.6	V	21.74	1.85	23.59	38.5	-14.91
	846.6	H	21.31	1.54	22.85	38.5	-15.65

WCDMA1900 TEST DATA

Channel	Frequency (MHz)	Antenna Pol.	Reading level (Peak) (dB)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
9262	1852.4	V	20.32	2.34	22.66	33	-10.34
	1852.4	H	20.79	1.88	22.67	33	-10.33
9400	1880	V	20.43	2.12	22.55	33	-10.45
	1880	H	20.58	2.41	22.99	33	-10.01
9538	1907.6	V	20.64	2.34	22.98	33	-10.02
	1907.6	H	20.71	1.98	22.69	33	-10.31

**HSUPA 850 TEST DATA**

Channel	Frequency (MHz)	Antenna Pol.	Reading level (Peak) (dB)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
4132	826.4	V	21.86	1.01	22.87	38.5	-15.63
	826.4	H	21.43	0.96	22.39	38.5	-16.11
4183	836.6	V	21.77	1.77	23.54	38.5	-14.96
	836.6	H	21.19	1.46	22.65	38.5	-15.85
4233	846.6	V	21.15	1.85	23	38.5	-15.5
	846.6	H	21.52	1.54	23.06	38.5	-15.44

HSUPA 1900 TEST DATA

Channel	Frequency (MHz)	Antenna Pol.	Reading level (Peak) (dB)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
9262	1852.4	V	20.21	2.34	22.55	33	-10.45
	1852.4	H	20.25	1.88	22.13	33	-10.87
9400	1880	V	20.33	2.12	22.45	33	-10.55
	1880	H	19.91	2.41	22.32	33	-10.68
9538	1907.6	V	20.32	2.34	22.66	33	-10.34
	1907.6	H	20.14	1.98	22.12	33	-10.88

**HSDPA 850 TEST DATA**

Channel	Frequency (MHz)	Antenna Pol.	Reading level (Peak) (dB)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
4132	826.4	V	21.52	1.01	22.53	38.5	-15.97
	826.4	H	21.23	0.96	22.19	38.5	-16.31
4183	836.6	V	21.69	1.77	23.46	38.5	-15.04
	836.6	H	21.75	1.46	23.21	38.5	-15.29
4233	846.6	V	21.81	1.85	23.66	38.5	-14.84
	846.6	H	21.52	1.54	23.06	38.5	-15.44

HADPA 1900 TEST DATA

Channel	Frequency (MHz)	Antenna Pol.	Reading level (Peak) (dB)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
9262	1852.4	V	20.37	2.34	22.71	33	-10.29
	1852.4	H	20.58	1.88	22.46	33	-10.54
9400	1880	V	20.19	2.12	22.31	33	-10.69
	1880	H	19.83	2.41	22.24	33	-10.76
9538	1907.6	V	20.37	2.34	22.71	33	-10.29
	1907.6	H	20.63	1.98	22.61	33	-10.39



8. OUT OF BAND EMISSION AT ANTENNA TERMINALS

8.1. Test Limit

According to FCC §2.1051, FCC §22.917, FCC §24.238(a).

Out of Band Emissions: The mean power of emission must be attenuated below the mean power of the non-modulated carrier (P) on any frequency twice or more than twice the fundamental frequency by at least $43 + 10 \log P$ dB.

Mobile Emissions in Base Frequency Range: The mean power of any emissions appearing in the base station frequency range from cellular mobile transmitters operated must be attenuated to a level not exceed -80 dBm at the transmit antenna connector.

Band Edge Requirements: In the 1MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 1% of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the Out of band Emission.


8.2. Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 1MHz, sufficient scans were taken to show the out of band Emissions if any up to 10th harmonic.

For the out of band: Set the RBW, VBW = 1MHz, Start=30MHz, Stop= 10 th harmonic. Limit = -13dBm

Band Edge Requirements (824 MHz and 849 MHz /1850MHz and 1910MHz): In the 1 MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 1 percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions. Limit, -13dBm.

8.3. Test Setup Layout



8.4. Measurement Equipment


Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	Agilent	E4407B	MY44211883	2013.09.25	2014.09.25
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-002	2014.03.31	2015.03.30



8.5. Test Result and Data


Test Item	Conducted spurious emissions, 30MHz - 20GHz
Test Mode	WCDMA 850
Test Date	2014-10-13

Channel 4132






Channel 4183




Channel 4233






Test Item	Conducted spurious emissions, 30MHz - 20GHz
Test Mode	WCDMA 1900
Test Date	2014-10-13

Channel 9262






Channel 9400




Channel 9538






Test Item	Conducted spurious emissions, 30MHz - 20GHz
Test Mode	HSUPA 850
Test Date	2014-10-13

Channel 4132






Channel 4183




Channel 4233






Test Item	Conducted spurious emissions, 30MHz - 20GHz
Test Mode	HSUPA 1900
Test Date	2014-10-13

Channel 9262






Channel 9400




Channel 9538






Test Item	Conducted spurious emissions, 30MHz - 20GHz
Test Mode	HSDPA 850
Test Date	2014-10-14

Channel 4132






Channel 4183




Channel 4233






Test Item	Conducted spurious emissions, 30MHz - 20GHz
Test Mode	HSDPA 1900
Test Date	2014-10-14

Channel 9262






Channel 9400




Channel 9538






Test Item	Band Edge emissions
Test Mode	WCDMA 850
Test Date	2014-10-14

Channel 4132




Channel 4233






Test Item	Band Edge emissions
Test Mode	WCDMA 1900
Test Date	2014-10-14

Channel 9262




Channel 9538






Test Item	Band Edge emissions
Test Mode	HSUPA 850
Test Date	2014-10-14

Channel 4132



Channel 4233







Report No.: SEFW1410001
FCC ID: ONGASTRO4

Test Item	Band Edge emissions
Test Mode	HSUPA 1900
Test Date	2014-10-14

Channel 9262




Channel 9538






Test Item	Band Edge emissions
Test Mode	HSDPA 850
Test Date	2014-10-14

Channel 4132




Channel 4233






Test Item	Band Edge emissions
Test Mode	HSDPA 1900
Test Date	2014-10-14

Channel 9262



Channel 9538





9. FREQUENCY STABILITY V.S. TEMPERATURE MEASUREMENT

9.1. Test Limit


According to FCC §2.1055, FCC §22.355, .FCC §24.235.

Frequency Tolerance: 2.5 ppm

9.2. Test Procedure

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency. Turn EUT off and set the chamber temperature to –30°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached.

9.3. Test Setup Layout



9.4. Measurement Equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	N9010A	Agilent	MY51350515	2014.09.29	2015.09.28
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-002	2014.03.31	2015.03.30

**9.5. Test Result and Data**

Test Item	FREQUENCY STABILITY V.S. TEMPERATURE
Test Mode	WCDMA 850 Channel 4183
Test Date	2014-10-14

Reference Frequency: WCDMA Mid Channel 836.6 MHz @ 20 °C				
Limit: +/- 2.5 ppm = 2090 Hz				
Power Supply Vac	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
3.7	50	836600062	62	2090
	40	836600080	80	
	30	836600045	45	
	20	836600000	0	
	10	836600057	57	
	0	836600041	41	
	-30	836600020	20	

Test Item	FREQUENCY STABILITY V.S. TEMPERATURE
Test Mode	WCDMA 1900 Channel 9440
Test Date	2014-10-14

Reference Frequency: WCDMA Mid Channel 1880 MHz @ 20 °C				
Limit: ± 2.5 ppm = 4700 Hz				
Power Supply Vac	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
3.7	50	1880000041	41	4700
	40	1880000032	32	
	30	1880000078	78	
	20	1880000000	0	
	10	1880000055	55	
	0	1880000067	67	
	-30	1880000083	83	



Test Item	FREQUENCY STABILITY V.S. TEMPERATURE
Test Mode	HSUPA 850 Channel 4183
Test Date	2014-10-14

Reference Frequency: HSUPA Mid Channel 836.6 MHz @ 20°C				
Limit: +/- 2.5 ppm = 2090 Hz				
Power Supply Vac	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
3.7	50	836600048	48	2090
	40	836600071	71	
	30	836600057	57	
	20	836600000	0	
	10	836600093	93	
	0	836600080	80	
	-30	836600041	41	

Test Item	FREQUENCY STABILITY V.S. TEMPERATURE
Test Mode	HSUPA 1900 Channel 9400
Test Date	2014-10-14

Reference Frequency: HSUPA Mid Channel 1880 MHz @ 20°C				
Limit: ± 2.5 ppm = 4700 Hz				
Power Supply Vac	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
3.7	50	1880000055	55	4700
	40	1880000080	80	
	30	1880000025	25	
	20	1880000000	0	
	10	1880000058	58	
	0	1880000049	49	
	-30	1880000038	38	



Test Item	FREQUENCY STABILITY V.S. TEMPERATURE
Test Mode	HSDPA 850 Channel 4183
Test Date	2014-10-14

Reference Frequency: HSDPA Mid Channel 836.6 MHz @ 20°C				
Limit: +/- 2.5 ppm = 2090 Hz				
Power Supply Vac	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
3.7	50	836600058	58	2090
	40	836600081	81	
	30	836600075	75	
	20	836600000	0	
	10	836600037	37	
	0	836600094	94	
	-30	836600077	77	

Test Item	FREQUENCY STABILITY V.S. TEMPERATURE
Test Mode	HSDPA 1900 Channel 9400
Test Date	2014-10-14

Reference Frequency: HSDPA Mid Channel 1880 MHz @ 20°C				
Limit: ± 2.5 ppm = 4700 Hz				
Power Supply Vac	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
3.7	50	1880000051	51	4700
	40	1880000033	33	
	30	1880000070	70	
	20	1880000000	0	
	10	1880000092	92	
	0	1880000043	43	
	-30	1880000075	75	



10. FREQUENCY STABILITY V.S. VOLTAGE MEASUREMENT

10.1. Test Limit


According to FCC §2.1055, FCC §22.355, .FCC §24.235.

10.2. Test Procedure

Set chamber temperature to 20 °C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation ($\pm 10\%$) and endpoint, record the maximum frequency change.

10.3. Test Setup Layout



10.4. Measurement Equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	N9010A	Agilent	MY51350515	2014.09.29	2015.09.28
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-002	2014.03.31	2015.03.30

**10.5. Test Result and Data**

Test Item	REQUENCY STABILITY V.S. VOLTAGE
Test Mode	WCDMA 850 Channel 4183
Test Date	2014-10-14

Reference Frequency: WCDMA Mid Channel 836.6 MHz @ 20 °C				
Limit: ± 2.5 ppm = 2090Hz				
Power Supply Vac	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
4.2	20	836599971	29	2090
3.7		836600000	0	
3.6		836599965	35	

Test Item	REQUENCY STABILITY V.S. VOLTAGE
Test Mode	WCDMA 1900 Channel 9400
Test Date	2014-10-14

Reference Frequency: WCDMA Mid Channel 1880 MHz @ 20 °C				
Limit: ± 2.5 ppm = 4700 Hz				
Power Supply Vac	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
4.2	20	1879999931	69	4700
3.7		1880000000	0	
3.6		1879999982	18	



Test Item	REQUENCY STABILITY V.S. VOLTAGE
Test Mode	HSUPA 850 Channel 4183
Test Date	2014-10-14

Reference Frequency: HSUPA Mid Channel 836.6 MHz @ 20 °C				
Limit: ± 2.5 ppm = 2090Hz				
Power Supply Vac	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
4.2	20	836599955	45	2090
3.7		836600000	0	
3.6		836599968	32	

Test Item	REQUENCY STABILITY V.S. VOLTAGE
Test Mode	HSUPA 1900 Channel 9400
Test Date	2014-10-14

Reference Frequency: HSUPA Mid Channel 1880 MHz @ 20 °C				
Limit: ± 2.5 ppm = 4700 Hz				
Power Supply Vac	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
4.2	20	1879999952	48	4700
3.7		1880000000	0	
3.6		1879999969	31	



Test Item	REQUENCY STABILITY V.S. VOLTAGE
Test Mode	HSDPA 850 Channel 4183
Test Date	2014-10-14

Reference Frequency: HSDPA Mid Channel 836.6 MHz @ 20 °C				
Limit: ± 2.5 ppm = 2090Hz				
Power Supply Vac	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
4.2	20	836599987	13	2090
3.7		836600000	0	
3.6		836599937	63	

Test Item	REQUENCY STABILITY V.S. VOLTAGE
Test Mode	HSDPA 1900 Channel 9400
Test Date	2014-10-14

Reference Frequency: HSDPA Mid Channel 1880 MHz @ 20 °C				
Limit: ± 2.5 ppm = 4700 Hz				
Power Supply Vac	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
4.2	20	1879999959	41	4700
3.7		1880000000	0	
3.6		1879999988	12	