



Engineering and Testing for EMC and Safety Compliance

APPLICATION FOR FCC CERTIFICATION DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

Part 15 Unlicensed Spread Spectrum DSSS Transceiver

Tellmut (PTY) Limited
64-74 White Road Retreat.
Cape Town
South Africa

Model: MDR5800
FCC ID: ONJMDR5800

March 22, 2001


STANDARDS REFERENCED FOR THIS REPORT	
PART 2: 1999	FREQUENCY ALLOCATIONS AND RADIO TREATY MATTERS; GENERAL RULES AND REGULATIONS
PART 15: 1999	RADIO FREQUENCY DEVICES
FCC 97-114	GUIDANCE ON MEASUREMENTS FOR DIRECT SEQUENCE SPREAD SPECTRUM SYSTEMS
ANSI C63.4-1992	STANDARD FORMAT MEASUREMENT/TECHNICAL REPORT PERSONAL COMPUTER AND PERIPHERALS
RSS-210, Issue 3: 2000	LOW POWER LICENSE-EXEMPT RADIO -COMMUNICATION DEVICES (ALL FREQUENCY BANDS)
RSS-102, Issue 1: 1999	EVALUATION PROCEDURE FOR MOBILE AND PORTABLE RADIO TRANSMITTERS

FCC Rules Parts	Frequency Range	Output Power (W)	Freq. Tolerance	Emission Designator
Part 15.247	5735 to 5840 MHz	0.24	N/A	N/A

This report concerns (check one): Original Grant: ☒ Class II Change: ☐	
Equipment Type : PCI Board	
Deferred grant requested per 47 CFR 0.457 (d) (1) (ii) Yes: ☐ No: ☒	
If yes, defer until: _____	
Company name agrees to notify the Commission by: ____ (date) of the intended date of announcement of the product so that the grant can be issued on that date.	
Transition Rules Request per 15.37? Yes: ☐ No: ☒	
If no, assumed Part 15, subpart B for unintentional radiators- the new 47 CFR. [10-1-90 Edition] provision.	

REPORT PREPARED BY:


EMC Technician: Elizabeth Szrajer

Signature: 

EMC Engineer: Rachid Sehb

Signature: 

Supervising Engineer: Desmond A. Fraser

Signature: 

Document Number: 2001066

No part of this report may be reproduced without the full written approval of Rhein Tech Laboratories, Inc.

360 Herndon Parkway, Suite 1400
Herndon, VA 20170
Phone: 703-689-0368; Fax: 703-689-2056; Metro: 703-471-6441



TABLE OF CONTENTS

1	INTRODUCTION	4
1.1	RELATED SUBMITTAL (S)/GRANT (S)	4
1.2	TEST METHODOLOGY	4
1.3	TEST FACILITY	4
1.4	EMISSIONS EQUIPMENT LIST.....	5
2	SYSTEM TEST CONFIGURATION	8
2.1	JUSTIFICATION.....	8
2.2	EUT EXERCISE SOFTWARE	8
2.3	SPECIAL ACCESSORIES	8
2.4	TEST SYSTEM DETAILS.....	9
2.5	CONFIGURATION OF TESTED SYSTEM.....	10
3	CONFORMANCE STATEMENT	11
4	FIELD STRENGTH CALCULATION	12
5	CONDUCTED EMISSIONS MEASUREMENTS	13
5.1	CONDUCTED EMISSIONS TEST.....	14
5.1.1	CONDUCTED EMISSIONS (CHANNEL 1 Parabolic DISH EXTERNAL ANTENNA)	15
5.1.2	CONDUCTED EMISSIONS (CHANNEL 6 Parabolic DISH EXTERNAL ANTENNA)	16
5.1.3	CONDUCTED EMISSIONS (CHANNEL 11 Parabolic DISH EXTERNAL ANTENNA).....	17
6	RADIATED EMISSIONS MEASUREMENTS	18
6.1	RADIATED EMISSIONS TEST	19
6.1.1	Radiated EMISSION DIGITAL noise (Channel 1 with Parabolic DISH / PANEL Antenna).....	19
7	MODULATED BANDWIDTH	20
8	CONDUCTED POWER OUTPUT.....	20
9	ANTENNA CONDUCTED SPURIOUS EMISSIONS	21
10	RADIATED SPURIOUS EMISSIONS	23
10.1.1	Radiated Emissions Harmonics/spurious (Channel 1) HIGH GAIN FLAT PANEL	23
10.1.2	Radiated Emissions Harmonics/spurious (Channel 6) HIGH GAIN FLAT PANEL.....	23
10.1.3	Radiated Emissions Harmonics/spurious (Channel 11) HIGH GAIN FLAT PANEL	24
10.1.4	Radiated Emissions Harmonics/spurious (Channel 1) PARABOLIC DISH	24
10.1.5	Radiated Emissions Harmonics/spurious (Channel 6) PARABOLIC DISH.....	25
10.1.6	Radiated Emissions Harmonics/spurious (Channel 11) PARABOLIC DISH	25
11	POWER SPECTRAL DENSITY	26
12	COMPLIANCE WITH THE RESTRICTED BAND EDGE.....	26
13	RECIEVER/DIGITAL INTERFACE DATA	27



14	ANTENNA SPECIFICATIONS	28
15	BANDEDGE PLOTS	29
15.1	LOWER BAND EDGE	29
15.2	UPPER BAND EDGE	30
16	SPECTRAL DENSITY PLOTS	31
17	6dB PLOTS	34
18	RF EXPOSURE CALCULATIONS FOR HIGH GAIN ANTENNAS	37
19	PROCESSING GAIN REPORT	39
20	PRODUCT DESCRIPTION.....	40
21	LABEL INFORMATION	41
21.1	FCC ID LABEL	41
21.2	WARNING STATEMENT	41
22	SCHEMATICS.....	44
23	MANUAL	45
24	TEST PHOTOGRAPHS	46
24.1	CONDUCTED MEASUREMENT PHOTOS	46
24.2	RADIATED MEASUREMENT PHOTOS.....	48
25	INTERNAL PHOTOGRAPHS	52
26	EXTERNAL PHOTOGRAPHS.....	53
27	ANTENNA PHOTOGRAPHS.....	54



360 Herndon Parkway
Suite 1400
Herndon, VA 20170
<http://www.rheintech.com>

1 INTRODUCTION

The following Application for FCC Certification for a Direct Sequence Spread Spectrum transmitter is prepared on behalf of TELLUMAT in accordance with Part 15.247 of the Federal Communications Commissions. The Equipment Under Test hereafter called (EUT) was the **MDR5800, FCC ID: ONJMDR5800**. The test results reported in this document relate only to the item that was tested. The mentioned device fulfills the requirement for a Part 15 Unlicensed Spread spectrum 5.8 GHz transceiver

All measurements contained in this Application were conducted in accordance with ANSI C63.4 Methods of Measurement of Radio Noise Emissions, 1992. The instrumentation utilized for the measurements conforms to the ANSI C63.4 standard for EMI and Field Strength Instrumentation. Some accessories are used to increase sensitivity and prevent overloading of the measuring instrument. These are explained in the appendix of this report. Calibration checks are performed regularly on the instruments, and all accessories including the high pass filter, preamplifier and cables.

1.1 RELATED SUBMITTAL (S)/GRANT (S)

This is an original application for certification.

1.2 TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.4 1992. Radiated testing was performed at an antenna to EUT distance of 3 meters. Emissions above 1 GHz were video averaged.

1.3 TEST FACILITY

The open area test site and conducted measurement facility used to collect the radiated data is located on the parking lot of Rhein Tech Laboratories, Inc. 360 Herndon Parkway, Suite 1400, Herndon, Virginia 20170. This site has been fully described in a report dated March 3, 1994, submitted to and approved by the Federal Communication Commission to perform AC line conducted and radiated emissions testing (ANSI C63.4 1992).



1.4 EMISSIONS EQUIPMENT LIST

RTL Asset Number	Manufacturer	Model	Part Type	Serial Number	Calibration due date
900969	Hewlett Packard	85650A	Quasi-Peak Adapter (30 Hz – 40 GHz)	2412A00414	03/23/01
900929	Hewlett Packard	85650A	Quasi-Peak Adapter (30 Hz – 40 GHz)	2811A01276	03/28/01
900901	Hewlett Packard	85650A	Quasi-Peak Adapter (30 Hz – 40 GHz)	3145A01599	11/02/01
900339	Hewlett Packard	85650A	Quasi-Peak Adapter (30 Hz – 40 GHz)	2521A00743	03/27/01
900042	Hewlett Packard	85650A	Quasi-Peak Adapter (30 Hz – 40 GHz)	2521A01032	11/05/01
900924	Amplifier Research	75A220	Amplifier (10 kHz – 220 MHz)		N/A
900933	Hewlett Packard	11975A	Power Amplifier (2 - 8 GHz)	2304A00348	11/15/01
901067	Hewlett Packard	8903B	Audio Analyzer	2303A00307	06/28/01
901055	Hewlett Packard	8901A Opt. 002-003	Modulation Analyzer	2545A04102	06/08/01
900718	Voltech	PM3000A	Power Analyzer	6836-002-10	11/08/01
900397	Associated Research, Inc.	6554SA	Electrical Safety Compliance Analyzer	940281	11/08/01
900926	Hewlett Packard	8753D	RF Vector Network Analyzer	3410A09659	03/28/01
901089	Hewlett Packard	HP875ET	Transmission/Reflection Network Analyzer	US39170052	N/A
900968	Hewlett Packard	8567A	Spectrum Analyzer (10 kHz – 1.5 GHz)	2602A00160	03/23/01
900903	Hewlett Packard	8567A	Spectrum Analyzer (10 kHz – 1.5 GHz)	2841A00614	11/02/01
900897	Hewlett Packard	8567A	Spectrum Analyzer (10 kHz – 1.5 GHz)	2727A00535	11/08/01
900931	Hewlett Packard	8566B	Spectrum Analyzer (100 Hz – 22 GHz)	3138A07771	03/27/01
900912	Hewlett Packard	8568A	RF Spectrum Analyzer (100 Hz – 1.5 GHz)	2634A02704	08/02/01
900824	Hewlett Packard	8591E	RF Spectrum Analyzer (9 KHz – 1.8 GHz)	3710A06135	11/14/01
900724	ARA	LPB-2520	Log Periodic / Biconical Antenna (25-1000 MHz)	1037	2/1/01
900725	ARA	LPB-2520	Log Periodic / Biconical Antenna (25-1000 MHz)	1036	07/12/01
900967	A.H. Systems	TDS-206/535-1 through TDS-206/535-4	Tuned Dipole set (30 – 1000 MHz)	126, 128, 129, 132	12/15/00
900154	Compliance Design	Roberts Dipole	Adjustable Elements Dipole antenna (30-1000MHz)	N/A	7/26/01
900814	Electro-Metrics	RGA-60	Double Ridges Guide Antenna (1-18 GHz)	2310	2/26/01
900081	EMCO	3146	Log-Periodic Antenna (200-1000 MHz)	1850	
900800	EMCO	3301B	Active Monopole (Rod antenna) (30 Hz – 50 MHz)	9809-4071	05/02/01
900151	Rohde@Schwarz	HFH@-Z2	Loop Antenna (9kHz-30 MHz)	82825/019	05/26/01
900791	Schaffner –Chase	CSL6112	Bilog antenna (30 MHz – 2GHz)	2099	2/22/01
901053	Schaffner –Chase	CBL6112B	Bilog Chase antenna (200 MHz – 2 GHz)	2648	05/24/01
900060	Hewlett Packard	86634B	Auxiliary Section for External Pulse Modulator	1314A02913	11/08/01
901041	ACO Pacific	511E	Sound Level Calibrator	028751	In calibration
900970	Hewlett Packard	85662A	Spectrum Analyzer Display	254211239	03/23/01
900930	Hewlett Packard	85662A	Spectrum Analyzer Display	3144A20839	03/28/01
900911	Hewlett Packard	85662A	Spectrum Analyzer Display	2542A12739	08/02/01
900902	Hewlett Packard	85662A	Spectrum Analyzer Display	2848A17585	11/02/01



360 Herndon Parkway
Suite 1400
Herndon, VA 20170
<http://www.rheintech.com>

RTL Asset Number	Manufacturer	Model	Part Type	Serial Number	Calibration due date
900896	Hewlett Packard	85662A	Spectrum Analyzer Display	2816A16471	11/02/01
900914	Hewlett Packard	8546OA	RF Filter Section, (100 KHz to 6.5 GHz)	3330A00107	11/07/01
901057	Hewlett Packard	3336B	Synthesizer/Level Generator	2514A02585	06/21/01
900059	Hewlett Packard	8660C	Signal Generator (9 KHz – 3200 MHz)	1947A02956	11/08/01
900960	Hewlett Packard	8444A	Tracking Generator (0.5 –1500MHz)	2325A07827	03/08/01
900917	Hewlett Packard	8648C	Synthesized. Signal Generator (9 KHz – 3200 MHz)	3537A01741	03/28/01
900821	Hewlett Packard	33120A	15 MHz Function / Arbitrary Waveform Generator	US36029992	11/14/01
900059	Hewlett Packard	8660C	Synthesized. Signal Generator (9 kHz –3200 MHz)	1947A02956	11/08/01
900560	Haefely	PESD 1600	ESD Generator	H 703146	10/05/01
900099	Marconi	52022-910E	Signal Generator (10 kHz – 1 GHz)	119044-189	11/14/01
900195	Tektronix	CFG280	Function Generator (0.1 Hz – 11 MHz)	TW12167	N/A
900927	Tektronix	ASG 100	Audio Signal Generator	B03274 V2.3	N/A
900935	Wavetek	3510B	Signal Generator	5372160	03/28/00
900660	Philips	PM5418TDS	TV Generator	LO 604891	11/21/01
900369	Philips	PM5418TDS	TV Generator	LR81436C	N/A
900268	Taylor	5565	Hygrometer / Thermometer	N/A	09/05/01
901056	Hewlett Packard	8954A, Opt.H03	Transceiver Interface	2924A00830	06/02/01
901088	Hewlett Packard	8954A	Transceiver Interface	2146A00139	07/28/01
901082	AFJ International	AFJ LS16	LISN (9 kHz – 30 MHz)	16010020081	06/16/01
901083	AFJ International	AFJ LS16	LISN (9 kHz – 30 MHz)	16010020082	06/16/01
901084	AFJ International	AFJ LS16	LISN (9 kHz – 30 MHz)	16010020080	06/16/01
901090	Bajog electronic	4V-100/200	LISN (150 kHz – 30 MHz)	00-44-007	08/03/01
900726	Solar	7225-1	LISN	N/A	03/29/01
900727	Solar	7225-1	LISN	N/A	03/29/01
900078	Solar	7225-1	LISN	N/A	03/29/01
900077	Solar	7225-1	LISN	N/A	03/29/01
901054	Hewlett Packard	HP 3586B	Selective Level Meter	1928A01892	06/08/01
900770	Hewlett Packard	437B	Power Meter	2949A02966	In cal.
900793	Hewlett Packard	432A	Thermistor Power Meter	1848a22632	N/A
900126	Hewlett Packard	11970A	Harmonic Mixer (26-40 GHz)	2332A01199	11/10/02
900396	Hewlett Packard	11970K	Harmonic Mixer (18-26 GHz)	2332A00563	11/00/02
900921	Haefely	IP 6.2	Coupling Network	083-334-13	11/10/01
900918	Voltech	IEC Standard 555	Reference Impedance Network (rented)	7701	11/08/01
900061	Hewlett Packard	86603A	RF Plug-in (1 to 2600 MHz)	2221A02967	11/08/01
900160	Pacific	112-AMX	AC Power Source (rented)	0187	11/15/01
900932	Hewlett Packard	8449B OPT H02	Preamplifier (1-26.5 GHz)	3008A00505	09/15/01
900045	Hewlett Packard	8447F	Preamplifier	2944A03783	N/A
901040	Industrial	SMX100	Wide Band Preamplifier (0.01-1000 MHz)	1736-0696	11/17/01
900721	Hewlett Packard	8447D	Preamplifier (0.1-1300 MHz)	2727A05397	N/A
900889	Hewlett Packard	85685A	RF Preselector for HP 8566B or 8568B (20Hz-2GHz)	3146A01309	11/14/01
900566	Amplifier Research	FP 2000	Isotropic Field Probe	20760	08/29/01
900174	FCC	F-120-9A	RF Injection Probe (10 kHz – 300 MHz)	N/A	05/31/01
901044	FCC	F-120-5	Bulk Current Injection Probe (10 kHz – 150 MHz)	17	05/12/01
901042	FCC	F-72-1	RF Current Probe (10 Hz – 100 MHz)	44	05/11/01



360 Herndon Parkway
Suite 1400
Herndon, VA 20170
<http://www.rheintech.com>

RTL Asset Number	Manufacturer	Model	Part Type	Serial Number	Calibration due date
900704	FCC	F-14-1	Current Probe (10 Hz – 500 kHz)	33	05/12/01
900894	FCC	F-33-1	RF Current Probe (10 kHz – 250 MHz)	303	05/30/01
900854	Solar Electronics Co	9119-IN	RF Current Probe	972501	
900849	Solar Electronics Co	9121-IN	Injection Probe (10 MHz – 1 GHz)	953501	
900848	Solar Electronics Co	9320-IN	RF Current Probe	990521	
900913	Hewlett Packard	85462A	EMI Receiver RF Section (9 KHz – 6.5 GHz)	3325A00159	03/29/01
900769	Hewlett Packard	8481B	Power Sensor	2702A05059	In cal.
900937	Hewlett Packard	8482H	3-watt Power Sensor (100 KHz to 4.2 GHz)	3318A08961	12/02/01
900928	Hewlett Packard	83752A	Synthesized Sweeper, 0.01 to 20 GHz	3610A00866	03/28/01
900946	Tenney Engineering, Inc.	TH65	Temperature Chamber with Humidity	11380	11/07/01
900111	Omega Engineering	DP41-TC-DSS	Temperature Monitor	2060123	In cal.
901043	FCC		Terminator for RF Current Probe F-72-1		05/12/01
900731	Haefely	PEFT.1	Burst Tester with Coupling Network	082 106-29	11/10/01
900402	BAPCO Electro-Com	IEC 601 L	Safety Tester	000028	11/10/01
900720	Haefely	Psurge 4.1	Surge Tester	083-342-02	11/10/01
900839	Bird	43P	Peak Reading Wattmeter	3110	11/10/01
901137	Par Electronics	Notch	Notch Filter (2.3 GHz to 2.5 GHz)	N/A	N/A



360 Herndon Parkway
Suite 1400
Herndon, VA 20170
<http://www.rheintech.com>

2 SYSTEM TEST CONFIGURATION

2.1 JUSTIFICATION

The EUT was tested in all three orthogonal planes in order to determine worst-case emission. Low Channel at 5.735 GHz, Mid Channel at 5.804 GHz and High Channel at 5.840 GHz were tested and investigated from 9 kHz to 40 GHz. All three channels were investigated and tested. Data for all three channels are presented in this report.

The EUT was investigated with the highest gain of each external antenna type. The worst-case data taken in this report represents the highest data rate at 11 MBPS. Data rates of 5.5MBPS, 2 MBPS and 1 MBPS were investigated and found to be in compliance.

2.2 EUT EXERCISE SOFTWARE

The EUT was provided with the software to continuously transmit during testing. The carrier was also checked to verify that the information was being transmitted.

2.3 SPECIAL ACCESSORIES

N/A.



2.4 TEST SYSTEM DETAILS


The FCC Identifiers for all equipment, plus descriptions of all cables used in the tested system (including antennas) are:

EXTERNAL COMPONENTS

PART	MANUFACTURER	MODEL	SERIAL NUMBER	FCC ID	CABLE DESCRIPTION	RTL BAR CODE
FLATPANEL ANTENNA (EUT)	PLESSEY MICROWAVE	DFPD-52	P90487	N/A	50 OHM LOW LOSS COAXIAL	013035
FLAT PLANEL ANTENNA (EUT)	HARRIS	MTI-20004	00621	N/A	50 OHM LOW LOSS COAXIAL	013115
TRANSCEIVER (EUT)	PLESSEY MICROWAVE	MDR5800 (FREQ. L)	MDR58000172	ONJ-MDR5800	SHIELDED CAT 5 CABLE UNSHIELDED DC POWER CABLE	013114
TRANSCEIVER (EUT)	PLESSEY MICROWAVE	MDR5800 (FREQ. H)	MDR58000169	ONJ-MDR5800		013113
DISH ANTENNA (EUT)	GABRIEL ELECTRONICS	SSP2-52B	T92457	N/A	50 OHM LOW LOSS COAXIAL	013044
DIGITAL RADIO (EUT)	PLESSEY MICROWAVE	MDR DIGITAL RADIO (FAR)	MDRTE000016	ONJ-MDR5800	SHIELDED CAT 5 CABLE UNSHIELDED DC POWER CABLE	013039
DIGITAL RADIO (EUT)	PLESSEY MICROWAVE	MDR DIGITAL RADIO (NEAR)	MDRTE000035	ONJ-MDR5800	SHIELDED CAT 5 CABLE UNSHIELDED DC POWER CABLE	013038



2.5 CONFIGURATION OF TESTED SYSTEM





360 Herndon Parkway
Suite 1400
Herndon, VA 20170
<http://www.rheintech.com>

3 CONFORMANCE STATEMENT

STANDARDS REFERENCED FOR THIS REPORT	
PART 2: 1999	FREQUENCY ALLOCATIONS AND RADIO TREATY MATTERS; GENERAL RULES AND REGULATIONS
PART 15: 1999	RADIO FREQUENCY DEVICES
FCC 97-114	GUIDANCE ON MEASUREMENTS FOR DIRECT SEQUENCE SPREAD SPECTRUM SYSTEMS
ANSI C63.4-1992	STANDARD FORMAT MEASUREMENT/TECHNICAL REPORT PERSONAL COMPUTER AND PERIPHERALS

FCC Rules Parts	Frequency Range	Output Power (W)	Freq. Tolerance	Emission Designator
Part 15.247	5735 to 5840 MHz	0.24	N/A	N/A

I, the undersigned, hereby declare that the equipment tested and referenced in this report conforms to the identified standard(s) as described above. Modifications were not made during testing to the equipment in order to achieve compliance with these standards.

Furthermore, there was no deviation from, additions to or exclusions from the ANSI C63.4 test methodology.

Signature: 

Date: *March 22, 2001*

Typed/Printed Name: Desmond A. Fraser

Position: President
(NVLAP Signatory)



Accredited by the National Voluntary Accreditation Program for the specific scope of accreditation under Lab Code 20061-0.

Note: This report may not be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government.



4 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FI(\text{dBuV/m}) = SAR(\text{dBuV}) + SCF(\text{dB/m})$$

FI = Field Intensity

SAR = Spectrum Analyzer Reading

SCF = Site Correction Factor

The Site Correction Factor (SCF) used in the above equation is determined empirically, and is expressed in the following equation:

$$SCF(\text{dB/m}) = -PG(\text{dB}) + AF(\text{dB/m}) + CL(\text{dB})$$

SCF = Site Correction Factor

PG = Pre-amplifier Gain

AF = Antenna Factor

CL = Cable Loss

The field intensity in microvolts per meter can then be determined according to the following equation:

$$FI(\text{uV/m}) = 10^{FI(\text{dBuV/m})/20}$$

For example, assume a signal at a frequency of 125 MHz has a received level measured as 49.3 dBuV. The total Site Correction Factor (antenna factor plus cable loss minus preamplifier gain) for 125 MHz is

-11.5 dB/m. The actual radiated field strength is calculated as follows:

$$49.3 \text{ dBuV} - 11.5 \text{ dB/m} = 37.8 \text{ dBuV/m}$$

$$10^{37.8/20} = 10^{1.89} = 77.6 \text{ uV/m}$$

EIRP calculation: Power from power meter in (dBm) + antenna gain in (dBi)



5 CONDUCTED EMISSIONS MEASUREMENTS

The power line conducted emission measurements were performed in a Series 81 type shielded enclosure manufactured by Rayproof. The EUT was assembled on a wooden table 80 centimeters high. Power was fed to the EUT through a 50 ohm / 50 microhenry Line Impedance Stabilization Network (EUT LISN). The EUT LISN was fed power through an A.C. filter box on the outside of the shielded enclosure. The filter box and EUT LISN housing are bonded to the ground plane of the shielded enclosure. A second LISN, the peripheral LISN, provides isolation for the EUT test peripherals. This peripheral LISN was also fed A.C. power. A metal power outlet box, which is bonded to the ground plane and electrically connected to the peripheral LISN, powers the EUT host peripherals.

The spectrum analyzer was connected to the A.C. line through an isolation transformer. The 50-ohm output of the EUT LISN was connected to the spectrum analyzer input through a Solar 7 kHz high-pass filter. The filter is used to prevent overload of the spectrum analyzer from noise below 7 kHz. Conducted emission levels were measured on each current-carrying line with the spectrum analyzer operating in the CISPR quasi-peak mode (or average mode if applicable). The analyzer's 6 dB bandwidth was set to 9 kHz. No video filter less than 10 times the resolution bandwidth was used. Average measurements are performed in linear mode using a 10 kHz resolution bandwidth, a 1 Hz video bandwidth, and by increasing the sweep time in order to obtain a calibrated measurement. The range of the frequency spectrum to be investigated is specified in FCC Part 15. The highest emission amplitudes relative to the appropriate limit were measured and have been recorded in this report.



360 Herndon Parkway
Suite 1400
Herndon, VA 20170
<http://www.rheintech.com>

5.1 CONDUCTED EMISSIONS TEST

The following table lists worst-case conducted emission data. Specifically: Emission Frequency, Test Detector, Analyzer Reading, Site Correction Factor, corrected Emission Level, Quasi Peak Limit and Margin, and the Average Limit and Margin.

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. If the conducted emissions exceed the limit with the instrument set to the quasi-peak mode, then measurements are made in the average mode.

The conducted test was performed with the EUT exercise program loaded, and the emissions were scanned between 450 kHz to 30 MHz on the NEUTRAL SIDE and HOT SIDE, herein referred to as L1 and L2, respectively.



5.1.1 CONDUCTED EMISSIONS (CHANNEL 1 PARABOLIC DISH EXTERNAL ANTENNA)

NEUTRAL SIDE (Line 1)

Temperature: 73°F Humidity: 38%									
Emission Frequency (MHz)	Test Detector	Analyzer Reading (dBuV)	Site Correction Factor (dB)	Emission Level (dBuV)	FCC B QP Limit (dBuV)	FCC B QP Margin (dBuV)	FCC B AV Limit (dBuV)	FCC B AV Margin (dBuV)	Pass/Fail
0.454	Pk	38.8	0.8	39.6	48.0	-8.4	48.0	-8.4	Pass
1.073	Pk	36.9	0.8	37.7	48.0	-10.3	48.0	-10.3	Pass
2.830	Pk	35.2	1.4	36.6	48.0	-11.4	48.0	-11.4	Pass
3.806	Pk	34.9	1.5	36.4	48.0	-11.6	48.0	-11.6	Pass
4.586	Pk	37.6	1.7	39.3	48.0	-8.7	48.0	-8.7	Pass
11.710	Pk	30.0	2.6	32.6	48.0	-15.4	48.0	-15.4	Pass

HOT SIDE (Line 2)

Temperature: 73°F Humidity: 38%									
Emission Frequency (MHz)	Test Detector	Analyzer Reading (dBuV)	Site Correction Factor (dB)	Emission Level (dBuV)	FCC B QP Limit (dBuV)	FCC B QP Margin (dBuV)	FCC B AV Limit (dBuV)	FCC B AV Margin (dBuV)	Pass/Fail
0.584	Pk	37.5	0.7	38.2	48.0	-9.8	48.0	-9.8	Pass
1.369	Pk	37.9	0.9	38.8	48.0	-9.2	48.0	-9.2	Pass
2.834	Pk	37.4	1.4	38.8	48.0	-9.2	48.0	-9.2	Pass
3.907	Pk	37.6	1.5	39.1	48.0	-8.9	48.0	-8.9	Pass
4.397	Pk	40.3	1.6	41.9	48.0	-6.1	48.0	-6.1	Pass
9.999	Pk	40.6	2.3	42.9	48.0	-5.1	48.0	-5.1	Pass

⁽¹⁾Pk = Peak; QP = Quasi-Peak; Av = Average



5.1.2 CONDUCTED EMISSIONS (CHANNEL 6 PARABOLIC DISH EXTERNAL ANTENNA)

NEUTRAL SIDE (Line 1)

Temperature: 74°F Humidity: 36									
Emission Frequency (MHz)	Test Detector	Analyzer Reading (dBuV)	Site Correction Factor (dB)	Emission Level (dBuV)	FCC B QP Limit (dBuV)	FCC B QP Margin (dBuV)	FCC B AV Limit (dBuV)	FCC B AV Margin (dBuV)	Pass/Fail
0.585	Pk	40.3	0.7	41.0	48.0	-7.0	48.0	-7.0	Pass
0.883	Pk	37.5	0.8	38.3	48.0	-9.7	48.0	-9.7	Pass
1.018	Pk	42.4	0.8	43.2	48.0	-4.8	48.0	-4.8	Pass
3.905	Pk	37.5	1.5	39.0	48.0	-9.0	48.0	-9.0	Pass
4.313	Pk	40.6	1.6	42.2	48.0	-5.8	48.0	-5.8	Pass
10.008	Pk	40.7	1.5	42.2	48.0	-5.8	48.0	-5.8	Pass

HOT SIDE (Line 2)

Emission Frequency (MHz)	Test Detector	Analyzer Reading (dBuV)	Site Correction Factor (dB)	Emission Level (dBuV)	FCC B QP Limit (dBuV)	FCC B QP Margin (dBuV)	FCC B AV Limit (dBuV)	FCC B AV Margin (dBuV)	Pass/Fail
0.587	Pk	40.1	0.7	40.8	48.0	-7.2	48.0	-7.2	Pass
1.059	Pk	42.5	0.8	43.3	48.0	-4.7	48.0	-4.7	Pass
2.648	Pk	37.8	1.3	39.1	48.0	-8.9	48.0	-8.9	Pass
3.919	Pk	40.2	1.5	41.7	48.0	-6.3	48.0	-6.3	Pass
4.410	Pk	43.9	1.6	45.5	48.0	-2.5	48.0	-2.5	Pass
10.004	Pk	40.3	2.3	42.6	48.0	-5.4	48.0	-5.4	Pass

⁽¹⁾Pk = Peak; QP = Quasi-Peak; Av = Average



360 Herndon Parkway
Suite 1400
Herndon, VA 20170
<http://www.rheintech.com>

5.1.3 CONDUCTED EMISSIONS (CHANNEL 11 PARABOLIC DISH EXTERNAL ANTENNA)

NEUTRAL SIDE (Line 1)

Temperature: 74°F Humidity: 36%									
Emission Frequency (MHz)	Test Detector	Analyzer Reading (dBuV)	Site Correction Factor (dB)	Emission Level (dBuV)	FCC B QP Limit (dBuV)	FCC B QP Margin (dBuV)	FCC B AV Limit (dBuV)	FCC B AV Margin (dBuV)	Pass/Fail
0.585	Pk	41.2	0.7	41.9	48.0	-6.1	48.0	-6.1	Pass
1.058	Pk	41.8	0.8	42.6	48.0	-5.4	48.0	-5.4	Pass
2.834	Pk	37.4	1.4	38.8	48.0	-9.2	48.0	-9.2	Pass
3.913	Pk	38.0	1.5	39.5	48.0	-8.5	48.0	-8.5	Pass
4.400	Pk	41.1	1.6	42.7	48.0	-5.3	48.0	-5.3	Pass
9.994	Pk	41.1	1.5	42.6	48.0	-5.4	48.0	-5.4	Pass

HOT SIDE (Line 2)

Temperature: 74°F Humidity: 36%									
Emission Frequency (MHz)	Test Detector	Analyzer Reading (dBuV)	Site Correction Factor (dB)	Emission Level (dBuV)	FCC B QP Limit (dBuV)	FCC B QP Margin (dBuV)	FCC B AV Limit (dBuV)	FCC B AV Margin (dBuV)	Pass/Fail
0.586	Pk	39.8	0.7	40.5	48.0	-7.5	48.0	-7.5	Pass
1.274	Pk	42.4	0.9	43.3	48.0	-4.7	48.0	-4.7	Pass
2.836	Pk	37.8	1.4	39.2	48.0	-8.8	48.0	-8.8	Pass
3.909	Pk	40.3	1.5	41.8	48.0	-6.2	48.0	-6.2	Pass
4.398	Pk	43.7	1.6	45.3	48.0	-2.7	48.0	-2.7	Pass
11.637	Pk	37.6	2.5	40.1	48.0	-7.9	48.0	-7.9	Pass

⁽¹⁾Pk = Peak; QP = Quasi-Peak; Av = Average

TEST PERSONNEL: ELIZABETH SZRAJER

Typed/Printed Name:

Elizabeth Szrajer

Date: March 22, 2001



360 Herndon Parkway
Suite 1400
Herndon, VA 20170
<http://www.rheintech.com>

6 RADIATED EMISSIONS MEASUREMENTS

Before final measurements of radiated emissions were made on the open-field three/ten meter range; the EUT was scanned indoor at one and three meter distances. This was done in order to determine its emissions spectrum signature. The physical arrangement of the test system and associated cabling was varied in order to determine the effect on the EUT's emissions in amplitude, direction and frequency. This process was repeated during final radiated emissions measurements on the open-field range, at each frequency, in order to insure that maximum emission amplitudes were attained.

Final radiated emissions measurements were made on the three/ten-meter, open-field test site. The EUT was placed on a nonconductive turntable 0.8 meters above the ground plane.

At each frequency, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters in order to determine the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarizations. The spectrum analyzer's 6 dB bandwidth was set to 120 kHz, and the analyzer was operated in the CISPR quasi-peak detection mode. No video filter less than 10 times the resolution bandwidth was used. The range of the frequency spectrum to be investigated is specified in FCC Part 15. The highest emission amplitudes relative to the appropriate limit were measured and recorded in this report. .
For radiated measurements above 1 GHz, a resolution bandwidth of 1 MHz and a video bandwidth of 10 Hz are used.

Note: Rhein Tech Laboratories, Inc. has implemented procedures to minimize errors that occur from test instruments, calibration, procedures, and test setups. Test instrument and calibration errors are documented from the manufacturer or calibration lab. Other errors have been defined and calculated within the Rhein Tech quality manual, section 6.1. Rhein Tech implements the following procedures to minimize errors that may occur: yearly as well as daily calibration methods, technician training, and emphasis to employees on avoiding error.



360 Herndon Parkway
Suite 1400
Herndon, VA 20170
<http://www.rheintech.com>

6.1 RADIATED EMISSIONS TEST

The following data lists the significant emission frequencies, measured levels, correction factor (includes cable and antenna corrections), the corrected reading, plus the limit.

6.1.1 RADIATED EMISSION DIGITAL NOISE (CHANNEL 1 WITH PARABOLIC DISH / PANEL ANTENNA)

Emission Frequency (MHz)	Test Detector	Antenna Polarity (H/V)	Turntable Azimuth (deg)	Antenna Height (m)	Analyzer Reading (dBuV)	Site Correction Factor (dB/m)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
44.000	Qp	V	90	1.0	58.5	-19.9	38.6	40.0	-1.4
52.000	Qp	V	265	1.0	57.2	-22.4	34.8	40.0	-5.2
76.000	Qp	V	90	1.0	61.6	-22.9	38.7	40.0	-1.3
80.000	Qp	V	90	1.0	60.4	-22.6	37.8	40.0	-2.2
132.000	Qp	V	310	1.0	48.1	-15.5	32.6	43.5	-10.9
176.000	Qp	V	180	1.0	59.8	-17.5	42.3	43.5	-1.2
180.000	Qp	H	90	1.8	54.9	-18.3	36.6	43.5	-6.9
220.000	Qp	H	125	1.4	56.8	-17.4	39.4	46.0	-6.6
352.000	Qp	H	180	1.0	47.9	-11.4	36.5	46.0	-9.5
380.000	Qp	V	145	1.0	45.4	-11.2	34.2	46.0	-11.8
480.095	Qp	V	110	1.0	39.2	-9.0	30.2	46.0	-15.8
528.000	Qp	V	345	1.0	40.1	-7.9	32.2	46.0	-13.8

QUASI PEAK =120 KHz

TEST PERSONNEL: ELIZABETH SZRAJER

Typed/Printed Name:

Elizabeth Szrajer

Date: March 22, 2001



7 MODULATED BANDWIDTH

The minimum 6 dB bandwidth per FCC 15.247(a)(2) was measured using a 50 ohm spectrum analyzer with the resolution bandwidth set at 100 kHz, and the video bandwidth set at 300 kHz. The Minimum 6 dB modulated bandwidths are the following:

Channel	6(dB) Bandwidth (MHz)
1	11.83
6	11.35
11	11.63

The 6dB bandwidth is listed in figures Section 26 of this report.

8 CONDUCTED POWER OUTPUT

The conducted output power per FCC 15.247(b) was measured on the EUT using an HP Peak power meter.

Channel	Calculated EIRP (dBm)* DISH	Calculated EIRP (dBm)* PANEL 1	Calculated EIRP (dBm)* PANEL 2	Power Conducted output (dBm)
1	52.8	51.8	47.7	23.8
6	51.7	50.7	46.6	22.7
11	52.8	51.8	47.7	23.8

*Measurement accuracy is +/- 0.5 dB



9 ANTENNA CONDUCTED SPURIOUS EMISSIONS

Antenna spurious emission per FCC 15.247(c) was measured from the EUT antenna port using a 50 ohm spectrum analyzer with the resolution bandwidth set at 100 kHz, and the video bandwidth set at 300 kHz. The modulated carrier was identified at 5.735 GHz for Channel 1, 5.804 GHz for Channel 6 and 5.840 GHz for Channel 11. No other harmonics or spurs were found within 20 dB of the carrier level, and from 9kHz to the carriers 10th harmonic. See antenna conducted spurious noise table. FCC 97 114 appendix C specifies 100kHz/300kHz resolution and video bandwidth for the authorized band up to the 10th harmonic. All spurs and harmonic must be 20 dB down from the carrier within the authorized band. A 5.8 GHz notch filter was used to attenuate the carrier so that the spectrum analyzer would not be overloaded. The insertion loss of the notch filter was added to the spurious level on the table below.

Channel 1		
Frequency (MHz)	Spurious level (dBm)	FCC Margin (dB)
18.990	-45.0	-30.0
602.300	-28.0	-13.0
801.760	-33.0	-18.0
951.954	-46.0	-31.0
1808.600	-35.0	-20.0
2445.510	-49.0	-34.0
2548.070	-55.0	-40.0
2785.510	-51.0	-36.0
4824.060	-41.7	-26.7

Channel 6		
Frequency (MHz)	Spurious level (dBm)	FCC Margin (dB)
8.000	-28.8	-14.8
10.990	-28.5	-14.5
27.440	-37.0	-23.0
82.300	-37.6	-23.6
631.320	-19.6	-5.6
841.735	-31.7	-17.7
946.950	-52.0	-38.0
2815.510	-54.0	-40.0
4884.030	-36.1	-22.1



360 Herndon Parkway
Suite 1400
Herndon, VA 20170
<http://www.rheintech.com>

Channel 11		
Frequency (MHz)	Spurious level (dBm)	FCC Margin (dB)
8.0200	-41.0	-24.4
144.500	-48.0	-31.4
650.800	-28.5	-11.9
850.100	-38.7	-22.1
1880.000	-42.7	-26.1
2407.489	-57.0	-40.4
2440.940	-50.0	-33.4
2835.000	-59.0	-42.4
4922.000	-43.0	-26.4
4927.000	-57.0	-40.4



10 RADIATED SPURIOUS EMISSIONS

Radiated Spurious Emissions applies to harmonics and spurious emissions that fall in the restricted and non-restricted bands. The restricted bands are listed in Section 15.205. The maximum permitted average field strength for the restricted band is listed in Section 15.209. A 5.8 GHz notch filter was used to attenuate the carrier so that the spectrum analyzer would not be overloaded. The insertion loss of the notch filter was added to the spurious level on the table below.

10.1.1 RADIATED EMISSIONS HARMONICS/SPURIOUS (CHANNEL 1) HIGH GAIN FLAT PANEL

Frequency (GHz)	Test Detector	Antenna Polarity (H/V)	Turntable Azimuth (deg)	Antenna Height (m)	Analyzer Reading (dBμV)	Site Correction Factor (dB/m)	Level in (dBμV/m)	Limit in (dBμV/m)	Margin (dB)
5.735	Av	H	90	1.1	87.9	19.8	107.7		
5.735	Pk	H	90	1.1	98.7	19.8	118.5		
11.470	Av	H	95	1.1	30.7		NF	54.0	
11.470	Pk	H	95	1.1	41.4		NF	54.0	
17.205	Av	H	210	1.1	30.7		NF	87.7	
17.205	Pk	H	210	1.1	43.9		NF	98.5	
22.940	Av	H	215	1.0	32.3		NF	54.0	
22.94	Pk	H	215	1.0	41.0		NF	54.0	
28.675	Av	H	300	1.0	32.3		NF	87.7	
28.675	Pk	H	300	1.0	40.3		NF	98.5	
34.410	Av	H	125	1.0	32.3		NF	87.7	
34.410	Pk	H	125	1.0	41.3		NF	98.5	

Average Measurement (AV: resolution bandwidth. =1 MHz, video bandwidth = 10 Hz; NF = Noise floor

Peak Measurement (PK) = resolution bandwidth = 1 MHz, video bandwidth = 1 MHz

10.1.2 RADIATED EMISSIONS HARMONICS/SPURIOUS (CHANNEL 6) HIGH GAIN FLAT PANEL

Frequency (GHz)	Test Detector	Antenna Polarity (H/V)	Turntable Azimuth (deg)	Antenna Height (m)	Analyzer Reading (dBμV)	Site Correction Factor (dB/m)	Level in (dBμV/m)	Limit in (dBμV/m)	Margin (dB)
5.804	Av	H	130	1.1	87.5	19.3	106.8		
5.804	Pk	H	130	1.1	98.5	19.3	117.8		
11.608	Av	H	195	1.1	31.2		NF	54.0	
11.608	Pk	H	195	1.1	43.8		NF	54.0	
17.412	Av	H	305	1.1	33.2		NF	86.8	
17.412	Pk	H	305	1.1	43.7		NF	97.8	
23.216	Av	H	345	1.0	34.2		NF	86.8	
23.216	Pk	H	345	1.0	42.9		NF	97.8	
29.020	Av	H	290	1.0	33.7		NF	86.8	
29.020	Pk	H	290	1.0	43.4		NF	97.8	
34.824	Av	H	115	1.0	33.6		NF	86.8	
34.824	Pk	H	115	1.0	42.1		NF	97.8	

Average Measurement (AV: resolution bandwidth. =1 MHz, video bandwidth = 10 Hz; NF = Noise floor



360 Herndon Parkway
Suite 1400
Herndon, VA 20170
<http://www.rheintech.com>

Peak Measurement (PK) = resolution bandwidth = 1 MHz, video bandwidth = 1 MHz

10.1.3 RADIATED EMISSIONS HARMONICS/SPURIOUS (CHANNEL 11) HIGH GAIN FLAT PANEL

Frequency (GHz)	Test Detector	Antenna Polarity (H/V)	Turntable Azimuth (deg)	Antenna Height (m)	Analyzer Reading (dBμV)	Site Correction Factor (dB/m)	Level in (dBμV/m)	Limit in (dBμV/m)	Margin (dB)
5.840	Av	H	355	1.1	88.1	19.1	107.2		
5.840	Pk	H	355	1.1	99.2	19.1	118.3		
11.680	Av	H	185	1.1	31.7		NF	54.0	
11.680	Pk	H	185	1.1	42.3		NF	54.0	
17.520	Av	H	150	1.1	32.9		NF	87.2	
17.520	Pk	H	150	1.1	44.3		NF	98.3	
23.360	Av	H	190	1.0	34.5		NF	87.2	
23.360	Pk	H	190	1.0	43.6		NF	98.3	
29.200	Av	H	45	1.0	33.4		NF	87.2	
29.200	Pk	H	45	1.0	43.0		NF	98.3	
35.040	Av	H	95	1.0	34.8		NF	87.2	
35.040	Pk	H	95	1.0	44.3		NF	98.3	

Average Measurement (AV: resolution bandwidth. =1 MHz, video bandwidth = 10 Hz; NF = noise floor

Peak Measurement (PK) = resolution bandwidth = 1 MHz, video bandwidth = 1 MHz

NF = Noise Floor

TEST PERSONNEL:

Typed/Printed Name: Rachid SEHB

Date: March 22, 2001

10.1.4 RADIATED EMISSIONS HARMONICS/SPURIOUS (CHANNEL 1) PARABOLIC DISH

Frequency (GHz)	Test Detector	Antenna Polarity (H/V)	Turntable Azimuth (deg)	Antenna Height (m)	Analyzer Reading (dBμV)	Site Correction Factor (dB/m)	Level in (dBμV/m)	Limit in (dBμV/m)	Margin (dB)
5.735	Av	H	90	1.1	88.9	19.8	108.7		
5.735	Pk	H	90	1.1	99.9	19.8	119.7		
11.470	Av	H	295	1.1	30.3		NF	54.0	
11.470	Pk	H	295	1.1	41.2		NF	54.0	
17.205	Av	H	210	1.1	32.6		NF	88.7	
17.205	Pk	H	210	1.1	43.7		NF	99.7	
22.94	Av	H	290	1.0	34.1		NF	54.0	
22.94	Pk	H	290	1.0	42.9		NF	54.0	
28.675	Av	H	245	1.0	33.0		NF	88.7	
28.675	Pk	H	245	1.0	42.4		NF	99.7	
34.410	Av	H	245	1.0	34.6		NF	88.7	
34.410	Pk	H	245	1.0	43.1		NF	99.7	

Average Measurement (AV: resolution bandwidth. =1 MHz, video bandwidth = 10 Hz; NF = Noise floor

Peak Measurement (PK) = resolution bandwidth = 1 MHz, video bandwidth = 1 MHz



10.1.5 RADIATED EMISSIONS HARMONICS/SPURIOUS (CHANNEL 6) PARABOLIC DISH

Frequency (GHz)	Test Detector	Antenna Polarity (H/V)	Turntable Azimuth (deg)	Antenna Height (m)	Analyzer Reading (dBμV)	Site Correction Factor (dB/m)	Level in (dBμV/m)	Limit in (dBμV/m)	Margin (dB)
5.804	Av	H	180	1.1	87.2	19.3	106.5		
5.804	Pk	H	180	1.1	98.2	19.3	117.5		
11.608	Av	H	295	1.1	31.8		NF	54.0	
11.608	Pk	H	295	1.1	41.3		NF	54.0	
17.412	Av	H	0	1.1	33.2		NF	86.5	
17.412	Pk	H	0	1.1	43.7		NF	97.5	
23.216	Av	H	235	1.0	32.6		NF	86.5	
23.216	Pk	H	235	1.0	42.1		NF	97.5	
29.020	Av	H	10	1.0	33.9		NF	86.5	
29.020	Pk	H	10	1.0	43.6		NF	97.5	
34.824	Av	H	300	1.0	32.8		NF	86.5	
34.824	Pk	H	300	1.0	41.9		NF	97.5	

Average Measurement (AV: resolution bandwidth. =1 MHz, video bandwidth = 10 Hz; NF = Noise floor

Peak Measurement (PK) = resolution bandwidth = 1 MHz, video bandwidth = 1 MHz

10.1.6 RADIATED EMISSIONS HARMONICS/SPURIOUS (CHANNEL 11) PARABOLIC DISH

Frequency (GHz)	Test Detector	Antenna Polarity (H/V)	Turntable Azimuth (deg)	Antenna Height (m)	Analyzer Reading (dBμV)	Site Correction Factor (dB/m)	Level in (dBμV/m)	Limit in (dBμV/m)	Margin (dB)
5.840	Av	H	90	1.1	88.1	19.1	107.2		
5.840	Pk	H	90	1.1	99.0	19.1	118.1		
11.680	Av	H	295	1.1	30.7		NF	54.0	
11.680	Pk	H	295	1.1	42.2		NF	54.0	
17.520	Av	H	210	1.1	32.3		NF	87.2	
17.520	Pk	H	210	1.1	44.7		NF	98.1	
23.360	Av	H	290	1.0	33.3		NF	87.2	
23.360	Pk	H	290	1.0	42.7		NF	98.1	
29.200	Av	H	245	1.0	34.3		NF	87.2	
29.200	Pk	H	245	1.0	42.1		NF	98.1	
35.040	Av	H	245	1.0	33.2		NF	87.2	
35.040	Pk	H	245	1.0	43.7		NF	98.1	

Average Measurement (AV: resolution bandwidth. =1 MHz, video bandwidth = 10 Hz; NF = Noise floor

Peak Measurement (PK) = resolution bandwidth = 1 MHz, video bandwidth = 1 MHz

TEST PERSONNEL:

Typed/Printed Name: Rachid SEHB

Date: March 22, 2001



11 POWER SPECTRAL DENSITY

The Power spectral density per FCC 15.247(d) was measured from the antenna port of the EUT using a 50 ohm spectrum analyzer with the resolution bandwidth set at 3kHz, the video bandwidth set at 3kHz, and the sweep time set at 17 second. The spectral lines were resolved for the modulated carriers at Channel 1, Channel 6 and Channel 11 respectively. These levels are well below the +8 dBm limit. See power spectral density table below and the plots in Section 16 of this report.

Channel	Power Spectral Density limit = +8dBm
1	5.30
6	4.03
11	4.97

12 COMPLIANCE WITH THE RESTRICTED BAND EDGE

The Band Edges at Compliance with the band edges was performed using the FCC's "Radiated Measurement at a Band Edge" guidance document.

Note: Band Edge measurements were not performed on the EUT. The restricted Band Edges were far removed from the lower and upper operating channel frequencies at 5.725 GHz and 5.840 GHz respectively. Plots were taken to verify this fact. See plots Lower and Upper Band Edges.



360 Herndon Parkway
Suite 1400
Herndon, VA 20170
<http://www.rheintech.com>

13 RECEIVER/DIGITAL INTERFACE DATA

Radiated Test

Temperature: 47°F		Humidity: 41%							
Emission Frequency (MHz)	Test Detector	Antenna Polarity (H/V)	Turntable Azimuth (deg)	Antenna Height (m)	Analyzer Reading (dBuV)	Site Correction Factor (dB/m)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
44.000	Qp	V	90	1.0	58.5	-19.9	38.6	40.0	-1.4
52.000	Qp	V	265	1.0	57.2	-22.4	34.8	40.0	-5.2
76.000	Qp	V	90	1.0	61.6	-22.9	38.7	40.0	-1.3
80.000	Qp	V	90	1.0	60.4	-22.6	37.8	40.0	-2.2
132.000	Qp	V	310	1.0	48.1	-15.5	32.6	43.5	-10.9
176.000	Qp	V	180	1.0	59.8	-17.5	42.3	43.5	-1.2
180.000	Qp	H	90	1.8	54.9	-18.3	36.6	43.5	-6.9
220.000	Qp	H	125	1.4	56.8	-17.4	39.4	46.0	-6.6
352.000	Qp	H	180	1.0	47.9	-11.4	36.5	46.0	-9.5
380.000	Qp	V	145	1.0	45.4	-11.2	34.2	46.0	-11.8
480.095	Qp	V	110	1.0	39.2	-9.0	30.2	46.0	-15.8
528.000	Qp	V	345	1.0	40.1	-7.9	32.2	46.0	-13.8