



Certification Exhibit

FCC ID: ONTJETIR900US

FCC Rule Part: 15.247

TÜV SÜD Project Number: 72128518

**Manufacturer: Esprit Model Inc.
Model: JETIR900US**

RF Exposure

General Information:

Applicant: Esprit Model Inc.
 Device Category: Mobile
 Environment: General Population/Uncontrolled Exposure

Technical Information:

Antenna Type: PCB Antenna
 Antenna Gain: 1.2 dBi
 Maximum Transmitter Conducted Power: 15.78 dBm, 37.844 mW
 Maximum System EIRP: 16.98 dBm, 49.888 mW
 Exposure Conditions: 20 centimeters or greater

MPE Calculation

The Power Density (mW/cm²) is calculated as follows:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Table 1: MPE Calculation

Transmit Frequency (MHz)	Radio Power (dBm)	Power Density Limit (mW/Cm ²)	Radio Power (mW)	Antenna Gain (dBi)	Antenna Gain (mW eq.)	Distance (cm)	Power Density (mW/cm ²)
900	15.78	0.60	37.84	1.2	1.318	20	0.010