

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF
ENSEMBLE COMMUNICATIONS INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT
THE WRITTEN PERMISSION OF ENSEMBLE COMMUNICATIONS INC. IS PROHIBITED

REVISIONS


REV	DESCRIPTION	PREPARED	DATE	APPROVED
1	INITIAL RELEASE			

NOTES: UNLESS OTHERWISE SPECIFIED

1. INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994.
2. MATERIAL: 3M, PN - 7817, 2 MIL, WHITE, POLYESTER.
3. LABEL SHALL HAVE ADHESIVE BACKING.
4. LABEL SHALL BE SUBJECTED TO THE ENVIROMENT.
-5°C TO 50°C, 5% TO 95% RELATIVE HUMIDITY.
5. BACKING AND TEXT SHALL BE CONTRASTING TO EACH OTHER.
6. ALL TEXT SHALL BE SILKSCREEN ONTO LABEL AS SHOWN.
7. BAG AND/OR TAG WITH PART NUMBER AND CURRENT REVISION.

THIS DEVICE COMPLIES WITH THE
FCC RF EXPOSURE REQUIREMENTS,
47 CFR 1.1310, GENERAL
POPULATION.

4 X R.100

		-1	ITEM NO.	CAGE CODE	PART OR IDENTIFYING NO.	SPECIFICATION	NOMENCLATURE OR DESCRIPTION		NOTE NO.	
		QTY PER ASSY	PARTS LIST							
		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES. TOLERANCES ARE: DECIMALS ANGLES XX = ±.03 ±1/2 DEGREE XXX = ±.010			PREPARED		DATE		<div>8890 Towne Centre Dr. San Diego CA, 92121</div>	
					CHECKED		JDD 5/23/01			
					HOLE DIA		TOLERANCE			
					.0135 THRU .125		+.004 — —.001			
					.128 THRU .250		+.008 — —.001			
					DSGN ENGR		TITLE LABEL, RF EXPOSURE			
					PROJ ENGR					
					MFG ENGR					
					QA					
-1										
DASH NO.	NEXT ASSEMBLY	USED ON	APPLICATION			SIZE		CAGE CODE	DWG NO.	REV
						D		XXXXXX	930-0022-001	
						SCALE	2/1		SHEET 1 OF 1	