



**Spectrum Research &
Testing Lab., Inc.**
No. 101-10, Ling 8,
Shan-Tong Li, Chung-Li
City, Taoyuan, Taiwan

TEST REPORT

Reference No.: A10070606
Report No.: FCCA10070606
FCCID: OOB2018
Page:1 of 21
Date :Jul. 26, 2010

Product Name: Wireless Call Pendant
Model Number: 2018
Applicant: Inter Page Limited Partnership
7354 Central Industrial Drive, West Palm Beach,
Florida, U.S.A. 33404
Date of Receipt: Jul. 06, 2010
Finished date of Test: Jul. 23, 2010
Applicable Standards: 47 CFR Part 15, Subpart C
ANSI C63.4:2003

We, **Spectrum Research & Testing Laboratory Inc.**, hereby certify that one sample of the above was tested in our laboratory with positive results according to the above-mentioned standards. The records in the report are an accurate account of the results. Details of the results are given in the subsequent pages of this report.

Checked By : Shun Wang, Date: Jul. 26, 2010
(Shun Wang)

Approved By : JH, Date: 6/26/2010
(Johnson Ho, Director)

NVLAP[®]

Lab Code: 200099-0



TABLE OF CONTENTS

1. DOCUMENT POLICY AND TEST STATEMENT.....	3
1.1 DOCUMENT POLICY	3
1.2 TEST STATEMENT	3
1.3 EUT MODIFICATION.....	3
2. DESCRIPTION OF EUT AND TEST MODE	4
2.1 GENERAL DESCRIPTION OF EUT	4
2.2 DESCRIPTION OF SUPPORT UNIT	4
2.3 DESCRIPTION OF TEST MODE	5
3 DESCRIPTION OF APPLIED STANDARDS.....	5
4. CONDUCTED EMISSION TEST	5
5 20dB BANDWIDTH.....	6
5.1 LIMIT	6
5.2 TEST EQUIPMENT	6
5.3 TEST SET-UP.....	6
5.4 TEST PROCEDURE.....	6
5.5 EUT OPERATING CONDITION.....	6
5.6 TEST RESULT.....	7
6. RELEASE OR OPERATING TIME	8
6.1 LIMIT	8
6.2 TEST EQUIPMENT	8
6.3 TEST SET-UP.....	8
6.4 TEST PROCEDURE.....	8
6.5 EUT OPERATING CONDITION.....	9
6.6 TEST RESULT.....	9
7. FUNDAMENTAL & SPURIOUS RADIATED EMISSION TEST	10
7.1 LIMIT	10
7.2 TEST EQUIPMENT	11
7.3 TEST SET-UP.....	12
7.4 TEST PROCEDURE.....	14
7.5 EUT OPERATING CONDITION.....	14
7.6 TEST RESULT.....	15
8. PHOTOS OF TESTING	19
9. TERMS OF ABBREVIATION	21

 <p>Spectrum Research & Testing Lab., Inc. No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.: A10070606 Report No.: FCCA10070606 FCCID: OOB2018 Page:3 of 21 Date :Jul. 26, 2010
--	----------------------	---

1. DOCUMENT POLICY AND TEST STATEMENT

1.1 DOCUMENT POLICY

- The report shall not be reproduced except in full, without the written approval of SRT Lab, Inc.
- The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

1.2 TEST STATEMENT

- The test results in the report apply only to the unit tested by SRT Lab.
- There was no deviation from the requirements of test standards during the test.
- DC power source, 9 VDC, was used during the test.

1.3 EUT MODIFICATION

- Serial R180 between X1 and R5
- Remove ANT,L4
- R4 change to 180
- R7,R8 change to 150
- ANT add in 51pf to ground

 <p>Spectrum Research & Testing Lab., Inc. No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.: A10070606 Report No.: FCCA10070606 FCCID: OOB2018 Page:4 of 21 Date :Jul. 26, 2010
---	----------------------	---

2. DESCRIPTION OF EUT AND TEST MODE

2.1 GENERAL DESCRIPTION OF EUT

Product	Wireless Call Pendant
Model NO.	2018
Power Supply	DC 9V / 0.1A
Frequency Band	UHF Band 430-470 MHz
Carrier Frequency	433.92 MHz
Number of Channel	1
RF Output Power	4mW
Modulation Type	FSK
I.F. & L.O.	I.F. : None ; L.O. : 72.320 MHz
Duty Cycle	10 %
Mode of operation	Simplex
Bit Rate of Transmission	512 or 1200 or 2400 bps
Antenna Type	NA
Antenna Gain	NA
Operating Temperature Range	0 ~ 50 °C

NOTE :

1. For more detailed information, please refer to the EUT's specification or user's manual provided by manufacturer.

2.2 DESCRIPTION OF SUPPORT UNIT

The transmitter part of EUT was tested along and configured by the requirement of ANSI C63.4. All interface ports were connected to the appropriate support units via specific cables. The support units and cables are listed below.

No	Device	Brand	Model #	FCC ID/DoC	Cable
	N/A				

NOTE : For the actual test configuration, please refer to the photos of testing.



**Spectrum Research &
Testing Lab., Inc.**
No. 101-10, Ling 8,
Shan-Tong Li, Chung-Li
City, Taoyuan, Taiwan

TEST REPORT

Reference No.: A10070606
Report No.: FCCA10070606
FCCID: OOB2018
Page:5 of 21
Date :Jul. 26, 2010

2.3 DESCRIPTION OF TEST MODE

Mode	
1	TX
2	Standby

Note: The axis X, Y and Z we evaluate in chamber, the X axis is worst case.

X axis:



Y axis:



Z axis:



3 DESCRIPTION OF APPLIED STANDARDS

The EUT is a kind of wireless product and according to the specifications provided by the applicant, must comply with the requirements of the following standards:

47 CFR Part 15, Subpart C
ANSI C63.4: 2003

All tests have been performed and recorded as the above standards.

4. CONDUCTED EMISSION TEST

The test item was not performed, because the EUT uses 9Vdc battery as power source.

 <p>Spectrum Research & Testing Lab., Inc. No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.: A10070606 Report No.: FCCA10070606 FCCID: OOB2018 Page:6 of 21 Date :Jul. 26, 2010
---	----------------------	---

5 20dB BANDWIDTH

5.1 LIMIT

FREQUENCY (MHz)	BANDWIDTH LIMIT(kHz)
Above 70-900	0.25%×Center Frequency(MHz)
Above 900	0.5%×Center Frequency(MHz)

NOTE:

1. Bandwidth is determined at the points 20dB down from the modulated carrier.


5.2 TEST EQUIPMENT

The following test equipment was used during the test:

Equipment/ Facilities	Specifications	Manufacturer	Model#/ Serial#	Due Date of Cal. & Cal. center
SPECTRUM	9kHz-40GHz	ROHDE & SCHWARZ	FSP40/ 100093	Dec. 2010 R&S

NOTE: The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

5.3 TEST SET-UP



The EUT was connected to a spectrum through a 50Ω RF cable.

5.4 TEST PROCEDURE

Please refer to FCC Part15C 15.231(C).

5.5 EUT OPERATING CONDITION

The EUT was operated in continually transmitting mode.



**Spectrum Research &
Testing Lab., Inc.**
No. 101-10, Ling 8,
Shan-Tong Li, Chung-Li
City, Taoyuan, Taiwan


TEST REPORT

Reference No.: A10070606
Report No.: FCCA10070606
FCCID: OOB2018
Page: 7 of 21
Date : Jul. 26, 2010

5.6 TEST RESULT

Temperature:	25°C	Humidity:	61%RH
Spectrum Detector:	PK	Tested by:	Shunm Wang
Test Result:	PASS	Tested Date:	Jul. 09, 2010

CHANNEL UMBER	CHANNEL FREQUENCY (MHz)	20dB DOWN BW (kHz)	MAXIMUM LIMIT (kHz)
1	433.924	264.0	1084.8



 <p>Spectrum Research & Testing Lab., Inc. No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.: A10070606 Report No.: FCCA10070606 FCCID: OOB2018 Page:8 of 21 Date :Jul. 26, 2010
---	----------------------	---

6. RELEASE OR OPERATING TIME

6.1 LIMIT

1. A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.
2. A transmitter activated automatically shall cease transmission within 5 seconds after activation.
- 3). Periodic transmissions at regular predetermined intervals are not permitted. However, polling or supervision transmissions to determine system integrity of transmitters used in security or safety applications are allowed if the periodic rate of transmission does not exceed one transmission of not more than one second duration per hour for each transmitter.
4. Intentional radiators, which are employed for radio control purposes during emergencies involving fire, security, and safety of life, when activated to signal an alarm, may operate during the pungency of the alarm condition.

6.2 TEST EQUIPMENT


The following test equipment was used during the radiated emission test :

EQUIPMENT/ FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/ SERIAL#	DUE DATE OF CAL. & CAL. CENTER
OSCILLOSCOPE	500MHz	HP	54616B/ US39150351	NOV. 2010 ETC

NOTE:

1. The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

6.3 TEST SET-UP



6.4 TEST PROCEDURE

A specific loop antenna was connected to oscilloscope to detect the EUT's release time. The oscilloscope displayed the EUT's release time and took a picture of measurement.



**Spectrum Research &
Testing Lab., Inc.**
No. 101-10, Ling 8,
Shan-Tong Li, Chung-Li
City, Taoyuan, Taiwan

TEST REPORT

Reference No.: A10070606
Report No.: FCCA10070606
FCCID: OOB2018
Page:9 of 21
Date :Jul. 26, 2010


6.5 EUT OPERATING CONDITION

The EUT is normal use function.

6.6 TEST RESULT

Temperature:	25°C	Humidity:	61%RH
Test Result:	PASS	Tested by:	Shunm Wang
		Tested Date:	Jul. 09, 2010

Start release time(s)	Stop time(s)	Total release time(s)	Limit of release time<(s)
-1.590	1.520	3.11	5



 <p>Spectrum Research & Testing Lab., Inc. No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.: A10070606 Report No.: FCCA10070606 FCCID: OOB2018 Page:10 of 21 Date :Jul. 26, 2010
---	----------------------	--

7. FUNDAMENTAL & SPURIOUS RADIATED EMISSION TEST

7.1 LIMIT

FCC Part15, Subpart C Section 15.209 limit of radiated emission for frequency below1000MHz. The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Distance (m)	Field Strength (dB μ V/m)
30 - 88	3	40.0
88 - 216	3	43.5
216 - 960	3	46.0
ABOVE 960	3	54.0

NOTE : 1. In the emission tables above , the tighter limit applies at the band edges.

2. Distance refers to the distance between measuring instrument , antenna , and the closest point of any part of the device or system.

FCC part15C 15.231(b) limit of fundamental and spurious emissions measurement.

FREQUENCY (MHz)	Field Strength of Fundamental (microvolts/meter)	Field Strength of Spurious Emissions (microvolts/meter)
40.66-40.70	2250	225
70-130	1250	125
130-174	1250 to 3750 (NOTE 5)	125 to 375 (NOTE 7)
174-260	3750	375 (NOTE 7)
260-470	3750 to 12500 (NOTE 6)	375 to 1250
Above 470	12500	1250

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB μ V/m) = 20 log Emission level (μ V/m).
3. In the emission tables above, the tighter limit applies at the band edges.
4. Distance refers to the distance between measuring instrument, antenna, and the closest point of any part of the device or system.
5. Limit = $20\log(56.81818(F) - 6136.3636)$; F : Fundamental Frequency (MHz)
6. Limit = $20\log(41.667 \times F - 7083.3333)$; F : Fundamental Frequency (MHz)
7. Limit = The Limit of Fundamental Frequency – 20dB
8. The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.

 <p>Spectrum Research & Testing Lab., Inc. No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.: A10070606 Report No.: FCCA10070606 FCCID: OOB2018 Page:11 of 21 Date :Jul. 26, 2010
---	----------------------	--

7.2 TEST EQUIPMENT

The following test equipment was used during the radiated emission test :

Equipment/ Facilities	Specification	Manufacturer	Model#/ Serial#	Due Date of Cal. & Cal. Center
EMI TEST RECEIVER	20 MHz TO 1000 MHz	ROHDE & SCHWARZ	ESVS30 / 841977/003	DEC. 2010 ETC
BI-LOG ANTENNA	30 MHz TO 2 GHz	SCHAFFNER	CBL6141A / 4181	MAY. 2011 ETC
OATS MEASUREMENT	3 – 10 M MEASUREMENT	SRT	SRT-1	NOV. 2010 SRT
COAXIAL CABLE	30M	TIMES	LMR-400 / #30M	MAY. 2011 ETC
FILTER	2 LINE, 30A	FIL.COIL	FC-943 / 869	NCR
SPECTRUM ANALYZER	9K-40GHz	R&S	FSP40/ 100093	DEC. 2010 ETC
PRE-AMPLIFIER	1 GHz TO 26.5 GHz	HP	8449B/ 3008A01995	JAN. 2011 ETC
HORN ANTENNA	1 GHz TO 18 GHz	EMCO	3115/ 6881	NOV. 2010 ETC
K-TYPE CABLE	15M	HUBER SUHNER	SF 102-40/2*11/ 23932/2	MAY. 2011 ETC
K-TYPE CABLE	1M	HUBER SUHNER	SF 102-40/2*11/ 23934/2	NOV. 2010 ETC


NOTE:

The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.



7.3 TEST SET-UP

30MHz – 1GHz




NOTE :

1. The EUT system was put on a wooden table with 0.8m heights above a ground plane.
2. For the actual test configuration, please refer to the photos of testing.



1GHz - 5GHz



NOTE :

- 1.The EUT system was put on a wooden table with 0.8m heights above a ground plane.
- 2.For the actual test configuration, please refer to the photos of testing.



**Spectrum Research &
Testing Lab., Inc.**
No. 101-10, Ling 8,
Shan-Tong Li, Chung-Li
City, Taoyuan, Taiwan

TEST REPORT

Reference No.: A10070606
Report No.: FCCA10070606
FCCID: OOB2018
Page:14 of 21
Date :Jul. 26, 2010

7.4 TEST PROCEDURE

The EUT was tested according to the requirement of ANSI C63.4 and CISPR 22. The measurements were made at an open area test site with 3 meter measurement distance under 1 GHz and with 3m distance above 1GHz. The frequency spectrum measured started from 30 MHz. Under 1 GHz. All readings were quasi-peak values with 120 kHz resolution bandwidth of the test receiver. Above 1 GHz, the measurements were made at an open area test site with 3 meter measurement distance and all readings were peak and average values with 1 MHz resolution bandwidth of the test receiver. The EUT system was operated in all typical methods by users. The cables connected to EUT and support units were moved to find the maximum emission levels for each frequency.

7.5 EUT OPERATING CONDITION

The EUT was operated in continuunely transmitting and standby mode.



**Spectrum Research &
Testing Lab., Inc.**
No. 101-10, Ling 8,
Shan-Tong Li, Chung-Li
City, Taoyuan, Taiwan

TEST REPORT

Reference No.: A10070606
Report No.: FCCA10070606
FCCID: OOB2018
Page:15 of 21
Date :Jul. 26, 2010

7.6 TEST RESULT

Temperature: 30°C
Frequency Range: 30 – 1000 MHz
Receiver Detector: Q.P.
Tested By: Shunm Wang

Humidity: 54 %RH
Measured Distance: 3m
Tested Mode: Tx
Tested Date: Jul. 23, 2010

Antenna Polarization: Horizontal

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Data (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	AZ(°)	EL(m)
145.4100	1.70	12.65	19.1	33.5	43.5	-10.1	253	2.05
218.0663	2.00	13.00	25.4	40.4	46.0	-5.6	274	1.74
290.8010	2.40	13.30	23.9	39.6	46.0	-6.4	269	1.51
363.1560	2.65	15.41	20.2	38.3	46.0	-7.7	281	1.43
433.920(F)	2.93	16.96	55.6	75.5	80.8	-5.3	259	1.53
580.4320	3.46	19.20	17.5	40.2	46.0	-5.8	262	1.49

Antenna Polarization: Vertical

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Data (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	AZ(°)	EL(m)
145.4110	1.70	12.65	16.2	30.6	43.5	-13.0	194	1.36
218.0660	2.00	13.00	23.1	38.1	46.0	-7.9	203	1.27
290.8009	2.40	13.30	20.6	36.3	46.0	-9.7	185	1.49
363.1558	2.65	15.41	16.9	35.0	46.0	-11.0	209	1.22
433.920(F)	2.93	16.96	52.7	72.6	80.8	-8.2	211	1.31
580.4319	3.46	19.20	14.8	37.5	46.0	-8.5	195	1.18

NOTE :

1. Measurement uncertainty is +/-2.3dB.
2. **: Measurement does not apply for this frequency.
3. Emission Level = Reading Value + Ant. Factor + Cable Loss.
4. The field strength of other emission frequencies were very low against the limit.
5. (F): The field strength of fundamental frequency.
6. Fundamental Limit = $(41.6667 * F) - 7083.3333 = 10996.6811 \mu\text{V/m} = 80.82 \text{ dB}\mu\text{V/m}$



**Spectrum Research &
Testing Lab., Inc.**
No. 101-10, Ling 8,
Shan-Tong Li, Chung-Li
City, Taoyuan, Taiwan

TEST REPORT

Reference No.: A10070606
Report No.: FCCA10070606
FCCID: OOB2018
Page:16 of 21
Date :Jul. 26, 2010

Temperature: 30 °C
Frequency Range: 1 – 5 GHz
Receiver Detector: PK. or AV.
Tested By: Shunm Wang

Humidity: 54 %RH
Measured Distance: 3m
Tested Mode: Tx
Tested Date: Jul. 23, 2010

Antenna Polarization : Horizontal

Frequency (MHz)	Correct Factor (dB)	Ant. Factor (dB/m)	Reading Data (dB μ V)		Emission Level (dB μ V/m)		Limit (dB μ V/m)		Margin (dB)		AZ (°)	EL (m)
			PK.	AV.	PK.	AV.	PK.	AV.	PK.	AV.		
1089.25	-28.20	24.51	46.9	39.3	43.2	35.6	74.0	54.0	-30.8	-18.4	151	1.51
1161.50	-27.80	24.69	48.2	41.2	45.0	38.1	74.0	54.0	-29.0	-15.9	193	1.49
1233.75	-27.40	24.86	44.3	37.5	41.8	35.0	74.0	54.0	-32.2	-19.0	175	1.25
1820.25	-24.62	26.65	46.2	39.9	48.3	41.9	74.0	54.0	-25.7	-12.1	166	1.37
1909.50	-24.26	26.97	44.4	37.5	47.1	40.2	74.0	54.0	-26.9	-13.8	169	1.14
3855.75	-18.82	32.09	29.4	*	42.7	*	74.0	54.0	-31.3	*	200	1.05

Antenna Polarization : Vertical

Frequency (MHz)	Correct Factor (dB)	Ant. Factor (dB/m)	Reading Data (dB μ V)		Emission Level (dB μ V/m)		Limit (dB μ V/m)		Margin (dB)		AZ (°)	EL (m)
			PK.	AV.	PK.	AV.	PK.	AV.	PK.	AV.		
1089.25	-28.20	24.51	48.5	41.3	44.8	37.6	74.0	54.0	-29.2	-16.4	292	1.25
1161.50	-27.80	24.69	51.7	44.7	48.6	41.5	74.0	54.0	-25.4	-12.5	251	1.16
1233.75	-27.40	24.86	48.5	41.9	45.9	39.4	74.0	54.0	-28.1	-14.6	266	1.12
1606.00	-25.48	25.88	49.4	42.7	49.8	43.1	74.0	54.0	-24.2	-10.9	305	1.26
1378.25	-26.58	25.21	45.9	38.2	44.5	36.8	74.0	54.0	-29.5	-17.2	259	1.41
3447.50	-19.77	30.99	29.6	*	40.8	*	74.0	54.0	-33.2	*	312	1.11

NOTE :

1. Measurement uncertainty is +/-2.4dB.
2. **: The Peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. Emission Level = Reading Value + Ant. Factor + Correct Factor (incl.:Cable Loss and Pre-Amplifier Gain)
4. The field strength of other emission frequencies were very low against the limit.



**Spectrum Research &
Testing Lab., Inc.**
No. 101-10, Ling 8,
Shan-Tong Li, Chung-Li
City, Taoyuan, Taiwan

TEST REPORT

Reference No.: A10070606
Report No.: FCCA10070606
FCCID: OOB2018
Page:17 of 21
Date :Jul. 26, 2010

Temperature: 30°C
Frequency Range: 30 – 1000 MHz
Receiver Detector: Q.P.
Tested By: Shunm Wang

Humidity: 54 %RH
Measured Distance: 3m
Tested Mode: Standby
Tested Date: Jul. 23, 2010

Antenna Polarization: Horizontal

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Data (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	AZ(°)	EL(m)
39.7100	0.99	19.50	10.6	31.1	40.0	-8.9	107	1.95
56.6750	1.16	11.26	15.3	27.7	40.0	-12.3	224	1.61
78.5330	1.28	8.16	9.8	19.2	40.0	-20.8	116	1.81
117.3050	1.50	11.63	7.9	21.0	43.5	-22.5	195	1.43
192.4750	1.90	11.08	13.5	26.5	43.5	-17.0	201	1.52
342.8250	2.57	14.91	8.7	26.2	46.0	-19.8	161	1.29

Antenna Polarization: Vertical

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Data (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	AZ(°)	EL(m)
39.7120	0.99	19.50	11.5	32.0	40.0	-8.0	358	1.34
56.6753	1.16	11.26	14.9	27.3	40.0	-12.7	305	1.28
78.5330	1.28	8.16	9.1	18.5	40.0	-21.5	6	1.41
117.3048	1.50	11.63	7.1	20.2	43.5	-23.3	341	1.22
224.0530	2.04	13.00	12.6	27.6	46.0	-18.4	329	1.15
493.1753	3.17	17.90	8.2	29.3	46.0	-16.7	338	1.19

NOTE :

1. Measurement uncertainty is +/-2.3dB.
2. **: Measurement does not apply for this frequency.
3. Emission Level = Reading Value + Ant. Factor + Cable Loss.
4. The field strength of other emission frequencies were very low against the limit.



**Spectrum Research &
Testing Lab., Inc.**
No. 101-10, Ling 8,
Shan-Tong Li, Chung-Li
City, Taoyuan, Taiwan

TEST REPORT

Reference No.: A10070606
Report No.: FCCA10070606
FCCID: OOB2018
Page:18 of 21
Date :Jul. 26, 2010

Temperature: 30 °C
Frequency Range: 1 – 5 GHz
Receiver Detector: PK. or AV.
Tested By: Shunm Wang

Humidity: 54 %RH
Measured Distance: 3m
Tested Mode: Standby
Tested Date: Jul. 23, 2010

Antenna Polarization : Horizontal

Frequency (MHz)	Correct Factor (dB)	Ant. Factor (dB/m)	Reading Data (dB μ V)		Emission Level (dB μ V/m)		Limit (dB μ V/m)		Margin (dB)		AZ (°)	EL (m)
			PK.	AV.	PK.	AV.	PK.	AV.	PK.	AV.		
1085.00	-28.22	24.50	*	*	*	*	74.0	54.0	*	*	*	*
1399.50	-26.47	25.26	*	*	*	*	74.0	54.0	*	*	*	*
1599.25	-25.50	25.86	*	*	*	*	74.0	54.0	*	*	*	*
1930.75	-24.18	27.05	*	*	*	*	74.0	54.0	*	*	*	*
2385.50	-22.75	28.07	*	*	*	*	74.0	54.0	*	*	*	*
4011.00	-18.47	32.50	*	*	*	*	74.0	54.0	*	*	*	*

Antenna Polarization : Vertical

Frequency (MHz)	Correct Factor (dB)	Ant. Factor (dB/m)	Reading Data (dB μ V)		Emission Level (dB μ V/m)		Limit (dB μ V/m)		Margin (dB)		AZ (°)	EL (m)
			PK.	AV.	PK.	AV.	PK.	AV.	PK.	AV.		
1042.50	-28.46	24.40	*	*	*	*	74.0	54.0	*	*	*	*
1433.50	-26.28	25.34	*	*	*	*	74.0	54.0	*	*	*	*
1994.50	-23.92	27.28	*	*	*	*	74.0	54.0	*	*	*	*
2470.50	-22.49	28.24	*	*	*	*	74.0	54.0	*	*	*	*
2734.50	-21.84	29.14	*	*	*	*	74.0	54.0	*	*	*	*
3924.75	-18.67	32.29	*	*	*	*	74.0	54.0	*	*	*	*

NOTE :

1. Measurement uncertainty is +/-2.4dB.
2. "": The Peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. Emission Level = Reading Value + Ant. Factor + Correct Factor (incl.:Cable Loss and Pre-Amplifier Gain)
4. The field strength of other emission frequencies were very low against the limit.



**Spectrum Research &
Testing Lab., Inc.**
No. 101-10, Ling 8,
Shan-Tong Li, Chung-Li
City, Taoyuan, Taiwan

TEST REPORT

Reference No.: A10070606
Report No.: FCCA10070606
FCCID: OOB2018
Page:21 of 21
Date :Jul. 26, 2010

9. TERMS OF ABBREVIATION

AV.	Average detection
AZ(°)	Turn table azimuth
Correct.	Correction
EL(m)	Antenna height (meter)
EUT	Equipment Under Test
Horiz.	Horizontal direction
LISN	Line Impedance Stabilization Network
NSA	Normalized Site Attenuation
Q.P.	Quasi-peak detection
SRT Lab	Spectrum Research & Testing Laboratory, Inc.
Vert.	Vertical direction