



Nemko Test Report: 3W07093

Applicant: WaveCom Electronics Inc.
250 Cardinal Place
Saskatoon, Saskatchewan
S7L 6H7

**Equipment Under Test:
(E.U.T.)** TR2126SE

FCC ID: 0PPTR2126SE

In Accordance With: **FCC PART 21, Subpart K**
Multipoint Distribution Service

Tested By: Nemko Canada Inc.
303 River Road, R.R. 5
Ottawa, Ontario K1V 1H2

Authorized By: 
Russell Grant, Senior Technical Assessor

Date: 23 May 2003

Total Number of Pages: 22

EQUIPMENT: TR2126SE
FCC ID: 0PPTR2126SE

Table of Contents

Section 1.	Summary of Test Results	3
Section 2.	General Equipment Specification.....	5
Section 3.	RF Power Output.....	6
Section 4.	Occupied Bandwidth	7
Section 5.	Spurious Emissions at Antenna Terminals	16
Section 6.	Field Strength of Spurious	19
Section 7.	Frequency Stability	21
Section 8.	Test Equipment List	22
Annex A	Test Diagrams.....	A1

EQUIPMENT: TR2126SE

FCC ID: 0PPTR2126SE

Section 1. Summary of Test Results

General

All measurements are traceable to national standards.

These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with FCC Part 21, Subpart K.



New Submission



Production Unit



Class II Permissive Change



Pre-Production Unit

THIS TEST REPORT RELATES ONLY TO THE ITEM(S) TESTED.

THE FOLLOWING DEVIATIONS FROM, ADDITIONS TO, OR EXCLUSIONS FROM THE TEST SPECIFICATIONS HAVE BEEN MADE.

See " Summary of Test Data".



TESTED BY: _____ DATE: 22 May 2003

Glen Westwell, Wireless Technologist

Nemko Canada Inc. authorizes the above named company to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko Canada Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

This report applies only to the items tested.

EQUIPMENT: TR2126SE
FCC ID: 0PPTR2126SE

Summary Of Test Data

Name Of Test	Para. No.	Result
RF Power Output	2.1046	Complies
Occupied Bandwidth	2.1049	Complies
Spurious Emissions @ Antenna Terminals	2.1051	Complies
Field Strength of Spurious Radiation	2.1053	Complies
Frequency Stability	2.1055	Complies

Footnotes For N/A's:

Test Conditions:

Indoor Temperature: 22°C
 Humidity: 40%

Outdoor Temperature: 10°C
 Humidity: 42%

EQUIPMENT: TR2126SE
FCC ID: 0PPTR2126SE

Section 2. General Equipment Specification

Manufacturer:	WaveCom Electronics Inc.
Model No.:	TR2126SE
Serial No.:	#3936
Date Received In Laboratory:	28 April 2003
Nemko Identification No.:	Item #1
Power Input:	120 VAC Wall Plug Power Supply
Frequency Range:	2150 – 2162 MHz
Type(s) of Modulation:	QPSK & 16 QAM at: 2560, 1280, 640, 320 & 160ksym/s
Emission Designator:	3M2G1W 3M2D1W
RF Power Output Rated:	0.316W (25dBm)

EQUIPMENT: TR2126SE
FCC ID: 0PPTR2126SE

Section 3. RF Power Output

Para. No.: 2.1046

Test Performed By: Glen Westwell	Date of Test: 12 May 2003
---	----------------------------------

Minimum Standard: Para. No.21.107

Test Results: Complies. The RF power output power is within 1 dB of the manufacturer's rating.

Rated Power: 25.0dBm (0.316W)

Measurement Data

Measured Power at antenna port (dBm)		
kSym/s	16 QAM	QPSK
2560	25.4	25.2
1280	25.6	25.4
640	25.7	25.3
320	25.6	25.3
160	25.5	25.3

EQUIPMENT: TR2126SE
FCC ID: 0PPTR2126SE

Section 4. Occupied Bandwidth

Para. No.: 2.1049

Test Performed By: Glen Westwell	Date of Test: 12 May 2003
---	----------------------------------

Minimum Standard: Para. No. 21.908 (d).


Test Results: Complies.

Test Data: See attached graph(s).

Note: Measured in accordance with 21.908(d) for relative power measurements.
RBW1=RBW2=300kHz
Compliance was determined at maximum and minimum symbol rates using QPSK & 16QAM modulations at band edges.


EQUIPMENT: TR2126SE

FCC ID: 0PPTR2126SE




EQUIPMENT: TR2126SE

FCC ID: 0PPTR2126SE




EQUIPMENT: TR2126SE

FCC ID: 0PPTR2126SE




EQUIPMENT: TR2126SE

FCC ID: 0PPTR2126SE




EQUIPMENT: TR2126SE

FCC ID: 0PPTR2126SE




EQUIPMENT: TR2126SE

FCC ID: 0PPTR2126SE




EQUIPMENT: TR2126SE

FCC ID: 0PPTR2126SE



EQUIPMENT: TR2126SE

FCC ID: 0PPTR2126SE



EQUIPMENT: TR2126SE
FCC ID: 0PPTR2126SE

Section 5. Spurious Emissions at Antenna Terminals

Para. No.: 2.1051

Test Performed By: Glen Westwell	Date of Test: 13 May 2003
---	----------------------------------


Minimum Standard: Para. No. 21.908(d) 60 dB.

Test Results: Complies.
 No emissions detected.


Test Data: See attached graph(s).

Note: Measured in accordance with 21.908 (d) for relative power
 measurements. RBW 1 = RBW2 = 100 kHz.

EQUIPMENT: TR2126SE
FCC ID: 0PPTR2126SE



EQUIPMENT: TR2126SE
FCC ID: 0PPTR2126SE



EQUIPMENT: TR2126SE
FCC ID: 0PPTR2126SE

Section 6. Field Strength of Spurious

Para. No.: 2.1053

Test Performed By: Glen Westwell	Date of Test: 13 May 2003
---	----------------------------------


Minimum Standard: Para. No. 21.908(d)

Test Results: Complies.

Test Data: No emissions were detected within 20dB of the specification limit.

EQUIPMENT: TR2126SE
FCC ID: 0PPTR2126SE

Radiated Emissions Set-Up



EQUIPMENT: TR2126SE
FCC ID: 0PPTR2126SE

Section 7. Frequency Stability

Para. No.: 2.1055

Test Performed By: Glen Westwell	Date of Test: 15 May 2003
---	----------------------------------

Minimum Standard: Para. No. 21.101(a), 0.001% (21.6kHz)

Test Results: Complies.

The maximum frequency drift is 6000 Hz.
This is 0.0003%.

Measurement Data: Standard Test Frequency: 2159MHz
Standard Test Voltage: 120 VAC

Test Condition	Frequency Drift (kHz)
20°C STV	0
20°C 115%STV	0
20°C 85% STV	0
-30°C STV	6.0
-20°C STV	1.0
-10°C STV	3.0
0°C STV	1.0
+10°C STV	1.0
+30°C STV	0
+40°C STV	0
+50°C STV	1.0

EQUIPMENT: TR2126SE
FCC ID: 0PPTR2126SE

Section 8. Test Equipment List

CAL CYCLE	EQUIPMENT	MANUFACTURER	MODEL	SERIAL	LAST CAL.	NEXT CAL.
1 Year	Spectrum Analyzer	Hewlett Packard	8565E	FA000981	15 Jul 02	15 Jul 03
1 Year	Climate Chamber	Thermotron	SM-16C	15649-S	COU	COU
1 Year	Signal Generator	Rhode & Schwarz	SM1Q03E	FA001269	06 Dec 02	06 Dec 03
1 Year	Power Meter	Hewlett Packard	E4418B	FA001678	01 Apr 03	01 Apr 04
1 Year	Power Sensor	Hewlett Packard	8487A	FA001741	28 Mar 03	28 Mar 04
1 Year	RF Millivoltmeter	Rohde & Schwarz	URV5	FA001570	10 Apr 03	10 Apr 04
1 Year	Insertion Unit	Rohde & Schwarz	URV5-Z4	FA000905	10 Apr 03	10 Apr 04
1 Year	Horn Antenna	EMCO #2	3115	FA000825	09 Dec 02	09 Dec 03
Extended	Spectrum Analyzer	Hewlett-Packard	8566B	FA001309	Nov. 27/01	May. 27/03
Extended	Spectrum Analyzer Display	Hewlett-Packard	85662A	FA001309	Nov. 27/01	May. 27/03
1 Year	RF AMP	Narda	5 - 18GHz	FA001409	COU	COU
1 Year	RF AMP	JCA	4-8 GHz	FA001497	COU	COU
1 Year	Frequency Counter	Hewlett Packard	HP5350A	FA000086	11 Jan 02	11 Jan 03

NA: Not Applicable
NCR: No Cal Required
COU: CAL On Use

Nemko Canada Inc.

FCC PART 21, SUBPART K
MULTIPOINT DISTRIBUTION SERVICE
PROJECT NO.: 3W07093

EQUIPMENT: TR2126SE
FCC ID: 0PPTR2126SE

Annex A
Test Diagrams


EQUIPMENT: TR2126SE

FCC ID: 0PPTR2126SE

Para. No. 2.1046 - R.F. Power Output




Para. No. 2.1049 - Occupied Bandwidth



EQUIPMENT: TR2126SE


FCC ID: 0PPTR2126SE

Para. No. 2.1051 - Spurious Emissions at Antenna Terminals



Para. No. 2.1053 - Field Strength of Radiation

TIA/EIA-603, Signal Substitution



EQUIPMENT: TR2126SE

FCC ID: 0PPTR2126SE

Para. No. 2.1055 - Frequency Stability

