



AUDIX Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

APPENDIX A

Tel: +886 2 26099301
Fax: +886 2 26099303

APPENDIX A

TEST PLOTS

(Model: AEX-AR9590-NI)

File Number: C1M1604073

Report Number: EM-F160311

This test report may be reproduced in full only. The document may only be updated by AUDIX Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

TABLE OF CONTENTS

A.1 EMISSION BANDWIDTH MEASUREMENT	2
A.1.1 Emission Bandwidth Result.....	2
A.1.2 Measurement Plots	3
A.2 MAXIMUM OUTPUT POWER MEASUREMENT	9
A.2.1 Emission Bandwidth Result.....	9
A.3 EMISSION LIMITATIONS MEASUREMENT.....	11
A.4 POWER SPECTRAL DENSITY.....	35
A.4.1 Power Spectral Density	35

A.1 EMISSION BANDWIDTH MEASUREMENT

Test Date	2016/04/14 ~ 05/20	Temp./Hum.	25 ~ 26°C/54 ~ 60%
Cable Loss	N/A	Test Voltage	DC 3.3V

A.1.1 Emission Bandwidth Result

Modulation Type	UNII Band	Centre Frequency (MHz)	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit
802.11a	I	5180	36.42	18.538	Reference only
		5200	34.79	18.715	
		5240	36.57	18.758	
	II-2A	5260	27.95	16.692	
		5280	28.07	16.683	
		5320	28.84	16.648	
802.11n-HT20	I	5180	22.66	17.818	
		5200	31.56	18.522	
		5240	33.10	18.389	
	II-2A	5260	25.13	17.740	
		5280	23.62	17.707	
		5320	23.40	17.703	
802.11n-HT40	I	5190	57.65	36.392	Reference only
		5230	59.83	36.356	
	II-2A	5270	50.98	36.355	
		5310	40.87	36.147	

Modulation Type	UNII Band	Centre Frequency (MHz)	6dB Bandwidth (MHz)	Limit
802.11a	III	5745	16.35	≥ 500kHz
		5785	16.33	
		5825	16.30	
802.11n-HT20	III	5745	17.07	
		5785	16.08	
		5825	15.80	
802.11n-HT40	III	5755	35.27	
		5795	35.82	


AUDIX Technology Corp.
No. 53-11, Dingkou, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303






A.1.2 Measurement Plots


802.11a

UNII Band I




UNII Band II-2A











802.11n-HT20

UNII Band I



UNII Band II-2A






AUDIX Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan




Tel: +886 2 26099301
Fax: +886 2 26099303


802.11n-HT40

UNII Band I



UNII Band II-2A





A.2 MAXIMUM OUTPUT POWER MEASUREMENT

A.2.1 Emission Bandwidth Result

Test Date	2016/05/15	Temp./Hum.	26°C/54%
Cable Loss	N/A	Test Voltage	DC 3.3V

Modulation Type	UNII Band	Centre Frequency (MHz)	Output Power	10log (1/X)	MAX Output Power		Limit
			(dBm)		(dBm)	(W)	
802.11a	I	5180	14.24	0.22	14.46	0.028	< 250 mW (24 dBm)
		5200	14.20		14.42	0.028	
		5240	15.45		15.67	0.037	
	II-2A	5260	15.50		15.72	0.037	< 250 mW (24 dBm)
		5280	14.85		15.07	0.032	
		5320	15.11		15.33	0.034	
	III	5745	16.65		16.87	0.049	< 1 W (30 dBm)
		5785	18.03		18.25	0.067	
		5825	17.85		18.07	0.064	

Note: The results have been included cable loss.

AUDIX Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

Modulation Type	UNII Band	Centre Frequency (MHz)	Output Power			10log (1/X)	MAX Output Power		Limit
			Chain 0	Chain 1	Chain 2		(dBm)	(W)	
802.11n-HT20	I	5180	10.24	10.46	9.62	0.51	15.40	0.035	<0.105 W (20.23 dBm) Note 2
		5200	10.22	10.29	10.04		15.46	0.035	
		5240	10.36	10.43	10.32		15.65	0.037	
	II-2A	5260	10.87	11.15	11.02		16.29	0.043	<0.105 W (20.23 dBm) Note 2
		5280	10.25	10.43	11.37		15.99	0.040	
		5320	10.12	10.03	10.58		15.53	0.036	
	III	5745	13.23	13.65	13.76		18.83	0.076	< 0.420 W (26.23 dBm) Note 3
		5785	16.62	17.24	16.82		22.18	0.165	
		5825	16.74	17.28	16.84		22.24	0.167	
802.11n-HT40	I	5190	9.79	9.83	8.86	0.76	15.04	0.032	<0.105 W (20.23 dBm) Note 2
		5230	14.91	13.63	13.94		19.72	0.094	
	II-2A	5270	14.85	13.63	13.85		19.67	0.093	<0.105 W (20.23 dBm) Note 2
		5310	9.80	8.67	9.65		14.93	0.031	
	III	5755	10.24	11.19	11.40		16.50	0.045	< 0.420 W (26.23 dBm) Note 3
		5795	14.02	14.17	14.51		19.77	0.095	

Note 1: The results have been included cable loss.

Note 2: 802.11n Directional gain is 9.77dBi > 6dBi, the Limit is 24 – (9.77-6) = 20.23 dBm

Note 3: 802.11n Directional gain is 9.77dBi > 6dBi, the Limit is 30 – (9.77-6) = 26.23dBm