



PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA

Tel. 410.290.6652 / Fax 410.290.6554

<http://www.pctestlab.com>



CERTIFICATE OF COMPLIANCE FCC PART 15.247 Certification

Applicant Name:

ProSoft Technology, Inc.
1675 Chester Ave 4th Floor
Bakersfield, CA 93301

Date of Testing:

August 28 - 29, 2007

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Test Report Serial No.:

0707060700.OQ7

FCC ID: OQ7IHW

APPLICANT: ProSoft Technology, Inc.

Model(s): RLX-IHW

EUT Type: 802.11a/b/g Transmitter

6.64 mW (8.22 dBm) Conducted (b)

Max. RF Output Power: 6.34 mW (8.02 dBm) Conducted (g)

2.79 mW (4.46 dBm) Conducted (a)

Frequency Range: 2412 - 2462 MHz (DSSS/OFDM)

5745 – 5825 MHz (OFDM)

FCC Classification: Digital Transmission System (DTS)

FCC Rule Part(s): Part 15.247

Test Device Serial No.: N/A

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C-63.4-2003.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Grant Conditions: Listed output power is conducted.

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.

Randy Ortanez
President





FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter	Page 1 of 56

T A B L E O F C O N T E N T S

FCC PART 15.247 MEASUREMENT REPORT.....	3
1.0 INTRODUCTION.....	4
1.1 EVALUATION PROCEDURE.....	4
1.2 SCOPE.....	4
1.3 PCTEST TEST LOCATION.....	4
2.0 PRODUCT INFORMATION	5
2.1 EQUIPMENT DESCRIPTION.....	5
2.2 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS.....	5
2.3 LABELING REQUIREMENTS.....	5
3.0 DESCRIPTION OF TEST	6
3.1 CONDUCTED EMISSIONS.....	6
3.2 RADIATED EMISSIONS	7
4.0 ANTENNA REQUIREMENTS.....	8
5.0 TEST EQUIPMENT CALIBRATION DATA.....	9
6.0 TEST RESULTS	10
6.1 SUMMARY	10
6.2 6DB BANDWIDTH MEASUREMENT – 802.11A/B/G	11
6.3 OUTPUT POWER MEASUREMENT – 802.11B.....	17
6.4 OUTPUT POWER MEASUREMENT – 802.11G.....	18
6.5 OUTPUT POWER MEASUREMENT – 802.11A (5.8GHZ)	19
6.6 POWER SPECTRAL DENSITY (802.11A/B/G).....	20
6.7 OUT OF BAND EMISSIONS AT THE BAND EDGE	26
6.8 OUT OF BAND EMISSIONS.....	29
6.9 RADIATED SPURIOUS EMISSION MEASUREMENTS.....	35
6.10 RADIATED RESTRICTED BAND EDGE MEASUREMENTS	48
6.11 LINE-CONDUCTED TEST DATA.....	50
7.0 CONCLUSION	56

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter	Page 2 of 56



MEASUREMENT REPORT

FCC Part 15.247

§ 2.1033 General Information

APPLICANT: ProSoft Technology, Inc.

APPLICANT ADDRESS: 1675 Chester Ave 4th Floor
Bakersfield, CA 93301

TEST SITE: PCTEST ENGINEERING LABORATORY, INC.

TEST SITE ADDRESS: 6660-B Dobbin Road, Columbia, MD 21045 USA

FCC RULE PART(S): Part 15.247

MODEL NAME: RLX-IHW

FCC ID: OQ7IHW

Test Device Serial No.: N/A Production Pre-Production Engineering

FCC CLASSIFICATION: Digital Transmission System (DTS)


DATE(S) OF TEST: August 28 - 29, 2007

TEST REPORT S/N: 0707060700.OQ7

Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21045, U.S.A.

- PCTEST facility is an FCC registered (PCTEST Reg. No. 90864) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (IC-2451).
 - PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
 - PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
 - PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
 - PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
 - PCTEST facility is an IC registered (IC-2451) test laboratory with the site description on file at Industry Canada.
 - PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.



FCC ID: OQ7IHW	 FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter	Page 3 of 56

1.0 INTRODUCTION

1.1 Evaluation Procedure

The measurement procedure described in the American National Standard for Methods of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz (ANSI C63.4-2003) and FCC procedure dated March 23, 2005 entitled "Measurements of Digital Transmission Systems Operating Under Section 15.247" were used in the measurement of the **ProSoft 802.11a/b/g Transmitter FCC ID: OQ7IHW**.

Deviation from measurement procedure.....None

1.2 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.

1.3 PCTEST Test Location

The map at the right shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity are, the Baltimore-Washington Internt'l (BWI) airport, the city of Baltimore and the Washington, DC area. (see Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2003 on January 27, 2006 and Industry Canada.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 4 of 56

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **ProSoft 802.11a/b/g Transmitter FCC ID: OQ7IHW**. The EUT consisted of the following component(s):

Manufacturer / Model	FCC ID	Description
ProSoft / Model: RLX-IHW	OQ7IHW	802.11a/b/g Transmitter
Maxrad / Model: MP24580809PT	N/A	2.4GHz Mast Mount Directional Panel Antenna (8dBi Gain)
Maxrad / Model: MMO24580608NF	N/A	2.4/5.8GHz Omni-directional Monopole Antenna (6dBi Gain at 2.4GHz / 8dBi Gain at 5.8GHz)
Pacific Wireless / Model: GD58-29	N/A	5.8GHz Parabolic Grid Antenna (29dBi Gain)

Table 2-1. EUT Equipment Description

2.2 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

2.3 Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the trade name and FCC ID must be displayed on the device per Section 15.19(b)(2).

Please see attachment for FCC ID label and label location.

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 5 of 56

3.0 DESCRIPTION OF TEST

3.1 Conducted Emissions




Figure 3-1. Shielded Enclosure Line-Conducted Test Facility




Figure 3-2. Line Conducted Emission Test Set-Up




Figure 3-3. Wooden Table & Bonded LISNs




Figure 3-4. LISN Schematic Diagram

The line-conducted facility is located inside a 16'x20'x10' shielded enclosure, manufactured by Ray Proof Series 81 (see *Figure 3-1*). The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 1.5m away from the sidewall of the shielded room (see *Figure 3-2*). Solar Electronics and EMCO Model 3725/2 (10kHz-30MHz) 50Ω/50µH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room (see *Figure 3-3*). The EUT is powered from the Solar LISN and the support equipment is powered from the EMCO LISN. Power to the LISNs are filtered by a high-current high-insertion loss Ray Proof power line filter (100dB 14Hz-10GHz). The purpose of the filter is to attenuate ambient signal interference and this filter is also bonded to the shielded enclosure. All electrical cables are shielded by braided tinned copper zipper tubing with an inner diameter of 1/2". If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the Solar LISN. The LISN schematic diagram is shown (see *Figure 3-4*). All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion). Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer to determine the frequency producing the maximum EME from the EUT.

The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to CISPR quasi-peak and average mode. The bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each EME emission. Each emission was maximized by: switching power lines; varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and/or support equipment, and powering the monitor from the floor mounted outlet box and the computer aux AC outlet, if applicable; whichever determined the worst-case emission. Photographs of the worst-case emission can be seen in the test setup photographs. Each EME reported was calibrated using the Agilent E8257D (250kHz – 20GHz) PSG Signal Generator.

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter	Page 6 of 56

3.2 Radiated Emissions




Figure 3-5. 3-Meter Test Site




Figure 3-6. Dimensions of Outdoor Test Site




Figure 3-7. Turntable and System Setup




Figure 3-8. Normalized Site Attenuation Curves (H&V)

Preliminary measurements were made indoors at 1-meter using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequency producing the maximum EME. Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, and turntable azimuth with respect to the antenna was noted for each frequency found. The spectrum was scanned from 30 to 200 MHz using a bi-conical antenna and from 200 to 1000 MHz using a log-spiral antenna. Above 1 GHz, linearly polarized double ridge horn antennas were used.

Final measurements were made outdoors at 3-meter test range using Roberts™ Dipole antennas or horn antennas (see *Figure 3-5*). The test equipment was placed on a wooden and plastic bench situated on a 1.5m x 2m area adjacent to the measurement area (see *Figure 3-6*). Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The detector function was set to CISPR quasi-peak mode and the bandwidth of the spectrum analyzer was set to 100kHz for frequencies below 1GHz or 1MHz for frequencies above 1GHz. Above 1GHz the detector function was set to average mode (RBW = 1MHz, VBW = 10Hz).

The half-wave dipole antenna was tuned to the frequency found during preliminary radiated measurements. The EUT, support equipment and interconnecting cables were re-configured to the set-up producing the maximum emission for the frequency and were placed on top of a 0.8-meter high non-metallic 1 x 1.5 meter table (see *Figure 3-7*). The EUT, support equipment, and interconnecting cables were re-arranged and manipulated to maximize each EME emission. The turntable containing the system was rotated and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by: varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and/or support equipment, and powering the monitor from the floor mounted outlet box and the computer aux AC outlet, if applicable; and changing the polarity of the antenna, whichever determined the worst-case emission. Photographs of the worst-case emission can be seen in test setup photographs. Each EME reported was calibrated using the Agilent E8257D (250kHz – 20GHz) PSG Signal Generator. The Theoretical Normalized Site Attenuation Curves for both horizontal and vertical polarization are shown in *Figure 3-8*.

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter	Page 7 of 56

4.0 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

- The antennas of the 802.11a/b/g Transmitter are **professionally installed**.
- There are provisions for connection to an external antenna requiring professional installation

Conclusion:

The **ProSoft 802.11a/b/g Transmitter FCC ID: OQ7IHW** unit complies with the requirement of §15.203.

Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437		

Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
-	:	157	5785
-	:	-	:
-	:	-	:
-	:	-	:
-	:	-	:
149	5745	165	5825

Table 4-1. Frequency/ Channel Operations

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 8 of 56

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model / Equipment	Calibration Date	Cal Interval	Calibration Due	Serial No.
Agilent	E4407B ESA Spectrum Analyzer	04/29/07	Annual	04/28/08	US39210313
Agilent	N4010A Wireless Connectivity Test Set	06/11/07	Annual	06/10/08	GB46170464
EMCO	Model 3115 (1-18GHz) Horn Antenna	09/24/06	Biennial	09/23/08	9203-2178
EMCO	Model 3115 (1-18GHz) Horn Antenna	09/25/06	Biennial	09/24/08	9704-5182
Rohde & Schwarz	NRVS Power Meter	07/03/07	Biennial	07/02/09	835360/079
Rohde & Schwarz	NRV-Z53 Power Sensor	07/03/07	Biennial	07/02/09	846076/007
Agilent	HP 8566B (100Hz-22GHz) Spectrum Analyzer	12/21/06	Annual	12/21/07	3638A08713
Agilent	HP 8591A (9kHz-1.8GHz) Spectrum Analyzer	09/20/06	Annual	09/20/07	3144A02458
Agilent	E4448A (3Hz-50GHz) Spectrum Analyzer	09/22/06	Annual	09/22/07	US42510244
Agilent	HP 8591A (9kHz-1.8GHz) Spectrum Analyzer	09/20/06	Annual	09/20/07	3108A02053, 3034A01395
Agilent	E8257D (250kHz-20GHz) Signal Generator	03/08/07	Annual	03/07/08	MY45470194
CCA-7	CISPR QP Adapter	12/21/06	Annual	12/21/07	0194-04082
Agilent	HP 85650A Quasi-Peak Adapter	12/21/06	Annual	12/21/07	2043A00301
CCA-7	CISPR QP Adapter	12/21/06	Annual	12/21/07	0194-04082
Agilent	HP 85650A Quasi-Peak Adapter	12/21/06	Annual	12/21/07	2043A00301
Agilent	HP 8449B (1-26.5GHz) Pre-Amplifier	12/12/06	Annual	12/12/07	3008A00985
Agilent	HP 11713A Attenuation/Switch Driver	12/12/06	Annual	12/12/07	N/A
Agilent	HP 85685A (20Hz-2GHz) Preselector	12/12/06	Annual	12/12/07	N/A
Agilent	HP 8566B Opt. 462 Impulse Bandwidth	12/12/06	Annual	12/12/07	3701A22204
EMCO	Dipole Pair	09/21/06	Biennial	09/20/08	23951
SOLAR	8012-50 LISN (2)	11/18/05	Biennial	11/18/07	0313233, 0310234
-	No.165 (30MHz - 1000MHz) RG58 Coax Cable	N/A		N/A	N/A
-	No.166 (1000-26500MHz) Microwave RF Cable	N/A		N/A	N/A
-	No.167 (100kHz - 100MHz) RG58 Coax Cable	N/A		N/A	N/A

Table 5-1. Annual Test Equipment Calibration Schedule

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 9 of 56

6.0 TEST RESULTS

6.1 Summary

Company Name: ProSoft Technology, Inc.
 FCC ID: OQ7IHW
 FCC Classification: Digital Transmission System (DTS)
 Data Rate(s) Tested: 1Mbps, 2Mbps, 5.5Mbps, 11Mbps (b)
6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps (a/g)

FCC Part Section(s)	RSS 210 Section	Test Description	Test Limit	Test Condition	Test Result	Reference
TRANSMITTER MODE (TX)						
15.247(a)(2)	RSS-210 [A8.2 (1)]	6dB Bandwidth	> 500kHz	CONDUCTED	PASS	Section 6.2
15.247(b)(3)	RSS-210 [A8.4 (4)]	Transmitter Output Power	< 1 Watt		PASS	Sections 6.3, 6.4, 6.5
15.247(e)	RSS-210 [A8.2 (2)]	Transmitter Power Spectral Density	< 8dBm / 3kHz Band		PASS	Section 6.6
15.247(d)	RSS-210 [A8.5]	Band Edge / Out-of-Band Emissions	Conducted < 20dBc		PASS	Sections 6.7, 6.8
15.205 15.209	RSS-210 [A8.5]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-210 table 3 limits)	RADIATED	PASS	Sections 6.9, 6.10
15.207	RSS-Gen [7.2.2]	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 limits or < RSS-Gen table 2 limits	LINE CONDUCTED	PASS	Section 6.11
RECEIVER MODE (RX) / DIGITAL EMISSIONS						
15.107	RSS-Gen [7.2.2]	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.107 limits or < RSS-Gen table 2 limits	LINE CONDUCTED	PASS	Part 15B Test Report
15.109	RSS-Gen [7.2.3.2]	General Field Strength Limits (Restricted Bands and Radiated Emissions Limits)	< FCC 15.109 limits or < RSS-210 table 3 limits	RADIATED (30MHz-1GHz) (1-25 GHz)	PASS	Part 15B Test Report
RF EXPOSURE						
2.1091 / 2.1093	RSS-102	MPE Test	1 mW/cm ² (MPE) @ 20cm	MPE	PASS	MPE Report

Table 6-1. Summary of Test Results

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 10 of 56

6.2 6dB Bandwidth Measurement – 802.11a/b/g

§15.247(a)(2); RSS-210(A8.2 (1))

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the receive antenna while the EUT is operating in transmission mode at the appropriate frequencies. ***The minimum permissible 6dB bandwidth is 500 kHz.***

Frequency [MHz]	Channel No.	802.11 Mode	Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]	Pass / Fail
2412	1	b	13.04	0.500	Pass
2437	6	b	13.04	0.500	Pass
2462	11	b	13.08	0.500	Pass
2412	1	g	15.62	0.500	Pass
2437	6	g	15.64	0.500	Pass
2462	11	g	15.64	0.500	Pass
5745	149	a	15.66	0.500	Pass
5785	157	a	15.66	0.500	Pass
5825	165	a	15.64	0.500	Pass

Table 6-2. Conducted Bandwidth Measurements




Figure 6-1. Test Instrument & Measurement Setup

FCC ID: OQ7IHW	 FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter



Plot 6-1. 6dB Bandwidth Plot (802.11b – Ch. 1)




Plot 6-2. 6dB Bandwidth Plot (802.11b – Ch. 6)

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 12 of 56




Plot 6-3. 6dB Bandwidth Plot (802.11b – Ch. 11)




Plot 6-4. 6dB Bandwidth Plot (802.11g – Ch. 1)

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 13 of 56




Plot 6-5. 6dB Bandwidth Plot (802.11g – Ch. 6)




Plot 6-6. 6dB Bandwidth Plot (802.11g – Ch. 11)

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 14 of 56




Plot 6-7. 6dB Bandwidth Plot (802.11a – Ch. 149)



Plot 6-8. 6dB Bandwidth Plot (802.11a – Ch. 157)

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 15 of 56



Plot 6-9. 6dB Bandwidth Plot (802.11a – Ch. 165)

FCC ID: OQ7IHW	 FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter

6.3 Output Power Measurement – 802.11b

§15.247(b)(3); RSS-210(A8.4 (4))

A transmitter antenna terminal of EUT is connected to the input of a RF power sensor. Measurement is made while the EUT is operating in transmission mode at the appropriate frequencies. ***The maximum permissible conducted output power is 1 Watt.***

Freq [MHz]	Channel	Data Rate [Mbps]	Main Ant. Measured Power [dBm]
2412	1	1	8.07
		2	8.05
		5.5	8.04
		11	8.01
2437	6	1	7.92
		2	7.89
		5.5	7.92
		11	7.98
2462	11	1	8.22
		2	8.15
		5.5	8.20
		11	8.18

Table 6-3. Conducted Output Power Measurements




Figure 6-2. Test Instrument & Measurement Setup

FCC ID: OQ7IHW	 FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter

6.4 Output Power Measurement – 802.11g

§15.247(b)(3); RSS-210(A8.4 (4))

A transmitter antenna terminal of EUT is connected to the input of a RF power sensor. Measurement is made while the EUT is operating in transmission mode at the appropriate frequencies. ***The maximum permissible conducted output power is 1 Watt.***

Freq [MHz]	Channel	Data Rate [Mbps]	Main Ant. Measured Power [dBm]
2412	1	6	7.38
		9	7.34
		12	7.62
		18	7.73
		24	5.52
		36	5.64
		48	4.96
		54	4.94
2437	6	6	7.03
		9	7.04
		12	7.41
		18	7.53
		24	5.70
		36	5.70
		48	4.98
		54	4.96

Table 6-4. Conducted Output Power Measurements

Freq [MHz]	Channel	Data Rate [Mbps]	Main Ant. Measured Power [dBm]
2462	11	6	7.55
		9	7.52
		12	7.89
		18	8.02
		24	5.92
		36	5.89
		48	5.30
		54	5.26




Figure 6-3. Test Instrument & Measurement Setup

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 18 of 56

6.5 Output Power Measurement – 802.11a (5.8GHz)

§15.247(b)(3); RSS-210(A8.4 (4))

A transmitter antenna terminal of EUT is connected to the input of a RF power sensor. Measurement is made while the EUT is operating in transmission mode at the appropriate frequencies. ***The maximum permissible conducted output power is 1 Watt.***

Freq [MHz]	Channel	Data Rate [Mbps]	Main Ant. Measured Power [dBm]
5745	149	6	3.95
		9	3.98
		12	4.32
		18	4.46
		24	2.61
		36	2.56
		48	1.15
		54	1.13
5785	157	6	4.01
		9	3.96
		12	4.31
		18	4.42
		24	2.36
		36	2.34
		48	0.81
		54	0.77

Table 6-5. Conducted Output Power Measurements

Freq [MHz]	Channel	Data Rate [Mbps]	Main Ant. Measured Power [dBm]
5825	165	6	2.86
		9	2.83
		12	3.19
		18	3.29
		24	1.10
		36	1.07
		48	-0.33
		54	-0.36




Figure 6-4. Test Instrument & Measurement Setup

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 19 of 56

6.6 Power Spectral Density (802.11a/b/g)

§15.247(e); RSS-210(A8.2 (2))

The peak power density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies. ***The maximum permissible power spectral density is 8 dBm in any 3 kHz band.***

Frequency [MHz]	Channel No.	802.11 Mode	Measured Power Spectral Density [dBm]	Maximum Permissible Power Density [dBm / 3kHz]	Margin [dB]
2412	1	b	-19.570	8.0	-27.6
2437	6	b	-18.800	8.0	-26.8
2462	11	b	-18.750	8.0	-26.8
2412	1	g	-20.500	8.0	-28.5
2437	6	g	-20.480	8.0	-28.5
2462	11	g	-20.180	8.0	-28.2
5745	149	a	-23.730	8.0	-31.7
5785	157	a	-22.630	8.0	-30.6
5825	165	a	-23.340	8.0	-31.3

Table 6-6. Conducted Power Density Measurements






Figure 6-5. Test Instrument & Measurement Setup

FCC ID: OQ7IHW	 FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter




Plot 6-10. Power Spectral Density Plot (802.11b – Ch. 1)




Plot 6-11. Power Spectral Density Plot (802.11b – Ch. 6)

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 21 of 56




Plot 6-12. Power Spectral Density Plot (802.11b – Ch. 11)




Plot 6-13. Power Spectral Density Plot (802.11g – Ch. 1)

FCC ID: OQ7IHW	 PCTEST WIRELESS	FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)	 ProSoft TECHNOLOGY	Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 22 of 56




Plot 6-14. Power Spectral Density Plot (802.11g – Ch. 6)




Plot 6-15. Power Spectral Density Plot (802.11g – Ch. 11)

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 23 of 56




Plot 6-16. Power Spectral Density Plot (802.11a – Ch. 149)



Plot 6-17. Power Spectral Density Plot (802.11a – Ch. 157)

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 24 of 56




Plot 6-18. Power Spectral Density Plot (802.11a – Ch. 165)


FCC ID: OQ7IHW	 PCTEST	FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter	Page 25 of 56

6.7 Out of Band Emissions at the Band Edge

§15.247(d); RSS-210(A8.5)




Plot 6-19. Band Edge Plot (802.11b – Ch. 1)




Plot 6-20. Band Edge Plot (802.11b – Ch. 11)

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 26 of 56




Plot 6-21. Band Edge Plot (802.11g- Ch. 1)




Plot 6-22. Band Edge Plot (802.11g – Ch. 11)

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 27 of 56



Plot 6-23. Band Edge Plot (802.11a – Ch. 149)




Plot 6-24. Band Edge Plot (802.11a – Ch. 165)


FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 28 of 56

6.8 Out of Band Emissions

§15.247(d); RSS-210(A8.5)




Plot 6-25. Conducted Spurious Plot (802.11b – Ch. 1)




Plot 6-26. Conducted Spurious Plot (802.11b – Ch. 1)

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 29 of 56




Plot 6-27. Conducted Spurious Plot (802.11b – Ch. 6)




Plot 6-28. Conducted Spurious Plot (802.11b – Ch. 6)

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 30 of 56




Plot 6-29. Conducted Spurious Plot (802.11b – Ch. 11)



Plot 6-30. Conducted Spurious Plot (802.11b – Ch. 11)

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 31 of 56




Plot 6-31. Conducted Spurious Plot (802.11a – Ch. 149)



Plot 6-32. Conducted Spurious Plot (802.11a – Ch. 149)

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 32 of 56




Plot 6-33. Conducted Spurious Plot (802.11a – Ch. 157)




Plot 6-34. Conducted Spurious Plot (802.11a – Ch. 157)

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 33 of 56



Plot 6-35. Conducted Spurious Plot (802.11a – Ch. 165)



Plot 6-36. Conducted Spurious Plot (802.11a – Ch. 165)

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 34 of 56

6.9 Radiated Spurious Emission Measurements

§15.247(d) / §15.205 & §15.209

The EUT was tested from 9kHz to the tenth harmonic of the fundamental frequency of the transmitter. Below 1GHZ a CISPR quasi peak detector was used. Above 1 GHz average measurements were taken, using RBW= 1MHz, VBW= 10Hz, and linearly polarized horn antennas. In addition, peak measurements (RBW= 1MHz, VBW= 1MHz) were taken to ensure that the peak levels are not more than 20dB above the average limit. No harmonics/spurs peak emissions are more than 20dB above the average limit. Special attention is taken for the EUT's harmonic and spurious radiated emissions in the restricted bands of operations, as defined in Section 15.205.

Frequency	Field Strength [μ V/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 6-7. Radiated Limits

Sample Calculation

- Field Strength Level $[\text{dB}_{\mu\text{V/m}}]$ = Analyzer Level $[\text{dBm}]$ + 107 + AFCL $[\text{dB}]$

Notes:

- AFCL = Antenna Factor $[\text{dB}]$ + Cable Loss $[\text{dB}]$

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter	Page 35 of 56



Radiated Spurious Emission Measurements (Cont'd)

§15.247(d) / §15.205 & §15.209; RSS-210(A8.5)

Mode: 802.11b
Antenna: White Panel
Transfer Rate: 1 Mbps
Operating Frequency: 2412MHz
Channel: 01

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
4824.00	-106.41	Avg	V	40.3	40.92	53.98	-13.06
4824.00	-97.13	Peak	V	40.3	50.20	73.98	-23.78
12060.00	-135.00	Avg	V	51.4	23.39	53.98	-30.58
12060.00	-135.00	Peak	V	51.4	23.39	73.98	-50.58

Table 6-8. Radiated Measurements @ 3 meters

NOTES:

1. All emissions shown lie in the restricted bands specified in §15.205 and RSS-210 section 2.7, Table 1 and are below the limit shown in Table 6-7.
2. Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
5. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported. No significant emissions were found beyond the fifth harmonic for this device.
6. Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
7. Above 960MHz the limit is 500 μ V/m (54dB μ /m) at 3 meters radiated.

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 36 of 56

Radiated Spurious Emission Measurements (Cont'd)

§15.247(d) / §15.205 & §15.209; RSS-210(A8.5)

Mode: 802.11b
 Antenna: White Panel
 Transfer Rate: 1 Mbps
 Operating Frequency: 2437MHz
 Channel: 06

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
4874.00	-104.68	Avg	V	40.50	42.82	53.98	-11.16
4874.00	-96.02	Peak	V	40.50	51.48	73.98	-22.50
7311.00	-108.75	Avg	V	45.96	44.21	53.98	-9.77
7311.00	-100.21	Peak	V	45.96	52.75	73.98	-21.23
12185.00	-135.00	Avg	V	51.35	23.35	53.98	-30.63
12185.00	-135.00	Peak	V	51.35	23.35	73.98	-50.63

Table 6-9. Radiated Measurements @ 3 meters

NOTES:

1. All emissions shown lie in the restricted bands specified in §15.205 and RSS-210 section 2.7, Table 1 and are below the limit shown in Table 6-7.
2. Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
5. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported. No significant emissions were found beyond the fifth harmonic for this device.
6. Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
7. Above 960MHz the limit is 500 μ V/m (54dB μ /m) at 3 meters radiated.

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 37 of 56



Radiated Spurious Emission Measurements (Cont'd)

§15.247(d) / §15.205 & §15.209; RSS-210(A8.5)

Mode: 802.11b
Antenna: White Panel
Transfer Rate: 1 Mbps
Operating Frequency: 2462MHz
Channel: 11

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
4924.00	-105.78	Avg	V	40.66	41.88	53.98	-12.10
4924.00	-96.59	Peak	V	40.66	51.07	73.98	-22.91
7386.00	-109.75	Avg	V	46.02	43.27	53.98	-10.71
7386.00	-98.25	Peak	V	46.02	54.77	73.98	-19.21
12310.00	-135.00	Avg	V	51.30	23.30	53.98	-30.68
12310.00	-135.00	Peak	V	51.30	23.30	73.98	-50.68

Table 6-10. Radiated Measurements @ 3 meters

NOTES:

1. All emissions shown lie in the restricted bands specified in §15.205 and RSS-210 section 2.7, Table 1 and are below the limit shown in Table 6-7.
2. Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
5. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported. No significant emissions were found beyond the fifth harmonic for this device.
6. Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
7. Above 960MHz the limit is 500 μ V/m (54dB μ /m) at 3 meters radiated.

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 38 of 56

Radiated Spurious Emission Measurements (Cont'd)

§15.247(d) / §15.205 & §15.209; RSS-210(A8.5)

Mode: 802.11b
 Antenna: Monopole
 Transfer Rate: 1 Mbps
 Operating Frequency: 2412MHz
 Channel: 01

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
4824.00	-106.14	Avg	V	42.9	43.79	53.98	-10.19
4824.00	-97.00	Peak	V	42.9	52.93	73.98	-21.05
12060.00	-135.00	Avg	V	56.7	28.70	53.98	-25.28
12060.00	-135.00	Peak	V	56.7	28.70	73.98	-45.28

Table 6-11. Radiated Measurements @ 3 meters

NOTES:

1. All emissions shown lie in the restricted bands specified in §15.205 and RSS-210 section 2.7, Table 1 and are below the limit shown in Table 6-7.
2. Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
5. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported. No significant emissions were found beyond the fifth harmonic for this device.
6. Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
7. Above 960MHz the limit is 500 μ V/m (54dB μ /m) at 3 meters radiated.

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 39 of 56



Radiated Spurious Emission Measurements (Cont'd)

§15.247(d) / §15.205 & §15.209; RSS-210(A8.5)

Mode: 802.11b
Antenna: Monopole
Transfer Rate: 1 Mbps
Operating Frequency: 2437MHz
Channel: 06

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
4874.00	-106.43	Avg	V	43.1	43.68	53.98	-10.30
4874.00	-96.35	Peak	V	43.1	53.76	73.98	-20.22
7311.00	-110.86	Avg	V	49.8	45.97	53.98	-8.01
7311.00	-106.57	Peak	V	49.8	50.26	73.98	-23.72
12185.00	-135.00	Avg	V	56.6	28.63	53.98	-25.35
12185.00	-135.00	Peak	V	56.6	28.63	73.98	-45.35

Table 6-12. Radiated Measurements @ 3 meters

NOTES:

1. All emissions shown lie in the restricted bands specified in §15.205 and RSS-210 section 2.7, Table 1 and are below the limit shown in Table 6-7.
2. Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
5. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported. No significant emissions were found beyond the fifth harmonic for this device.
6. Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
7. Above 960MHz the limit is 500 μ V/m (54dB μ /m) at 3 meters radiated.

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 40 of 56



Radiated Spurious Emission Measurements (Cont'd)

§15.247(d) / §15.205 & §15.209; RSS-210(A8.5)

Mode: 802.11b
Antenna: Monopole
Transfer Rate: 1 Mbps
Operating Frequency: 2462MHz
Channel: 11

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
4924.00	-106.69	Avg	V	43.3	43.58	53.98	-10.40
4924.00	-95.86	Peak	V	43.3	54.41	73.98	-19.57
7386.00	-111.47	Avg	V	49.9	45.45	53.98	-8.53
7386.00	-105.41	Peak	V	49.9	51.51	73.98	-22.47
12310.00	-135.00	Avg	V	56.6	28.56	53.98	-25.42
12310.00	-135.00	Peak	V	56.6	28.56	73.98	-45.42

Table 6-13. Radiated Measurements @ 3 meters

NOTES:

1. All emissions shown lie in the restricted bands specified in §15.205 and RSS-210 section 2.7, Table 1 and are below the limit shown in Table 6-7.
2. Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
5. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported. No significant emissions were found beyond the fifth harmonic for this device.
6. Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
7. Above 960MHz the limit is 500 μ V/m (54dB μ /m) at 3 meters radiated.

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 41 of 56



Radiated Spurious Emission Measurements (Cont'd)

§15.247(d) / §15.205 & §15.209; RSS-210(A8.5)

Mode: 802.11a

Antenna: Parabolic Dish

Transfer Rate: 18 Mbps

Operating Frequency: 5745MHz

Channel: 149

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
11490.00	-97.04	Avg	V	42.5	52.4	53.98	-1.55
11490.00	-84.08	Peak	V	42.5	65.4	73.98	-8.59
22980.00	-135.00	Avg	V	50.4	22.4	53.98	-31.56
22980.00	-135.00	Peak	V	50.4	22.4	73.98	-51.56

Table 6-14. Radiated Measurements @ 3 meters

NOTES:

1. All emissions shown lie in the restricted bands specified in §15.205 and RSS-210 section 2.7, Table 1 and are below the limit shown in Table 6-7.
2. Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
5. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported. No significant emissions were found beyond the fifth harmonic for this device.
6. Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
7. Above 960MHz the limit is 500 μ V/m (54dB μ /m) at 3 meters radiated.

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 42 of 56



Radiated Spurious Emission Measurements (Cont'd)

§15.247(d) / §15.205 & §15.209; RSS-210(A8.5)

Mode: 802.11a
Antenna: Parabolic Dish
Transfer Rate: 18 Mbps
Operating Frequency: 5785MHz
Channel: 157

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
11570.00	-100.45	Avg	V	42.7	49.2	53.98	-4.76
11570.00	-87.40	Peak	V	42.7	62.3	73.98	-11.71

Table 6-15. Radiated Measurements @ 3 meters

NOTES:

1. All emissions shown lie in the restricted bands specified in §15.205 and RSS-210 section 2.7, Table 1 and are below the limit shown in Table 6-7.
2. Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
5. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported. No significant emissions were found beyond the fifth harmonic for this device.
6. Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
7. Above 960MHz the limit is 500 μ V/m (54dB μ /m) at 3 meters radiated.

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 43 of 56



Radiated Spurious Emission Measurements (Cont'd)

§15.247(d) / §15.205 & §15.209; RSS-210(A8.5)

Mode: 802.11a
Antenna: Parabolic Dish
Transfer Rate: 18 Mbps
Operating Frequency: 5825MHz
Channel: 165

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
11650.00	-102.71	Avg	V	42.9	47.2	53.98	-6.81
11650.00	-89.53	Peak	V	42.9	60.4	73.98	-13.63

Table 6-16. Radiated Measurements @ 3 meters

NOTES:

1. All emissions shown lie in the restricted bands specified in §15.205 and RSS-210 section 2.7, Table 1 and are below the limit shown in Table 6-7.
2. Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
5. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported. No significant emissions were found beyond the fifth harmonic for this device.
6. Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
7. Above 960MHz the limit is 500 μ V/m (54dB μ /m) at 3 meters radiated.

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 44 of 56



Radiated Spurious Emission Measurements (Cont'd)

§15.247(d) / §15.205 & §15.209; RSS-210(A8.5)

Mode: 802.11a
Antenna: Monopole
Transfer Rate: 18 Mbps
Operating Frequency: 5745MHz
Channel: 149

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
11490.00	-107.58	Avg	V	42.5	41.9	53.98	-12.09
11490.00	-95.10	Peak	V	42.5	54.4	73.98	-19.61
22980.00	-135.00	Avg	V	50.4	22.4	53.98	-31.56
22980.00	-135.00	Peak	V	50.4	22.4	73.98	-51.56

Table 6-17. Radiated Measurements @ 3 meters

NOTES:

1. All emissions shown lie in the restricted bands specified in §15.205 and RSS-210 section 2.7, Table 1 and are below the limit shown in Table 6-7.
2. Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
5. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported. No significant emissions were found beyond the fifth harmonic for this device.
6. Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
7. Above 960MHz the limit is 500 μ V/m (54dB μ /m) at 3 meters radiated.

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 45 of 56



Radiated Spurious Emission Measurements (Cont'd)

§15.247(d) / §15.205 & §15.209; RSS-210(A8.5)

Mode: 802.11a
Antenna: Monopole
Transfer Rate: 18 Mbps
Operating Frequency: 5785MHz
Channel: 157

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
11570.00	-107.35	Avg	V	42.7	42.3	53.98	-11.66
11570.00	-95.56	Peak	V	42.7	54.1	73.98	-19.87

Table 6-18. Radiated Measurements @ 3 meters

NOTES:

1. All emissions shown lie in the restricted bands specified in §15.205 and RSS-210 section 2.7, Table 1 and are below the limit shown in Table 6-7.
2. Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
5. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported. No significant emissions were found beyond the fifth harmonic for this device.
6. Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
7. Above 960MHz the limit is 500 μ V/m (54dB μ /m) at 3 meters radiated.

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 46 of 56



Radiated Spurious Emission Measurements (Cont'd)

§15.247(d) / §15.205 & §15.209; RSS-210(A8.5)

Mode: 802.11a
Antenna: Monopole
Transfer Rate: 18 Mbps
Operating Frequency: 5825MHz
Channel: 165

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
11650.00	-107.65	Avg	V	42.9	42.2	53.98	-11.75
11650.00	-96.43	Peak	V	42.9	53.5	73.98	-20.53

Table 6-19. Radiated Measurements @ 3 meters

NOTES:

1. All emissions shown lie in the restricted bands specified in §15.205 and RSS-210 section 2.7, Table 1 and are below the limit shown in Table 6-7.
2. Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
5. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported. No significant emissions were found beyond the fifth harmonic for this device.
6. Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
7. Above 960MHz the limit is 500 μ V/m (54dB μ /m) at 3 meters radiated.

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 47 of 56

6.10 Radiated Restricted Band Edge Measurements

§15.205 / §15.209; RSS-210(A8.5)

Mode: 802.11g

Antenna: White Panel

Transfer Rate: 18 Mbps

Operating Frequency: 2462MHz

Channel: 11

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
2483.50	-88.57	Avg	V	34.2	52.63	53.98	-1.35
2483.50	-79.34	Peak	V	34.2	61.86	73.98	-12.12
2484.74	-88.83	Avg	V	34.2	52.38	53.98	-1.60
2484.74	-78.48	Peak	V	34.2	62.73	73.98	-11.25
2498.42	-89.24	Avg	V	34.3	52.03	53.98	-1.95
2498.42	-79.10	Peak	V	34.3	62.17	73.98	-11.81

Table 6-20. Radiated Restricted Band Measurements at 3-meters

NOTES:

1. All emissions shown lie in the restricted bands specified in §15.205 and RSS-210 section 2.7, Table 1 and are below the limit shown in Table 6-7.
2. Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
5. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported. No significant emissions were found beyond the fifth harmonic for this device.
6. Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
7. Above 960MHz the limit is 500 μ V/m (54dB μ /m) at 3 meters radiated.

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 48 of 56



Radiated Restricted Band Edge Measurements (Cont'd)

§15.205 / §15.209; RSS-210(A8.5)

Mode: 802.11g
Antenna: Monopole
Transfer Rate: 18 Mbps
Operating Frequency: 2462MHz
Channel: 11

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
2483.50	-92.28	Avg	V	35.8	50.55	53.98	-3.43
2483.50	-79.87	Peak	V	35.8	62.96	73.98	-11.02
2485.56	-92.87	Avg	V	35.8	49.97	53.98	-4.01
2485.56	-83.28	Peak	V	35.8	59.56	73.98	-14.42
2498.28	-93.62	Avg	V	35.9	49.28	53.98	-4.70
2498.28	-85.20	Peak	V	35.9	57.70	73.98	-16.28

Table 6-21. Radiated Restricted Band Measurements at 3-meters

NOTES:

1. All emissions shown lie in the restricted bands specified in §15.205 and RSS-210 section 2.7, Table 1 and are below the limit shown in Table 6-7.
2. Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
5. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported. No significant emissions were found beyond the fifth harmonic for this device.
6. Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
7. Above 960MHz the limit is 500 μ V/m (54dB μ /m) at 3 meters radiated.

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 49 of 56


6.11 Line-Conducted Test Data

§15.207; RSS-Gen(7.2.2)

PCTEST Engineering Laboratory Inc.

Company : ProSoft Technology, Inc.
 Model Number : RLX-IHW
 FCC ID Code : OQ7IHW
 Standard : FCC Part 15B class B

Power Source : AC120V/60Hz
 Tested Date : 08/29/2007
 Note : Tested with WLAN b ON



Ver.1.1 ©PCTEST 2006.08

Plot 6-37. Line Conducted Plot with 802.11b

Notes:

1. All Modes of operation were investigated and the worst-case emissions are reported.
2. The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
3. Line A = Phase; Line B = Neutral
4. Traces shown in plot are made using a peak detector.
5. Deviations to the Specifications: None.

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter	Page 50 of 56

Line-Conducted Test Data (Cont'd)

§15.207; RSS-Gen(7.2.2)

No.	Line	Frequency	Factor	QP	Limit	Margin	Average	Limit	Margin
		[MHz]	[dB]	[dB μ V]	[dB μ V]	[dB]	[dB μ V]	[dB μ V]	[dB]
1	A	0.187	7.99	49.05	64.16	-15.11	28.35	54.16	-25.81
2	A	0.213	7.88	48.10	63.10	-15.00	27.41	53.10	-25.69
3	A	0.219	7.86	48.00	62.85	-14.85	26.64	52.85	-26.21
4	A	0.224	7.84	47.80	62.67	-14.87	28.29	52.67	-24.38
5	A	0.245	7.77	47.23	61.92	-14.69	26.39	51.92	-25.53
6	A	0.251	7.75	46.98	61.74	-14.76	23.72	51.74	-28.02
7	A	0.258	7.72	46.71	61.50	-14.79	24.37	51.50	-27.13
8	A	0.278	7.65	46.24	60.87	-14.63	23.50	50.87	-27.37
9	A	0.289	7.61	45.59	60.57	-14.98	23.27	50.57	-27.30
10	A	0.303	7.57	45.03	60.17	-15.14	22.02	50.17	-28.15
11	B	0.150	8.20	52.55	66.00	-13.45	44.61	56.00	-11.39
12	B	0.151	8.19	51.31	65.95	-14.64	42.58	55.95	-13.37
13	B	0.169	8.09	49.77	65.02	-15.25	39.38	55.02	-15.64
14	B	0.178	8.04	49.22	64.56	-15.34	39.56	54.56	-15.00
15	B	0.222	7.85	47.40	62.76	-15.36	34.32	52.76	-18.44
16	B	0.244	7.77	46.62	61.95	-15.33	31.16	51.95	-20.79
17	B	0.249	7.76	46.28	61.81	-15.53	32.09	51.81	-19.72
18	B	0.266	7.69	45.69	61.23	-15.54	30.63	51.23	-20.60
19	B	0.289	7.61	44.73	60.55	-15.82	28.57	50.55	-21.98
20	B	0.353	7.53	42.04	58.88	-16.84	25.48	48.88	-23.40

Table 6-22. Line Conducted Data with 802.11b

Notes:

1. All Modes of operation were investigated and the worst-case emissions are reported.
2. The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
3. Line A = Phase; Line B = Neutral
4. Traces shown in plot are made using a peak detector.
5. Deviations to the Specifications: None.

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 51 of 56


Line-Conducted Test Data (Cont'd)

§15.207; RSS-Gen(7.2.2)

PCTEST Engineering Laboratory Inc.

Company : ProSoft Technology, Inc.
 Model Number : RLX-IHW
 FCC ID Code : OQ7IHW
 Standard : FCC Part 15B class B

Power Source : AC120V/60Hz
 Tested Date : 08/29/2007
 Note : Tested with WLAN g ON



Ver.1.1 ©PCTEST 2006.08

Plot 6-38. Line Conducted Plot with 802.11g

Notes:

1. All Modes of operation were investigated and the worst-case emissions are reported.
2. The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
3. Line A = Phase; Line B = Neutral
4. Traces shown in plot are made using a peak detector.
5. Deviations to the Specifications: None.

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter	Page 52 of 56

Line-Conducted Test Data (Cont'd)

§15.207; RSS-Gen(7.2.2)

No.	Line	Frequency	Factor	QP	Limit	Margin	Average	Limit	Margin
		[MHz]	[dB]	[dB μ V]	[dB μ V]	[dB]	[dB μ V]	[dB μ V]	[dB]
1	A	0.205	7.91	48.21	63.39	-15.18	30.38	53.39	-23.01
2	A	0.218	7.86	47.78	62.88	-15.10	27.85	52.88	-25.03
3	A	0.231	7.82	47.28	62.41	-15.13	25.07	52.41	-27.34
4	A	0.262	7.71	46.27	61.38	-15.11	26.04	51.38	-25.34
5	A	0.264	7.70	46.28	61.32	-15.04	24.58	51.32	-26.74
6	A	0.265	7.70	46.23	61.31	-15.08	23.34	51.31	-27.97
7	A	0.276	7.65	45.83	60.92	-15.09	23.33	50.92	-27.59
8	A	0.290	7.61	45.26	60.53	-15.27	23.42	50.53	-27.11
9	A	0.314	7.56	44.35	59.86	-15.51	21.77	49.86	-28.09
10	A	0.332	7.54	43.55	59.41	-15.86	21.97	49.41	-27.44
11	B	0.150	8.20	51.40	66.00	-14.60	43.07	56.00	-12.93
12	B	0.155	8.17	50.97	65.75	-14.78	42.22	55.75	-13.53
13	B	0.164	8.12	50.25	65.26	-15.01	40.83	55.26	-14.43
14	B	0.176	8.05	49.43	64.69	-15.26	39.31	54.69	-15.38
15	B	0.184	8.01	48.94	64.31	-15.37	38.41	54.31	-15.90
16	B	0.218	7.86	47.66	62.91	-15.25	35.32	52.91	-17.59
17	B	0.230	7.82	47.17	62.46	-15.29	33.34	52.46	-19.12
18	B	0.244	7.77	46.64	61.95	-15.31	32.55	51.95	-19.40
19	B	0.354	7.53	41.83	58.87	-17.04	25.39	48.87	-23.48
20	B	0.393	7.50	39.77	58.01	-18.24	24.04	48.01	-23.97

Table 6-23. Line Conducted Data with 802.11g

Notes:

1. All Modes of operation were investigated and the worst-case emissions are reported.
2. The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
3. Line A = Phase; Line B = Neutral
4. Traces shown in plot are made using a peak detector.
5. Deviations to the Specifications: None.

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 53 of 56


Line-Conducted Test Data (Cont'd)

§15.207; RSS-Gen(7.2.2)

PCTEST Engineering Laboratory Inc.

Company : ProSoft Technology, Inc.
 Model Number : RLX-IHW
 FCC ID Code : OQ7IHW
 Standard : FCC Part 15B class B

Power Source : AC120V/60Hz
 Tested Date : 08/29/2007
 Note : Tested with WLAN a ON



Ver.1.1 ©PCTEST 2006.08

Plot 6-39. Line Conducted Plot with 802.11a

Notes:

1. All Modes of operation were investigated and the worst-case emissions are reported.
2. The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
3. Line A = Phase; Line B = Neutral
4. Traces shown in plot are made using a peak detector.
5. Deviations to the Specifications: None.

FCC ID: OQ7IHW		FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter	Page 54 of 56

Line-Conducted Test Data (Cont'd)

§15.207; RSS-Gen(7.2.2)

No.	Line	Frequency	Factor	QP	Limit	Margin	Average	Limit	Margin
		[MHz]	[dB]	[dB μ V]	[dB μ V]	[dB]	[dB μ V]	[dB μ V]	[dB]
1	A	0.158	8.15	50.00	65.58	-15.58	31.49	55.58	-24.09
2	A	0.192	7.97	48.58	63.96	-15.38	31.54	53.96	-22.42
3	A	0.227	7.83	47.29	62.58	-15.29	26.18	52.58	-26.40
4	A	0.236	7.80	47.00	62.24	-15.24	26.35	52.24	-25.89
5	A	0.256	7.73	46.33	61.56	-15.23	23.76	51.56	-27.80
6	A	0.279	7.65	45.46	60.85	-15.39	23.12	50.85	-27.73
7	A	0.308	7.57	44.39	60.03	-15.64	22.15	50.03	-27.88
8	A	0.327	7.55	43.72	59.53	-15.81	21.75	49.53	-27.78
9	A	0.347	7.53	42.79	59.04	-16.25	21.69	49.04	-27.35
10	A	0.348	7.53	42.82	59.02	-16.20	21.49	49.02	-27.53
11	B	0.150	8.20	52.58	66.00	-13.42	44.66	56.00	-11.34
12	B	0.150	8.20	51.70	66.00	-14.30	43.03	56.00	-12.97
13	B	0.158	8.15	50.63	65.57	-14.94	41.42	55.57	-14.15
14	B	0.171	8.08	49.68	64.91	-15.23	38.86	54.91	-16.05
15	B	0.185	8.00	49.03	64.25	-15.22	37.97	54.25	-16.28
16	B	0.196	7.95	48.51	63.77	-15.26	37.39	53.77	-16.38
17	B	0.222	7.85	47.61	62.73	-15.12	33.30	52.73	-19.43
18	B	0.253	7.74	46.49	61.67	-15.18	31.73	51.67	-19.94
19	B	0.276	7.66	45.53	60.94	-15.41	29.08	50.94	-21.86
20	B	0.291	7.60	44.82	60.49	-15.67	28.20	50.49	-22.29

Table 6-24. Line Conducted Data with 802.11a

Notes:

1. All Modes of operation were investigated and the worst-case emissions are reported.
2. The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
3. Line A = Phase; Line B = Neutral
4. Traces shown in plot are made using a peak detector.
5. Deviations to the Specifications: None.

FCC ID: OQ7IHW	 PCTEST	FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)	 ProSoft TECHNOLOGY	Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter		Page 55 of 56



7.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **ProSoft 802.11a/b/g Transmitter** **FCC ID: OQ7IHW** is in compliance with Part 15C of the FCC Rules.

FCC ID: OQ7IHW	 FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0707060700.OQ7	Test Dates: August 28 - 29, 2007	EUT Type: 802.11a/b/g Transmitter