



M. Flom Associates, Inc. - Global Compliance Center

3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176

www.mflom.com general@mflom.com (480) 926-3100, FAX: 926-3598

Date: October 20, 1999

Federal Communications Commission

Via: Electronic Filing

Attention: Authorization & Evaluation Division

Applicant: Temco Japan Co., Ltd.

Equipment: SR20A-01

FCC ID: OQB SR20A-01

FCC Rules: 90

Gentlemen:

On behalf of the Applicant, enclosed please find Application Form 731, Engineering Test Report and all pertinent documentation, the whole for approval of the referenced equipment as shown.

Filing fees are attached.

We trust the same is in order. Should you need any further information, kindly contact the writer who is authorized to act as agent.

Sincerely yours,

A handwritten signature in black ink, appearing to read 'William H. Graff'.

William H. Graff, Director
of Engineering

enclosure(s)

cc: Applicant

W.H.G./cvr

LIST OF EXHIBITS
(FCC CERTIFICATION (TRANSMITTERS) - REVISED 9/28/98)

APPLICANT: Temco Japan Co., Ltd.

FCC ID: OQB SR20A-01

BY APPLICANT:

1. LETTER OF AUTHORIZATION
2. IDENTIFICATION DRAWINGS, 2.1033(c)(11)
 - LABEL
 - LOCATION OF LABEL
 - COMPLIANCE STATEMENT
 - LOCATION OF COMPLIANCE STATEMENT
3. PHOTOGRAPHS, 2.1033(c)(12)
4. DOCUMENTATION: 2.1033(c)
 - (3) USER MANUAL
 - (9) TUNE UP INFO
 - (10) SCHEMATIC DIAGRAM
 - (10) CIRCUIT DESCRIPTION
5. PART 90.203(e) & (g) ATTESTATION

BY M.F.A. INC.

- A. TESTIMONIAL & STATEMENT OF CERTIFICATION
- B. STATEMENT OF QUALIFICATIONS



M. Flom Associates, Inc. - Global Compliance Center

3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176

www.mflom.com general@mflom.com (480) 926-3100, FAX: 926-3598

Sub-part
2.1033(c):

EQUIPMENT IDENTIFICATION

FCC ID: OQB SR20A-01

NAMEPLATE DRAWING

ATTACHED, EXHIBIT 1.

LOCATION

AS PER LABEL DRAWING(S)

DATE OF REPORT

October 20, 1999

SUPERVISED BY:

A handwritten signature in black ink, appearing to read "William H. Graff".

William H. Graff, Director
of Engineering

THE APPLICANT HAS BEEN CAUTIONED AS TO THE FOLLOWING:

15.21 INFORMATION TO USER.

The users manual or instruction manual for an intentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

15.27(a) SPECIAL ACCESSORIES.

Equipment marketed to a consumer must be capable of complying with the necessary regulations in the configuration in which the equipment is marketed. Where special accessories, such as shielded cables and/or special connectors are required to enable an unintentional or intentional radiator to comply with the emission limits in this part, the equipment must be marketed with, i.e. shipped and sold with, those special accessories. However, in lieu of shipping or packaging the special accessories with the unintentional or intentional radiator, the responsible party may employ other methods of ensuring that the special accessories are provided to the consumer, without additional charge.

Information detailing any alternative method used to supply the special accessories for a grant of equipment authorization or retained in the verification records, as appropriate. The party responsible for the equipment, as detailed in § 2.909 of this chapter, shall ensure that these special accessories are provided with the equipment. The instruction manual for such devices shall include appropriate instructions on the first page of text concerned with the installation of the device that these special accessories must be used with the device. It is the responsibility of the user to use the needed special accessories supplied with the equipment.

TABLE OF CONTENTS

<u>RULE</u>	<u>DESCRIPTION</u>	<u>PAGE</u>
	Test Report	1
2.1033(c)	General Information Required	2
2.1033(c)(14)	Rule Summary	5
	Standard Test Conditions and Engineering Practices	6
2.1046(a)	Carrier Output Power (Conducted)	7
2.1051	Unwanted Emissions (Transmitter Conducted)	9
2.1053(a)	Field Strength of Spurious Radiation	13
2.1049(c)(1)	Emission Masks (Occupied Bandwidth)	17
90.214	Transient Frequency Behavior	22
2.1047(a)	Audio Low Pass Filter (Voice Input)	26
2.1047(a)	Audio Frequency Response	29
2.1047(b)	Modulation Limiting	31
2.1055(a)(1)	Frequency Stability (Temperature Variation)	33
2.1055(b)(1)	Frequency Stability (Voltage Variation)	36
2.202(g)	Necessary Bandwidth and Emission Bandwidth	37

PAGE NO.

1 of 37.

Required information per ISO/IEC Guide 25-1990, paragraph 13.2:

a)

TEST REPORT

b) Laboratory: M. Flom Associates, Inc.
(FCC: 31040/SIT) 3356 N. San Marcos Place, Suite 107
(Canada: IC 2044) Chandler, AZ 85224

c) Report Number: d99a0074

d) Client: Temco Communications Inc.
13 Chipping Campden Dr.
South Barrington, IL 60010

e) Identification: SR20A-01

Description: FCC ID: OQB SR20A-01
VHF-FM Voice Activated Digitally Enhanced
Professional Secure Radio

f) EUT Condition: Not required unless specified in individual
tests.

g) Report Date: October 20, 1999
EUT Received: September 27, 1999

h, j, k): As indicated in individual tests.

i) Sampling method: No sampling procedure used.

l) Uncertainty: In accordance with MFA internal quality manual.

m) Supervised by:



William H. Graff, Director
of Engineering

n) Results: The results presented in this report relate
only to the item tested.

o) Reproduction: This report must not be reproduced, except in
full, without written permission from this
laboratory.

PAGE NO. 2 of 37.

LIST OF GENERAL INFORMATION REQUIRED FOR CERTIFICATIONIN ACCORDANCE WITH FCC RULES AND REGULATIONS,
VOLUME II, PART 2 AND TO

90.217

Sub-part 2.1033

(c)(1): NAME AND ADDRESS OF APPLICANT:Temco Japan Co., Ltd.
Silver Palace Honancho 1f,
2-12-26, Honan, Suginami-Ku
Tokyo, Japan 168 0082MANUFACTURER:

Applicant

(c)(2): FCC ID: OQB SR20A-01MODEL NO: SR20A-01(c)(3): INSTRUCTION MANUAL(S):

PLEASE SEE ATTACHED EXHIBITS

(c)(4): TYPE OF EMISSION: 16K0F3E(c)(5): FREQUENCY RANGE, MHz: 150 to 162(c)(6): POWER RATING, Watts: 0.01 to 0.1
 Switchable Variable N/A(c)(7): MAXIMUM POWER RATING, Watts: 0.120

PAGE NO.

3 of 37.

M. Flom Associates, Inc. is accredited by the American Association for Laboratory Association (A2LA) as shown in the scope below.



THE AMERICAN
ASSOCIATION
FOR LABORATORY
ACCREDITATION

ACCREDITED LABORATORY

A2LA has accredited

M. FLOM ASSOCIATES, INC.

Chandler, AZ

for technical competence in the field of

Electrical (EMC) Testing

The accreditation covers the specific tests and types of tests listed on the agreed scope of accreditation. This laboratory meets the requirements of ISO/IEC Guide 25-1990 "General Requirements for the Competence of Calibration and Testing Laboratories" (equivalent to relevant requirements of the ISO 9000 series of standards) and any additional program requirements in the identified field of testing.

Presented this 24th day of November, 1998.



Pete Flom
President
For the Accreditation Council
Certificate Number 1008.01
Valid to December 31, 2000

For tests or types of tests to which this accreditation applies, please refer to the laboratory's Electrical (EMC) Scope of Accreditation



American Association for Laboratory Accreditation

SCOPE OF ACCREDITATION TO ISO/IEC GUIDE 25-1990 AND EN 45001

M. FLOM ASSOCIATES, INC.
Electronic Testing Laboratory
3356 North San Marcos Place, Suite 107
Chandler, AZ 85224-1571
Morton Flom Phone: 602 926 3100

ELECTRICAL (EMC)

Valid to: December 31, 2000

Certificate Number: 1008-01

In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory to perform the following electromagnetic compatibility tests:

Tests	Standard(s)
RF Emissions	FCC Part 15 (Subparts B and C) using ANSI C63.4-1992; CISPR 11; CISPR 13; CISPR 14; CISPR 22; EN 55011; EN 55013; EN 55014; EN 55022; EN 50081-1; EN 50081-2; FCC Part 18; ICES-003; AS/NZS 1044; AS/NZS 1053; AS/NZS 3548; AS/NZS 4251.1
RF Immunity	EN 50082-1; EN 50082-2; AS/NZS 4251.1
Radiated Susceptibility	EN 61000-4-3; ENV 50140; ENV 50204; IEC 1000-4-3; IEC 801-3
ESD	EN 61000-4-2; IEC 1000-4-2; IEC 801-2
EFT	EN 61000-4-4; IEC 1000-4-4; IEC 801-4
Surge	EN 61000-4-5; ENV 50142; IEC 1000-4-5; IEC 801-5
47 CFR (FCC)	2, 21, 22, 23, 24, 74, 80, 87, 90, 95, 97

Pete Flom

5301 Buckeystown Pike, Suite 350 • Frederick, MD 21704-8307 • Phone: 301 644 3200 • Fax: 301 662 2974



"This laboratory is accredited by the American Association for Laboratory Accreditation (A2LA) and the results shown in this report have been determined in accordance with the laboratory's terms of accreditation unless stated otherwise in the report."

Should this report contain any data for tests for which we are not accredited, or which have been undertaken by a subcontractor that is not A2LA accredited, such data would not be covered by this laboratory's A2LA accreditation.

PAGE NO. 4 of 37.

Subpart 2.1033 (continued)

(c)(8): VOLTAGES & CURRENTS IN ALL ELEMENTS IN FINAL R. F. STAGE,
INCLUDING FINAL TRANSISTOR OR SOLID STATE DEVICE:

COLLECTOR CURRENT, A = per manual
COLLECTOR VOLTAGE, Vdc = per manual
SUPPLY VOLTAGE, Vdc = 9

(c)(9): TUNE-UP PROCEDURE:

PLEASE SEE ATTACHED EXHIBITS

(c)(10): CIRCUIT DIAGRAM/CIRCUIT DESCRIPTION:

Including description of circuitry & devices provided for determining and stabilizing frequency, for suppression of spurious radiation, for limiting modulation and limiting power.

PLEASE SEE ATTACHED EXHIBITS

(c)(11): LABEL INFORMATION:

PLEASE SEE ATTACHED EXHIBITS

(c)(12): PHOTOGRAPHS:

PLEASE SEE ATTACHED EXHIBITS

(c)(13): DIGITAL MODULATION DESCRIPTION:

 ATTACHED EXHIBITS
x N/A

(c)(14): TEST AND MEASUREMENT DATA:

FOLLOWS

PAGE NO.

5 of 37.

Sub-part

2.1033(c)(14):TEST AND MEASUREMENT DATA

All tests and measurement data shown were performed in accordance with FCC Rules and Regulations, Volume II; Part 2, Sub-part J, Sections 2.947, 2.1033(c), 2.1041, 2.1046, 2.1047, 2.1079, 2.1051, 2.1053, 2.1055, 2.1057 and the following individual Parts:

- ____ 21 - Domestic Public Fixed Radio Services
- ____ 22 - Public Mobile Services
- ____ 22 Subpart H - Cellular Radiotelephone Service
- ____ 22.901(d) - Alternative technologies and auxiliary services
- ____ 23 - International Fixed Public Radiocommunication services
- ____ 24 - Personal Communications Services
- ____ 74 Subpart H - Low Power Auxiliary Stations
- ____ 80 - Stations in the Maritime Services
- ____ 80 Subpart E - General Technical Standards
- ____ 80 Subpart F - Equipment Authorization for Compulsory Ships
- ____ 80 Subpart K - Private Coast Stations and Marine Utility Stations
- ____ 80 Subpart S - Compulsory Radiotelephone Installations for Small Passenger Boats
- ____ 80 Subpart T - Radiotelephone Installation Required for Vessels on the Great Lakes
- ____ 80 Subpart U - Radiotelephone Installations Required by the Bridge-to-Bridge Act
- ____ 80 Subpart V - Emergency Position Indicating Radiobeacons (EPIRB'S)
- ____ 80 Subpart W - Global Maritime Distress and Safety System (GMDSS)
- ____ 80 Subpart X - Voluntary Radio Installations
- ____ 87 - Aviation Services
- x 90 - Private Land Mobile Radio Services
- ____ 94 - Private Operational-Fixed Microwave Service
- ____ 95 Subpart A - General Mobile Radio Service (GMRS)
- ____ 95 Subpart C - Radio Control (R/C) Radio Service
- ____ 95 Subpart D - Citizens Band (CB) Radio Service
- ____ 95 Subpart E - Family Radio Service
- ____ 95 Subpart F - Interactive Video and Data Service (IVDS)
- ____ 97 - Amateur Radio Service
- ____ 101 - Fixed Microwave Services

PAGE NO.

6 of 37.

STANDARD TEST CONDITIONS
and
ENGINEERING PRACTICES

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.4-1992, section 6.1.9, and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104 °F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing.

Measurement results, unless otherwise noted, are worst case measurements.

PAGE NO. 7 of 37.

NAME OF TEST: Carrier Output Power (Conducted)

SPECIFICATION: 47 CFR 2.1046(a)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.1

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The EUT was connected to a resistive coaxial attenuator of normal load impedance, and the unmodulated output power was measured by means of an R. F. Power Meter.
2. Measurement accuracy is $\pm 3\%$.

MEASUREMENT RESULTS

FREQUENCY OF CARRIER, MHz = 156.025, 150.025, 161.975

POWER SETTING	R. F. POWER, WATTS
Low	0.01
High	0.1

SUPERVISED BY:




William H. Graff, Director
of Engineering

PAGE NO.

8 of 37.

TRANSMITTER POWER CONDUCTED MEASUREMENTS

TEST 1: R. F. POWER OUTPUT
 TEST 2: FREQUENCY STABILITY



Asset Description (as applicable)	s/n
(1) COAXIAL ATTENUATOR	
i00122 Narda 766-10	7802
i00123 Narda 766-10	7802A
i00069 Bird 8329 (30 dB)	1006
i00113 Sierra 661A-3D	1059
(2) POWER METERS	
i00014 HP 435A	1733A05836
i00039 HP 436A	2709A26776
i00020 HP 8901A POWER MODE	2105A01087
(3) FREQUENCY COUNTER	
i00042 HP 5383A	1628A00959
i00019 HP 5334B	2704A00347
i00020 HP 8901A FREQUENCY MODE	2105A01087

PAGE NO. 9 of 37.

NAME OF TEST: Unwanted Emissions (Transmitter Conducted)

SPECIFICATION: 47 CFR 2.1051

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.13

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The emissions were measured for the worst case as follows:
 - (a): within a band of frequencies defined by the carrier frequency plus and minus one channel.
 - (b): from the lowest frequency generated in the EUT and to at least the 10th harmonic of the carrier frequency, or 40 GHz, whichever is lower.
2. The magnitude of spurious emissions that are attenuated more than 20 dB below the permissible value need not be specified.
3. MEASUREMENT RESULTS: ATTACHED FOR WORST CASE

FREQUENCY OF CARRIER, MHz = 156.025, 150.025, 161.975

SPECTRUM SEARCHED, GHz = 0 to 10 x F_c

MAXIMUM RESPONSE, Hz = 2820

ALL OTHER EMISSIONS = = 20 dB BELOW LIMIT

LIMIT(S), dBc

$-(43+10 \times \log P) = -23$ (0.01 Watts)

$-(43+10 \times \log P) = -33$ (0.1 Watts)

SUPERVISED BY:




William H. Graff, Director
of Engineering

PAGE NO.

10 of 37.

TRANSMITTER SPURIOUS EMISSION

TEST A. OCCUPIED BANDWIDTH (IN-BAND SPURIOUS)
 TEST B. OUT-OF-BAND SPURIOUS



Asset Description (as applicable)	s/n
(1) <u>AUDIO OSCILLATOR/GENERATOR</u>	
i00010 HP 204D	1105A04683
i00017 HP 8903A	2216A01753
i00012 HP 3312A	1432A11250
(2) <u>COAXIAL ATTENUATOR</u>	
i00122 Narda 766-10	7802
i00123 Narda 766-10	7802A
i00069 Bird 8329 (30 dB)	1006
i00113 Sierra 661A-3D	1059
(3) <u>FILTERS; NOTCH, HP, LP, BP</u>	
i00126 Eagle TNF-1	100-250
i00125 Eagle TNF-1	50-60
i00124 Eagle TNF-1	250-850
(4) <u>SPECTRUM ANALYZER</u>	
i00048 HP 8566B	2511A01467
i00029 HP 8563E	3213A00104

PAGE NO.

11 of 37.

NAME OF TEST: Unwanted Emissions (Transmitter Conducted)
 g99a0209: 1999-Oct-15 Fri 08:01:00
 STATE: 1:Low Power

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	LEVEL, dBm	LEVEL, dBc	MARGIN, dB
150.025000	300.046000	-50.8	-61	-37.8
156.025000	312.061000	-54.2	-64.4	-41.2
161.975000	323.953000	-72.2	-82.4	-59.2
150.025000	450.077000	-51.1	-61.3	-38.1
156.025000	468.240000	-54.5	-64.7	-41.5
161.975000	486.258000	-73.8	-84	-60.8
150.025000	600.095000	-59.5	-69.7	-46.5
156.025000	624.118000	-60.9	-71.1	-47.9
161.975000	648.374000	-74.4	-84.6	-61.4
150.025000	750.140000	-52.1	-62.3	-39.1
156.025000	780.111000	-52.9	-63.1	-39.9
161.975000	809.703000	-74.4	-84.6	-61.4
150.025000	900.124000	-60.3	-70.5	-47.3
156.025000	936.145000	-65.6	-75.8	-52.6
161.975000	971.852000	-73.6	-83.8	-60.6
150.025000	1050.195000	-64.3	-74.5	-51.3
156.025000	1092.154000	-63.4	-73.6	-50.4
161.975000	1133.695000	-73.3	-83.5	-60.3
150.025000	1200.243000	-69	-79.2	-56
156.025000	1248.212000	-63.9	-74.1	-50.9
161.975000	1295.988000	-73.9	-84.1	-60.9
150.025000	1350.238000	-66.2	-76.4	-53.2
156.025000	1404.252000	-65	-75.2	-52
161.975000	1457.974000	-73.3	-83.5	-60.3
150.025000	1500.295000	-70.4	-80.6	-57.4
156.025000	1560.277000	-66.6	-76.8	-53.6
161.975000	1620.053000	-72	-82.2	-59
150.025000	1650.298000	-70.3	-80.5	-57.3
156.025000	1716.238000	-66.6	-76.8	-53.6
161.975000	1781.815000	-72.5	-82.7	-59.5
150.025000	1800.354000	-65.7	-75.9	-52.7
156.025000	1872.348000	-68.7	-78.9	-55.7
161.975000	1943.863000	-72.8	-83	-59.8
150.025000	1950.374000	-70.4	-80.6	-57.4
156.025000	2028.363000	-69.6	-79.8	-56.6
150.025000	2100.294000	-69.6	-79.8	-56.6
161.975000	2105.346000	-72.1	-82.3	-59.1
156.025000	2184.335000	-70.6	-80.8	-57.6
150.025000	2250.429000	-72.2	-82.4	-59.2
161.975000	2267.951000	-72.3	-82.5	-59.3
156.025000	2339.910000	-71.5	-81.7	-58.5
161.975000	2429.722000	-71.8	-82	-58.8

PAGE NO.

12 of 37.

NAME OF TEST: Unwanted Emissions (Transmitter Conducted)
 g99a0208: 1999-Oct-15 Fri 07:54:00
 STATE: 2:High Power

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	LEVEL, dBm	LEVEL, dBc	MARGIN, dB
150.025000	300.055000	-41.3	-61.3	-28.3
156.025000	312.039000	-44.5	-64.5	-31.5
161.975000	323.670000	-63.6	-83.6	-50.6
150.025000	450.095000	-43.6	-63.6	-30.6
156.025000	468.180000	-45.6	-65.6	-32.6
161.975000	485.490000	-64.3	-84.3	-51.3
150.025000	600.108000	-53.6	-73.6	-40.6
156.025000	624.107000	-54	-74	-41
161.975000	648.299000	-63.3	-83.3	-50.3
150.025000	750.152000	-52.1	-72.1	-39.1
156.025000	780.145000	-52.5	-72.5	-39.5
161.975000	809.408000	-63.8	-83.8	-50.8
150.025000	900.132000	-54.7	-74.7	-41.7
156.025000	936.171000	-57.2	-77.2	-44.2
161.975000	971.447000	-62.3	-82.3	-49.3
150.025000	1050.190000	-63.9	-83.9	-50.9
156.025000	1091.708000	-64.2	-84.2	-51.2
161.975000	1133.408000	-63.4	-83.4	-50.4
150.025000	1200.232000	-62.5	-82.5	-49.5
156.025000	1248.178000	-61.6	-81.6	-48.6
161.975000	1295.355000	-63	-83	-50
150.025000	1350.122000	-63.3	-83.3	-50.3
156.025000	1404.566000	-63.3	-83.3	-50.3
161.975000	1457.917000	-63.3	-83.3	-50.3
150.025000	1500.426000	-63.4	-83.4	-50.4
156.025000	1560.234000	-63.3	-83.3	-50.3
161.975000	1619.356000	-62.3	-82.3	-49.3
150.025000	1650.021000	-63.2	-83.2	-50.2
156.025000	1716.124000	-63.1	-83.1	-50.1
161.975000	1781.233000	-63.1	-83.1	-50.1
150.025000	1800.520000	-63.5	-83.5	-50.5
156.025000	1871.886000	-63.2	-83.2	-50.2
161.975000	1944.079000	-62.9	-82.9	-49.9
150.025000	1950.111000	-63.1	-83.1	-50.1
156.025000	2028.525000	-61.6	-81.6	-48.6
150.025000	2100.301000	-61.6	-81.6	-48.6
161.975000	2106.091000	-62.9	-82.9	-49.9
156.025000	2184.496000	-62.4	-82.4	-49.4
150.025000	2250.041000	-61.7	-81.7	-48.7
161.975000	2267.638000	-62	-82	-49
156.025000	2340.279000	-61.9	-81.9	-48.9
161.975000	2429.917000	-61.2	-81.2	-48.2

PAGE NO. 13 of 37.

NAME OF TEST: Field Strength of Spurious Radiation

SPECIFICATION: 47 CFR 2.1053(a)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.12


TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. A description of the measurement facilities was filed with the FCC and was found to be in compliance with the requirements of Section 2.948, by letter from the FCC dated March 3, 1997, FILE 31040/SIT. All pertinent changes will be reported to the Commission by up-date prior to March 2000.
2. At first, in order to locate all spurious frequencies and approximate amplitudes, and to determine proper equipment functioning, the test sample was set up at a distance of three meters from the test instrument. Valid spurious signals were determined by switching the power on and off.
3. In the field, the test sample was placed on a wooden turntable above ground at three (or thirty) meters away from the search antenna. Excess power leads were coiled near the power supply.

The cables were oriented in order to obtain the maximum response. At each emission frequency, the turntable was rotated and the search antennas were raised and lowered vertically.

4. The emission was observed with both a vertically polarized and a horizontally polarized search antenna and the worst case was used.
5. The field strength of each emission within 20 dB of the limit was recorded and corrected with the appropriate cable and transducer factors.
6. The worst case for all channels is shown.
7. Measurement results: ATTACHED FOR WORST CASE

RADIATED TEST SETUP

NOTES:

- (a) Search Antenna - Rotatable on boom
- (b) Non-metallic boom
- (c) Non-metallic mast
- (d) Adjustable horizontally
- (e) Equipment Under Test
- (f) Turntable
- (g) Boom adjustable in height.
- (h) External control cables routed horizontally at least one wavelength.
- (i) Rotatable
- (j) Cables routed through hollow turntable center
- (k) 30 cm or less
- (l) External power source
- (m) 10 cm diameter coil of excess cable
- (n) 25 cm (V), 1 m-7 m (V, H)
- (o) 25 cm from bottom end of 'V', 1m normally
- (p) Calibrated Cable at least 10m in length
- (q) Amplifier (optional)
- (r) Spectrum Analyzer

Asset Description (as applicable)	s/n	Cycle	Last Cal
per ANSI C63.4-1992, 10.1.4			
<u>TRANSDUCER</u>			
i00088 EMCO 3109-B 25MHz-300MHz	2336	12 mo.	Sep-99
i00065 EMCO 3301-B Active Monopole	2635	12 mo.	Sep-99
i00089 Aprel 2001 200MHz-1GHz	001500	12 mo.	Sep-99
i00103 EMCO 3115 1GHz-18GHz	9208-3925	12 mo.	Sep-99
<u>AMPLIFIER</u>			
i00028 HP 8449A	2749A00121	12 mo.	Mar-99
<u>SPECTRUM ANALYZER</u>			
i00029 HP 8563E	3213A00104	12 mo.	Aug-99
i00033 HP 85462A	3625A00357	12 mo.	May-99
i00048 HP 8566B	2511AD1467	6 mo.	May-99

PAGE NO. 15 of 37.

NAME OF TEST: Field Strength of Spurious Radiation

ALL OTHER EMISSIONS = = 20 dB BELOW LIMIT

EMISSION, MHz/HARMONIC	SPURIOUS LEVEL, dBc	
	Low	High
2nd to 10th	<-47	<-47

SUPERVISED BY:



William H. Graff, Director
of Engineering

PAGE NO.

16 of 37.

NAME OF TEST: Field Strength of Spurious Radiation
 g99a0164: 1999-Oct-08 Fri 11:35:00
 STATE: 2:High Power 150-158 MHz

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	METER, dBuV	CF, dB	ERP, dBm	MARGIN, dB
166.025000	312.050080	15.51	18.96	-62.9	-42.9
166.025000	468.075130	16.82	23.75	-56.8	-36.8
166.025000	624.100180	2.24	27.53	-67.6	-47.6
166.025000	780.125050	4.45	29.58	-63.3	-43.4
166.025000	936.149600	10.27	33.64	-53.5	-33.5
166.025000	1092.174600	-3.91	33.02	-68.3	-48.3
166.025000	1248.199850	-12.1	34.87	-74.6	-54.6
166.025000	1404.225150	-12.27	36.55	-73.1	-53.1
166.025000	1560.250150	-11.02	38.07	-70.3	-50.4

NAME OF TEST: Field Strength of Spurious Radiation
 g99a0165: 1999-Oct-08 Fri 15:23:00
 STATE: 2:High Power 154-162 MHz

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	METER, dBuV	CF, dB	ERP, dBm	MARGIN, dB
156.025000	312.055000	23.92	18.96	-54.5	-34.5
156.025000	468.075300	13.59	23.75	-60	-40.1
156.025000	624.100300	5.29	27.53	-64.6	-44.6
156.025000	780.125300	11.64	29.58	-56.2	-36.2
156.025000	936.150300	6.53	33.64	-57.2	-37.2
166.025000	1092.175500	-4.55	33.02	-68.9	-48.9
166.025000	1248.200530	-10.42	34.87	-72.9	-53
166.025000	1404.225530	-11.9	36.55	-72.7	-52.8
166.025000	1560.248780	0.36	38.07	-58.9	-39

PAGE NO. 17 of 37.

NAME OF TEST: Emission Masks (Occupied Bandwidth)

SPECIFICATION: 47 CFR 2.1049(c)(1)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.11

TEST EQUIPMENT: As per previous page


MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page, with the Spectrum Analyzer connected.
2. For EUTs supporting audio modulation, the audio signal generator was adjusted to the frequency of maximum response and with output level set for ± 2.5 kHz deviation (or 50% modulation). With level constant, the signal level was increased 16 dB.
3. For EUTs supporting digital modulation, the digital modulation mode was operated to its maximum extent.
4. The Occupied Bandwidth was measured with the Spectrum Analyzer controls set as shown on the test results.
5. MEASUREMENT RESULTS: ATTACHED

PAGE NO.

18 of 37.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g99a0204: 1999-Oct-15 Fri 07:38:00
 STATE: 1:Low Power



POWER: LOW
 MODULATION: NONE


SUPERVISED BY:

William H. Graff, Director
of Engineering

PAGE NO.

19 of 37.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g99a0206: 1999-Oct-15 Fri 07:44:00
 STATE: 2:High Power



POWER:
 MODULATION:

HIGH
 VOICE: 2500 Hz SINE WAVE
 MASK: B, VHF/UHF 25kHz,
 w/LPF

SUPERVISED BY:




William H. Graff, Director
 of Engineering

PAGE NO.

20 of 37.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g99a0203: 1999-Oct-15 Fri 07:29:00
 STATE: 2:High Power



POWER: HIGH
 MODULATION: NONE

SUPERVISED BY:




William H. Graff, Director
 of Engineering

PAGE NO.

21 of 37.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g99a0205: 1999-Oct-15 Fri 07:41:00
 STATE: 2:High Power



POWER:
 MODULATION:

HIGH
 VOICE: 2500 Hz SINE WAVE
 MASK: B, VHF/UHF 25kHz,
 w/LPF

SUPERVISED BY:



William H. Graff, Director
 of Engineering

PAGE NO. 22 of 37.

NAME OF TEST: Transient Frequency Behavior

SPECIFICATION: 47 CFR 90.214

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.19

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The EUT was setup as shown on the attached page, following TIA/EIA-603 steps a, b, and c as a *guide*.

2. The transmitter was turned on.

3. Sufficient attenuation was provided so that the transmitter carrier level measured at the output of the combiner was 40 dB below the maximum input level of the test receiver. This level was recorded as step f.

4. The transmitter was turned off.

5. An RF signal generator (1) modulated with a 1 kHz tone at either 25, 12.5, or 6.25 kHz deviation, and set to the same frequency as the assigned transmitter frequency, (2) was adjusted to a level -20 dB below the level recorded for step f, as measured at the output of the combiner. This level was then fixed for the remainder of the test and is recorded at step h.

6. The oscilloscope was setup using TIA/EIA-603 steps j and k as a guide, and to either 10 ms/div (UHF) or 5 ms/div (VHF).

7. The 30 dB attenuator was removed, the transmitter was turned on, and the level of the carrier at the output of the combiner was recorded as step l.

8. The carrier on-time as referenced in TIA/EIA-603 steps m, n, and o was captured and plotted. The carrier off-time as referenced in TIA/EIA-603 steps p, q, r, and s was captured and plotted.

LEVELS MEASURED:


step f, dBm	= -20.0
step h, dBm	= -49.2
step l, dBm	= 1.2

SUPERVISED BY:



William H. Graff, Director
of Engineering

TRANSIENT FREQUENCY BEHAVIOR




Asset Description (as applicable)	s/n
(1) ATTENUATOR (Removed after 1st step) i00112 Philco 30 dB	989
(2) ATTENUATOR i00112 Philco 30 dB i00172 Bird 30 dB i00122 Narda 10 dB i00123 Narda 10 dB i00110 Kay Variable	989 989 7802 7802A 145-387
(3) COMBINER i00154 4 x 25 Ω COMBINER	154
(4) CRYSTAL DETECTOR i00159 HP 8470B	1822A10054
(5) RF SIGNAL GENERATOR i00018 HP 8656A i00031 HP 8656A i00067 HP 8920A	2228A03472 2402A06180 3345U01242
(6) MODULATION ANALYZER i00020 HP 8901A	2105A01087
(7) SCOPE i00030 HP 54502A	2927A00209

PAGE NO.

24 of 37.

NAME OF TEST: Transient Frequency Behavior
 g99a0220: 1999-Oct-15 Fri 08:39:00
 STATE: 2:High Power



+25

FC

-25

Main Timebase 5.00 ms/div Delay/Pos 20.0000 ms Reference Center Mode Repetitive
 Sensitivity Offset Probe Coupling
 Channel 1 500 mV/div 0.00000 V 1.000 :1 dc (1M ohm)

Trigger mode : Edge
 On Negative Edge Of Chan2
 Trigger Level
 Chan2 = -4.000 mV (noise reject ON)
 Holdoff = 40.000 ns

POWER:
 MODULATION:
 DESCRIPTION:

HIGH
 Ref Gen=25 kHz Deviation
 CARRIER ON TIME

SUPERVISED BY:




William H. Graff, Director
 of Engineering

PAGE NO.

25 of 37.

NAME OF TEST: Transient Frequency Behavior
 g99a0221: 1999-Oct-15 Fri 08:42:00
 STATE: 2:High Power

0



+25

FC

-25

Main Timebase 5.00 ms/div Delay/Pos -15.0000 ms Reference Center Mode Repetitive
 Channel 1 Sensitivity 500 mV/div Offset 0.00000 V Probe 1.000 :1 Coupling dc (1M ohm)
 Trigger mode : Edge
 On Positive Edge Of Chan2
 Trigger Level
 Chan2 = -756.300 mV (noise reject ON)
 Holdoff = 40.000 ns

POWER:
 MODULATION:
 DESCRIPTION:

HIGH
 Ref Gen=25 kHz Deviation
 CARRIER OFF TIME

SUPERVISED BY:

William H. Graff, Director
 of Engineering

PAGE NO. 26 of 37.

NAME OF TEST: Audio Low Pass Filter (Voice Input)

SPECIFICATION: 47 CFR 2.1047(a)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.15

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE


1. The EUT and test equipment were set up such that the audio input was connected at the input to the modulation limiter, and the modulated stage.
2. The audio output was connected at the output to the modulated stage.
3. MEASUREMENT RESULTS: ATTACHED

PAGE NO.

27 of 37.

TRANSMITTER TEST SET-UP

TEST A. MODULATION CAPABILITY/DISTORTION
 TEST B. AUDIO FREQUENCY RESPONSE
 TEST C. HUM AND NOISE LEVEL
 TEST D. RESPONSE OF LOW PASS FILTER
 TEST E. MODULATION LIMITING




Transmitter Test Set Up

Asset Description (as applicable)	s/n
(1) <u>Audio Oscillator</u> i00010 HP 204D i00017 HP 8903A i00118 HP 33120A	1105A04683 2216A01753 US36002064
(2) <u>COAXIAL ATTENUATOR</u> i00122 NARDA 766-10 i00123 NARDA 766-10 i00113 SIERRA 661A-3D i00069 BIRD 8329 (30 dB)	7802 7802A 1059 10066
(3) <u>MODULATION ANALYZER</u> i00020 HP 8901A	2105A01087
(4) <u>AUDIO ANALYZER</u> i00017 HP 8903A	2216A01753

PAGE NO.

28 of 37.

NAME OF TEST: Audio Low Pass Filter (Voice Input)
g99a0188: 1999-Oct-14 Thu 15:48:00
STATE: 0:General



SUPERVISED BY:



William H. Graff, Director
of Engineering

PAGE NO. 29 of 37.

NAME OF TEST: Audio Frequency Response

SPECIFICATION: 47 CFR 2.1047(a)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.6

TEST EQUIPMENT: As per previous page


MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page.
2. The audio signal generator was connected to the audio input circuit/microphone of the EUT.
3. The audio signal input was adjusted to obtain 20% modulation at 1 kHz, and this point was taken as the 0 dB reference level.
4. With input levels held constant and below limiting at all frequencies, the audio signal generator was varied from 100 Hz to 50 kHz.
5. The response in dB relative to 1 kHz was then measured, using the HP 8901A Modulation Analyzer.
6. MEASUREMENT RESULTS: ATTACHED

PAGE NO.

30 of 37.

NAME OF TEST: Audio Frequency Response
 g99a0189: 1999-Oct-14 Thu 15:52:00
 STATE: 0:General



Frequency of Maximum Audio Response, Hz = 2820

Additional points:

FREQUENCY, Hz	LEVEL, dB
300	-28.65
20000	-32.74
30000	-32.74
50000	-32.80

SUPERVISED BY:



William H. Graff, Director
of Engineering

PAGE NO. 31 of 37.

NAME OF TEST: Modulation Limiting

SPECIFICATION: 47 CFR 2.1047(b)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.3

TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE

1. The signal generator was connected to the input of the EUT as for "Frequency Response of the Modulating Circuit."
2. The modulation response was measured for each of three frequencies (one of which was the frequency of maximum response), and the input voltage was varied and was observed on an HP 8901A Modulation Analyzer.
3. The input level was varied from 30% modulation (± 1.5 kHz deviation) to at least 20 dB higher than the saturation point.
4. Measurements were performed for both negative and positive modulation and the respective results were recorded.


5. MEASUREMENT RESULTS: ATTACHED

PAGE NO.


32 of 37.

NAME OF TEST: Modulation Limiting
 g99a0197: 1999-Oct-14 Thu 16:05:00
 STATE: 0:General

Positive
 Peaks:



Negative
 Peaks:



SUPERVISED BY:

William H. Graff, Director
 of Engineering

PAGE NO. 33 of 37.

NAME OF TEST: Frequency Stability (Temperature Variation)

SPECIFICATION: 47 CFR 2.1055(a)(1)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.2

TEST CONDITIONS: As Indicated

TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE


1. The EUT and test equipment were set up as shown on the following page.
2. With all power removed, the temperature was decreased to -30°C and permitted to stabilize for three hours. Power was applied and the maximum change in frequency was noted within one minute.
3. With power OFF, the temperature was raised in 10°C steps. The sample was permitted to stabilize at each step for at least one-half hour. Power was applied and the maximum frequency change was noted within one minute.
4. The temperature tests were performed for the worst case.
5. MEASUREMENT RESULTS: ATTACHED

PAGE NO.

34 of 37.

TRANSMITTER TEST SET-UP

TEST A. OPERATIONAL STABILITY
 TEST B. CARRIER FREQUENCY STABILITY
 TEST C. OPERATIONAL PERFORMANCE STABILITY
 TEST D. HUMIDITY
 TEST E. VIBRATION
 TEST F. ENVIRONMENTAL TEMPERATURE
 TEST G. FREQUENCY STABILITY: TEMPERATURE VARIATION
 TEST H. FREQUENCY STABILITY: VOLTAGE VARIATION




Transmitter Test Set-Up

Asset Description (as applicable)		s/n
(1) TEMPERATURE, HUMIDITY, VIBRATION		
i00027 Tenny Temp. Chamber		9083-765-234
i00 Weber Humidity Chamber		
i00 L.A.B. RVH 18-100		
(2) COAXIAL ATTENUATOR		
i00122 NARDA 766-10		7802
i00123 NARDA 766-10		7802A
i00113 SIERRA 661A-3D		1059
i00069 BIRD 8329 (30 dB)		10066
(3) R.F. POWER		
i00014 HP 435A POWER METER		1733A05839
i00039 HP 436A POWER METER		2709A26776
i00020 HP 8901A POWER MODE		2105A01087
(4) FREQUENCY COUNTER		
i00042 HP 5383A		1628A00959
i00019 HP 5334B		2704A00347
i00020 HP 8901A		2105A01087

PAGE NO.

35 of 37.

NAME OF TEST: Frequency Stability (Temperature Variation)
g99a0200: 1999-Oct-14 Thu 16:37:00
STATE: 0:General



SUPERVISED BY:

William H. Graff, Director
of Engineering

PAGE NO. 36 of 37.

NAME OF TEST: Frequency Stability (Voltage Variation)

SPECIFICATION: 47 CFR 2.1055(b)(1)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.2

TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE

1. The EUT was placed in a temperature chamber at $25\pm5^{\circ}\text{C}$ and connected as for "Frequency Stability - Temperature Variation" test.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

RESULTS: Frequency Stability (Voltage Variation)

g99a0201: 1999-Oct-14 Thu 16:29:44

STATE: 0:General

LIMIT, ppm	=	2.5
LIMIT, Hz	=	390
BATTERY END POINT (Voltage)	=	7.2

% of STV	Voltage	Frequency, MHz	Change, Hz	Change, ppm
85	7.65	156.025010	10	0.06
100	9	156.025000	0	0.00
115	10.35	156.025010	10	0.06
80	7.2	156.025010	10	0.06

SUPERVISED BY:



William H. Graff, Director
of Engineering

PAGE NO. 37 of 37.

NAME OF TEST: Necessary Bandwidth and Emission Bandwidth

SPECIFICATION: 47 CFR 2.202(g)

MODULATION = 16K0F3E

NECESSARY BANDWIDTH CALCULATION:

MAXIMUM MODULATION (M), kHz	= 3
MAXIMUM DEVIATION (D), kHz	= 5
CONSTANT FACTOR (K)	= 1
NECESSARY BANDWIDTH (B _N), kHz	= (2 x M) + (2 x D x K)
	= 16.0

SUPERVISED BY:



William H. Graff, Director
of Engineering

TESTIMONIAL
AND
STATEMENT OF CERTIFICATION

THIS IS TO CERTIFY THAT:

1. THAT the application was prepared either by, or under the direct supervision of, the undersigned.
2. THAT the technical data supplied with the application was taken under my direction and supervision.
3. THAT the data was obtained on representative units, randomly selected.
4. THAT, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.

CERTIFYING ENGINEER:



William H. Graff, Director
of Engineering