



Lab Code: 200707-0



FCC PART 15B

TEST REPORT

For

XIAMEN SCALETECH CO., LTD.

ZoneA, 4th Floor, #10 of Ai-de Air Industry Park, Gaoqi South 12th Road,
Xiamen, Fujian, China

FCC ID: ORBSDC35SCALE

Report Type: Original Report	Product Type: Digital Scale
Test Engineer: <u>Star Xie</u> <i>Star Xie</i>	
Report Number: <u>R1XM120809051-00</u>	
Report Date: <u>2012-08-20</u>	
Reviewed By: EMC Engineer	Harry Wu <i>Harry Wu</i>
Prepared by: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, or any agency of the Federal Government.

* This report contains data that are not covered by the NVLAP accreditation and are marked with an asterisk “★” (Rev.2)

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST FACILITY	3
SYSTEM TEST CONFIGURATION.....	4
JUSTIFICATION	4
EUT EXERCISE SOFTWARE	4
EQUIPMENT MODIFICATIONS	4
LOCAL SUPPORT EQUIPMENT LIST AND DETAILS	4
EXTERNAL I/O CABLE.....	4
PRINTER	4
KEYBOARD	4
USB PORT OF EUT	4
BLOCK DIAGRAM OF TEST SETUP	5
SUMMARY OF TEST RESULTS.....	6
FCC §15.107 – AC LINE CONDUCTED EMISSIONS.....	7
MEASUREMENT UNCERTAINTY	7
EUT SETUP	7
EMI TEST RECEIVER SETUP.....	7
TEST PROCEDURE	8
TEST EQUIPMENT LIST AND DETAILS.....	8
TEST RESULTS SUMMARY	8
TEST DATA	8
FCC §15.109 - RADIATED EMISSIONS	11
MEASUREMENT UNCERTAINTY	11
EUT SETUP	11
EMI TEST RECEIVER SETUP.....	11
TEST PROCEDURE	12
CORRECTED AMPLITUDE & MARGIN CALCULATION	12
TEST EQUIPMENT LIST AND DETAILS.....	12
TEST RESULTS SUMMARY	12
TEST DATA	13

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *XIAMEN SCALETECH CO. ,LTD.*'s product, model number: *SDC 3550 35LB (FCC ID: ORBSDC35SCALE)* (the "EUT") in this report is a Stamps.com Stainless Steel 35 Ib, Digital Scale, which was measured approximately:24.15 cm (L) x21.6cm (W) x 3.5 cm (H), rated input voltage: DC 5.0V from PC, the highest operating frequency is 6 MHz.

All measurement and test data in this report was gathered from production sample serial number: 120809051 (Assigned by BACL, Dongguan). The EUT was received on 2012-08-15.

Objective

This report is prepared on behalf of *XIAMEN SCALETECH CO.,LTD* in accordance with Part 2, Subpart J, Part 15, Subparts A and B of the Federal Communication Commissions rules.

The objective of the manufacturer is to determine compliance with FCC Part 15 Class B.

Related Submittal(s)/Grant(s)

No Related Submittal(s)/Grant(s)

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 02, 2012. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2007070.htm>.

SYSTEM TEST CONFIGURATION

Justification

The system was configured for testing in a typical fashion (as normally used by a typical user).

EUT Exercise Software

The Elane USB Scale Weight Display was used.

Equipment Modifications


No modification was made to the EUT.

Local Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
DELL	Notebook computer	PP11L	QDS-BRCM1017
HP	Laser Jet5L	C3941A	JPTVOB2337
DELL	Keyboard	L100	CNORH656658907BL 05DC
SAST	Modem	AEM-2100	0293

External I/O Cable

Cable Description	Length (m)	From	To
Shielded Detachable Printer Cable	1.2	Parallel Port of PC	Printer
Shielded Detachable Serial Cable	1.2	Serial Port of PC	Modem
Shielded Detachable Keyboard Cable	1.5	Keyboard Port of PC	Keyboard
USB Cable	1.5	USB Port of PC	USB Port of EUT

Block Diagram of Test Setup

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
§15.107	AC Line Conducted Emissions	Compliance
§15.109	Radiated Emissions	Compliance


FCC §15.107 – AC LINE CONDUCTED EMISSIONS

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, and LISN.

Based on CISPR 16-4-2, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement at Bay Area Compliance Laboratories Corp. (Dongguan) is 1.5 dB.

EUT Setup



Note:

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2009 measurement procedure. The specification used was with the FCC Part 15.107 Class B limits.

The notebook adapter was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the notebook adapter was connected to the outlet of the first LISN and the other support equipments were connected to the outlet of the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R & S	EMI Test Receiver	ESCS 30	830245/006	2011-10-08	2012-10-07
R & S	LISN1	ESH3-Z5	843331/015	2011-10-08	2012-10-07
R & S	LISN2	ESH3-Z5	100113	2011-10-08	2012-10-07

* **Statement of Traceability:** Bay Area Compliance Laboratory Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.107, with the worst margin reading of:

17.70 dB at 0.365 MHz in the Line conducted

Test Data


Environmental Conditions

Temperature:	25 °C
Relative Humidity:	48 %
ATM Pressure:	100.0 kPa

The testing was performed by Star Xie on 2012-08-17.


Test mode: Running

120 V, 60 Hz, Line:



Frequency (MHz)	Cord. Reading (dB μ V)	Correction Factor (dB)	Limit (dB μ V)	Margin (dB)	Detector (PK/Ave/QP)
0.365	42.16	0.42	59.86	17.70	QP
0.440	29.24	0.42	47.71	18.47	Ave.
0.230	43.44	0.42	63.71	20.27	QP
0.585	25.38	0.43	46.00	20.62	Ave.
0.440	36.00	0.42	57.71	21.71	QP
0.580	32.83	0.43	56.00	23.17	QP
0.850	22.23	0.44	46.00	23.77	Ave.
0.725	22.15	0.44	46.00	23.85	Ave.
0.365	25.94	0.42	49.86	23.92	Ave.
0.720	32.04	0.44	56.00	23.96	QP
0.850	30.10	0.44	56.00	25.90	QP
0.230	26.78	0.42	53.71	26.93	Ave.

120 V, 60 Hz, Neutral:



Frequency (MHz)	Cord. Reading (dB μ V)	Correction Factor (dB)	Limit (dB μ V)	Margin (dB)	Detector (PK/Ave./QP)
0.365	41.48	0.42	59.86	18.38	QP
0.165	47.00	0.41	65.57	18.57	QP
0.220	43.95	0.42	64.00	20.05	QP
0.440	26.91	0.42	47.71	20.80	Ave.
0.190	43.29	0.42	64.86	21.57	QP
0.325	39.31	0.42	61.00	21.69	QP
0.440	33.88	0.42	57.71	23.83	QP
0.220	30.10	0.42	54.00	23.90	Ave.
0.365	24.48	0.42	49.86	25.38	Ave.
0.165	28.69	0.41	55.57	26.88	Ave.
0.325	23.22	0.42	51.00	27.78	Ave.
0.190	26.99	0.42	54.86	27.87	Ave.


FCC §15.109 - RADIATED EMISSIONS

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR 16-4-2, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement from 30 MHz to 1 GHz at Bay Area Compliance Laboratories Corp. (Dongguan) is 4.9 dB.

EUT Setup



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC Part 15.109, Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The notebook adapter connected to a 120 VAC/60 Hz power source.

EMI Test Receiver Setup

According to FCC 15.33 requirements, the system was measured from 30 MHz to 1 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	Detector
30MHz – 1000 MHz	120 kHz	300 kHz	QP

Test Procedure

For the radiated emissions test, the notebook adapter was connected to the first AC floor outlet and the other support equipments were connected to the second AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2011-11-11	2012-11-10
Sunol Sciences	Hybrid Antennas	JB3	A060611-1	2011-09-06	2012-09-05
HP	Pre-amplifier	8447E	2434A02181	2011-10-08	2012-10-07
R&S	Spectrum Analyzer	FSEM	1079 8500	2011-10-09	2012-10-08
Beijingdayang	Horn Antenna	OMCDH10180	10279001B	2010-07-30	2015-07-29
Mini-Circuits	Wideband Amplifier	ZVA-183-S+	96901149	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratory Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Results Summary

According to the data in the following table, the EUT complied with the FCC §15.109, Class B, with the worst margin reading of:

3.20 dB at 120.2766 MHz in the Horizontal polarization

Test Data


Environmental Conditions

Temperature:	26°C
Relative Humidity:	60 %
ATM Pressure:	100.0 kPa

The testing was performed by Star Xie on 2012-08-17.


Test mode: Running

Horizontal:



Frequency (MHz)	Receiver Reading (dBuV/m)	Detector (QP/Ave.)	Correction Factor (dB/m)	Cord. Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
120.2766	46.22	QP	-5.92	40.30	43.50	3.20*
250.3011	48.20	QP	-7.40	40.80	46.00	5.20
30.1054	30.18	QP	1.62	31.80	40.00	8.20
400.4320	40.74	QP	-3.14	37.60	46.00	8.40
903.3094	32.62	QP	4.48	37.10	46.00	8.90
501.1790	36.09	QP	-1.19	34.90	46.00	11.10

*Within measurement uncertainty!

Vertical:

Frequency (MHz)	Receiver Reading (dBuV/m)	Detector (QP/Ave.)	Correction Factor (dB/m)	Cord. Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
115.7256	44.78	QP	-6.38	38.40	43.50	5.10
146.3735	42.91	QP	-7.11	35.80	43.50	7.70
166.0680	42.68	QP	-7.58	35.10	43.50	8.40
30.3173	29.66	QP	1.44	31.10	40.00	8.90
903.3093	32.22	QP	4.48	36.70	46.00	9.30
250.3012	42.70	QP	-7.40	35.30	46.00	10.70

***** END OF REPORT *****