

TEST REPORT

Application No.: SZCR2506002548AT
Applicant: Beyerdynamic
Address of Applicant: 56 Central Avenue, Farmingdale, New York, 11735, United States
Manufacturer: beyerdynamic GmbH & Co.KG
Address of Manufacturer: Theresienstrasse 8, 74072 Heilbronn, Germany
Equipment Under Test (EUT):
EUT Name: Gaming Headset
Model No.: MMX 150 wireless
Trade Mark: beyerdynamic
FCC ID: OSDMMX150WL
Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2025-06-17
Date of Test: 2025-06-19 to 2025-07-01
Date of Issue: 2025-07-03

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 2 of 136

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2025-07-03		Original

Authorized for issue by:				
		Bill Chen/Project Engineer		
		Eric Fu/Reviewer		

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 3 of 136

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass
Other requirements Frequency Hopping Spread Spectrum System Hopping Sequence		N/A	47 CFR Part 15, Subpart C 15.247(a)(1),(g),(h)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Radiated Emissions which fall in the restricted bands		ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Below 1GHz		ANSI C63.10 (2013) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Above 1GHz		ANSI C63.10 (2013) Section 6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Conducted Peak Output Power		ANSI C63.10 (2013) Section 7.8.5	47 CFR Part 15, Subpart C 15.247(b)(1)	Pass
20dB Bandwidth		ANSI C63.10 (2013) Section 7.8.7	47 CFR Part 15, Subpart C 15.247(a)(1)	Pass
Carrier Frequencies Separation		ANSI C63.10 (2013) Section 7.8.2	47 CFR Part 15, Subpart C 15.247a(1)	Pass
Hopping Channel Number		ANSI C63.10 (2013) Section 7.8.3	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Dwell Time		ANSI C63.10 (2013) Section 7.8.4	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Conducted Band Edges Measurement		ANSI C63.10 (2013) Section 7.8.6	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions		ANSI C63.10 (2013) Section 7.8.8	47 CFR Part 15, Subpart C 15.247(d)	Pass

3 Contents

	Page
1 Cover Page	1
2 Test Summary	3
3 Contents	4
4 General Information.....	6
4.1 Details of E.U.T.	6
4.2 Description of Support Units	6
4.3 Measurement Uncertainty	7
4.4 Test Location.....	8
4.5 Test Facility	8
4.6 Deviation from Standards.....	8
4.7 Abnormalities from Standard Conditions	8
5 Equipment List	9
6 Radio Spectrum Technical Requirement	11
6.1 Antenna Requirement	11
6.1.1 Test Requirement:	11
6.1.2 Conclusion	11
6.2 Other requirements Frequency Hopping Spread Spectrum System Hopping Sequence.....	12
6.2.1 Test Requirement:	12
6.2.2 Conclusion	12
7 Radio Spectrum Matter Test Results	13
7.1 Conducted Emissions at AC Power Line (150kHz-30MHz).....	13
7.1.1 E.U.T. Operation	13
7.1.2 Test Mode Description	13
7.1.3 Test Setup Diagram	14
7.1.4 Measurement Procedure and Data.....	14
7.2 Radiated Emissions which fall in the restricted bands	19
7.2.1 E.U.T. Operation	19
7.2.2 Test Mode Description	20
7.2.3 Test Setup Diagram	20
7.2.4 Measurement Procedure and Data.....	21
7.3 Radiated Spurious Emissions Below 1GHz	30
7.3.1 E.U.T. Operation	30
7.3.2 Test Mode Description	30
7.3.3 Test Setup Diagram	31
7.3.4 Measurement Procedure and Data.....	31
7.4 Radiated Spurious Emissions Above 1GHz.....	36
7.4.1 E.U.T. Operation	36
7.4.2 Test Mode Description	36
7.4.3 Test Setup Diagram	37

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 5 of 136

7.4.4	Measurement Procedure and Data.....	38
7.5	Conducted Peak Output Power.....	51
7.5.1	E.U.T. Operation.....	51
7.5.2	Test Mode Description.....	51
7.5.3	Test Setup Diagram.....	52
7.5.4	Measurement Procedure and Data.....	52
7.6	20dB Bandwidth.....	53
7.6.1	E.U.T. Operation.....	53
7.6.2	Test Mode Description.....	53
7.6.3	Test Setup Diagram.....	53
7.6.4	Measurement Procedure and Data.....	54
7.7	Carrier Frequencies Separation.....	55
7.7.1	E.U.T. Operation.....	55
7.7.2	Test Mode Description.....	55
7.7.3	Test Setup Diagram.....	55
7.7.4	Measurement Procedure and Data.....	55
7.8	Hopping Channel Number.....	56
7.8.1	E.U.T. Operation.....	56
7.8.2	Test Mode Description.....	56
7.8.3	Test Setup Diagram.....	56
7.8.4	Measurement Procedure and Data.....	56
7.9	Dwell Time.....	57
7.9.1	E.U.T. Operation.....	57
7.9.2	Test Mode Description.....	57
7.9.3	Test Setup Diagram.....	57
7.9.4	Measurement Procedure and Data.....	58
7.10	Conducted Band Edges Measurement.....	59
7.10.1	E.U.T. Operation.....	59
7.10.2	Test Mode Description.....	59
7.10.3	Test Setup Diagram.....	60
7.10.4	Measurement Procedure and Data.....	60
7.11	Conducted Spurious Emissions.....	61
7.11.1	E.U.T. Operation.....	61
7.11.2	Test Mode Description.....	61
7.11.3	Test Setup Diagram.....	62
7.11.4	Measurement Procedure and Data.....	62
8	Test Setup Photo.....	63
9	EUT Constructional Details (EUT Photos).....	63
10	Appendix.....	64

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 6 of 136

4 General Information

4.1 Details of E.U.T.

Power supply:	Rechargeable battery DC 3.7V 850mAh 3.145Wh(Charging by Type C port) Dongle: DC Input 5V
Cable(s):	Type C cable:180cm unshielded Type C to AUX in cable:180cm unshielded
RF cable(Provided by the customer):	0.5dB
BT	
Operation Frequency:	2402MHz to 2480MHz
Modulation Type:	GFSK, pi/4DQPSK, 8DPSK
Number of Channels:	79
Channel Spacing:	1MHz
Spectrum Spread Technology:	Frequency Hopping Spread Spectrum(FHSS)
Antenna Type:	PCB Antenna
Antenna Gain:	3.6dBi
2.4GHz	
Operation Frequency:	2402MHz to 2480MHz
Modulation Type:	Pi/4DQPSK
Channel Spacing:	1MHz
Number of Channels:	79
Antenna Type:	PCB Antenna
Antenna Gain:	3.6dBi

Remark:The information in this section is provided by the applicant or manufacturer, SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Adapter	Apple	A1443	REF. No.SEA05D11D

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 7 of 136

4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Emissions at AC Power Line (150kHz-30MHz)	$\pm 3.1\text{dB}$
Radiated Emissions which fall in the restricted bands	$\pm 6.0\text{dB}$ (Below 1GHz); $\pm 4.6\text{dB}$ (Above 1GHz)
Radiated Spurious Emissions Below 1GHz	$\pm 6.0\text{dB}$ for 3m; $\pm 5.0\text{dB}$ for 10m
Radiated Spurious Emissions Above 1GHz	$\pm 4.6\text{dB}$ (1-18GHz); $\pm 4.8\text{dB}$ (18-40GHz)
Conducted Peak Output Power	$\pm 0.75\text{dB}$
20dB Bandwidth	$\pm 3\%$
Carrier Frequencies Separation	$\pm 7.25 \times 10^{-8}$
Hopping Channel Number	$\pm 7.25 \times 10^{-8}$
Dwell Time	$\pm 0.37\%$
Conducted Band Edges Measurement	$\pm 0.75\text{dB}$
Conducted Spurious Emissions	$\pm 0.75\text{dB}$
Remark: The U_{lab} (lab Uncertainty) is less than $U_{\text{CISPR/ETSI}}$ (CISPR/ETSI Uncertainty), so the test results – compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit; – non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.	

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 8 of 136

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• VCCI (Member No. 1937)

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• FCC –Designation Number: CN1336

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1336. Test Firm Registration Number: 787754.

• Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 9 of 136

5 Equipment List

Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2025-05-07	2028-05-06
EMI Test Receiver	Rohde&Schwarz	ESR	SZ-WRG-M-047	2025-01-08	2026-01-07
Measurement Software	AUDIX	e3 V8.2014-6-27a	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM024-01	2025-07-05	2026-07-04
LISN	Rohde&Schwarz	ENV216	SEM007-01	2024-08-15	2025-08-14
LISN	ETS-LINDGREN	3816/2	SEM007-02	2025-03-03	2026-03-02

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
3m Fully-Anechoic Chamber	AUDIX	N/A	SEM001-02	2025-05-07	2028-05-06
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2025-03-04	2026-03-03
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2023-07-23	2025-07-22
Microwave system amplifier	Agilent	83017A	SEM005-25	2024-09-14	2025-09-13
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2025-07-05	2026-07-04
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2024-08-10	2025-08-09
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2025-03-21	2026-03-20

Radiated Spurious Emissions Below 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Loop Antenna	ETS-Lindgren	6502	SEM003-08	2023-11-20	2025-11-19
3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2023-06-19	2026-06-18
MXE EMI Receiver	Agilent Technologies	N9038A	SEM004-15	2024-08-14	2025-08-13
BiConiLog Antenna	ETS-LINDGREN	3142C	SEM003-01	2023-09-16	2025-09-15
Pre-Amplifier	Agilent Technologies	8447D	SEM005-01	2025-03-04	2026-03-03
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM025-01	2025-07-05	2026-07-04

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 10 of 136

Radiated Spurious Emissions Above 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
3m Fully-Anechoic Chamber	AUDIX	N/A	SEM001-02	2025-05-07	2028-05-06
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2025-03-04	2026-03-03
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2023-07-23	2025-07-22
Microwave system amplifier	Agilent	83017A	SEM005-25	2024-09-14	2025-09-13
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2025-07-05	2026-07-04
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2024-08-10	2025-08-09
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2025-03-21	2026-03-20

RF Conducted Test					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Power Sensor	TST PASS	TSPS2023R	SEM009-26	2025-03-04	2026-03-03
Power Sensor	KEYSIGHT	U2021XA	SEM009-16	2025-03-04	2026-03-03
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2024-08-14	2025-08-13
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2025-03-04	2026-03-03
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2025-07-05	2026-07-04
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2025-03-03	2026-03-02

General used equipment					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	deli	8838	SEM002-32	2024-07-24	2025-07-23
Humidity/ Temperature Indicator	deli	8838	SEM002-33	2024-07-24	2025-07-23
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2025-03-03	2026-03-02

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 3.6dBi.

Antenna location: Refer to internal photo.

6.2 Other requirements Frequency Hopping Spread Spectrum System Hopping Sequence

6.2.1 Test Requirement:

47 CFR Part 15, Subpart C 15.247(a)(1),(g),(h)

6.2.2 Conclusion

Standard Requirement:

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

Compliance for section 15.247(a)(1):

According to Technical Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones.

> Number of shift register stages: 9

> Length of pseudo-random sequence: $2^9 - 1 = 511$ bits

> Longest sequence of zeros: 8 (non-inverted signal)

Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:

Each frequency used equally on the average by each transmitter.

According to Technical Specification, the receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any transmitters and shift frequencies in synchronization with the transmitted signals.

Compliance for section 15.247(g):

According to Technical Specification, the system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

Compliance for section 15.247(h):

According to Technical specification, the system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

The system is designed not have the ability to coordinated with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.

7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207

Test Method: ANSI C63.10 (2013) Section 6.2

Limit:

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency.		
Detector: Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz		

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 22.5 °C


Humidity: 44.5 % RH

Atmospheric Pressure: 1020 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	01	Charge + TX_non-Hop mode_Keep the EUT in charging and continuously transmitting mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.
Final test	11	Charge + TX_non-Hop mode(2.4GHz Headset)_Keep the EUT in charging and continuously transmitting mode with Pi/4DQPSK modulation.

7.1.3 Test Setup Diagram



7.1.4 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 50\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark : $\text{Level} = \text{Read Level} + \text{Cable Loss} + \text{LISN Factor}$


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 15 of 136

Test Mode: 01; Line: Live line



Site : Shielding Room
 Condition: Line
 Job No. : 02548AT/02549AT
 Test mode: 01

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.1508	0.06	10.19	5.54	15.79	65.96	-50.17	QP
2	0.1508	0.06	10.19	-1.37	8.88	55.96	-47.08	Average
3	0.3692	0.07	9.72	5.76	15.55	58.52	-42.97	QP
4	0.3692	0.07	9.72	-2.14	7.65	48.52	-40.87	Average
5	0.9839	0.09	9.58	1.84	11.51	56.00	-44.49	QP
6	0.9839	0.09	9.58	-6.24	3.43	46.00	-42.57	Average
7	1.6981	0.10	9.58	-6.07	3.61	56.00	-52.39	QP
8	1.6981	0.10	9.58	-13.41	-3.73	46.00	-49.73	Average
9	4.9782	0.12	9.66	1.94	11.72	56.00	-44.28	QP
10	4.9782	0.12	9.66	-6.80	2.98	46.00	-43.02	Average
11 *	12.4495	0.23	9.81	12.36	22.40	60.00	-37.60	QP
12 *	12.4495	0.23	9.81	1.96	12.00	50.00	-38.00	Average


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 16 of 136

Test Mode: 01; Line: Neutral Line



Site : Shielding Room
Condition: Neutral
Job No. : 02548AT/02549AT
Test mode: 01

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.1508	0.06	10.15	8.06	18.27	65.96	-47.69	QP
2	0.1508	0.06	10.15	-2.15	8.06	55.96	-47.90	Average
3	0.3149	0.07	9.76	3.44	13.27	59.84	-46.57	QP
4	0.3149	0.07	9.76	-4.45	5.38	49.84	-44.46	Average
5	0.8992	0.09	9.57	-7.04	2.62	56.00	-53.38	QP
6	0.8992	0.09	9.57	-15.54	-5.88	46.00	-51.88	Average
7	2.0012	0.10	9.55	-3.14	6.51	56.00	-49.49	QP
8	2.0012	0.10	9.55	-10.34	-0.69	46.00	-46.69	Average
9	4.9782	0.12	9.56	1.99	11.67	56.00	-44.33	QP
10	4.9782	0.12	9.56	-7.07	2.61	46.00	-43.39	Average
11 *	14.7497	0.26	9.84	15.41	25.51	60.00	-34.49	QP
12 *	14.7497	0.26	9.84	4.66	14.76	50.00	-35.24	Average


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 17 of 136

Test Mode: 11; Line: Live line



Site : Shielding Room

Condition: Line

Job No. : 02548AT

Test mode: 11

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.1598	0.05	10.18	30.73	40.96	65.47	-24.51	QP
2	0.1598	0.05	10.18	11.47	21.70	55.47	-33.77	Average
3	0.1874	0.06	10.14	33.21	43.41	64.15	-20.74	QP
4	0.1874	0.06	10.14	19.26	29.46	54.15	-24.69	Average
5	0.2562	0.06	9.96	31.19	41.21	61.56	-20.35	QP
6	0.2562	0.06	9.96	20.30	30.32	51.56	-21.24	Average
7	0.3166	0.07	9.82	24.19	34.08	59.80	-25.72	QP
8	0.3166	0.07	9.82	11.03	20.92	49.80	-28.88	Average
9 *	4.6469	0.13	9.66	28.39	38.18	56.00	-17.82	QP
10 *	4.6469	0.13	9.66	18.45	28.24	46.00	-17.76	Average
11	6.7333	0.16	9.68	22.16	32.00	60.00	-28.00	QP
12	6.7333	0.16	9.68	13.85	23.69	50.00	-26.31	Average


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 18 of 136

Test Mode: 11; Line: Neutral Line



Site : Shielding Room

Condition: Neutral

Job No. : 02548AT

Test mode: 11

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.1633	0.05	10.13	30.16	40.34	65.30	-24.96	QP
2	0.1633	0.05	10.13	11.38	21.56	55.30	-33.74	Average
3	0.1777	0.05	10.11	31.32	41.48	64.59	-23.11	QP
4	0.1777	0.05	10.11	13.71	23.87	54.59	-30.72	Average
5	0.2575	0.06	9.89	30.68	40.63	61.51	-20.88	QP
6	0.2575	0.06	9.89	20.09	30.04	51.51	-21.47	Average
7	0.3200	0.07	9.76	25.00	34.83	59.71	-24.88	QP
8	0.3200	0.07	9.76	15.94	25.77	49.71	-23.94	Average
9 *	4.2918	0.13	9.55	27.06	36.74	56.00	-19.26	QP
10 *	4.2918	0.13	9.55	18.09	27.77	46.00	-18.23	Average
11	13.6228	0.25	9.79	23.82	33.86	60.00	-26.14	QP
12	13.6228	0.25	9.79	16.41	26.45	50.00	-23.55	Average

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 19 of 136

7.2 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.10.5

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C


Humidity: 56.3 % RH

Atmospheric Pressure: 1020 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.
Pre-scan	01	Charge + TX_non-Hop mode_Keep the EUT in charging and continuously transmitting mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.
Final test	10	TX_non-Hop mode(2.4GHz Headset)_ Keep the EUT in charging and continuously transmitting mode with Pi/4DQPSK modulation.
Pre-scan	11	Charge + TX_non-Hop mode(2.4GHz Headset)_Keep the EUT in charging and continuously transmitting mode with Pi/4DQPSK modulation.

7.2.3 Test Setup Diagram



7.2.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: $\text{Level} = \text{Read Level} + \text{Cable Loss} + \text{Antenna Factor} - \text{Preamp Factor}$

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Remark 3: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.

Remark 4: For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 22 of 136

Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02548AT\02549AT
Mode : 2402 Band edge
: BT

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2353.877	15.79	29.10	32.80	35.01	47.10	74.00	-26.90	peak
2	2390.000	15.81	29.10	32.78	34.81	46.94	74.00	-27.06	peak
3 p	2402.000	15.82	29.09	32.77	90.29	102.43	74.00	28.43	peak


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 23 of 136

Test Mode: 00; Polarity: Vertical; Modulation:GFSK; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 02548AT\02549AT
Mode : 2402 Band edge
: BT

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2383.793	15.81	29.10	32.78	35.91	48.04	74.00	-25.96	peak
2	2390.000	15.81	29.10	32.78	34.83	46.96	74.00	-27.04	peak
3 p	2402.000	15.82	29.09	32.77	91.39	103.53	74.00	29.53	peak


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 24 of 136

Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02548AT\02549AT
Mode : 2480 Band edge
: BT

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p	2480.000	15.86	28.90	32.73	89.49	101.52	74.00	27.52	peak
2	2483.500	15.86	28.90	32.73	35.90	47.93	74.00	-26.07	peak
3	2485.294	15.86	28.90	32.73	37.23	49.26	74.00	-24.74	peak


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 25 of 136

Test Mode: 00; Polarity: Vertical; Modulation:GFSK; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 02548AT\02549AT
Mode : 2480 Band edge
: BT

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	2480.000	15.86	28.90	32.73	91.68	103.71	74.00	29.71 peak
2	2483.500	15.86	28.90	32.73	37.23	49.26	74.00	-24.74 peak
3	2484.071	15.86	28.90	32.73	38.08	50.11	74.00	-23.89 peak


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 26 of 136

Test Mode: 10; Polarity: Horizontal; Modulation: Pi/4DQPSK; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02548AT\02549AT
Mode : 2402 Band edge

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2343.923	15.78	29.01	32.80	36.11	48.10	74.00	-25.90 Peak
2	2390.000	15.81	29.10	32.78	34.24	46.37	74.00	-27.63 peak
3 p	2402.000	15.82	29.09	32.77	93.81	105.95	74.00	31.95 peak


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 27 of 136

Test Mode: 10; Polarity: Vertical; Modulation: Pi/4DQPSK; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 02548AT\02549AT
Mode : 2402 Band edge

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2340.250	15.78	28.96	32.81	35.69	47.62	74.00	-26.38 Peak
2	2390.000	15.81	29.10	32.78	34.30	46.43	74.00	-27.57 peak
3 p	2402.000	15.82	29.09	32.77	87.21	99.35	74.00	25.35 peak


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 28 of 136

Test Mode: 10; Polarity: Horizontal; Modulation: Pi/4DQPSK; Channel:High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02548AT\02549AT
Mode : 2480 Band edge

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	2480.000	15.86	28.90	32.73	92.42	104.45	74.00	30.45 peak
2	2483.500	15.86	28.90	32.73	33.95	45.98	74.00	-28.02 peak
3	2491.772	15.87	28.90	32.73	35.96	48.00	74.00	-26.00 Peak


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 29 of 136

Test Mode: 10; Polarity: Vertical; Modulation: Pi/4DQPSK; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 02548AT\02549AT
Mode : 2480 Band edge

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	2480.000	15.86	28.90	32.73	87.46	99.49	74.00	25.49 peak
2	2483.500	15.86	28.90	32.73	34.37	46.40	74.00	-27.60 peak
3	2492.975	15.87	28.90	32.73	35.21	47.25	74.00	-26.75 Peak

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 30 of 136

7.3 Radiated Spurious Emissions Below 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C


Humidity: 45.6 % RH

Atmospheric Pressure: 1020 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	00	TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.
Final test	01	Charge + TX_non-Hop mode_Keep the EUT in charging and continuously transmitting mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.
Pre-scan	10	TX_non-Hop mode(2.4GHz Headset)_ Keep the EUT in charging and continuously transmitting mode with Pi/4DQPSK modulation.
Final test	11	Charge + TX_non-Hop mode(2.4GHz Headset)_Keep the EUT in charging and continuously transmitting mode with Pi/4DQPSK modulation.

7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark:

- Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
- Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 32 of 136

Test Mode: 01; Polarity: Horizontal



Site : chamber
Condition: 3m HORIZONTAL
Job No. : 02548AT/02549AT
Test Mode: 01

		Ant	Cable	Preamp	Read	Limit	Over	
	Freq	Factor	Loss	Factor	Level	Level	Line	Limit Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB
1	30.531	20.95	0.68	27.65	23.31	17.29	40.00	-22.71 QP
2	50.586	12.67	0.87	27.63	23.98	9.89	40.00	-30.11 QP
3	101.289	12.32	1.23	27.60	29.13	15.08	43.50	-28.42 QP
4	346.809	19.70	2.39	27.63	25.50	19.96	46.00	-26.04 QP
5	675.208	25.71	3.47	27.89	24.83	26.12	46.00	-19.88 QP
6 q	912.862	28.00	4.16	26.89	24.28	29.55	46.00	-16.45 QP


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 33 of 136

Test Mode: 01; Polarity: Vertical



Site : chamber
Condition: 3m VERTICAL
Job No. : 02548AT/02549AT
Test Mode: 01

		Ant	Cable	Preamp	Read	Limit	Over	
	Freq	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB
1	34.037	19.41	0.72	27.65	25.94	18.42	40.00	-21.58 QP
2	66.034	10.93	0.99	27.62	34.83	19.13	40.00	-20.87 QP
3	101.289	12.32	1.23	27.60	35.33	21.28	43.50	-22.22 QP
4	390.723	20.75	2.55	27.73	24.20	19.77	46.00	-26.23 QP
5	699.305	25.93	3.54	27.83	24.23	25.87	46.00	-20.13 QP
6 q	906.482	27.83	4.14	26.93	24.80	29.84	46.00	-16.16 QP


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 34 of 136

Test Mode: 11; Polarity: Horizontal



Site : chamber
Condition: 3m HORIZONTAL
Job No. : 02548AT
Test Mode: 11

		Ant	Cable	Preamp	Read	Limit	Over	
	Freq	Factor	Loss	Factor	Level	Level	Line	Limit Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB
1	31.731	20.39	0.69	27.65	23.75	17.18	40.00	-22.82 QP
2	52.391	12.40	0.88	27.63	23.91	9.56	40.00	-30.44 QP
3	193.773	14.18	1.74	27.79	25.09	13.22	43.50	-30.28 QP
4	377.259	20.81	2.50	27.70	24.69	20.30	46.00	-25.70 QP
5	684.745	25.76	3.50	27.87	24.48	25.87	46.00	-20.13 QP
6 q	948.761	28.23	4.25	26.68	24.12	29.92	46.00	-16.08 QP


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 35 of 136

Test Mode: 11; Polarity: Vertical



Site : chamber
Condition: 3m VERTICAL
Job No. : 02548AT
Test Mode: 11

		Ant	Cable	Preamp	Read	Limit	Over	
	Freq	Factor	Loss	Factor	Level	Level	Line	Limit Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB
1	30.745	20.85	0.68	27.65	23.21	17.09	40.00	-22.91 QP
2	51.121	12.59	0.87	27.63	23.64	9.47	40.00	-30.53 QP
3	197.893	14.08	1.75	27.80	23.80	11.83	43.50	-31.67 QP
4	392.095	20.73	2.55	27.73	24.04	19.59	46.00	-26.41 QP
5	682.348	25.83	3.49	27.88	24.12	25.56	46.00	-20.44 QP
6 q	932.272	28.19	4.21	26.78	23.88	29.50	46.00	-16.50 QP

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 36 of 136

7.4 Radiated Spurious Emissions Above 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.6

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
Above 1000	500	3

7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C


Humidity: 56.3 % RH

Atmospheric Pressure: 1020 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.
Pre-scan	01	Charge + TX_non-Hop mode_Keep the EUT in charging and continuously transmitting mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.
Final test	10	TX_non-Hop mode(2.4GHz Headset)_ Keep the EUT in charging and continuously transmitting mode with Pi/4DQPSK modulation.
Pre-scan	11	Charge + TX_non-Hop mode(2.4GHz Headset)_Keep the EUT in charging and continuously transmitting mode with Pi/4DQPSK modulation.

7.4.3 Test Setup Diagram



7.4.4 Measurement Procedure and Data

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 1GHz to 25GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
- 4: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.
- 5:For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle<98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 39 of 136

Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:Low



Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 02548AT\02549AT
 Mode : 2402 TX RSE
 : BT

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1592.571	4.77	26.83	54.80	58.38	35.18	74.00	-38.82	peak
2	4367.058	8.04	34.54	54.26	56.25	44.57	74.00	-29.43	peak
3 p	4804.000	8.00	34.32	54.22	63.92	52.02	74.00	-21.98	peak
4	6088.991	9.45	35.08	53.11	56.02	47.44	74.00	-26.56	peak
5	7206.000	9.32	35.70	53.18	54.53	46.37	74.00	-27.63	peak
6	9608.000	11.41	37.42	53.35	52.86	48.34	74.00	-25.66	peak


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 40 of 136

Test Mode: 00; Polarity: Vertical; Modulation:GFSK; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 02548AT\02549AT
Mode : 2402 TX RSE
: BT

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1615.754	4.82	26.64	54.81	59.14	35.79	74.00	-38.21	peak
2	3186.869	6.77	32.79	54.85	60.91	45.62	74.00	-28.38	peak
3 p	4804.000	8.00	34.32	54.22	64.94	53.04	74.00	-20.96	peak
4	6835.278	9.40	35.44	53.18	55.10	46.76	74.00	-27.24	peak
5	7206.000	9.32	35.70	53.18	55.91	47.75	74.00	-26.25	peak
6	9608.000	11.41	37.42	53.35	54.21	49.69	74.00	-24.31	peak


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 41 of 136

Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:middle



Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 02548AT\02549AT
 Mode : 2441 TX RSE
 : BT

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1485.841	4.57	26.40	54.77	58.32	34.52	74.00	-39.48	peak
2	4367.058	8.04	34.54	54.26	56.73	45.05	74.00	-28.95	peak
3 p	4882.000	8.03	34.63	54.21	63.38	51.83	74.00	-22.17	peak
4	6995.172	9.53	35.71	53.20	55.18	47.22	74.00	-26.78	peak
5	7323.000	9.20	35.70	53.17	54.09	45.82	74.00	-28.18	peak
6	9764.000	11.32	37.37	53.29	54.97	50.37	74.00	-23.63	peak


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 42 of 136

Test Mode: 00; Polarity: Vertical; Modulation:GFSK; Channel:middle



Site : chamber
Condition: 3m VERTICAL
Job No : 02548AT\02549AT
Mode : 2441 TX RSE
: BT

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1319.794	4.56	24.68	54.72	61.78	36.30	74.00	-37.70	peak
2	4354.454	8.06	34.44	54.26	56.57	44.81	74.00	-29.19	peak
3 p	4882.000	8.03	34.63	54.21	64.83	53.28	74.00	-20.72	peak
4	5967.033	9.51	34.77	53.13	55.44	46.59	74.00	-27.41	peak
5	7323.000	9.20	35.70	53.17	54.45	46.18	74.00	-27.82	peak
6	9764.000	11.32	37.37	53.29	54.24	49.64	74.00	-24.36	peak


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 43 of 136

Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:High



Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 02548AT\02549AT
 Mode : 2480 TX RSE
 : BT

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1398.336	4.57	24.60	54.75	62.58	37.00	74.00	-37.00	peak
2	4405.090	7.99	34.74	54.26	56.91	45.38	74.00	-28.62	peak
3 p	4960.000	8.06	34.56	54.20	63.87	52.29	74.00	-21.71	peak
4	6995.172	9.53	35.71	53.20	55.32	47.36	74.00	-26.64	peak
5	7440.000	9.09	35.96	53.15	54.55	46.45	74.00	-27.55	peak
6	9920.000	11.23	37.30	53.23	53.54	48.84	74.00	-25.16	peak


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 44 of 136

Test Mode: 00; Polarity: Vertical; Modulation:GFSK; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 02548AT\02549AT
Mode : 2480 TX RSE
: BT

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	4.56	24.59	54.73	61.99	36.41	74.00	-37.59	peak
2	4367.058	8.04	34.54	54.26	57.28	45.60	74.00	-28.40	peak
3 p	4960.000	8.06	34.56	54.20	65.37	53.79	74.00	-20.21	peak
4	6340.436	9.26	34.92	53.14	55.62	46.66	74.00	-27.34	peak
5	7440.000	9.09	35.96	53.15	54.87	46.77	74.00	-27.23	peak
6	9920.000	11.23	37.30	53.23	53.27	48.57	74.00	-25.43	peak


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 45 of 136

Test Mode: 10; Polarity: Horizontal; Modulation: Pi/4DQPSK; Channel:Low



Site : chamber

Condition: 3m HORIZONTAL

Job No : 02548AT\02549AT

Mode : 2402 TX RSE

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1542.733	4.66	26.97	54.79	55.79	32.63	74.00	-41.37	peak
2	4341.886	8.07	34.34	54.26	53.66	41.81	74.00	-32.19	peak
3 p	4804.000	8.00	34.32	54.22	64.73	52.83	74.00	-21.17	peak
4	6488.754	9.15	35.58	53.15	53.76	45.34	74.00	-28.66	peak
5	7206.000	9.32	35.70	53.18	52.26	44.10	74.00	-29.90	peak
6	9608.000	11.41	37.42	53.35	52.40	47.88	74.00	-26.12	peak


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 46 of 136

Test Mode: 10; Polarity: Vertical; Modulation: Pi/4DQPSK; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 02548AT\02549AT
Mode : 2402 TX RSE

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1503.119	4.58	26.81	54.78	58.08	34.69	74.00	-39.31	peak
2	4392.376	8.00	34.74	54.26	54.12	42.60	74.00	-31.40	peak
3 p	4804.000	8.00	34.32	54.22	64.76	52.86	74.00	-21.14	peak
4	6954.852	9.50	35.79	53.20	52.99	45.08	74.00	-28.92	peak
5	7206.000	9.32	35.70	53.18	52.79	44.63	74.00	-29.37	peak
6	9608.000	11.41	37.42	53.35	52.26	47.74	74.00	-26.26	peak


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 47 of 136

Test Mode: 10; Polarity: Horizontal; Modulation: Pi/4DQPSK; Channel:middle



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02548AT\02549AT
Mode : 2441 TX RSE

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1601.804	4.79	26.78	54.80	55.62	32.39	74.00	-41.61	peak
2	4379.699	8.02	34.64	54.26	54.97	43.37	74.00	-30.63	peak
3 p	4882.000	8.03	34.63	54.21	63.99	52.44	74.00	-21.56	peak
4	6432.732	9.19	35.40	53.15	52.59	44.03	74.00	-29.97	peak
5	7323.000	9.20	35.70	53.17	51.88	43.61	74.00	-30.39	peak
6	9764.000	11.32	37.37	53.29	52.37	47.77	74.00	-26.23	peak


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 48 of 136

Test Mode: 10; Polarity: Vertical; Modulation: Pi/4DQPSK; Channel:middle



Site : chamber
Condition: 3m VERTICAL
Job No : 02548AT\02549AT
Mode : 2441 TX RSE

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1498.781	4.57	26.77	54.78	57.05	33.61	74.00	-40.39	peak
2	4267.237	8.18	33.87	54.27	55.25	43.03	74.00	-30.97	peak
3 p	4882.000	8.03	34.63	54.21	64.80	53.25	74.00	-20.75	peak
4	6071.417	9.46	35.04	53.11	52.63	44.02	74.00	-29.98	peak
5	7323.000	9.20	35.70	53.17	49.94	41.67	74.00	-32.33	peak
6	9764.000	11.32	37.37	53.29	52.48	47.88	74.00	-26.12	peak


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 49 of 136

Test Mode: 10; Polarity: Horizontal; Modulation: Pi/4DQPSK; Channel:High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02548AT\02549AT
Mode : 2480 TX RSE

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1490.142	4.57	26.52	54.77	56.83	33.15	74.00	-40.85	peak
2	4354.454	8.06	34.44	54.26	53.76	42.00	74.00	-32.00	peak
3 p	4960.000	8.06	34.56	54.20	64.19	52.61	74.00	-21.39	peak
4	5567.137	9.33	34.70	53.55	53.72	44.20	74.00	-29.80	peak
5	7440.000	9.09	35.96	53.15	51.92	43.82	74.00	-30.18	peak
6	9920.000	11.23	37.30	53.23	50.00	45.30	74.00	-28.70	peak


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 50 of 136

Test Mode: 10; Polarity: Vertical; Modulation: Pi/4DQPSK; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 02548AT\02549AT
Mode : 2480 TX RSE

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1611.091	4.81	26.69	54.81	56.69	33.38	74.00	-40.62	peak
2	3890.255	8.21	33.66	54.37	54.46	41.96	74.00	-32.04	peak
3 p	4960.000	8.06	34.56	54.20	64.28	52.70	74.00	-21.30	peak
4	5898.442	9.48	34.59	53.20	53.79	44.66	74.00	-29.34	peak
5	7440.000	9.09	35.96	53.15	52.71	44.61	74.00	-29.39	peak
6	9920.000	11.23	37.30	53.23	50.79	46.09	74.00	-27.91	peak

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 51 of 136

7.5 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(1)

Test Method: ANSI C63.10 (2013) Section 7.8.5

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 24.9 °C


Humidity: 42.8 % RH

Atmospheric Pressure: 1020 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.
Final test	10	TX_non-Hop mode(2.4GHz Headset)_Keep the EUT in continuously transmitting mode with Pi/4DQPSK modulation.

7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

Note: Since the verify power the same operating range bandwidth and smaller power can be covered by the higher power.

Please Refer to Appendix for Details

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 53 of 136

7.6 20dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247(a)(1)

Test Method: ANSI C63.10 (2013) Section 7.8.7

Limit:

20 dB bandwidth of the hopping channel	Hopping frequencies	Average time of occupancy
less than 250 kHz	least 50 hopping frequencies	shall not be greater than 0.4 seconds within a 20 second period
250 kHz to 500kHz	least 25 hopping frequencies	shall not be greater than 0.4 seconds within a 10 second period.

7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 24.9 °C


Humidity: 42.8 % RH

Atmospheric Pressure: 1020 mbar

7.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.
Final test	10	TX_non-Hop mode(2.4GHz Headset)_Keep the EUT in continuously transmitting mode with Pi/4DQPSK modulation.

7.6.3 Test Setup Diagram



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 54 of 136

7.6.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.7 Carrier Frequencies Separation

Test Requirement 47 CFR Part 15, Subpart C 15.247a(1)

Test Method: ANSI C63.10 (2013) Section 7.8.2

Limit:

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 24.9 °C


Humidity: 42.8 % RH

Atmospheric Pressure: 1020 mbar

7.7.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX_Hop mode_Keep the EUT in frequency hopping mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.
Final test	12	TX_Hop mode(2.4GHz Headset)_Keep the EUT in frequency hopping mode with Pi/4DQPSK modulation.

7.7.3 Test Setup Diagram



7.7.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.8 Hopping Channel Number

Test Requirement 47 CFR Part 15, Subpart C 15.247a(1)(iii)
Test Method: ANSI C63.10 (2013) Section 7.8.3

Limit:

Frequency range(MHz)	Number of hopping channels (minimum)
902-928	50 for 20dB bandwidth <250kHz
	25 for 20dB bandwidth ≥250kHz
2400-2483.5	15
5725-5850	75


7.8.1 E.U.T. Operation

Operating Environment:
Temperature: 24.9 °C Humidity: 42.8 % RH Atmospheric Pressure: 1020 mbar

7.8.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX_Hop mode_Keep the EUT in frequency hopping mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.
Final test	12	TX_Hop mode(2.4GHz Headset)_Keep the EUT in frequency hopping mode with Pi/4DQPSK modulation.

7.8.3 Test Setup Diagram



7.8.4 Measurement Procedure and Data

Please Refer to Appendix for Details

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 57 of 136

7.9 Dwell Time

Test Requirement 47 CFR Part 15, Subpart C 15.247a(1)(iii)

Test Method: ANSI C63.10 (2013) Section 7.8.4

Limit:

Frequency(MHz)	Limit
902-928	0.4S within a 20S period(20dB bandwidth<250kHz)
	0.4S within a 10S period(20dB bandwidth≥250kHz)
2400-2483.5	0.4S within a period of 0.4S multiplied by the number of hopping channels
5725-5850	0.4S within a 30S period

7.9.1 E.U.T. Operation

Operating Environment:

Temperature: 24.9 °C


Humidity: 42.8 % RH

Atmospheric Pressure: 1020 mbar

7.9.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX_Hop mode_Keep the EUT in frequency hopping mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.
Final test	12	TX_Hop mode(2.4GHz Headset)_Keep the EUT in frequency hopping mode with Pi/4DQPSK modulation.

7.9.3 Test Setup Diagram



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 58 of 136

7.9.4 Measurement Procedure and Data

Please Refer to Appendix for Details

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 59 of 136

7.10 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 7.8.6

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.10.1 E.U.T. Operation

Operating Environment:

Temperature: 24.9 °C


Humidity: 42.8 % RH

Atmospheric Pressure: 1020 mbar

7.10.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.
Final test	02	TX_Hop mode_Keep the EUT in frequency hopping mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.
Final test	10	TX_non-Hop mode(2.4GHz Headset)_Keep the EUT in continuously transmitting mode with Pi/4DQPSK modulation.
Final test	12	TX_Hop mode(2.4GHz Headset)_Keep the EUT in frequency hopping mode with Pi/4DQPSK modulation.

7.10.3 Test Setup Diagram



7.10.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.11 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)
Test Method: ANSI C63.10 (2013) Section 7.8.8

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


7.11.1 E.U.T. Operation

Operating Environment:
Temperature: 24.9 °C Humidity: 42.8 % RH Atmospheric Pressure: 1020 mbar

7.11.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.
Final test	10	TX_non-Hop mode(2.4GHz Headset)_Keep the EUT in continuously transmitting mode with Pi/4DQPSK modulation.

7.11.3 Test Setup Diagram



7.11.4 Measurement Procedure and Data

Please Refer to Appendix for Details

8 Test Setup Photo

Refer to Appendix - Test Setup Photo for SZCR2506002548AT

9 EUT Constructional Details (EUT Photos)

Refer to External and Internal Photos for SZCR2506002548AT

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 64 of 136

10 Appendix

BT

1. Duty Cycle


1.1 Test Result


1.1.1 Ant1


Ant1								
Mode	TX Type	Frequency (MHz)	Packet Type	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
GFSK	SISO	2402	DH5	2.904	3.729	77.88	1.09	0.00
		2441	DH5	2.905	3.729	77.90	1.08	0.00
		2480	DH5	2.904	3.729	77.88	1.09	0.00
Pi/4DQPSK	SISO	2402	2DH5	2.910	3.735	77.91	1.08	0.00
		2441	2DH5	2.909	3.734	77.91	1.08	0.03
		2480	2DH5	2.908	3.733	77.90	1.08	0.01
8DPSK	SISO	2402	3DH5	2.911	3.736	77.92	1.08	0.03
		2441	3DH5	2.911	3.736	77.92	1.08	0.04
		2480	3DH5	2.910	3.735	77.91	1.08	0.01

1.2 Test Graph

1.2.1 Ant1









SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 68 of 136





SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 70 of 136

2. Bandwidth

2.1 Test Result

2.1.1 OBW


Mode	TX Type	Frequency (MHz)	Packet Type	ANT	99% Occupied Bandwidth (MHz)		Verdict
					Result	Limit	
GFSK	SISO	2402	DH5	1	0.893	/	Pass
		2441	DH5	1	0.893	/	Pass
		2480	DH5	1	0.893	/	Pass
Pi/4DQPSK	SISO	2402	2DH5	1	1.196	/	Pass
		2441	2DH5	1	1.196	/	Pass
		2480	2DH5	1	1.197	/	Pass
8DPSK	SISO	2402	3DH5	1	1.203	/	Pass
		2441	3DH5	1	1.202	/	Pass
		2480	3DH5	1	1.202	/	Pass


2.1.2 20dB BW

Mode	TX Type	Frequency (MHz)	Packet Type	ANT	20dB Bandwidth (MHz)		Verdict
					Result	Limit	
GFSK	SISO	2402	DH5	1	0.964	/	Pass
		2441	DH5	1	0.965	/	Pass
		2480	DH5	1	0.964	/	Pass
Pi/4DQPSK	SISO	2402	2DH5	1	1.373	/	Pass
		2441	2DH5	1	1.372	/	Pass
		2480	2DH5	1	1.374	/	Pass
8DPSK	SISO	2402	3DH5	1	1.354	/	Pass
		2441	3DH5	1	1.353	/	Pass
		2480	3DH5	1	1.353	/	Pass

2.2 Test Graph

2.2.1 OBW






SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 73 of 136




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 74 of 136




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch


SZEMC-TRF-01 Rev. A/1


Report No.: SZCR250600254802

Page: 75 of 136



2.2.2 20dB BW






SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 78 of 136





SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 79 of 136





3.1 Test Result

3.1.1 Power

Mode	TX Type	Frequency (MHz)	Packet Type	Maximum Peak Conducted Output Power (dBm)		Verdict
				ANT1	Limit	
GFSK	SISO	2402	DH5	6.15	<=30	Pass
		2441	DH5	6.37	<=30	Pass
		2480	DH5	6.48	<=30	Pass
Pi/4DQPSK	SISO	2402	2DH5	6.42	<=20.97	Pass
		2441	2DH5	6.64	<=20.97	Pass
		2480	2DH5	6.76	<=20.97	Pass
8DPSK	SISO	2402	3DH5	6.70	<=20.97	Pass
		2441	3DH5	6.92	<=20.97	Pass
		2480	3DH5	7.02	<=20.97	Pass

Note1: Antenna Gain: Ant1: 3.60dBi;

4. Carrier Frequency Separation


4.1 Test Result

4.1.1 Ant1

Ant1							
Mode	TX Type	Frequency (MHz)	Packet Type	Channel Separation (MHz)	20dB Bandwidth (MHz)	Limit (MHz)	Verdict
GFSK	SISO	HOPP	DH5	1.016	0.965	>=0.965	Pass
Pi/4DQPSK	SISO	HOPP	2DH5	0.972	1.374	>=0.916	Pass
8DPSK	SISO	HOPP	3DH5	0.986	1.354	>=0.903	Pass

4.2 Test Graph

4.2.1 Ant1




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 84 of 136



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 85 of 136

5. Number of Hopping Frequencies


5.1 Test Result

5.1.1 HoppNum

Mode	TX Type	Frequency (MHz)	Packet Type	Num of Hopping Frequencies		Verdict
				ANT1	Limit	
GFSK	SISO	HOPP	DH5	79	>=15	Pass
Pi/4DQPSK	SISO	HOPP	2DH5	79	>=15	Pass
8DPSK	SISO	HOPP	3DH5	79	>=15	Pass

5.2 Test Graph

5.2.1 HoppNum




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 87 of 136



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 88 of 136

6. Time of Occupancy (Dwell Time)


6.1 Test Result

6.1.1 Ant1

Ant1									
Mode	TX Type	Frequency (MHz)	Packet Type	Duration of Single Pulse (ms)	Observation Period (s)	Num of Pulse in Observation Period	Dwell Time (ms)	Limit (ms)	Verdict
GFSK	SISO	HOPP	DH1	0.388	31.600	320	124.160	<=400	Pass
			DH3	1.652	31.600	149	246.148	<=400	Pass
			DH5	2.898	31.600	116	336.168	<=400	Pass
Pi/4DQPSK	SISO	HOPP	2DH1	0.398	31.600	316	125.768	<=400	Pass
			2DH3	1.656	31.600	155	256.680	<=400	Pass
			2DH5	2.904	31.600	105	304.920	<=400	Pass
8DPSK	SISO	HOPP	3DH1	0.396	31.600	319	126.324	<=400	Pass
			3DH3	1.646	31.600	146	240.316	<=400	Pass
			3DH5	2.906	31.600	96	278.976	<=400	Pass

6.2 Test Graph

6.2.1 Ant1





SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 90 of 136







SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 92 of 136






SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 94 of 136




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 95 of 136





SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 96 of 136





SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 98 of 136

7. Unwanted Emissions In Non-restricted Frequency Bands

7.1 Test Result

7.1.1 Ref

Mode	TX Type	Frequency (MHz)	Packet Type	ANT	Level of Reference (dBm)
GFSK	SISO	2402	DH5	1	5.47
		2441	DH5	1	5.66
		2480	DH5	1	5.82
Pi/4DQPSK	SISO	2402	2DH5	1	2.19
		2441	2DH5	1	2.35
		2480	2DH5	1	2.49
8DPSK	SISO	2402	3DH5	1	1.81
		2441	3DH5	1	1.99
		2480	3DH5	1	5.47

Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2013, the channel contains the maximum PSD level was used to establish the reference level.

SZEMC-TRF-01 Rev. A/1


Page: 99 of 136


Mode	TX Type	Frequency (MHz)	Packet Type	ANT	Level of Reference (dBm)	Limit (dBm)	Verdict
GFSK	SISO	2402	DH5	1	5.82	-14.18	Pass
		2441	DH5	1	5.82	-14.18	Pass
		2480	DH5	1	5.82	-14.18	Pass
		HOPP	DH5	1	5.82	-14.18	Pass
					5.82	-14.18	Pass
Pi/4DQPSK	SISO	2402	2DH5	1	2.49	-17.51	Pass
		2441	2DH5	1	2.49	-17.51	Pass
		2480	2DH5	1	2.49	-17.51	Pass
		HOPP	2DH5	1	2.49	-17.51	Pass
					2.49	-17.51	Pass
8DPSK	SISO	2402	3DH5	1	2.11	-17.89	Pass
		2441	3DH5	1	2.11	-17.89	Pass
		2480	3DH5	1	2.11	-17.89	Pass
		HOPP	3DH5	1	2.11	-17.89	Pass
					2.11	-17.89	Pass

Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2013, the channel contains the maximum PSD level was used to establish the reference level.

7.2 Test Graph

7.2.1 Ref






SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 102 of 136




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250600254802

Page: 103 of 136

8DPSK_3DH5_LCH_2402MHz_Ant1_NTNV



8DPSK_3DH5_MCH_2441MHz_Ant1_NTNV

