



**TEST REPORT NUMBER: (8523)343-0033(C)**

## TEST REPORT

|             |                                                                |         |     |
|-------------|----------------------------------------------------------------|---------|-----|
| Applicant:  | Jakks Pacific (HK) Ltd.                                        | Fax:    | --- |
|             |                                                                | E-mail: | --- |
| Address :   | 12/F., Wharf T&T Centre, 7 Canton Road. Tsim Sha Tsui Hongkong |         |     |
| Test Date : | 2023-12-29 to 2024-1-10                                        |         |     |

|                            |                                                                                              |
|----------------------------|----------------------------------------------------------------------------------------------|
| Manufacturer or Supplier : | Jakks Pacific, Inc.                                                                          |
| Address :                  | 2951 28th St Santa Monica CA 90405 United States Of America (Excluding The States Of Alaska) |
| Sample Description:        | Mario Kart Mini Motorcycle RC Racer                                                          |
| Model number:              | 78969RXNT                                                                                    |
| Additional Model :         | N/A                                                                                          |
| Rated Voltage:             | DC6.0V (AA*4)                                                                                |
| FCC ID :                   | OTA78969RXNT                                                                                 |
| IC :                       | 7783A-78969RXNT                                                                              |

**The submitted sample of the above equipment has been tested according to following standard(s)**

47 CFR Part 1.1307

47 CFR Part 2.1093

KDB447498D01 General RF Exposure Guidance v06

RSS-102 Issue 5 March 2015

**CONCLUSION: The submitted sample was found to COMPLY with the test requirement**

Assistant Manager

Name: Nick Lung

Date: JAN 30, 2024



TEST REPORT NUMBER: (8523)343-0033(C)

1 Contents

|                                                 | Page |
|-------------------------------------------------|------|
| TEST REPORT .....                               | 1    |
| 1 CONTENTS .....                                | 2    |
| 2 GENERAL INFORMATION .....                     | 3    |
| 2.1 CLIENT INFORMATION .....                    | 3    |
| 2.2 GENERAL DESCRIPTION OF EUT .....            | 3    |
| 3 SAR EVALUATION .....                          | 4    |
| 3.1 IC RF EXPOSURE COMPLIANCE REQUIREMENT ..... | 4    |
| 3.1.1 <i>Standard Requirement</i> .....         | 4    |
| 3.1.2 <i>Limits</i> .....                       | 4    |
| 3.1.3 <i>EUT RF Exposure</i> .....              | 6    |



**TEST REPORT NUMBER: (8523)343-0033(C)**

## **2 General Information**

### **2.1 Client Information**

|                          |                                                                                                      |
|--------------------------|------------------------------------------------------------------------------------------------------|
| Applicant:               | Jakks Pacific (HK) Ltd.                                                                              |
| Address of Applicant:    | 12/F., Wharf T&T Centre, 7 Canton Road, Tsim Sha Tsui Kowloon Hong Kong                              |
| Manufacturer:            | Jakks Pacific, Inc.                                                                                  |
| Address of Manufacturer: | 2951 28th St Santa Monica CA 90405 United States Of America (Excluding The States Of Alaska)         |
| Factory:                 | Jun Teng Plastic Products Co.,Ltd.                                                                   |
| Address of Factory:      | 1st building, No.3 Tao Jin Road, Qian Long Village, San Xing Town, Zhong Shan City, Guangdong, China |

### **2.2 General Description of EUT**

|                     |                                     |
|---------------------|-------------------------------------|
| Name:               | Mario Kart Mini Motorcycle RC Racer |
| Tset Model No.:     | 78969RXNT                           |
| Trade Mark :        | N/A                                 |
| Serial No :         | --                                  |
| Software Version:   | V1.1                                |
| Hardware Version:   | 78969 RX V05                        |
| Frequency Range:    | 2405-2475MHz                        |
| Modulation Type:    | GFSK                                |
| Number of Channels: | 32                                  |
| Sample Type:        | Portable product                    |
| Antenna Type:       | wire antenna                        |
| Antenna Gain:       | 2.97dBi                             |
| Power Supply:       | DC6.0V (AA*4)                       |



TEST REPORT NUMBER: (8523)343-0033(C)

### 3 SAR Evaluation

#### 3.1 RF Exposure Compliance Requirement

##### 3.1.1 Standard Requirement

IC: According to RSS-102 Issue 5 March 2015

##### 2.5.1 Exemption Limits for Routine Evaluation – SAR Evaluation

SAR evaluation is required if the separation distance between the user and/or bystander and the antenna and/or radiating element of the device is less than or equal to 20 cm, except when the device operates at or below the applicable output power level (adjusted for tune-up tolerance) for the specified separation distance defined in Table 1.

FCC:

According to KDB447498D01 General RF Exposure Guidance v06

##### 4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

##### 3.1.2 Limits

FCC:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$\left[ \frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

# TEST REPORT NUMBER: (8523)343-0033(C)

IC:

**Table 1: SAR evaluation – Exemption limits for routine evaluation based on frequency and separation distance<sup>4,5</sup>**

| Frequency (MHz) | Exemption Limits (mW)           |                                 |                                 |                                 |                                 |
|-----------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|
|                 | At separation distance of ≤5 mm | At separation distance of 10 mm | At separation distance of 15 mm | At separation distance of 20 mm | At separation distance of 25 mm |
| ≤300            | 71 mW                           | 101 mW                          | 132 mW                          | 162 mW                          | 193 mW                          |
| 450             | 52 mW                           | 70 mW                           | 88 mW                           | 106 mW                          | 123 mW                          |
| 835             | 17 mW                           | 30 mW                           | 42 mW                           | 55 mW                           | 67 mW                           |
| 1900            | 7 mW                            | 10 mW                           | 18 mW                           | 34 mW                           | 60 mW                           |
| 2450            | 4 mW                            | 7 mW                            | 15 mW                           | 30 mW                           | 52 mW                           |
| 3500            | 2 mW                            | 6 mW                            | 16 mW                           | 32 mW                           | 55 mW                           |
| 5800            | 1 mW                            | 6 mW                            | 15 mW                           | 27 mW                           | 41 mW                           |

| Frequency (MHz) | Exemption Limits (mW)           |                                 |                                 |                                 |                                  |
|-----------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|----------------------------------|
|                 | At separation distance of 30 mm | At separation distance of 35 mm | At separation distance of 40 mm | At separation distance of 45 mm | At separation distance of ≥50 mm |
| ≤300            | 223 mW                          | 254 mW                          | 284 mW                          | 315 mW                          | 345 mW                           |
| 450             | 141 mW                          | 159 mW                          | 177 mW                          | 195 mW                          | 213 mW                           |
| 835             | 80 mW                           | 92 mW                           | 105 mW                          | 117 mW                          | 130 mW                           |
| 1900            | 99 mW                           | 153 mW                          | 225 mW                          | 316 mW                          | 431 mW                           |
| 2450            | 83 mW                           | 123 mW                          | 173 mW                          | 235 mW                          | 309 mW                           |
| 3500            | 86 mW                           | 124 mW                          | 170 mW                          | 225 mW                          | 290 mW                           |
| 5800            | 56 mW                           | 71 mW                           | 85 mW                           | 97 mW                           | 106 mW                           |

Remakr: If the operating frequency of the device is between two frequencies located in Table 1, linear interpolation shall be applied for the applicable separation distance. For test separation distance less than 5 mm, the exemption limits for a separation distance of 5 mm can be applied to determine if a routine evaluation is required.

**TEST REPORT NUMBER: (8523)343-0033(C)**

### 3.1.3 EUT RF Exposure

#### Measurement Data

IC:

$$e_{irp} = p_t \times g_t = (E \times d)^2 / 30$$

where:

$p_t$  = transmitter output power in watts,

$g_t$  = numeric gain of the transmitting antenna (unitless),

$E$  = electric field strength in V/m,  $10^{((dB_{\mu V/m})/20)/10^6}$ ,

$d$  = measurement distance in meters (m)---3m,

$$\text{So } p_t = (E \times d)^2 / 30 / g_t$$

The worst case refer to report ((8523)343-0033(B) is below:

| Antenna polarization: Horizontal |                      |       |
|----------------------------------|----------------------|-------|
| Frequency (MHz)                  | Level (dB $\mu$ V/m) | Value |
| 2.405                            | 91.35                | Peak  |

Field strength = 91.35dB  $\mu$  V/m @3m

Ant. gain 2.97dBi; so Ant numeric gain=1.982

So EIRP={ $[10^{(91.35/20)/10^6 \times 3}]^2 / 30$ }  $\times$  1000mW =0.409mW

0.409mW <4.0mW

So the SAR test is not required.



## TEST REPORT NUMBER: (8523)343-0033(C)

FCC:

The worst case refer to report ((8523)343-0033(B) is below:

| Antenna polarization: Horizontal |                      |       |
|----------------------------------|----------------------|-------|
| Frequency (MHz)                  | Level (dB $\mu$ V/m) | Value |
| 2.405                            | 91.35                | Peak  |

Field strength = 91.35dB  $\mu$  V/m @3m

Ant. gain 2.97dBi; so Ant numeric gain=1.982

So  $P_t = \{ [10^{(91.35/20)} / 10^6 \times 3]^2 / 30 / 1.982 \} \times 1000 \text{mW} = 0.2066 \text{mW}$

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g

Calculated value =  $0.2066 / 5 \cdot \sqrt{2.405} = 0.064 < 3$

So the SAR test is not required.