

MEASUREMENT REPORT of CORDLESS TELEPHONE

Applicant : Tele Matrix Equipment, LLC
Model No. : Marquis 9000MWD, Marquis 9000MWD5
EUT : Single S.S.T. Cordless Phone
FCC ID : OTH-9000MWD
Report No. : K1215522

Test by :

Training Research Co., Ltd.

TEL : 886-2-26935155 FAX : 886-2-26934440
2, Lane 194, Huan-Ho Street, Hsichih, Taipei Hsien 221, Taiwan, R.O.C.

CERTIFICATION


We here by verify that:

The test data, data evaluation, test procedures and equipment configurations shown in this report were made mainly in accordance with the procedures given in ANSI C63.4 (1992) as a reference. All test were conducted by *Training Research Co., Ltd.*, 2, Lane 194, Huan-Ho Street, Hsichih, Taipei Hsien 221, Taiwan, R.O.C. Also, we attest to the accuracy of each.

We further submit that the energy emitted by the sample EUT tested as described in the report is in compliance with the technical requirements set forth in the FCC Rules Part 15 Subpart C Section 15.233.

Applicant : Tele Matrix Equipment, LLC
Model No. : Marquis 9000MWD, Marquis 9000MWD5
EUT : Single S.S.T. Cordless Phone
FCC ID : OTH-9000MWD
Report No. : K1215522
Test Date : December 30, 2000

Prepared by:


Jack Tsai

Approved by:


Frank Tsai

Test by :

Training Research Co., Ltd.

TEL: 886-2-26935155

FAX: 886-2-26934440

2, Lane 194, Huan-Ho Street, Hsichih, Taipei Hsien 221, Taiwan, R.O.C.

Tables of Contents

I. GENERAL	5
1.1 Introduction	5
1.2 Description of EUT	5
1.3 Description of Support Equipment	5
1.4 Configuration of System Under Test	6
1.5 Verify the Frequency and Channel	7
1.5.1 Verify the Frequency Pairs	7
1.6 Test Procedure	8
1.7 Location of the Test Site	8
1.8 General Test Condition	8
 II. Section 15.207: Power line conducted emissions for AC powered units	 9
2.1 Test Condition & Setup	9
2.2 List of Test Instruments	9
2.3 Test Configuration	10
2.4 Test Result of Conducted Emissions	12
2.4.1 Base Station Transmit Only	12
 III. Section 15.247(a)(2): Bandwidth for direct sequence system	 17
3.1 Test Condition & Setup	17
3.2 Test Instruments Configuration	17
3.3 List of Test Instruments	17
3.4 Test Result of Bandwidth	18
 IV. Section 15.247(a) (2) : Power Output	 22
4.1 Test Condition & Setup	22
4.2 List of Test Instruments	23
4.3 Test Result of Fundamental Emission	24

V. Section 15.247(c) (2) : Spurious Emissions (Radiated)	25
5.1 Test Condition & Setup	25
5.2 List of Test Instruments	26
5.2.1 Duty Cycle Factor Measurement	26
5.3 Test Instruments Configuration	28
5.4 Test Result of Second Harmonic	30
5.5 Test Result of Spurious Radiated Emissions	31
5.5.1 Base and Handset Station Transmit Only	31
VI. Section 15.247(d) : Power Spectral Density	55
6.1 Test Condition & Setup	55
6.2 Test Instruments Configuration	56
6.3 List of Test Instruments.....	56
6.4 Required of Carrier Frequency	57
6.5 Test Result of Power Spectral Density	60
VII. Section 15.247(e): Processing Gain	64
7.1 Test Condition & Setup	64
7.2 Test Instruments Configuration	65
7.3 List of Test Instruments	67
7.4 Test Procedure	67
7.5 Test Result of Processing Gain	68
Appendix A : Set Up Procedure	70
Appendix B : Antenna Sketch	71
Appendix C : Part15.203	72
Appendix D : Security Code	73

GENERAL

1.1 Introduction

The following measurement report is submitted on behalf of Applicant in support of a Cordless Telephone certification in accordance with Part 2 Subpart J and Part 15 Subpart A and C of the Commission's Rules and Regulations.

1.2 Description of EUT

EUT	: Single S.S.T. Cordless Phone
Model No.	: Marquis 9000MWD, Marquis 9000MWD5
FCC ID	: OTH-9000MWD
Frequency Range	: Base : 904.20 – 925.80 MHz Handset : 904.20 – 925.80 MHz
Support Channel	: 20 Channel
Modulation Skill	: TDMA / Spread spectrum
Security Code	: 12-bit P/N code, 8-bit scramble, 16-bit 2D
Power Type	: Base Powered by 120Vac 60 Hz, 12W / 9Vdc 500mA Handset powered by 3.6 V / 720mAh
Power Cord	: Non-shielded , 185 cm long, No ferrite bead
Data Cable	: RJ-11C x 2 => Non-shielded, 7' long, Plastic hoods, No bead
Applicant	: Tele Matrix Equipment, LLC 5025 Galley Road, Colorado Springs, CO. 80915 USA

1.3 Description of Support Equipment

In order to construct the minimum testing, following equipment were used as the support units.

PSTN Simulator : King Design Public Switched Telephone Network Simulator
Model No. : 8705-A
Serial No. : N/A

Notebook : IBM Think Pad X20
 Type No. : 2662-11T
 Serial No. : FX-11922 00/09
 Power Type : Auto witching
 Power Core : Shielded, 180 cm long, Plastic hoods, ferrite bead
 FCC ID : Doc approved.

1.4 Configuration of System Under Test




Fig. 1 Configuration of system under test

The tests below are run with the DCT transmitter set at high power in TDD mode .A serial port from a computer to the DCT UUT is needed to force selection of output power level and channel number.

The setting up procedure was recorded in Appendix A.

1.5 Verify the Frequency and Channel

1.5.1 Verify the Frequency Pairs

Channel	Base(MHz)	Handset(MHz)	Channel	Base(MHz)	Handset(MHz)
1	904.20	904.20	11	915.60	915.60
2	904.80	904.80	12	916.80	916.80
3	906.00	906.00	13	918.00	918.00
4	907.20	907.20	14	919.20	919.20
5	908.10	908.10	15	920.40	920.40
6	909.60	909.60	16	921.40	921.40
7	910.80	910.80	17	922.80	922.80
8	912.00	912.00	18	924.00	924.00
9	913.20	913.20	19	925.20	925.20
10	914.40	914.40	20	925.80	925.80

Note:

1. This is for sure that all frequencies are in 902 MHz to 928 MHz.
2. Section 15.31(m): Measurements on intentional radiators or receivers shall be performed at three frequencies for operating frequency range over 10 MHz. (The locations of these frequencies one near the top, one near the middle and one near the bottom.)
3. After test, the EUT operating frequencies are in 904.20MHz to 925.80MHz. So all the items as followed in testing report are need to test these three frequencies: top: channel 1, middle: channel 11, bottom: channel 20.

1.6 Test Procedure

All measurements contained in this report were performed mainly according to the techniques described in ANSI C63.4 (1992) and the pre-setup was written on Appendix A, the detail setup was written on each test item.

1.7 Location of the Test Site

The radiated emissions measurements required by the rules were performed on the **three-meter, Anechoic Chamber (Registration Number: 93906)** maintained by *Training Research Co., Ltd.* 1F., No. 2, Lane 194, Huan-Ho Street, Hsichih, Taipei Hsien 221, Taiwan, R.O.C. Complete description and measurement data have been placed on file with the commission. The conducted power line emissions tests and other test items were performed in a shielded enclosure also located at Training Research Co., Ltd. 1F., No. 2, Lane 194, Huan-Ho Street, Hsichih, Taipei Hsien 221, Taiwan, R.O.C. *Training Research Co., Ltd.* is listed by the FCC as a facility available to do measurement work for others on a contract basis.

1.8 General Test Condition

The conditions under which the EUT operates were varied to determine their effect on the equipment's emission characteristics. The final configuration of the test system and the mode of operation used during these tests were chosen as that which produced the highest emission levels. However, only those conditions, which the EUT was considered likely to encounter in normal use were investigated.

In test, the base and handset are tested separately. They were set in high power and continuously transmitting mode that controlled by computer. The ch01, ch11 and ch20 of base and handset were all tested. The setting up procedure is recorded on Appendix A.

Section 15.207: Power Line Conducted Emissions for AC Powered Units

2.1 Test Condition & Setup

The power line conducted emission measurements were performed in an anechoic chamber. The EUT was assembled on a wooden table, which is 80 centimeters high, was placed 40 centimeters from the backwall and at least 1 meter from the sidewall.

Power was fed to the EUT from the public utility power grid through a line filter and Line Impedance Stabilization Networks (LISNs). The LISN housing, measuring instrumentation case, ground plane, etc., were electrically bonded together at the same RF potential. The Spectrum analyzer (or EMI receiver) was connected to the AC line through an isolation transformer. The 50-ohm output of the LISN was connected to the spectrum analyzer directly. Conducted emission levels were in the CISPER quasi-peak detection mode. The analyzer's 6 dB bandwidth was set to 9 KHz. No post-detector video filter was used.

The spectrum was scanned from 450 KHz to 30 MHz. The physical arrangement of the test system and associated cabling was varied (within the scope of arrangements likely to be encountered in actual use) to determine the effect on the unit's emanations in amplitude and frequency. All spurious emission frequencies were observed. The highest emission amplitudes relative to the appropriate limit were measured and have been recorded in paragraph 2.4.

There are tree test condition apply in this test item, the test procedure description as the following :

1. Base station transmit only:

Using the RS-232 port of PC and Rockwell software to control the base, handset.

Then making access to the mode of continuous transmission. Three channels were tested, one in the top (CH01), one in the middle (CH11) and the other in bottom (CH20).

2. Idle state (handset park, on hook mode)

The setting up procedure is recorded on Appendix A.

2.2 List of Test Instruments

Instrument Name	Model No.	Brand	Serial No.	Last time	Next time
EMI Receiver	8546A	H P	3520A00242	10/18/00	10/18/01
RF Filter Section	85460A	H P	3448A00217	10/18/00	10/18/01
LISN (EUT)	LISN-01	TRC	9912-03,04	12/09/00	12/09/01
LISN (Support E.)	LISN-01	TRC	9912-05	01/04/00	01/04/01
Switch/Control Unit (< 30MHz)	3488A	HP	N/A	11/20/00	11/20/01
Auto Switch Box (< 30MHz)	ASB-01	TRC	9904-01	11/20/00	11/20/01

2.3 Test configuration

Conducted Emissions Test Placement (Idle Only)



Conducted Emissions Test Placement (Operating Only)



2.4 Test Result of Conducted Emissions

2.4.1 Base station transmit only

The following table shows a summary of the highest emissions of power line conducted emissions on the HOT and NATURAL conductors of the EUT power cord.

FCC ID : OTH-9000MWD

Table 1 Power Line Conducted Emissions (Channel 1)

<i>Power</i>	<i>Connected</i>	<i>Emissions</i>	<i>FCC Class B</i>	
<i>Conductor</i>	<i>Frequency (KHz)</i>	<i>Peak Amplitude (dB μV)</i>	<i>Limit (dB μV)</i>	<i>Margin (dB)</i>
Line 1	477.00	27.63	48.00	-20.37
	489.00	31.91	48.00	-16.09
	734.00	29.59	48.00	-18.41
	1084.00	26.96	48.00	-21.04
	1458.00	28.09	48.00	-19.91
	2420.00	28.45	48.00	-19.55
	2630.00	26.02	48.00	-21.98
	3840.00	28.66	48.00	-19.34
	3970.00	25.41	48.00	-22.59
	27430.00	25.16	48.00	-22.84
LINE 2	489.00	32.24	48.00	-15.76
	724.00	32.16	48.00	-15.84
	851.00	31.36	48.00	-16.64
	1091.00	29.34	48.00	-18.66
	1458.00	26.69	48.00	-21.31
	2390.00	25.08	48.00	-22.92
	2540.00	25.11	48.00	-22.89
	2680.00	25.19	48.00	-22.81
	3810.00	27.93	48.00	-20.07
	3920.00	26.61	48.00	-21.39

NOTE:

1. Margin = Peak Amplitude – Limit
2. A "+" sign in the margin column means the emission is OVER the Class B Limit and "-" sign of means UNDER the Class B Limit.

Table 2 Power Line Conducted Emissions (Channel 11)

<i>Power Connected Emissions</i>			<i>FCC Class B</i>	
<i>Conductor</i>	<i>Frequency (KHz)</i>	<i>Peak Amplitude (dB μV)</i>	<i>Limit (dB μV)</i>	<i>Margin (dB)</i>
Line 1	480.00	29.62	48.00	-18.38
	729.00	31.40	48.00	-16.60
	1084.00	26.93	48.00	-21.07
	1332.00	25.38	48.00	-22.62
	1702.00	26.28	48.00	-21.72
	2040.00	25.45	48.00	-22.55
	2630.00	27.37	48.00	-20.63
	3730.00	26.43	48.00	-21.57
	3810.00	25.79	48.00	-22.21
	3970.00	25.97	48.00	-22.03
LINE 2	489.00	32.74	48.00	-15.26
	724.00	30.75	48.00	-17.25
	839.00	26.20	48.00	-21.80
	1458.00	28.64	48.00	-19.36
	2040.00	27.27	48.00	-20.73
	2560.00	26.48	48.00	-21.52
	2630.00	27.15	48.00	-20.85
	3810.00	27.97	48.00	-20.03
	3920.00	26.68	48.00	-21.32
	28980.00	26.19	48.00	-21.81

Table 3 Power Line Conducted Emissions (Channel 20)

<i>Power Connected Emissions</i>			<i>FCC Class B</i>	
<i>Conductor</i>	<i>Frequency (KHz)</i>	<i>Peak Amplitude (dB μV)</i>	<i>Limit (dB μV)</i>	<i>Margin (dB)</i>
Line 1	489.00	31.36	48.00	-16.64
	729.00	31.83	48.00	-16.17
	1713.00	24.48	48.00	-23.52
	2060.00	28.07	48.00	-19.93
	2590.00	24.86	48.00	-23.14
	2730.00	25.40	48.00	-22.60
	3680.00	27.13	48.00	-20.87
	3860.00	27.70	48.00	-20.30
	3970.00	24.97	48.00	-23.03
	4270.00	24.27	48.00	-23.73
LINE 2	734.00	29.96	48.00	-18.04
	845.00	30.49	48.00	-17.51
	1084.00	26.32	48.00	-21.68
	2060.00	26.55	48.00	-21.45
	2290.00	27.86	48.00	-20.14
	2470.00	26.11	48.00	-21.89
	2700.00	26.11	48.00	-21.89
	3750.00	26.14	48.00	-21.86
	3840.00	27.87	48.00	-20.13
	3920.00	27.79	48.00	-20.21

Table 4 Power Line Conducted Emissions (Charging)

<i>Power Connected Emissions</i>			<i>FCC Class B</i>	
<i>Conductor</i>	<i>Frequency (KHz)</i>	<i>Peak Amplitude (dB μV)</i>	<i>Limit (dB μV)</i>	<i>Margin (dB)</i>
Line 1	480.00	27.79	48.00	-20.21
	739.00	23.42	48.00	-24.58
	845.00	26.62	48.00	-21.38
	1099.00	23.97	48.00	-24.03
	1691.00	24.66	48.00	-23.34
	2680.00	26.07	48.00	-21.93
	2790.00	24.31	48.00	-23.69
	3680.00	27.31	48.00	-20.69
	3840.00	27.56	48.00	-20.44
	3920.00	26.46	48.00	-21.54
LINE 2	486.00	31.69	48.00	-16.31
	734.00	29.71	48.00	-18.29
	857.00	27.18	48.00	-20.82
	2420.00	26.95	48.00	-21.05
	2930.00	26.11	48.00	-21.89
	3630.00	26.38	48.00	-21.62
	3750.00	28.18	48.00	-19.82
	3840.00	28.49	48.00	-19.51
	3970.00	25.47	48.00	-22.53
	4610.00	26.12	48.00	-21.88

Table 5 Power Line Conducted Emissions (Linking)

<i>Power Connected Emissions</i>			<i>FCC Class B</i>	
<i>Conductor</i>	<i>Frequency (KHz)</i>	<i>Peak Amplitude (dB μV)</i>	<i>Limit (dB μV)</i>	<i>Margin (dB)</i>
Line 1	486.00	29.44	48.00	-18.56
	739.00	24.76	48.00	-23.24
	2510.00	25.49	48.00	-22.51
	2560.00	24.90	48.00	-23.10
	2650.00	26.58	48.00	-21.42
	2750.00	24.63	48.00	-23.37
	2830.00	25.38	48.00	-22.62
	2930.00	25.10	48.00	-22.90
	3730.00	24.97	48.00	-23.03
	29590.00	27.44	48.00	-20.56
LINE 2	483.00	31.76	48.00	-16.24
	2490.00	25.42	48.00	-22.58
	2590.00	26.82	48.00	-21.18
	2660.00	28.25	48.00	-19.75
	2770.00	26.05	48.00	-21.95
	2890.00	25.46	48.00	-22.54
	2990.00	25.84	48.00	-22.16
	3310.00	25.29	48.00	-22.71
	3700.00	25.92	48.00	-22.08
	3970.00	26.00	48.00	-22.00

Section 15.247(a)(2): Bandwidth for Direct Sequence System


3.1 Test Condition & Setup

The transmitter bandwidth measurements were performed in a shielded enclosure. The EUT was placed on a wooded table, which is 0.8 meters height. The EUT was set to transmit continuously. Various channels were also investigated to find the maximum occupied bandwidth. The minimum 6 dB bandwidth shall be at least 500 KHz.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 KHz. Set the span >> RBW. The detector function was set to peak and hold mode to clearly observe the components.

Setting up procedure is written on Appendix A.

3.2 Test Instruments Configuration



A serial port from notebook computer to control the EUT at maximal power output and channel number.

Fig 10. Test Configuration of bandwidth for direct sequence system

3.3 List of Test Instruments

Manufacturer	Device	Model	Input Impedance
Hewlett Packard	9KHz ~ 6.5GHz EMI Receiver	8546A	50.00
Schaffner	30MHz ~ 2GHz Bi-Log Antenna	CBL6141A	50.00
Hewlett Packard	RF Filter Section	85460A	50.00

3.4 Test Result of Bandwidth

Bandwidth of Channel 1

Bandwidth of Base : 1.63 MHz
Bandwidth of Handset : 1.58 MHz
The min. 6 dB BW at least : 500 KHz

Bandwidth of Channel 10



Bandwidth of Base : 1.63 MHz
Bandwidth of Handset : 1.57 MHz
The min. 6 dB BW at least : 500 KHz


Bandwidth of Channel 20



Bandwidth of Base : 1.60 MHz
Bandwidth of Handset : 1.60 MHz
The min. 6 dB BW at least : 500 KHz

Note:

1. The data in the above table are summarize the following attachment spectrum analyzer hard copy.
2. The attachment follow by this page and there is no page number.







. Section 15.247(B): Power Output

4.1 Test Condition & Setup

The EUT was placed in an anechoic chamber and scanned at 3-meter distance to determine its emission characteristics. The physical arrangement of the EUT was varied (within the scope of arrangements likely to be encountered in actual use) to determine the effect on the unit's emanations in amplitude, directivity, and frequency. The exact system configuration that produced the highest emissions was noted so it could be reproduced later during the final tests. This was done to ensure that the final measurements would demonstrate the worst-case interference potential of the EUT. Final radiation measurements were made on a three-meter, anechoic chamber. The EUT system was placed on a nonconductive turntable, which is 0.8 meters height, top surface 1.0 x 1.5 meter.

The spectrum was examined from 30 MHz to 1000 MHz using an Hewlett Packard 85460A EMI Receiver, Schaffner whole range Bi-Log antenna (Model No.: CBL6141A) is used to measure frequency from 30 MHz to 1GHz. The final test is used the spectrum HP 85460A. At each frequency, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters to find the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarization.

Appropriate preamplifiers were used for improving sensitivity and precautions were taken to avoid overloading or desensitizing the spectrum analyzer. The spectrum analyzer HP85460A used on this testing for frequency 30MHz to 1000MHz. No post-detector video filters were used in the test. Set the RB= 3 MHz, VB = 3MHz and the span = 5 MHz. The analyzer was operated in the maximum hold mode.

There are two test condition apply in this test item, the test procedure description as the following:
Base and handset station transmit only:

Using the RS-232 port of PC and Rockwell software to control the base, handset. Then making access to the mode of continuous transmission. Three channels were tested, one in the top (CH01), one in the middle (CH11) and the other in bottom (CH20).

With the transmitter operating from a fully charged battery and using the internal antenna,

Radiates spurious emissions falling within the restricted bands of 15.209 were measured at operating frequencies corresponding to low, mid and high channels in the 902 ~ 928 MHz band.

The actual field intensity in decibels referenced to 1 micro-volt per meter (dB μ V/m) is determined by algebraically adding the measured reading in dB μ V, the antenna factor (dB), and cable loss (dB) at the appropriate frequency.

4.2 List of Test Instruments

Manufacturer	Device	Model	Input Impedance
Hewlett Packard	9KHz ~ 6.5GHz EMI Receiver	8546A	50.00
Schaffner	30MHz ~ 2GHz Bi-Log Antenna	CBL6141A	50.00
Hewlett Packard	RF Filter Section	85460A	50.00

4.3 Test Result of Fundamental Emissions

The peak values of fundamental emissions from the EUT at various antenna heights, antenna polarization, EUT orientation, etc. are recorded on the following.

Table 6 Open Field Fundamental Emissions

Channel	Frequency (MHz)	A.P. (H/V)	A.H. (M)	Table (degree)	Amplitude (dBm V/m)	CF (dB)	Duty Cycle (dB)	Corrected Amplitude (dBm V/m)	Corrected Amplitude (dBm V/m)	E.I.R.P. Included Duty Cycle	
								Excluded Duty Cycle	Included Duty Cycle	m W	dB m
Base 01	904.20	H	1.00	48	66.62	-27.59	-6.66	87.55	94.21	0.791	-1.019
	904.20	V	1.00	112	73.12	-28.46	-6.66	94.92	101.58	4.316	6.351
Base 11	915.60	H	1.00	30	65.87	-27.77	-6.66	86.98	93.64	0.694	-1.589
	915.60	V	1.00	93	73.12	-28.76	-6.66	95.22	101.88	4.625	6.651
Base 20	925.80	H	1.00	15	65.64	-28.00	-6.66	86.98	93.64	0.694	-1.589
	925.80	V	1.00	140	74.16	-29.28	-6.66	96.78	103.44	6.624	8.211
Handset 01	904.20	H	1.00	53	73.20	-27.57	-6.66	94.11	100.77	3.582	5.541
	904.20	V	1.00	8	67.47	-28.44	-6.66	89.25	95.91	1.170	0.681
Handset 11	915.60	H	1.00	53	74.46	-27.77	-6.66	95.57	102.23	5.013	7.001
	915.60	V	2.42	115	66.76	-28.76	-6.66	88.86	95.52	1.069	0.291
Handset 20	925.80	H	1.00	6	69.42	-28.00	-6.66	90.76	97.42	1.656	2.191
	925.80	V	1.00	22	72.48	-29.27	-6.66	95.09	101.75	4.489	6.521

Note:

1. A.P. means antenna polarization, horizontal and vertical.
2. A.H. means antenna height.
3. Table means turntable turning position.
4. Corrected Factor (C. F.) = Cable Loss + Antenna Factor – Amplified Gain
Corrected Amplitude (Included Duty Cycle) = Peak Amplitude – Corrected Factor
Corrected Amplitude (Excluded Duty Cycle) = Peak Amplitude – Corrected Factor + Duty Cycle
5. Amplitude means the fundamental emission measured.
6. Conducted output power “P”, $P = (E d)^2 / 30G$
7. Since $G=1$, $P=EIRP$

E is the measured maximum field strength in V/m utilizing the maximum hold mode RBW (3MHz)

G is the numeric gain of the transmitting antenna over an isotropic radiator (1.00)

d is the distance in meters from which the field strength was measured (3M)

Example: the Max Radiation Emission of base ch20 = 103.44 dBμV/m

$$10^{(93.38/20)} \times 10^{-6} = 0.1485935 \text{ V}$$

$$E.I.R.P. = (0.1485935 \times 3)^2 / 30 = 6.6240 \text{ mW} = 10 \times \log (6.6240 \text{ mW} / 1 \text{ mW}) = 8.211 \text{ dBm}$$

. Section 15.247 (C)(2): Spurious Emissions (Radiated)

5.1 Test Condition & Setup

The EUT was placed in a anechoic chamber and scanned at 3 meter distance to determine its emission characteristics. The physical arrangement of the EUT was varied (within the scope of arrangements likely to be encountered in actual use) to determine the effect on the unit's emanations in amplitude, directivity, and frequency. The exact system configuration, which produced the highest emissions was noted so it could be reproduced later during the final tests. This was done to ensure that the final measurements would demonstrate the worst-case interference potential of the EUT.

Final radiation measurements were made on a three-meter, anechoic chamber. The EUT system was placed on a nonconductive turntable, which is 0.8 meters height, top surface 1.0 x 1.5 meter.

The spectrum was examined from 30 MHz to 1000 MHz using an Hewlett Packard 85460A EMI Receiver, Schaffner whole range Bi-Log antenna (Model No.: CBL6141A) is used to measure frequency from 30 MHz to 1GHz. The final test is used the spectrum HP 85460A and spectrum was examined from 1GHz to 18GHz using an Hewlett Packard 8564E Spectrum Analyzer, EMCO Horn Antenna (Model 3115) for 1G ~ 18GHz.

At each frequency, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters to find the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarization.

Appropriate preamplifiers were used for improving sensitivity and precautions were taken to avoid overloading or desensitizing the spectrum analyzer. There are two spectrum analyzers use on this testing, HP 85460A for frequency 30MHz to 1000MHz, and 8564E for frequency 1GHz to 18GHz. No post-detector video filters were used in the test. The spectrum analyzer's 6 dB bandwidth was set to 120KHz (spectrum was examined from 30 MHz to 1000 MHz), the spectrum analyzer's 6 dB bandwidth was set to 1 MHz (spectrum was examined from 1GHz to 18GHz) and the analyzer was operated in the maximum hold mode.

There are two test condition apply in this test item, the test procedure description as the following:

Base and handset station transmit only:

Using the RS-232 port of PC and Rockwell software to control the base, handset. Then making access to the mode of continuous transmission. Three channels is tested, one in the top (CH01), one in the middle (CH11) and the other in bottom (CH20).

With the transmitter operating from a fully charged battery and using the internal antenna, radiates spurious emissions falling within the restricted bands of 15.209 were measured at operating frequencies corresponding to low, mid and high channels in the 902 ~ 928 MHz band.

The actual field intensity in decibels referenced to 1 micro-volt per meter (dBμV/m) is determined by algebraically adding the measured reading in dBμV, the antenna factor (dB), and cable loss (dB) at the appropriate frequency.

For frequency between 30MHz to 1000MHz

$$F_{Ia} \text{ (dB}\mu\text{V/m)} = F_{Ir} \text{ (dB}\mu\text{V)} - \text{Correction Factors}$$

F_{Ia} : Actual Field Intensity

F_{Ir} : Reading of the Field Intensity

$$\text{Correction Factors} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

For frequency between 1 GHz to 18 GHz

$$F_{Ia} \text{ (dB}\mu\text{V/m)} = F_{Ir} \text{ (dB}\mu\text{V)} + \text{Correction Factor} - \text{Duty Cycle}$$

F_{Ia} : Actual Field Intensity

F_{Ir} : Reading of the Field Intensity

$$\text{Correction Factors} = \text{Antenna Factor} + \text{Cable Loss} - \text{Distance Factor (9.54dB)} - \text{Amplifier Gain}$$

The setting up procedure is recorded on Appendix A.



5.2 List of Test Instruments

Manufacturer	Device	Model	Input Impedance
Hewlett Packard	9KHz ~ 6.5GHz EMI Receiver	8546A	50.00
Schaffner	30MHz ~ 2GHz Bi-Log Antenna	CBL6141A	50.00
Hewlett Packard	RF Filter Section	85460A	50.00
Hewlett Packard	9KHz ~ 40GHz Spectrum Analyzer	8564E	50.00
EMCO	1G ~ 18GMHz Double Ridge Antenna	3115.00	50.00

5.2.1 Duty Cycle Factor Measurement

The duty cycle factor measurement is performed in a shield enclosure. The test condition and setup is as same as paragraph . Set the RB = 1MHz, VB=1MHz, and span = 0 MHz. Link the base and handset, then get the Time of duty and cycle as follow page.

$$\text{The duty cycle factor} = 20 \log (T_{\text{duty}} / T_{\text{cycle}}) = 20 \log (0.975/2.100) = - 6.664$$



5.3 Test Instruments Configuration



Pig 1 Front View of the Test Configuration (BASE)



Pig 2 Rear View of the Test Configuration (BASE)



Pig 1 Front View of the Test Configuration (HANDSET)



Pig 2 Rear View of the Test Configuration (HANDSET)

The test configuration for frequency between 1 GHz to 18 GHz is same as above.

5.4 Test Result of Second Harmonic

Set the spectrum RB= 3 MHz, VB = 3MHz and span = 5MHz. The correction factors of the second harmonic are the second harmonic must lower 20 dB than the fundamental.

EUT : Single S.S.T. Cordless Phone
FDD ID : OTH-9000MWD

Table 7 Second Harmonic Attenuation

Channel	Fundamental (MHz)	Fundamental (dBmV/m)	2nd Harmonic (GHz)	2nd Harmonic (dBmV/m)	Result (F/H dB)	Limit (dB)	Margin (dB)
B/S CH 01	904.20	101.58	1.800	46.13	55.45	20.00	35.45
B/S CH 11	915.60	101.88	1.825	45.63	56.25	20.00	36.25
B/S CH 20	925.80	103.44	1.850	43.96	59.48	20.00	39.48
H/S CH 01	904.20	100.77	1.807	43.29	57.48	20.00	37.48
H/S CH 11	915.60	102.23	1.833	41.96	60.27	20.00	40.27
H/S CH 20	925.80	101.75	1.850	37.63	64.12	20.00	44.12

Note:

1. The data in the above table are summarized the following attachment spectrum analyzer hard copy.
2. Result = Fundamental – 2nd Harmonic must over 20 dB.

5.5 Test Result of Spurious Radiated Emissions

5.5.1 Base and handset station transmit only

The highest peak values of radiated emissions from the EUT at various antenna heights, antenna polarization, EUT orientation, etc. are recorded on the following.

Test Conditions: Testing room : Temperature : 26 ° C Humidity : 73 % RH
 Testing site : Temperature : 31 ° C Humidity : 75 % RH

Table 8 Open Field Radiated Emissions For 30MHz 1GHz [Channel 1, Base Horizontal]

Radiated Emission				Correction Factors	Corrected Amplitude	FCC Class B (3 m)	
Frequency (MHz)	Amplitude (dBmV/m)	Ant. H. (m)	Table (°)			Limit (dBmV/m)	Margin (dB)
201.603	26.92	1.00	57	-13.51	40.43	43.50	-3.07
211.203	25.55	1.00	21	-14.19	39.74	43.50	-3.76
220.804	25.88	1.00	62	-15.46	41.34	46.00	-4.66
345.603	21.65	1.00	38	-17.87	39.52	46.00	-6.48
846.606	12.99	1.00	60	-27.59	40.58	46.00	-5.42

Note:

1. Margin = Corrected – Limit.
2. Peak Amplitude – Correction Factors = Corrected

Table 9 Open Field Radiated Emissions For 1GHz 18GHz [Channel 1, Base Horizontal]

Radiated Emission				Correction Factors (dB)	Duty Cycle (dB)	Corrected Amplitude (dBm V/m)	FCC Class B (3 m)	
Frequency (GHz)	Amplitude (dBm V/m)	Ant. H. (m)	Table (°)				Limit (dBm V/m)	Margin (dB)
1.800	56.96	1.00	77	-8.67	-6.66	41.63	54.00	-12.37
2.700	50.46	1.00	69	-6.84	-6.66	36.96	54.00	-17.04
3.625	60.09	1.00	149	-5.64	-6.66	47.79	54.00	-6.21
4.525	39.04	1.00	158	3.91	-6.66	36.29	54.00	-17.71
5.425	25.40	1.00	297	9.72	-6.66	28.46	54.00	-25.54

Note:

1. Margin = Corrected – Limit.
2. Peak Amplitude + Correction Factor + Duty Cycle = Corrected

Table 10 Open Field Radiated Emissions For 30MHz 1GHz [Channel 1, Base Vertical]

Radiated Emission				Correction Factors	Corrected Amplitude	FCC Class B (3 m)	
Frequency (MHz)	Amplitude (dBmV/m)	Ant. H. (m)	Table (°)			Limit (dBmV/m)	Margin (dB)
48.002	13.54	1.00	13	-15.73	29.27	40.00	-10.73
201.603	22.16	1.00	31	-13.74	35.90	43.50	-7.60
240.004	17.93	2.44	32	-15.06	32.99	46.00	-13.01
499.203	9.24	1.00	63	-21.80	31.04	46.00	-14.96
846.605	7.89	1.00	131	-27.49	35.38	46.00	-10.62
961.808	10.67	1.00	12	-30.14	40.81	54.00	-13.19

Table 11 Open Field Radiated Emissions For 1GHz 18GHz [Channel 1, Base Vertical]

Radiated Emission				Correction Factors (dB)	Duty Cycle (dB)	Corrected Amplitude (dBm V/m)	FCC Class B (3 m)	
Frequency (GHz)	Amplitude (dBm V/m)	Ant. H. (m)	Table (°)				Limit (dBm V/m)	Margin (dB)
1.800	61.46	1.00	179	-8.67	-6.66	46.13	54.00	-7.87
2.700	59.79	1.00	128	-6.84	-6.66	46.29	54.00	-7.71
3.625	53.76	1.00	225	-5.64	-6.66	41.46	54.00	-12.54
4.525	41.88	1.00	307	3.91	-6.66	39.13	54.00	-14.87
5.425	28.23	1.00	49	9.72	-6.66	31.29	54.00	-22.71

Table 12 Open Field Radiated Emissions For 30MHz 1GHz [Channel 11, Base Horizontal]

Radiated Emission				Correction Factors	Corrected Amplitude	FCC Class B (3 m)	
Frequency (MHz)	Amplitude (dBmV/m)	Ant. H. (m)	Table (°)			Limit (dBmV/m)	Margin (dB)
201.603	25.59	1.00	57	-13.51	39.10	43.50	-4.40
211.203	22.80	1.00	17	-14.19	36.99	43.50	-6.51
220.804	23.48	1.00	80	-15.46	38.94	46.00	-7.06
240.003	24.97	1.00	19	-15.09	40.06	46.00	-5.94
345.603	22.62	1.00	43	-17.87	40.49	46.00	-5.51

Table 13 Open Field Radiated Emissions For 1GHz 18GHz [Channel 11, Base Horizontal]

Radiated Emission				Correction Factors (dB)	Duty Cycle (dB)	Corrected Amplitude (dBm V/m)	FCC Class B (3 m)	
Frequency (GHz)	Amplitude (dBm V/m)	Ant. H. (m)	Table (°)				Limit (dBm V/m)	Margin (dB)
1.825	55.12	1.00	58	-8.67	-6.66	39.79	54.00	-14.21
2.738	47.96	1.00	138	-6.84	-6.66	34.46	54.00	-19.54
3.675	58.26	1.00	27	-5.64	-6.66	45.96	54.00	-8.04
4.588	40.21	1.00	119	3.91	-6.66	37.46	54.00	-16.54
5.500	33.90	1.00	207	9.72	-6.66	36.96	54.00	-17.04
8.250	27.53	1.00	341	9.72	-6.66	30.59	54.00	-23.41

Table 14 Open Field Radiated Emissions For 30MHz 1GHz [Channel 11, Base Vertical]

Radiated Emission				Correction Factors	Corrected Amplitude	FCC Class B (3 m)	
Frequency (MHz)	Amplitude (dBmV/m)	Ant. H. (m)	Table (°)			Limit (dBmV/m)	Margin (dB)
48.002	15.59	2.45	87	-15.73	31.32	40.00	-8.68
201.603	17.26	2.45	39	-13.74	31.00	43.50	-12.50
240.004	17.78	1.00	24	-15.06	32.84	46.00	-13.16
480.004	9.28	1.00	145	-21.32	30.60	46.00	-15.40
858.006	8.85	1.00	1	-27.51	36.36	46.00	-9.64
973.205	10.48	1.00	136	-30.21	40.69	54.00	-13.31

Table 15 Open Field Radiated Emissions For 1GHz 18GHz [Channel 11, Base Vertical]

Radiated Emission				Correction Factors (dB)	Duty Cycle (dB)	Corrected Amplitude (dBm V/m)	FCC Class B (3 m)	
Frequency (GHz)	Amplitude (dBm V/m)	Ant. H. (m)	Table (°)				Limit (dBm V/m)	Margin (dB)
1.825	60.96	1.00	58	-8.67	-6.66	45.63	54.00	-8.37
2.738	57.29	1.00	138	-6.84	-6.66	43.79	54.00	-10.21
3.675	54.76	1.00	27	-5.64	-6.66	42.46	54.00	-11.54
4.588	41.71	1.00	119	3.91	-6.66	38.96	54.00	-15.04
5.500	27.57	1.00	207	9.72	-6.66	30.63	54.00	-23.37
6.413	25.07	1.00	341	9.72	-6.66	28.13	54.00	-25.87
7.338	33.73	1.00	207	9.72	-6.66	36.79	54.00	-17.21
8.250	30.23	1.00	341	9.72	-6.66	33.29	54.00	-20.71

Table 16 Open Field Radiated Emissions For 30MHz 1GHz [Channel 20, Base Horizontal]

Radiated Emission				Correction Factors	Corrected Amplitude	FCC Class B (3 m)	
Frequency (MHz)	Amplitude (dBmV/m)	Ant. H. (m)	Table (°)			Limit (dBmV/m)	Margin (dB)
201.603	25.76	1.00	60	-13.51	39.27	43.50	-4.23
220.804	23.13	1.00	12	-15.46	38.59	46.00	-7.41
240.003	24.45	1.00	76	-15.09	39.54	46.00	-6.46
326.404	21.63	1.00	3	-17.23	38.86	46.00	-7.14
345.604	22.36	1.00	44	-17.87	40.23	46.00	-5.77

Table 17 Open Field Radiated Emissions For 1GHz 18GHz [Channel 20, Base Horizontal]

Radiated Emission				Correction Factors (dB)	Duty Cycle (dB)	Corrected Amplitude (dBm V/m)	FCC Class B (3 m)	
Frequency (GHz)	Amplitude (dBm V/m)	Ant. H. (m)	Table (°)				Limit (dBm V/m)	Margin (dB)
1.850	54.29	1.00	280	-8.67	-6.66	38.96	54.00	-15.04
2.763	46.29	1.00	264	-6.84	-6.66	32.79	54.00	-21.21
3.713	53.76	1.00	159	-5.64	-6.66	41.46	54.00	-12.54
4.638	37.88	1.00	341	3.91	-6.66	35.13	54.00	-18.87
5.563	31.07	1.00	56	9.72	-6.66	34.13	54.00	-19.87
7.425	27.23	1.00	179	9.72	-6.66	30.29	54.00	-23.71
8.350	29.57	1.00	204	9.72	-6.66	32.63	54.00	-21.37

Table 18 Open Field Radiated Emissions For 30MHz 1GHz [Channel 20, Base Vertical]

Radiated Emission				Correction Factors	Corrected Amplitude	FCC Class B (3 m)	
Frequency (MHz)	Amplitude (dBmV/m)	Ant. H. (m)	Table (°)			Limit (dBmV/m)	Margin (dB)
48.002	13.54	2.43	56	-15.73	29.27	40.00	-10.73
211.203	18.81	1.00	25	-14.33	33.14	43.50	-10.36
240.003	19.93	1.00	33	-15.06	34.99	46.00	-11.01
868.207	10.73	1.00	81	-27.61	38.34	46.00	-7.66
983.407	10.53	1.00	96	-30.30	40.83	54.00	-13.17

Table 19 Open Field Radiated Emissions For 1GHz 18GHz [Channel 20, Base Vertical]

Radiated Emission				Correction Factors (dB)	Duty Cycle (dB)	Corrected Amplitude (dBm V/m)	FCC Class B (3 m)	
Frequency (GHz)	Amplitude (dBm V/m)	Ant. H. (m)	Table (°)				Limit (dBm V/m)	Margin (dB)
1.850	59.29	1.00	64	-8.67	-6.66	43.96	54.00	-10.04
2.763	55.13	1.00	128	-6.84	-6.66	41.63	54.00	-12.37
3.713	55.26	1.00	346	-5.64	-6.66	42.96	54.00	-11.04
4.638	43.54	1.00	157	3.91	-6.66	40.79	54.00	-13.21
5.563	34.40	1.00	248	9.72	-6.66	37.46	54.00	-16.54
7.425	31.57	1.00	331	9.72	-6.66	34.63	54.00	-19.37
8.350	34.07	1.00	10	9.72	-6.66	37.13	54.00	-16.87

Table 20 Open Field Radiated Emissions For 30MHz 1GHz [Channel 1, Handset Horizontal]

Radiated Emission				Correction Factors	Corrected Amplitude	FCC Class B (3 m)	
Frequency (MHz)	Amplitude (dBmV/m)	Ant. H. (m)	Table (°)			Limit (dBmV/m)	Margin (dB)
297.611	12.73	1.00	31	-16.27	29.00	46.00	-17.00
374.414	10.39	1.00	9	-18.62	29.01	46.00	-16.99
451.217	9.98	2.45	57	-20.58	30.56	46.00	-15.44
624.003	8.43	1.00	11	-23.23	31.66	46.00	-14.34
643.222	8.73	1.00	78	-24.17	32.90	46.00	-13.10
866.280	6.11	1.00	36	-26.86	32.97	46.00	-13.03

Table 21 Open Field Radiated Emissions For 1GHz 18GHz [Channel 1, Handset Horizontal]

Radiated Emission				Correction Factors (dB)	Duty Cycle (dB)	Corrected Amplitude (dBm V/m)	FCC Class B (3 m)	
Frequency (GHz)	Amplitude (dBm V/m)	Ant. H. (m)	Table (°)				Limit (dBm V/m)	Margin (dB)
1.807	58.62	1.00	151	-8.67	-6.66	43.29	54.00	-10.71
2.707	57.96	1.00	246	-6.84	-6.66	44.46	54.00	-9.54
3.612	44.76	1.00	7	-5.64	-6.66	32.46	54.00	-21.54
5.420	26.23	1.00	209	9.72	-6.66	29.29	54.00	-24.71
6.327	26.90	1.00	46	9.72	-6.66	29.96	54.00	-24.04

Table 22 Open Field Radiated Emissions For 30MHz 1GHz [Channel 1, Handset Vertical]

Radiated Emission				Correction Factors	Corrected Amplitude	FCC Class B (3 m)	
Frequency (MHz)	Amplitude (dBmV/m)	Ant. H. (m)	Table (°)			Limit (dBmV/m)	Margin (dB)
489.618	14.84	1.00	63	-21.70	36.54	46.00	-9.46
508.818	15.01	1.00	148	-22.08	37.09	46.00	-8.91
528.019	14.28	1.00	10	-22.39	36.67	46.00	-9.33
547.220	14.42	1.00	66	-23.71	38.13	46.00	-7.87
566.420	13.22	1.00	83	-23.74	36.96	46.00	-9.04

Table 23 Open Field Radiated Emissions For 1GHz 18GHz [Channel 1, Handset Vertical]

Radiated Emission				Correction Factors (dB)	Duty Cycle (dB)	Corrected Amplitude (dBm V/m)	FCC Class B (3 m)	
Frequency (GHz)	Amplitude (dBm V/m)	Ant. H. (m)	Table (°)				Limit (dBm V/m)	Margin (dB)
1.807	56.29	1.00	264	-8.67	-6.66	40.96	54.00	-13.04
2.707	58.30	1.00	108	-6.84	-6.66	44.80	54.00	-9.20
3.613	40.43	1.00	34	-5.64	-6.66	28.13	54.00	-25.87
4.520	29.04	1.00	215	3.91	-6.66	26.29	54.00	-27.71
5.420	26.40	1.00	28	9.72	-6.66	29.46	54.00	-24.54
6.327	35.57	1.00	41	9.72	-6.66	38.63	54.00	-15.37
8.143	26.73	1.00	310	9.72	-6.66	29.79	54.00	-24.21

Table 24 Open Field Radiated Emissions For 30MHz 1GHz [Channel 11, Handset Horizontal]

Radiated Emission				Correction Factors	Corrected Amplitude	FCC Class B (3 m)	
Frequency (MHz)	Amplitude (dBmV/m)	Ant. H. (m)	Table (°)			Limit (dBmV/m)	Margin (dB)
278.412	14.57	1.00	44	-15.48	30.05	46.00	-15.95
297.612	12.99	1.00	42	-16.27	29.26	46.00	-16.74
441.616	9.04	1.00	24	-20.14	29.18	46.00	-16.82
624.023	10.24	1.00	10	-23.23	33.47	46.00	-12.53
643.222	9.89	1.00	76	-24.17	34.06	46.00	-11.94
877.683	4.01	1.00	31	-26.84	30.85	46.00	-15.15

Table 25 Open Field Radiated Emissions For 1GHz 18GHz [Channel 11, Handset Horizontal]

Radiated Emission				Correction Factors (dB)	Duty Cycle (dB)	Corrected Amplitude (dBm V/m)	FCC Class B (3 m)	
Frequency (GHz)	Amplitude (dBm V/m)	Ant. H. (m)	Table (°)				Limit (dBm V/m)	Margin (dB)
1.833	57.29	1.00	61	-8.67	-6.66	41.96	54.00	-12.04
2.743	62.29	1.00	207	-6.84	-6.66	48.79	54.00	-5.21
3.664	44.09	1.00	55	-5.64	-6.66	31.79	54.00	-22.21
4.580	27.04	1.00	167	3.91	-6.66	24.29	54.00	-29.71
5.491	24.40	1.00	294	9.72	-6.66	27.46	54.00	-26.54
6.401	27.23	1.00	241	9.72	-6.66	30.29	54.00	-23.71
8.239	26.90	1.00	33	9.72	-6.66	29.96	54.00	-24.04

Table 26 Open Field Radiated Emissions For 30MHz 1GHz [Channel 11, Handset Vertical]

Radiated Emission				Correction Factors	Corrected Amplitude	FCC Class B (3 m)	
Frequency (MHz)	Amplitude (dBmV/m)	Ant. H. (m)	Table (°)			Limit (dBmV/m)	Margin (dB)
489.618	15.24	1.00	85	-21.70	36.94	46.00	-9.06
508.819	15.32	1.00	148	-22.08	37.40	46.00	-8.60
528.019	15.21	1.00	86	-22.39	37.60	46.00	-8.40
547.220	15.24	1.00	152	-23.71	38.95	46.00	-7.05
566.420	14.46	1.00	86	-23.74	38.20	46.00	-7.80

Table 27 Open Field Radiated Emissions For 1GHz 18GHz [Channel 11, Handset Vertical]

Radiated Emission				Correction Factors (dB)	Duty Cycle (dB)	Corrected Amplitude (dBm V/m)	FCC Class B (3 m)	
Frequency (GHz)	Amplitude (dBm V/m)	Ant. H. (m)	Table (°)				Limit (dBm V/m)	Margin (dB)
1.833	55.79	1.00	357	-8.67	-6.66	40.46	54.00	-13.54
2.743	60.63	1.00	219	-6.84	-6.66	47.13	54.00	-6.87
3.664	44.09	1.00	46	-5.64	-6.66	31.79	54.00	-22.21
4.580	28.71	1.00	185	3.91	-6.66	25.96	54.00	-28.04
5.491	27.73	1.00	164	9.72	-6.66	30.79	54.00	-23.21
6.401	34.07	1.00	22	9.72	-6.66	37.13	54.00	-16.87
7.324	28.23	1.00	347	9.72	-6.66	31.29	54.00	-22.71

Table 28 Open Field Radiated Emissions For 30MHz 1GHz [Channel 20, Handset Horizontal]

Radiated Emission				Correction Factors	Corrected Amplitude	FCC Class B (3 m)	
Frequency (MHz)	Amplitude (dBmV/m)	Ant. H. (m)	Table (°)			Limit (dBmV/m)	Margin (dB)
278.412	7.64	2.43	93	-15.48	23.12	46.00	-22.88
297.612	5.68	2.43	62	-16.27	21.95	46.00	-24.05
624.020	11.70	1.00	143	-23.23	34.93	46.00	-11.07
643.221	7.21	1.00	84	-24.17	31.38	46.00	-14.62
887.881	1.79	1.00	67	-27.10	28.89	46.00	-17.11

Table 29 Open Field Radiated Emissions For 1GHz 18GHz [Channel 20, Handset Horizontal]

Radiated Emission				Correction Factors (dB)	Duty Cycle (dB)	Corrected Amplitude (dBm V/m)	FCC Class B (3 m)	
Frequency (GHz)	Amplitude (dBm V/m)	Ant. H. (m)	Table (°)				Limit (dBm V/m)	Margin (dB)
1.850	52.96	1.00	308	-8.67	-6.66	37.63	54.00	-16.37
2.772	58.46	1.00	44	-6.84	-6.66	44.96	54.00	-9.04
3.705	42.26	1.00	161	-5.64	-6.66	29.96	54.00	-24.04
4.663	27.38	1.00	137	3.91	-6.66	24.63	54.00	-29.37
5.555	25.23	1.00	259	9.72	-6.66	28.29	54.00	-25.71
6.485	25.73	1.00	27	9.72	-6.66	28.79	54.00	-25.21

Table 30 Open Field Radiated Emissions For 30MHz 1GHz [Channel 20, Handset Vertical]

Radiated Emission				Correction Factors	Corrected Amplitude	FCC Class B (3 m)	
Frequency (MHz)	Amplitude (dBmV/m)	Ant. H. (m)	Table (°)			Limit (dBmV/m)	Margin (dB)
489.618	14.41	1.00	82	-21.70	36.11	46.00	-9.89
508.818	14.94	1.00	145	-22.08	37.02	46.00	-8.98
547.220	13.71	1.00	81	-23.71	37.42	46.00	-8.58
566.420	13.26	1.00	149	-23.74	37.00	46.00	-9.00
585.621	13.21	1.00	80	-23.40	36.61	46.00	-9.39
886.977	5.07	1.00	82	-27.99	33.06	46.00	-12.94

Table 31 Open Field Radiated Emissions For 1GHz 18GHz [Channel 20, Handset Vertical]

Radiated Emission				Correction Factors (dB)	Duty Cycle (dB)	Corrected Amplitude (dBm V/m)	FCC Class B (3 m)	
Frequency (GHz)	Amplitude (dBm V/m)	Ant. H. (m)	Table (°)				Limit (dBm V/m)	Margin (dB)
1.850	52.47	1.00	29	-8.67	-6.66	37.14	54.00	-16.86
2.772	62.14	1.00	145	-6.84	-6.66	48.64	54.00	-5.36
3.705	39.44	1.00	16	-5.64	-6.66	27.14	54.00	-26.86
4.663	25.73	1.00	279	3.91	-6.66	22.98	54.00	-31.02
5.555	26.42	1.00	2	9.72	-6.66	29.48	54.00	-24.52
6.485	32.22	1.00	127	9.72	-6.66	35.28	54.00	-18.72
7.408	26.25	1.00	294	9.72	-6.66	29.31	54.00	-24.69

. Section 15.247(d): Power Spectral Density


6.1 Test Condition & Setup

The tests below are running with the DCT transmitter set at high power in TDD mode. A serial port from a computer to the DCT UUT is needed to force selection of output power level and channel number. While testing, EUT was set to transmit continuously. A log antenna was connected with the spectrum analyzer.

The EUT is tested in open field site. Put EUT on the middle of a wooden table. Set spectrum analyzer RBW = 3 KHz, VBW > RBW (e.g. VBW = 10 KHz), Span = 1.5 MHz. Turn around the table to find maximum emission. Then set the Span = 300 KHz and sweep time = 100 sec. Peak the maximum emission again. The peak level measured must be no greater than + 8dBm.

The setting up procedure is recorded on Appendix A.

6.2 Test Instruments Configuration



P.S. A serial port from notebook computer to control the EUT at maximal power output and channel Number.

Fig 12. Test Configuration of power spectral density



6.3 List of Test Instruments



Manufacturer	Device	Model	Input Impedance
Hewlett Packard	9KHz – 6.5GHz EMI Receiver	HP8546A	50.00
Hewlett Packard	RF Filter Section	HP85460A	50.00
Schaffner	30MHz-2GHz Bi-Log Antenna	CBL6141A	50.00

6.4 Required of Carrier frequency

If any 100 kHz bandwidth outside these frequency bands, the radio frequency power that is produced by the modulation products of the spreading sequence, the information sequence and the carrier frequency shall be either at least 20 dB below that in any 100 kHz bandwidth within the band that contains the highest level of the desired power or shall not exceed the general levels specified in § 15.209(a), whichever results in the lesser attenuation.

Test Condition & Setup: same as 3.1





6.5 Test Result of Power spectral density

The following table shows a summary of the highest power out of UT.

FDD ID : OTH-9000MWD
EUT : Single S.S.T. Cordless Phone

Table 33 Power Spectral Density

<i>Channel</i>	<i>Frequency (MHz)</i>	<i>Ppr (dBuV)</i>	<i>CF (dB)</i>	<i>Ppq (dBm)</i>	<i>Limit (dB)</i>	<i>Margin (dB)</i>
B/S CH 01	904.6543	56.79	-27.59	-10.85	8.00	-18.85
B/S CH 11	916.0555	58.71	-28.76	-7.76	8.00	-15.76
B/S CH 20	926.2553	59.17	-29.28	-6.78	8.00	-14.78
H/S CH 01	903.9803	51.92	-28.44	-14.87	8.00	-22.87
H/S CH 11	916.0804	49.78	-27.77	-17.68	8.00	-25.68
H/S CH 20	926.2825	51.85	-29.27	-14.11	8.00	-22.11

Note:

1. The attachment follow by this page and there is no page number.
2. Ppr: spectrum read power density (using peak search mode), CF: correct factor,
Ppq: actual peak power density in the spread spectrum band.

3. $Ppq = Ppr - CF$

4. Effective Radiation Power (E.R.P.) = $(E d)^2 / 30G$

"E" is the measured maximum field strength in V/m utilizing the maximum hold mode RBW (3KHz).



"G" is the numeric gain of the transmitting antenna over an isotropic radiator (1.00).



"d" is the distance in meters from which the field strength was measured (3M).



Example: the Max Radiation Emission of base ch01 = $56.79 - (-27.59) = 84.38 \text{ dB}\mu\text{V/m}$

$$10^{(84.38/20)} \times 10^{-6} = 0.016558 \text{ V}$$

$$\begin{aligned} \text{E.R.P.} &= (0.016558 \times 3)^2 / 30 = 0.082247 \text{ mW} = 10 \times \log (0.82247 \text{ mW/1mW}) \\ &= -10.85 \text{ dBm} \end{aligned}$$







. Section 15.247(e): Processing Gain

7.1 Test Condition & Setup

A. Bit Error Rate (Pe)

The subjective device RF module (base & handset) digital modulation by Differential Phase -Shift Keying (DPSK), the DPSK can use it's previous waveform as the phase reference for demodulation and thus requires no coherent detection, which greatly simplifies the receiver structure but with some Bit Error Rate (BER) degradation because of noisy phase reference. There is tradeoff between system complexity and system performance. In order to driver the DPSK error probability, we observe that DPSK using differential coding , we observable that DPSK using different coding is essentially an orthogonal signal scheme. A binary 1 is transmitted a sequence of two pulse (P,P) or (-P,-P) over 2 To seconds (no transition). Similarly, a binary 0 is transmitted by a sequence of two plus (P,-P) or (-P,P) over 2 TO seconds (transition). Either of the pulse sequences used for binary 1 is orthogonal to either of the pulse sequences used for binary 0. Because no local carrier is generated for demodulation, the detection is noncoherent , with an effective pulse energy equal to 2 Ep (twice the energy of pulse P). The actual energy transmitted per digit only Ep, however, the same as in noncoherent FSK, Consequently, the performance of DPSK is 3 dB superior to that of noncoherent FSK, We can write Pe for DPSK as :

The major component inside the subjective device are supplied by Rock well , Included RF block transmitter (RF101), Receiver (RF 100), and Base band block ASIC (c8502-13), CODEC (10497-14), above 4 IC chips are affected the processing gain as following :

$$J/S = (W/RD) / (ED/NO) \text{ [without CODING]}$$

Where: W= Spread Chip Rate = Required Transmitted Base band Bandwidth.

Rb = Information Data Rate

Eb/No = Require Energy per Bit over noise Spectral Density for a Specific Bit Error Probability.

The subjective Device Information Data Rate are 80k and the Spread Chip Rate are 960k So the processing gain ($10 \log w/Rb$) at least 10.79 dB (without Coding).

The ASIC (c8502-13) and CODEC (10497-14) these two chip included the coding function, So, it is great improve the processing gain and also improve the J/S ratio.

The Engineer work for Rock well System in Taiwan had pass us the information about the probability of error rate (Pe) must be lower than 0.001 that the system performance will satisfy for communication between Handset and Base station.

Why we need the Pe lower than 0.001, the Rockwell Semiconductor System is not explained, Since it relative with ASIC and Codec, it is confidential area that Rockwell is not allow to disdouse to the public. When $Pe = 0.001$ and then Signal to Noise Ratio $(S/N) = 6.2194 = 7.9dB$.

B. Jamming Margin Method

The Rockwell Semiconductor System give us a software operated in the personal computer, and use the computer series port COM1 and COM2 connect Handset and Base than we can measure the Bit Error Rate.

Using this software we can perform Jamming Margin method testing, The test consists of stepping a signal generator in 50 KHz increments across the pass band of the system (up to 960 KHz away in RI's DCT). At each point, the generator level required to produce the recommend Bit Error Rate (BER = $10e - 3$) is recorded. This level is the jamming level. The maximum implementation loss a system can claim in calculating processing gain is 2 dB. The equation to calculate the processing gain (Gp) is the following:

$$G_p = (S/N) + M_j + L_{sys}$$

$$G_p = 8 \text{ dB} + M_j + 2 \text{ dB}$$


FCC regulation section 15.247 (e) require the processing gain of a direct sequence system shall be at least 10 dB, when Gp must be greater than 10 dB, then the Jammer must be greater than 0 dB.

The processing gain may be measured using the CW jamming margin method. The Jammer to Signal (J/S) ratio is then calculated. Discard the worst 20% of the J/S data points.

1. For avoid the handset and basestation are situation, so, the UUT were in low power mode.
2. The signal generator was selected in interference band, using this software we can perform Jamming Margin method testing, the test consists of stepping a signal generator is 50 KHz increments across the pass band of the system (up to 960 KHz away in RI's DCT). So, the BER will keep in 0.1%.


The setting up procedure is recorded on Appendix A.

7.2 Test Instruments Configuration



P.S A serial port from notebook computer to control the EUT at power output and channel number.

Fig. 13. Test Configuration of processing gain for base station



P.S A serial port from notebook computer to control the EUT at power output and channel number.

Fig. 14. Test Configuration of processing gain for handset

7.3 List of Test Instruments

Instrument Name	Model No	Brand	Serial No.	Last time	Next time
Signal Generator	8648D	HP	3613A00117	05/19/00	05/19/01
Power Meter	E4418B	HP	GB39291240	09/11/00	09/11/01
Attenuator (6dB to 18 GHz)	MCL BW-S6W2	Mini Circuits			

7.4 Test Procedure

According to the Fig. 13, combine the stuffs.

Measure the low power output of the channel 11 of the handset while the handset is in "Transmit-Only-Test" and the whole circuit is as same as Fig. 13. What we measure in this step is "S".

Change to the "BER Test " program. Increase the RF output of the signal generator till the BER is close to the 0.1% but under 0.1%.

Stop the program and turn off the base, handset then record the highest point of the spectrum. What we measure in this step is "J".

Star the Program again and test the next point.

7.5 Test Result of Processing Gain

Table 34 Processing Gain [Channel 11, Base]

Jammer Frequency (MHz)	S (dBm)	J (dBm)	Mj (J/S)	Process Gain (dB)
914.600	-36.11	-31.40	4.71	14.61
914.650	-36.11	-32.17	3.94	13.84
914.700	-36.11	-31.94	4.17	14.07
914.750	-36.11	-31.62	4.49	14.39
914.800	-36.11	-31.34	4.77	14.67
914.850	-36.11	-33.23	2.88	12.78
914.900	-36.11	-32.37	3.74	13.64
914.950	-36.11	-31.36	4.75	14.65
915.000	-36.11	-31.50	4.61	14.51
915.050	-36.11	-27.20	8.91	18.81
915.100	-36.11	-30.49	5.62	15.52
915.150	-36.11	-30.79	5.32	15.22
915.200	-36.11	-28.75	7.36	17.26
915.250	-36.11	-27.97	8.14	18.04
915.300	-36.11	-27.97	8.14	18.04
915.350	-36.11	-26.57	9.54	19.44
915.400	-36.11	-24.47	11.64	21.54
915.450	-36.11	-24.29	11.82	21.72
915.500	-36.11	-23.43	12.68	22.58
915.550	-36.11	-22.47	13.64	23.54
915.600	-36.11	-19.70	16.41	26.31
915.650	-36.11	-19.70	16.41	26.31
915.700	-36.11	-22.57	13.54	23.44
915.750	-36.11	-22.57	13.54	23.44
915.800	-36.11	-21.03	15.08	24.98
915.850	-36.11	-21.03	15.08	24.98
915.900	-36.11	-21.03	15.08	24.98
915.950	-36.11	-20.45	15.66	25.56
916.000	-36.11	-20.45	15.66	25.56
916.050	-36.11	-20.45	15.66	25.56

Test Result : Processing Gain: 14.61 dB

- Note: 1. $GP = (S/No) + Mj + Lsys = 7.9dB + Mj + 2dB$
 2. S = Signal Level
 3. J = Signal Generator RF Output

Table 35 Processing Gain [Channel 11, Handset]

Jammer Frequency (MHz)	S (dBm)	J (dBm)	Mj (J/S)	Process Gain (dB)
914.600	-33.09	-31.70	1.39	11.29
914.650	-33.09	-31.58	1.51	11.41
914.700	-33.09	-32.22	0.87	10.77
914.750	-33.09	-32.44	0.65	10.55
914.800	-33.09	-32.03	1.06	10.96
914.850	-33.09	-32.10	0.99	10.89
914.900	-33.09	-32.40	0.69	10.59
914.950	-33.09	-31.52	1.57	11.47
915.000	-33.09	-31.16	1.93	11.83
915.050	-33.09	-31.42	1.67	11.57
915.100	-33.09	-30.30	2.79	12.69
915.150	-33.09	-32.00	1.09	10.99
915.200	-33.09	-31.36	1.73	11.63
915.250	-33.09	-30.38	2.71	12.61
915.300	-33.09	-30.20	2.89	12.79
915.350	-33.09	-29.75	3.34	13.24
915.400	-33.09	-28.54	4.55	14.45
915.450	-33.09	-27.35	5.74	15.64
915.500	-33.09	-27.23	5.86	15.76
915.550	-33.09	-26.05	7.04	16.94
915.600	-33.09	-26.05	7.04	16.94
915.650	-33.09	-26.05	7.04	16.94
915.700	-33.09	-24.20	8.89	18.79
915.750	-33.09	-24.20	8.89	18.79
915.800	-33.09	-24.22	8.87	18.77
915.850	-33.09	-23.33	9.76	19.66
915.900	-33.09	-23.23	9.86	19.76
915.950	-33.09	-23.33	9.76	19.66
916.000	-33.09	-23.33	9.76	19.66
916.050	-33.09	-23.30	9.79	19.69

Test Result : Processing Gain: 11.29 dB

- Note: 1. $GP = (S/No) + Mj + L_{sys} = 7.9dB + Mj + 2 dB$
 2. S = Signal Level
 3. J = Signal Generator RF Output

Appendix A

Setting up Procedure

1. Using an RS-232 Adaptor that is given by customer connected with the COM 1 of the computer.
2. The other end of the RS-232 Adaptor is connected with the EUT.
3. Use the software that is given by the customer and operated in the windows to control the EUT's continuous transmission.



Appendix B



Antenna Sketch

AMEND	MRK.	DATE	REVISION	SIGN
	1	88.10.7	20.2 10.11 20.12 20.13 20.14	20.15


僅供參考
REFERENCE ONLY

DIMENSION	LIMITS
1mm ~ 20mm	± 0.1
21mm ~ 40mm	± 0.2
41mm ~ 80mm	± 0.3
81mm ~ 100mm	± 0.4
101mm ~	± 0.5



3	RSW-9005	METAL ROD	Zn DC3	1	N% PLATED
2	STK-9001	SPRING	STEEL WIRE	1	N% PLATED
1	NSB87	PIPE	POLYURETHANE(S95A-55)	1	COLOR : B/K,GRAY
NO.	PARTS NO.	NAME	MATERIAL	Q'TY.	REMARKS
DRAW BY 計 研 H. 10.7		CHECK BY 	APPROVE BY 	SCALE 2/1	UNIT mm
DRAWING CODE NUMBER		MODEL NAME - NSB87-H375-TL1(B/K)-01 NSB87-H375-TL1(CRAY)-01		PARTS NAME	

僅供參考
REFERENCE ONLY



(1)					STAYSAIL			PP	1	PP PIPE	5
(2)					SCALE 1:1			BRASS BSBM2	1	SWIVEL BASE	4
(3)					UNIT MM			ABS	1	HOLDER	3
SIGN	DATE	REVISION	DRW	CHECK	TOLERANCE ± 0.2	REMARK	MATERIAL		QTY	SET	NO.
DRAWN BY C.C. Tu	DESIGNED BY	CHECKED BY	DATE 1999 0608	DRAWING NUMBER UL-9906-081	PART NAME TM902 BU ANTENNA	PART NO. UD-064	COUSTOM PARTS NO.				

THAI USE LINK ENTERPRISE LTD.

Appendix C

The antenna of the device is screwed inside the device, the user can not remove it freely without any tools from outside the device. This is comply with the FCC rules part 15.203

Appendix D

Security Code

Description of 900 MHz Direct Spectrum Cordless Phone

The subject device's 20 independent channels, autoscans at link establishment and smart channel hopping combine to find the clearest channels at all times, automatically. Spread spectrum technology ensures the highest level of security available in a cordless phone.

The spread spectrum technique provides better security than other solutions since only the receiver has a copy of the pre-assigned spreading code, making interception virtually impossible. The transmitting signal is diluted over a large bandwidth with power density at any point being very light, so the signal goes unnoticed by other systems since they are not tuned to receive it. Moreover the scrambling code changes every 8 times the phone is parked, and there are millions of codes.

Scrambler / Descrambler A16-code randomizes the voice and supervisory data for transmission and reception, more than 64K scramble codes are available from the 16-bit maximal length pseudo-noise sequence generator.

Spread Spectrum Spreader each transmitted bit is multiplied with a 12-chip spreading code, meeting FCC Part 15.247 requirements.