

EXHIBIT 5

User's Manual

User's Manual

TOK2001-F001
FCC ID: OU2CY65G41
TX: FCC ID
Peripheral: DoC

Instruction Manual
Federal Communication Commission Interference Statement

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

FCC Caution: To assure continued compliance, use only the provided shielded interface cable with ferrite core when connecting to host computer. Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Responsible Party: (Name)
(Address In U.S.A.)
Telephone No: (1-800 number located in U.S.A.)

Channels Frequency

Below is a table of our channels with their frequencies. The channels are given for the devices you have now on your hand. Before the test in your laboratory we had no idea that some channels are beyond the permitted range of frequencies. Now we have refused using channels 1,2,63,64. And use channels from 3 to 62. The new release of our software does not allow the work on the channels 1,2,63,64.

Ch	F _i , MHz												
1	902.4	11	906.4	21	910.4	31	914.4	41	918.4	51	922.4	61	926.4
2	902.8	12	906.8	22	910.8	32	914.8	42	918.8	52	922.8	62	926.8
3	903.2	13	907.2	23	911.2	33	915.2	43	919.2	53	923.2	63	927.2
4	903.6	14	907.6	24	911.6	34	915.6	44	919.6	54	923.6	64	927.6
5	904.0	15	908.0	25	912.0	35	916.0	45	920.0	55	924.0		
6	904.4	16	908.4	26	912.4	36	916.4	46	920.4	56	924.4		
7	904.8	17	908.8	27	912.8	37	916.8	47	920.8	57	924.8		
8	905.2	18	909.2	28	913.2	38	917.2	48	921.2	58	925.2		
9	905.6	19	909.6	29	913.6	39	917.6	49	921.6	59	925.6		
10	906.0	20	910.0	30	914.0	40	918.0	50	922.0	60	926.0		

Our device functions only with frequency-modulated signals, which are transmitted in packet mode. Width of the spectra when transmitting is 200 kHz (+/- 100 kHz) – one channel.