

RF-EXPOSURE ASSESSMENT REPORT**FCC 47 CFR Part 2.1091
ISED RSS-102****RF-Exposure evaluation of mobile equipment****Report Reference No.**: G0M-1904-8182-TFC091ME-V01**Testing Laboratory**: Eurofins Product Service GmbHAddress: Storkower Str. 38c
15526 Reichenwalde
Germany**Accreditation**:DAkkS - Registration number : D-PL-12092-01-03 (ISED)
ISED Testing Laboratory site: 3470A-2
DAkkS - Registration number : D-PL-12092-01-04 (FCC)
FCC Filed Test Laboratory, Reg.-No.: 96970**Applicant's name**: Kamstrup A/SAddress: Industriavej 28
8660 Skanderborg
DENMARK**Test specification:**Standard: FCC 47 CFR 2.1091
FCC KDB 447498 D01 v06:2015-10-23
ISED RSS-102, Issue 5:2015-03**Equipment under test (EUT):**

Product description	KWM2210 02K14xxxxxxxx / Ultrasonic water meter	
Model No.	flowIQ® 2200	
Additional Model(s)	None	
Brand Name(s)	flowIQ® 2200	
Hardware version	5550 1810D1 (top pcb) + 55501811 D1 (bottom pcb) + 5550 1350 A7 (Antenna)	
Firmware / Software version	50981547 E1 (fw top pcb) / 55141875 (flash top pcb)/55141876 eeprom file (top pcb) / 50981537 D1 (bottom pcb)	
	FCC-ID: OUY-KWM2210	IC: N/A
Test result	Passed	

Test Report No.: G0M-1904-8182-TFC091ME-V01

Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany

Possible test case verdicts:

- neither assessed nor tested: N/N
- required by standard but not appl. to test object.....: N/A
- required by standard but not tested.....: N/T
- not required by standard for the test object: N/R
- test object does meet the requirement.....: P (Pass)
- test object does not meet the requirement.....: F (Fail)

Testing:

Test Lab Temperature: 20 – 23 °C

Test Lab Humidity: 32 – 38 %

Date of receipt of test item: 2019-05-13

Date (s) of assessment: 2019-05-28

Compiled by: Toralf Jahn

Assessed by (+ signature): Burkhard Pudell
(Responsible for Assessment)



Approved by (+ signature): Christian Weber
(Head of Lab)



Date of issue: 2019-06-27

Total number of pages: 14

General remarks:

The test results presented in this report relate only to the object tested.

The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.

This report shall not be reproduced, except in full, without the written approval of the issuing testing laboratory.

Additional comments:

type nummer for flowIQ®2200 , prefix : KWM2210 typenr 02K14XXXXXX where

* 02 : generic for flowIQ® 2200

- K : 1-part body, PPS housing
- 14 : Wireless m-bus - 915MHz (1 way wireless communication)
- X : battery type
- X : dynamic range
- XX : meter size
- X : Meter type (hot/cold water)
- XX : country code

So the radio board electronic and setting is defined by the code "14" while the x corresponds to ordering details

Version History

Version	Issue Date	Remarks	Revised by
01	2019-06-27	Initial Release	

REPORT INDEX

1	EQUIPMENT (TEST ITEM) DESCRIPTION	6
1.1	Reference Documents	7
1.2	Standalone Radiation Sources	8
1.3	Concurrent-Transmitter Modes	8
2	RESULT SUMMARY	9
3	RF-EXPOSURE CLASSIFICATIONS	10
4	ASSESSMENT	11
4.1	MPE Assessment Conditions – 47 CFR 2.1091 / RSS-102	11
4.2	Single-Transmitter Assessment – 47 CFR 2.1091 / RSS-102	14

1 Equipment (Test item) Description

Description	KWM2210 02K14xxxxxxxx / Ultrasonic water meter
Model	flowIQ® 2200
Additional Model(s)	None
Brand Name(s)	flowIQ® 2200
Serial number	None
Hardware version	5550 1810D1 (top pcb) + 55501811 D1 (bottom pcb) + 5550 1350 A7 (Antenna)
Software / Firmware version	50981547 E1 (fw top pcb) / 55141875 (flash top pcb)/55141876 eeprom file (top pcb) / 50981537 D1 (bottom pcb)
PMN	N/A
HVIN	N/A
FVIN	N/A
HMN	N/A
FCC-ID	OUY-KWM2210
IC	N/A
Equipment type	End product

1.1 Reference Documents

Document type	Document No.	Issued by	Date
FCC 15.247 Test Report	G0M-1904-8182-TFC247DT-V01	Eurofins Product Service GmbH	2019-05-24

1.2 Standalone Radiation Sources

Mode #	Description	
Digital Transmission	Frequency range [MHz]	912.5 – 918.5
	Transmission modes	2-FSK
	Maximum conducted power [dBm]	15.5
	Maximum radiated power [dBm]	14.2
	Maximum transmission duty cycle [%]	100
	Antenna gain [dBi]	-1.3
	Antenna diameter [cm]	10
	Assessment Frequency [MHz]	912.5

1.3 Concurrent-Transmitter Modes

None

2 Result Summary

FCC 47 CFR Part 2.1091, IC RSS-102			
Product Specific Standard Section	Requirement	Result	Remarks
47 CFR 2.1091	Maximum permissible exposure @ 20cm below limit	PASS	
RSS-102 2.5.2	Maximum permissible exposure @ 20cm below limit	PASS	
Remarks:			

3 RF-Exposure Classifications

Device Types	
Fixed	A fixed device is defined as a device physically secured at one fixed location and cannot be easily re-located.
Mobile	A mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. (47 CFR 2.1091)
Portable	A portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. (47 CFR 2.1093)
Exposure Categories	
Occupational / Controlled	Limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.
General population / uncontrolled	Exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

4 Assessment

4.1 MPE Assessment Conditions – 47 CFR 2.1091 / RSS-102

MPE ASSESSMENT ACC. TO 47 CFR 2.1091 / ISED RSS-102		VERDICT: PASS		
Assessment according to reference		Reference Method		
		FCC OET Bulletin 65 / RSS-102		
Device type		mobile		
Exposure category		General public		
ISED Limits – Occupational / Controlled Exposure				
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [W/m ²]	Averaging time [min]
0.003-10*	170	180	-	Instantaneous*
0.1-10	-	1.6 / f	-	6**
1.29-10	193 / $f^{0.5}$	-	-	6**
10-20	61.4	0.163	-10	6
20-48	129.8 / $f^{0.25}$	0.3444 / $f^{0.25}$	44.72 / $f^{0.5}$	6
48-100	49.33	0.1309	6.455	6
100-6000	15.60 $f^{0.25}$	0.04138 $f^{0.25}$	0.6455 $f^{0.5}$	6
6000-15000	137	0.364	50	6
15000-150000	137	0.364	50	616000 / $f^{1.2}$
150000-300000	0.354 $f^{0.5}$	$9.40 \times 10^{-4} f^{0.5}$	$3.33 \times 10^{-4} f$	616000 / $f^{1.2}$
ISED Limits – General Population / Uncontrolled Exposure				
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [W/m ²]	Averaging time [min]
0.003-10*	83	90	-	Instantaneous*
0.1-10	-	0.73 / f	-	6**
1.1-10	87 / $f^{0.5}$	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07 / $f^{0.25}$	0.1540 / $f^{0.25}$	8.944 / $f^{0.5}$	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 $f^{0.3417}$	0.008335 $f^{0.3417}$	0.02619 $f^{0.6834}$	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000 / $f^{1.2}$
150000-300000	0.158 $f^{0.5}$	$4.21 \times 10^{-4} f^{0.5}$	$6.67 \times 10^{-5} f$	616000 / $f^{1.2}$
* = Based on nerve stimulation				
** = Bases on specific absorption rate				

FCC Limits – Occupational / Controlled Exposure				
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [mW/cm ²]	Averaging time [min]
0.3 – 3.0	614	1.63	(100)*	6
3.0 - 30	1842 / f	4.89 / f	(900 / f ²)*	6
30 - 300	61.4	0.163	1.0	6
300 - 1500	N/A	N/A	f / 300	6
1500 - 100000	N/A	N/A	5.0	6
FCC Limits – General Population / Uncontrolled Exposure				
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [mW/cm ²]	Averaging time [min]
0.3 – 1.34	614	1.63	(100)*	30
1.34 - 30	842 / f	2.19 / f	(180 / f ²)*	30
30 - 300	27.5	0.073	0.2	30
300 - 1500	N/A	N/A	f / 1500	30
1500 - 100000	N/A	N/A	1.0	30

* = Plane wave equivalent power density; f in MHz

Assessment Relations
$\lambda[m] = \frac{c \left[\frac{m}{s} \right]}{f[Hz]} ; R_{FF}[m] \geq \frac{2 \cdot D[m]^2}{\lambda[m]}$
$S[mW/cm^2] = \frac{P_{E.I.R.P.}[mW]}{4\pi R[cm]^2} ; R[cm] = \sqrt{\frac{P_{E.I.R.P.}[mW]}{4\pi S[mW/cm^2]}}$
$P_R[mW] = P_C[mW] \cdot G ; P_R[dBm] = P_C[dBm] + G[dBi]$
$DCC [dB] = 10 \cdot \log_{10} \left(\frac{DC[\%]}{100} \right)$
$\sum_{i=1}^N \frac{S_i \left[\frac{W}{m^2} \right]}{S_{Li} \left[\frac{W}{m^2} \right]} + \sum_{j=1}^M \left(\frac{E_j \left[\frac{V}{m} \right]}{E_{Lj} \left[\frac{V}{m} \right]} \right)^2 + \sum_{k=1}^O \left(\frac{H_k \left[\frac{A}{m} \right]}{H_{Lk} \left[\frac{A}{m} \right]} \right)^2 < 1$

Assessment procedureStandalone operation assessment:

For each radio and frequency band the worst case transmission mode with the highest peak conducted or radiated power is evaluated at the frequency that results in the most restrictive rf-exposure limit. From the peak power values, antenna gains and duty cycles taken from the reference documents, the source average radiated power values are calculated. From the average radiated power the power densities at antenna far-field distance, at 20cm separation distance from the radiation source is calculated. Compliance with the RF-Exposure limit is determined at 20cm separation distance.

Concurrent operation assessment:

First the evaluation distance is set to 20 cm. The ratios of the power densities and/or field strength values and the corresponding limits are calculated and summed and the sum is compared to the maximum of 1.

4.2 Single-Transmitter Assessment – 47 CFR 2.1091 / RSS-102

Assessment result - Digital Transmission		
Transmission mode		
Operating mode frequency range [MHz]	912.5 – 918.5	
Assessment frequency (f) [MHz]	912.5	
Transmission duty cycle (DC) [%]	100	
Peak conducted power (P _C) [dBm]	15.5	
Peak radiated power (P _R) [dBm e.i.r.p.]	14.2	
Peak Antenna gain (G) [dBi]	-1.3	
Maximum Antenna Diameter D [cm]	10	
Antenna far-field distance		
Transmission frequency wavelength (λ)	0.329 m	32.88 cm
Antenna far-field distance (R _{FF})	0.061 m	6.08 cm
Power evaluation		
Peak conducted power (P _C)	35.48 mW	15.50 dBm
Peak Antenna Gain (G)	0.74	-1.30 dBi
Calculated peak radiated power (P _{R-Calc})	26.30 mW	14.20 dBm
Measured peak radiated power (P _R)	26.30 mW	14.20 dBm
Source average Power		
Maximum transmission duty cycle (DC)	100.0 %	
Duty cycle correction (DCC)	1.00	0.00 dB
Measured peak radiated power (P _R)	26.30 mW	14.20 dBm
Averaged peak radiated power (P _{RAVG})	26.30 mW	14.20 dBm
Power density		
Compliance power density limit FCC (S _{FCCLimit})	0.608 mW/cm ²	6.08 W/m ²
Compliance power density limit IC (S _{ICLimit})	0.276 mW/cm ²	2.76 W/m ²
Power density @ Antenna far-field distance	0.057 mW/cm ²	0.566 W/m ²
Power density @ 20cm	0.005 mW/cm ²	0.052 W/m ²
Distance for compliance power density FCC	0.019 m	1.85 cm
Distance for compliance power density IC	0.028 m	2.75 cm
Verdict		
The power density of the EUT at 20cm is below the FCC MPE limit!		
The power density of the EUT at 20cm is below the IC MPE limit!		
Comments:		