



MPE TEST REPORT

Applicant FOCAL JMLab

FCC ID OV3-FH21041

Product DIVA UTOPIA

Brand FOCAL

Model DIVA UTOPIA

Report No. R2410A1479-M1

Issue Date November 8, 2024

Eurofins TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC 47 CFR Part 1 1.1310**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Prepared by: Wei Fangying

Approved by: Xu Kai

Eurofins TA Technology (Shanghai) Co., Ltd.

Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000

Table of Contents

1	Test Laboratory	3
1.1	Notes of the Test Report.....	3
1.2	Test Facility.....	3
1.3	Testing Location.....	3
1.4	Laboratory Environment	3
2	Description of Equipment Under Test	4
3	Maximum Output Power (Measured) and Antenna Gain.....	5
4	MPE Limit.....	6
5	RF Exposure Evaluation Result.....	8
	ANNEX A: The EUT Appearance	9

1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **Eurofins TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2 Test Facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

1.3 Testing Location

Company: Eurofins TA Technology (Shanghai) Co., Ltd.
Address: Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <https://www.eurofins.com/electrical-and-electronics>
E-mail: Kain.Xu@cpt.eurofinscn.com

1.4 Laboratory Environment

Temperature	Min. = 18°C, Max. = 25°C
Relative humidity	Min. = 20%, Max. = 80%
Ground system resistance	< 0.5 Ω
Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards.	

2 Description of Equipment Under Test

Client Information

Applicant	FOCAL JMLab
Applicant address	108 Avenue De l'Avenir, ZI Molina la Chazotte, 42350 LA TALAUDIERE, FRANCE
Manufacturer	FOCAL JMLab
Manufacturer address	108 Avenue De l'Avenir, ZI Molina la Chazotte, 42350 LA TALAUDIERE, FRANCE

General Technologies

EUT Description						
Model	DIVA UTOPIA					
Lab internal SN	R2410A1479/S01					
Hardware Version	R1					
Software Version	0.0.0.9862					
Frequency	Band	TX (MHz)	RX (MHz)			
	Bluetooth	2400 ~ 2483.5	2400 ~ 2483.5			
	Wi-Fi 2.4G	2400 ~ 2483.5	2400 ~ 2483.5			
	Wi-Fi 5G (U-NII-1)	5150 ~ 5250	5150 ~ 5250			
	Wi-Fi 5G (U-NII-2A)	5250 ~ 5350	5250 ~ 5350			
	Wi-Fi 5G (U-NII-2C)	5470 ~ 5600 5650 ~ 5725	5470 ~ 5600 5650 ~ 5725			
	Wi-Fi 5G (U-NII-3)	5725 ~ 5850	5725 ~ 5850			
	Zigbee	2405 ~ 2480	2405 ~ 2480			
	UWB	6000 ~9000	6000 ~9000			
Date of Sample Received	June 17, 2024					
Note:						
1. The EUT is sent from the applicant to Eurofins TA and the information of the EUT is declared by the applicant.						
2. All indications of Pass/Fail in this report are opinions expressed by Eurofins TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.						

3 Maximum Output Power (Measured) and Antenna Gain

The numeric gain (G) of the antenna with a gain specified in dB is determined by

Numeric gain (G)=10^(antenna gain/10)

Band	Maximum Output Power		Antenna Gain (dBi)	Numeric Gain
	(dBm)	(mW)		
Bluetooth	6.064	4.040	3.0	1.995
Wi-Fi 2.4G	19.970	99.312	3.0	1.995
Wi-Fi 5G	15.099	32.352	2.5	1.778
Zigbee	-0.501	0.891	3.0	1.995
UWB	6.880	4.875	1.8	1.514

Note: Maximum Output Power refer to the Module report.

4 MPE Limit

According to section 1.1310 of FCC 47 CFR Part 1, limits for maximum permissible exposure (MPE) are as following.

TABLE 1 – LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	f/300	6
1500-100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Note1. Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational / controlled limits apply provided he or she is made aware of the potential for exposure.

Note2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

The maximum permissible exposure for 1500~100,000MHz is 1.0. So

Band	The Maximum Permissible Exposure (mW/cm ²)
Bluetooth	1.000
Wi-Fi 2.4G	1.000
Wi-Fi 5G	1.000
Zigbee	1.000
UWB	1.000

5 RF Exposure Evaluation Result

RF exposure evaluation method is based on KDB 447498 D01, this calculation is based on the conducted power, maximum power and antenna gain with provides the minimum separation distance. The formula shown below is from OET Bulletin 65 Edition 97-01 Per KDB 447498 D01:

$$S = PG / 4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm²)

P = Time-average maximum tune up procedure (in appropriate units, e.g., mW)

G = the numeric gain of the antenna

R = distance to the center of radiation of the antenna (20 cm = limit for MPE)

Band	Maximum Output Power (dBm)	Antenna Gain (dBi)	Maximum EIRP (dBm)	PG (mW)	Result (mW/cm ²)	Limit Value (mW/cm ²)	The MPE Ratio
Bluetooth	6.064	3.0	9.064	8.061	0.0016	1.000	0.0016
Wi-Fi 2.4G	19.970	3.0	22.970	198.153	0.039	1.000	0.0394
Wi-Fi 5G	15.099	2.5	17.599	57.531	0.011	1.000	0.0114
Zigbee	-0.501	3.0	2.499	1.778	0.000	1.000	0.0004
UWB	6.880	1.8	8.680	7.379	0.001	1.000	0.0015
Note: R = 20cm $\pi = 3.1416$ The MPE Ratio = Mac Result ÷ Limit Value							

So the simultaneous transmitting antenna pairs as below:

TER = Bluetooth MPE ratio + Zigbee MPE ratio + Wi-Fi 2.4G MPE ratio+ Wi-Fi 5G MPE ratio+ UWB MPE ratio = 0.0016 + 0.0004 + 0.0394 + 0.0114 + 0.0015 = 0.0543 < 1

Note: For transmitters, minimum separation distance is 20cm, even if calculations indicate MPE distance is less.

IMPORTANT NOTE: To comply with the FCC RF exposure compliance requirements, the antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter. No change to the antenna or the device is permitted. Any change to the antenna or the device could result in the device exceeding the RF exposure requirements and void user's authority to operate the device.

ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.

*****END OF REPORT*****