

Re: Class II Permissive Change Request

FCC Part 15.212 Requirement	Comment/Declaration
(i) The radio elements of the modular transmitter must have their own shielding. The physical crystal and tuning capacitors may be located external to the shielded radio elements.	The radio elements have their own shielding.
(ii) The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with part 15 requirements under conditions of excessive data rates or over-modulation.	Complies.
(iii) The modular transmitter must have its own power supply regulation.	Complies. Internal 2.8V regulation.
(iv) The modular transmitter must comply with the antenna and transmission system requirements of §§15.203, 15.204(b) and 15.204(c). The antenna must either be permanently attached or employ a “unique” antenna coupler (at all connections between the module and the antenna, including the cable). The “professional installation” provision of §15.203 is not applicable to modules but can apply to limited modular approvals under paragraph (b) of this section.	Complies. RPSMA connection and documented antenna requirements.
(v) The modular transmitter must be tested in a stand-alone configuration, <i>i.e.</i> , the module must not be inside another device during testing for compliance with part 15 requirements. Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in §15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, unless they will be marketed with the module (see §15.27(a)). The length of these lines shall be the length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified and commercially available (see §15.31(i)).	Does not comply. The unit was tested as not a stand-alone device.

Schneider Electric

Process Automation, SCADA & Telemetry
415 Legget Drive, Suite 101,
Kanata, Ontario K2K 3R1 Canada
Phone: +1-613-591-1943
Toll Free North America: 888-267-2232
Fax: +1-613-591-1022

(vi) The modular transmitter must be equipped with either a permanently affixed label or must be capable of electronically displaying its FCC identification number.	Complies. The modular transmitter has a label affixed to the top of RF shielding.
(vii) The modular transmitter must comply with any specific rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization.	Complies.
(viii) The modular transmitter must comply with any applicable RF exposure requirements in its final configuration.	Complies.
(iX) Comment (b) A limited modular approval may be granted for single or split modular transmitters that do not comply with all of the above requirements, <i>e.g.</i> , shielding, minimum signaling amplitude, buffered modulation/data inputs, or power supply regulation, if the manufacturer can demonstrate by alternative means in the application for equipment authorization that the modular transmitter meets all the applicable part 15 requirements under the operating conditions in which the transmitter will be used. Limited modular approval also may be granted in those instances where compliance with RF exposure rules is demonstrated only for particular product configurations. The applicant for certification must state how control of the end product into which the module will be installed will be maintained such that full compliance of the end product is always ensured.	The module 16363F is submitted for Limited Modular Approval (LMA). In keeping with FCC Part 15.212 Unlicensed Modular Transmitter Approval, this letter affirms that Schneider Electric Systems Canada Inc. shall retain complete control over the final installation of the module in an end-product and ensure compliance of the end-product to FCC regulations. The module shall only be installed into an end-product by operators trained by Schneider Electric Systems Canada Inc. The module shall not be distributed, marketed or sold to the general public. It will only be available installed in a complete Accutech end-product. The complete Accutech end-product shall only be sold by Schneider Electric directly or through a Schneider Electric specified sales channel to authorized resellers.

Schneider Electric

Process Automation, SCADA & Telemetry
 415 Legget Drive, Suite 101,
 Kanata, Ontario K2K 3R1 Canada
 Phone: +1-613-591-1943
 Toll Free North America: 888-267-2232
 Fax: +1-613-591-1022

schneider-electric.com