



Attachment B (Human exposure)

according to

Test Report No. :	T42314-00-00KJ	02. September 2016 Date of issue
--------------------------	-----------------------	-------------------------------------

Type / Model Name : COR C-300-RI

Product Description : Portable radio interface for COR MS-3 & COR PT-3

Applicant : Seba Dynatronic Mess- und Ortungstechnik GmbH

Address : Dr.-Herbert-Iann-Str. 6
96148 BAUNACH, GERMANY

Manufacturer : Seba Dynatronic Mess- und Ortungstechnik GmbH

Address : Dr.-Herbert-Iann-Str. 6
96148 BAUNACH, GERMANY

Licence holder : Seba Dynatronic Mess- und Ortungstechnik GmbH

Address : Dr.-Herbert-Iann-Str. 6
96148 BAUNACH, GERMANY

Test Result according to the
standards listed in clause 1 test
standards:

POSITIVE



Deutsche
Akkreditierungsstelle
D-PL-12030-01-01
D-PL-12030-01-02

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test results
without the written permission of the test laboratory.

Contents

1 TEST STANDARDS	3
2 EQUIPMENT UNDER TEST	4
2.1 Photo documentation of the EUT – Detailed photos see ATTACHMENT A	4
2.2 Short description of the equipment under test (EUT)	4
2.3 Variants of the EUT	4
2.4 Operation frequency range	5
2.5 Technical description of the equipment under test (EUT)	5
2.6 Power supply system utilised	5
2.7 Determination of worst case conditions for final calculations	5
3 FINAL ASSESSMENT	6
4 TEST ENVIRONMENT	7
4.1 Address of the test laboratory	7
4.2 Environmental conditions	7
4.3 Statement of the measurement uncertainty	7
4.4 Measurement protocol for FCC and IC	8
5 HUMAN EXPOSURE	9
5.1 Co-location and Co-transmission	9
5.2 General SAR test exclusion consideration	10
ATTACHMENT (PHOTO DOCUMENTATION OF THE EUT)	A

Attachment A as separately supplement

1 TEST STANDARDS

The tests were performed according to following standards:

FCC Rules and Regulations Part 1, Subpart I - Procedures Implementing the National Environmental Policy Act of 1969

Part 1, Subpart I, Section 1.1310	Radiofrequency radiation exposure limits
Part 1, Subpart 2, Section 2.1093	Radiofrequency radiation exposure evaluation: portable device

OET Bulletin 65, 65A, 65B Edition 97-01, August 1997 – Evaluating Compliance with FCC Guidelines for Human Exposure to Radio Frequency Electromagnetic Fields.

KDB 447498 D01 v06	RF exposure procedures and equipment authorization policies for mobile and portable devices, October 23, 2015.
--------------------	--

ANSI C95.1: 2005	IEEE Standard for Safety Levels with respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz
------------------	--

CISPR 16-4-2: 2013	Uncertainty in EMC measurement
--------------------	--------------------------------

2 EQUIPMENT UNDER TEST

2.1 Photo documentation of the EUT – Detailed photos see ATTACHMENT A



2.2 Short description of the equipment under test (EUT)

The COR C-300-RI is a portable device, acting as a radio interface between a PC or laptop and the sensor devices of the COR C-3 system. With the C-300-RI it is possible to program/configure the Multisensors (COR MS-3) and receive the analog signal of the Power-Transmitters (COR PT-3).

The digital communication (programming/configuring) is done at a frequency of 913 MHz. The receiving of analog audio signals from the Power-Transmitter is done at a frequency of 469 MHz. The C-300-RI has two external connectors to connect two different antennas – one for digital communication and one for long range analog communication.

Number of tested samples: 1
Serial number: 12065920002

2.3 Variants of the EUT

- There are no other variants.

2.4 Operation frequency range

Equipment category	Range
PLMR (TX & RX)	902 MHz – 928 MHz

2.5 Technical description of the equipment under test (EUT)

Items	Description
Power supply	$V_{\text{nom}} = 5.0 \text{ V DC (USB)}$ ($V_{\text{min}} = 4.3 \text{ V DC}$, $V_{\text{max}} = 5.8 \text{ V DC}$)
Digital radio:	
Type of modulation	FSK
Operating frequency	913.02 MHz
Frequency band	902 MHz to 928 MHz
Data rate	9.6 kBd
Channel spacing	-
Number of channels	1
Antenna type	stub antenna
Antenna connector	TNC
Antenna gain	0 dBi
Digital radio (only RX):	
Type of modulation	analog FM
Operating frequency digital radio	468.5 MHz / 469.6 MHz
Frequency band	468.5 – 496.6 MHz
Data rate	
Channel spacing	25 kHz
Number of channels	1 per Transmitter UNIT
Antenna type	Antenne lambda 1/2 460MHz
Antenna connector	BNC
Antenna gain	7 dBi
Lowest internal frequency	32.768 kHz
Highest internal frequency	26.000 MHz
Serial number	0859000294
Firmware version	1.00.00
Number of tested samples	1

2.6 Power supply system utilised

Power supply voltage, V_{nom} : 7.4 V DC (Li-ion rechargeable battery)

2.7 Determination of worst case conditions for final calculations

Note:

No separate measurement was performed to generate test results for the present document. This test report is based on the results of the test reports **T42314-00-00KJ** from CSA Group Bayern. In this case only worst case considerations for the highest radiated output power are taken.

3 FINAL ASSESSMENT

The equipment under test fulfills the EMI requirements cited in clause 1 test standards.

Date of receipt of test sample : acc. to storage records

Testing commenced on : 08 March 2017

Testing concluded on : 08 March 2017

Checked by:

Tested by:

Klaus Gegenfurtner
Teamleader Radio

Josef Knab
Radio Team

4 TEST ENVIRONMENT

4.1 Address of the test laboratory

CSA Group Bayern GmbH
Ohmstrasse 1-4
94342 STRASSKIRCHEN
GERMANY

4.2 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature: 15-35 °C

Humidity: 30-60 %

Atmospheric pressure: 86-106 kPa

4.3 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. It is noted that the expanded measurement uncertainty corresponds to the measurement results from the standard measurement uncertainty multiplied by the coverage factor $k = 2$. The true value is located in the corresponding interval with a probability of 95 %. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16-4-2 / 11.2003 „Uncertainties, statistics and limit modelling – Uncertainty in EMC measurements“ and is documented in the quality system acc. to DIN EN ISO/IEC 17025. For all measurements shown in this report, the measurement uncertainty of the test laboratory, CSA Group Bayern GmbH, is below the measurement uncertainty as defined by CISPR. Therefore, no special measures must be taken into consideration with regard to the limits according to CISPR. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

4.4 Measurement protocol for FCC and IC

4.4.1 General information

4.4.1.1 Test methodology

The Open Area test site is a listed Open Site under the Canadian Test-Sites File-No:

**IC 3009A-1,
IC 3009A-2**

In compliance with RSS 210 testing for RSS compliance may be achieved by following the procedures set out in ANSI C63.10 and applying the CISPR 22 limits.

4.4.1.2 Justification

The equipment under test (EUT) is configured in a typical user arrangement in accordance with the manufacturer's instructions. A cable is connected to each available port and either terminated with a peripheral using the appropriate impedance characteristic or left unterminated. Where appropriate, cables are manually manipulated with respect to each other thus obtaining maximum disturbances from the unit.

4.4.1.3 Details of test procedures

In compliance with 47 CFR Part 15 Subpart A, Section 15.38 testing for FCC compliance may be achieved by following the procedures set out in ANSI C63.4 and applying the CISPR 22 limits.

5 HUMAN EXPOSURE

5.1 Co-location and Co-transmission

5.1.1 Applicable standard

OET Bulletin 65, Edition 97-01, Section 2: Multiple-transmitter sites and Complex Environments

The FCC's MPE limits vary with frequency. Therefore, in mixed or broadband RF fields where several sources and frequencies are involved, the fraction of the recommended limit (in terms of power density or square of the electric or magnetic field strength) incurred within each frequency interval should be determined, and the sum of all fractional contributions should not exceed 1.0, or 100 % in terms of percentage.

The requirements are **FULFILLED**.

Remarks: Not applicable, because the system has no multiple transmitters inside.

5.2 General SAR test exclusion consideration

5.2.1 Applicable standard

According to KDB 447498 D01, item 4.3.1:

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition(s), listed below, is (are) satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.²⁸ The minimum test separation distance defined in 4.1 f) is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander. To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified, typically in the SAR measurement or SAR analysis report, by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, according to the required published RF exposure KDB procedures. When no other RF exposure testing or reporting are required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for SAR test exclusion. When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions; for example, handheld PTT two-way radios, handsets, laptops and tablets, etc.

a) For 100 MHz to 6 GHz and test separation distances \leq 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \times \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR, and } \leq 7.5 \text{ for 10-g extremity SAR,} \text{ where}$$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation³¹
- The result is rounded to one decimal place for comparison
- The values 3.0 and 7.5 are referred to as numeric thresholds in step b) below

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is $<$ 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

5.2.2 Test result

Separation distance (mm)	Channel frequency (MHz)	Conducted power* (dBm)	Conducted power (mW)	1-g SAR (1)	Limit 1-g SAR (1)
5	913.02	11.0	12.59	2.4059	3.0

*) accd. tune up procedure the rated output power is 8 dBm \pm 3 dB.

The requirements are **FULFILLED**.

Remarks: