

Motorcycle Radio MPE Evaluation Report
(One of two antennas)

Declaration of Compliance

FCC Rule Part:	47 CFR §90; §2.1091; §1.1310
Device Classification:	Licensed Non-Broadcast Station Transmitter (TNB)
Device Type:	UHF PTT Radio Transceiver with Motorcycle Mount and Antenna
FCC ID:	OWDTR-0020-E
Model Name:	M7100 (IP)
Modulation:	FM
Tx Frequency Range:	378 - 430 MHz
Max. RF Conducted Power:	25 W (factory configured for motorcycle applications; 1.05 multiplier)
Power Supply:	12 VDC
Antenna Type:	Quarter wave vertical (P/N LE-OM406BKTNC)
Antenna Gain:	5.5 dbi (3.55 numerical)
Minimum Antenna Distance:	54.25 cm Limits for Occupational/Controlled Exposure. 121.78 cm Limits for General Population/Uncontrolled Exposure.

Calculation

$$S = \frac{PG}{4\pi R^2} \quad \text{therefore: } R = \sqrt{\frac{PG}{4\pi S}}$$

Where: S – power density (mW/cm²; as defined in 47 CFR § 1.1310), P – power input to antenna at 50% duty cycle (in mW), G – power gain of the antenna relative to isotropic (numeric value, not db), R – distance to center of antenna (result in cm).

$S = 1.26/.25$ (Controlled($f/300$)/Uncontrolled($f/1500$)) at Tx frequency 378 MHz (frequency when applicable).

Calculated controlled distance: 54.25 cm

Calculated uncontrolled distance: 121.78 cm



Daryl Popowitch
Regulatory Manager,
Engineering Project Manager