

TEST REPORT ADDENDUM - CONDUCTED

FROM



Test of: Sliver Spring Networks NIC 510

To: FCC CFR 47 Part 15 Subpart C 15.247 & IC RSS 247 (DTS)

Test Report Serial No.: SSNT113-U2_Conducted Rev A

Issue Date: 9th August 2016

| Master Document Number | Addendum Reports |
|-------------------------------|-------------------------|
| SSNT113-U2_Master | SSNT113-U2_Conducted |
| | SSNT113-U2_Radiated |

Table of Contents

| | |
|---|-----------|
| 1. MEASUREMENT AND PRESENTATION OF TEST DATA | 3 |
| 2. TEST SUMMARY | 4 |
| 3. TEST RESULTS | 5 |
| 3.1. 6 dB & 99% Bandwidth | 5 |
| 3.2. Conducted Output Power | 7 |
| 3.3. Emissions | 10 |
| 3.3.1. <i>Conducted Emissions</i> | 10 |
| 3.3.1.1. Conducted Spurious Emissions | 10 |
| 3.3.1.2. Conducted Band-Edge Emissions | 12 |
| <i>Conducted Low Band-Edge Emissions</i> | 12 |
| <i>Conducted High Band-Edge Emissions</i> | 13 |
| 3.4. Power Spectral Density | 14 |
| A. APPENDIX - GRAPHICAL IMAGES | 16 |
| A.1. 6 dB & 99% Bandwidth | 17 |
| A.2. Conducted Output Power | 20 |
| A.3. Emissions | 23 |
| A.3.1. <i>Conducted Emissions</i> | 23 |
| A.3.1.1. Conducted Spurious Emissions | 23 |
| A.3.1.2. Conducted Band-Edge Emissions | 26 |
| <i>Conducted Low Band-Edge Emissions</i> | 26 |
| <i>Conducted High Band-Edge Emissions</i> | 27 |
| A.4. Power Spectral Density | 28 |

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

1. MEASUREMENT AND PRESENTATION OF TEST DATA

The measurement and graphical data presented in this test report was generated automatically using state-of-the-art technology creating an easy to read report structure. Numerical measurement data is separated from supporting graphical data (plots) through hyperlinks. Numerical measurement data can be reviewed without scrolling through numerous graphical pages to arrive at the next data matrix.

Plots have been relegated into the Appendix 'Graphical Data'.

Test and report automation was performed by [MiTest](#). [MiTest](#) is an automated test system developed by MiCOM Labs. [MiTest](#) is the first cloud based modular test system enabling end-to-end automation of regulatory compliance testing for conducted RF testing.



The MiCOM Labs "[MiTest](#)" Automated Test System" (Patent Pending)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

2. TEST SUMMARY

List of Measurements

| Test Header | Result | Data Link |
|--|----------|---------------------------|
| 15.247(a)(2) 6 dB & 99% Bandwidth | Complies | View Data |
| 15.247(b), 15.31(e) Conducted Output Power | Complies | View Data |
| (1) Conducted Emissions | Complies | - |
| (i) Conducted Spurious Emissions | Complies | View Data |
| (ii) Conducted Band-Edge Emissions | Complies | View Data |
| 15.247(e) Power Spectral Density | Complies | View Data |

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

3. TEST RESULTS

3.1. 6 dB & 99% Bandwidth

| Conducted Test Conditions for 6 dB and 99% Bandwidth | | | |
|--|--------------------------|----------------------------|-------------|
| Standard: | FCC CFR 47:15.247 | Ambient Temp. (°C): | 24.0 - 27.5 |
| Test Heading: | 6 dB and 99 % Bandwidth | Rel. Humidity (%): | 32 - 45 |
| Standard Section(s): | 15.247 (a)(2) | Pressure (mBars): | 999 - 1001 |
| Reference Document(s): | See Normative References | | |

Test Procedure for 6 dB and 99% Bandwidth Measurement

The bandwidth at 6 dB and 99 % was measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate center frequency.

Testing was performed under ambient conditions at nominal voltage. Where the device operated with multiple antenna ports i.e. MIMO device, each port was measured and reported.

Test configuration and setup used for the measurement was per the Conducted Test Set-up specified in this document.

Limits for 6 dB and 99% Bandwidth

(a) Operation under the provisions of this Section is limited to frequency hopping and digitally modulated intentional radiators that comply with the following provisions:

(2) Systems using digital modulation techniques may operate in the 902-928 MHz and 2400-2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Equipment Configuration for 6 dB & 99% Bandwidth

| | | | |
|--------------------------------|----------------|-----------------------------------|----------------|
| Variant: | DSSS | Duty Cycle (%): | 99 |
| Data Rate: | 250 kbps | Antenna Gain (dBi): | Not Applicable |
| Modulation: | OQPSK | Beam Forming Gain (Y)(dB): | Not Applicable |
| TPC: | Not Applicable | Tested By: | CC |
| Engineering Test Notes: | None | | |

Test Measurement Results

| Test Frequency | Measured 6 dB Bandwidth (MHz) | | | | 6 dB Bandwidth (MHz) | | Limit | Lowest Margin |
|----------------|-------------------------------|----|----|----|----------------------|--------|--------------|---------------|
| | Port(s) | | | | | | | |
| MHz | a | b | c | d | Highest | Lowest | KHz | MHz |
| 2405.0 | 1.583 | -- | -- | -- | 1.583 | 1.583 | \geq 500.0 | -1.08 |
| 2440.0 | 1.583 | -- | -- | -- | 1.583 | 1.583 | \geq 500.0 | -1.08 |
| 2480.0 | 1.583 | -- | -- | -- | 1.583 | 1.583 | \geq 500.0 | -1.08 |

| Test Frequency | Measured 99% Bandwidth (MHz) | | | | Maximum 99% Bandwidth (MHz) | | |
|----------------|------------------------------|----|----|----|-----------------------------|--|--|
| | Port(s) | | | | | | |
| MHz | a | b | c | d | | | |
| 2405.0 | 2.204 | -- | -- | -- | 2.204 | | |
| 2440.0 | 2.204 | -- | -- | -- | 2.204 | | |
| 2480.0 | 2.204 | -- | -- | -- | 2.204 | | |

Traceability to Industry Recognized Test Methodologies

| | |
|--------------------------|----------------------------------|
| Work Instruction: | WI-03 MEASURING RF SPECTRUM MASK |
| Measurement Uncertainty: | \pm 2.81 dB |

Note: click the links in the above matrix to view the graphical image (plot).

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

3.2. Conducted Output Power

| Conducted Test Conditions for Fundamental Emission Output Power | | | |
|---|--------------------------|----------------------------|-------------|
| Standard: | FCC CFR 47:15.247 | Ambient Temp. (°C): | 24.0 - 27.5 |
| Test Heading: | Output Power | Rel. Humidity (%): | 32 - 45 |
| Standard Section(s): | 15.247 (b) & (c) | Pressure (mBars): | 999 - 1001 |
| Reference Document(s): | See Normative References | | |

Test Procedure for Fundamental Emission Output Power Measurement

In the case of average power measurements an average power sensor was utilized.

For peak power measurements the spectrum analyzer built-in power function was used to integrate peak power over the 20 dB bandwidth.

Testing was performed under ambient conditions at nominal voltage only. Where the device operated with multiple antenna ports i.e. MIMO device, each port was measured, summed (Σ) and reported.

Test configuration and setup used for the measurement was per the Conducted Test Set-up specified in this document.
Supporting Information

Calculated Power = $A + G + Y + 10 \log(1/x)$ dBm

A = Total Power $[10^{\log(10)} (10^{a/10} + 10^{b/10} + 10^{c/10} + 10^{d/10})]$

G = Antenna Gain

Y = Beamforming Gain

x = Duty Cycle (average power measurements only)

Limits for Fundamental Emission Output Power

(b) The maximum peak conducted output power of the intentional radiator shall not exceed the following for non-frequency hopping systems:

(3) For systems using digital modulation in the 902-928 MHz and 2400-2483.5 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(c) Operation with directional antenna gains greater than 6 dBi.

(1) Fixed point-to-point operation:

(i) Systems operating in the 2400-2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

(iii) Fixed, point-to-point operation, as used in paragraphs (c)(1)(i) and (c)(1)(ii) of this section, excludes the use of point-to-multipoint systems, omnidirectional applications, and multiple co-located intentional radiators transmitting the same information. The operator of the spread spectrum or digitally modulated intentional radiator or, if the equipment is professionally installed, the installer is responsible for ensuring that the system is used exclusively for fixed, point-to-point

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

operations. The instruction manual furnished with the intentional radiator shall contain language in the installation instructions informing the operator and the installer of this responsibility.

(2) In addition to the provisions in paragraphs (b)(3), (b)(4) and (c)(1)(i) of this section, transmitters operating in the 2400-2483.5 MHz band that emit multiple directional beams, simultaneously or sequentially, for the purpose of directing signals to individual receivers or to groups of receivers provided the emissions comply with the following:

(i) Different information must be transmitted to each receiver.

(ii) If the transmitter employs an antenna system that emits multiple directional beams but does not do emit multiple directional beams simultaneously, the total output power conducted to the array or arrays that comprise the device, i.e., the sum of the power supplied to all antennas, antenna elements, staves, etc. and summed across all carriers or frequency channels, shall not exceed the limit specified in paragraph (b)(1) or (b)(3) of this section, as applicable. However, the total conducted output power shall be reduced by 1 dB below the specified limits for each 3 dB that the directional gain of the antenna/antenna array exceeds 6 dBi. The directional antenna gain shall be computed as follows:

(A) The directional gain shall be calculated as the sum of $10 \log$ (number of array elements or staves) plus the directional gain of the element or stave having the highest gain.

(B) A lower value for the directional gain than that calculated in paragraph (c)(2)(ii)(A) of this section will be accepted if sufficient evidence is presented, e.g., due to shading of the array or coherence loss in the beamforming.

(iii) If a transmitter employs an antenna that operates simultaneously on multiple directional beams using the same or different frequency channels, the power supplied to each emission beam is subject to the power limit specified in paragraph (c)(2)(ii) of this section. If transmitted beams overlap, the power shall be reduced to ensure that their aggregate power does not exceed the limit specified in paragraph (c)(2)(ii) of this section. In addition, the aggregate power transmitted simultaneously on all beams shall not exceed the limit specified in paragraph (c)(2)(ii) of this section by more than 8 dB.

(iv) Transmitters that emit a single directional beam shall operate under the provisions of paragraph (c)(1) of this section.



Title: Silver Spring Networks NIC 511-0303
To: FCC 15.247 & RSS 247 (DTS)
Serial #: SSNT113-U2_Conducted Rev A
Issue Date: 9th August 2016
Page: 9 of 31

Equipment Configuration for Peak Output Power

| | | | |
|--------------------------------|----------------|-----------------------------------|----------------|
| Variant: | DSSS | Duty Cycle (%): | 99 |
| Data Rate: | 250 kbps | Antenna Gain (dBi): | Not Applicable |
| Modulation: | OQPSK | Beam Forming Gain (Y)(dB): | Not Applicable |
| TPC: | Not Applicable | Tested By: | CC |
| Engineering Test Notes: | None | | |

Test Measurement Results

| Test Frequency | Measured Output Power (dBm) | | | | Calculated Total Power Σ Port(s) | Limit | Margin |
|----------------|-----------------------------|----|----|----|---|-------|--------|
| | Port(s) | | | | | | |
| MHz | a | b | c | d | dBm | dBm | dBm |
| 2405.0 | 27.37 | -- | -- | -- | 27.37 | 30.00 | -2.63 |
| 2440.0 | 26.92 | -- | -- | -- | 26.92 | 30.00 | -3.08 |
| 2480.0 | 6.53 | -- | -- | -- | 6.53 | 30.00 | -23.47 |

Traceability to Industry Recognized Test Methodologies

| | |
|--------------------------|---------------------------------|
| Work Instruction: | WI-01 MEASURING RF OUTPUT POWER |
| Measurement Uncertainty: | ±1.33 dB |

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

3.3. Emissions

3.3.1. Conducted Emissions

3.3.1.1. Conducted Spurious Emissions

| Conducted Test Conditions for Transmitter Conducted Spurious and Band-Edge Emissions | | | |
|--|------------------------------|----------------------------|-------------|
| Standard: | FCC CFR 47:15.247 | Ambient Temp. (°C): | 24.0 - 27.5 |
| Test Heading: | Max Unwanted Emission Levels | Rel. Humidity (%): | 32 - 45 |
| Standard Section(s): | 15.247 (d) | Pressure (mBars): | 999 - 1001 |
| Reference Document(s): | See Normative References | | |

Test Procedure for Transmitter Conducted Spurious and Band-Edge Emissions Measurement

Transmitter Conducted Spurious and Band-Edge emissions were measured at a limit of 30 dBc (average detector) or 20 dBc (peak detector) below the highest in-band spectral density measured with a spectrum analyzer connected to the antenna terminal. Measurements were made while EUT was operating in transmit mode of operation at the appropriate centre frequency closest to the band-edge. Emissions were maximized during the measurement and limits derived from the peak spectral power and drawn on each plot.

Where the device operated with multiple antenna ports i.e. MIMO device, each port was measured separately. Testing was performed under ambient conditions at nominal voltage only.

Test configuration and setup used for the measurement was per the Conducted Test Set-up specified in this document.

Limits Transmitter Conducted Spurious and Band-Edge Emissions

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).



Title: Silver Spring Networks NIC 511-0303
To: FCC 15.247 & RSS 247 (DTS)
Serial #: SSNT113-U2_Conducted Rev A
Issue Date: 9th August 2016
Page: 11 of 31

Equipment Configuration for Transmitter Conducted Spurious Emissions

| | | | |
|--------------------------------|----------------|-------------------------------|----------------|
| Variant: | DSSS | Duty Cycle (%): | 99 |
| Data Rate: | 250 kbps | Antenna Gain (dBi): | Not Applicable |
| Modulation: | OQPSK | Beam Forming Gain (Y): | Not Applicable |
| TPC: | Not Applicable | Tested By: | CC |
| Engineering Test Notes: | None | | |

Test Measurement Results

| Test Frequency | Frequency Range | Transmitter Conducted Spurious Emissions (dBm) | | | | | | | |
|----------------|-----------------|--|--------|--------|-------|--------|-------|--------|-------|
| | | Port a | | Port b | | Port c | | Port d | |
| MHz | MHz | SE | Limit | SE | Limit | SE | Limit | SE | Limit |
| 2405.0 | 30.0 - 26000.0 | -42.961 | 0.09 | -- | -- | -- | -- | -- | -- |
| 2440.0 | 30.0 - 26000.0 | -42.749 | -0.97 | -- | -- | -- | -- | -- | -- |
| 2480.0 | 30.0 - 26000.0 | -50.453 | -21.00 | -- | -- | -- | -- | -- | -- |

Traceability to Industry Recognized Test Methodologies

| | |
|--------------------------|---|
| Work Instruction: | WI-05 MEASUREMENT OF SPURIOUS EMISSIONS |
| Measurement Uncertainty: | <=40 GHz ±2.37 dB, > 40 GHz ±4.6 dB |

Note: click the links in the above matrix to view the graphical image (plot).

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

3.3.1.2. Conducted Band-Edge Emissions

Conducted Low Band-Edge Emissions

Equipment Configuration for Conducted Low Band-Edge Emissions - Peak

| | | | |
|--------------------------------|----------------|-----------------------------------|----------------|
| Variant: | DSSS | Duty Cycle (%): | 99.0 |
| Data Rate: | 250 kbps | Antenna Gain (dBi): | Not Applicable |
| Modulation: | OQPSK | Beam Forming Gain (Y)(dB): | Not Applicable |
| TPC: | Not Applicable | Tested By: | CC |
| Engineering Test Notes: | None | | |

Test Measurement Results

| | | | | | |
|------------------------------|------------------------------------|-------------------------|---------------------------|------------------------|----------------------------|
| Channel Frequency: | 2405.0 MHz | | | | |
| Band-Edge Frequency: | 2400.0 MHz | | | | |
| Test Frequency Range: | 2350.0 - 2422.0 MHz | | | | |
| Port(s) | Band-Edge Markers and Limit | | | Revised Limit | |
| | M1 Amplitude (dBm) | Plot Limit (dBm) | M2 Frequency (MHz) | Amplitude (dBm) | M2A Frequency (MHz) |
| a | -35.20 | 0.00 | 2403.50 | -- | -- |
| | | | | | (MHz) |

Traceability to Industry Recognized Test Methodologies

| | | | |
|--------------------------|---|--|--|
| Work Instruction: | WI-05 MEASUREMENT OF SPURIOUS EMISSIONS | | |
| Measurement Uncertainty: | <=40 GHz ±2.37 dB, > 40 GHz ±4.6 dB | | |

Note: click the links in the above matrix to view the graphical image (plot).



Title: Silver Spring Networks NIC 511-0303
To: FCC 15.247 & RSS 247 (DTS)
Serial #: SSNT113-U2_Conducted Rev A
Issue Date: 9th August 2016
Page: 13 of 31

Conducted High Band-Edge Emissions

Equipment Configuration for Conducted High Band-Edge Emissions - Peak

| | | | |
|--------------------------------|----------------|-----------------------------------|----------------|
| Variant: | DSSS | Duty Cycle (%): | 99.0 |
| Data Rate: | 250 kbps | Antenna Gain (dBi): | Not Applicable |
| Modulation: | OQPSK | Beam Forming Gain (Y)(dB): | Not Applicable |
| TPC: | Not Applicable | Tested By: | CC |
| Engineering Test Notes: | None | | |

Test Measurement Results

| Channel Frequency: | 2480.0 MHz | | | | |
|------------------------------|------------------------------------|-------------------------|---------------------------|------------------------|----------------------------|
| Band-Edge Frequency: | 2483.5 MHz | | | | |
| Test Frequency Range: | 2452.0 - 2524.0 MHz | | | | |
| Port(s) | Band-Edge Markers and Limit | | | Revised Limit | Margin |
| | M3 Amplitude (dBm) | Plot Limit (dBm) | M2 Frequency (MHz) | Amplitude (dBm) | M2A Frequency (MHz) |
| a | -47.69 | -20.00 | 2481.30 | -- | -- |
| | | | | | -2.200 |

Traceability to Industry Recognized Test Methodologies

| | |
|--------------------------|---|
| Work Instruction: | WI-05 MEASUREMENT OF SPURIOUS EMISSIONS |
| Measurement Uncertainty: | <=40 GHz ±2.37 dB, > 40 GHz ±4.6 dB |

Note: click the links in the above matrix to view the graphical image (plot).

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

3.4. Power Spectral Density

| Conducted Test Conditions for Power Spectral Density | | | |
|--|--------------------------|----------------------------|-------------|
| Standard: | FCC CFR 47:15.247 | Ambient Temp. (°C): | 24.0 - 27.5 |
| Test Heading: | Power Spectral Density | Rel. Humidity (%): | 32 - 45 |
| Standard Section(s): | 15.247 (e) | Pressure (mBars): | 999 - 1001 |
| Reference Document(s): | See Normative References | | |

Test Procedure for Power Spectral Density

The transmitter output was connected to a spectrum analyzer and the measured made in a 3 kHz resolution bandwidth using the analyzer auto-coupled sweep-time. A peak value was found over the full emission bandwidth and the spectrum downloaded for post processing purposes.

Where the device operated with multiple antenna ports i.e. MIMO device, each port was measured separately. The Peak Power Spectral Density is the highest level found across the emission bandwidth. With multiple antenna port measurements the numerical analyzer data from each port is summed (à) and a link to this additional graphic is provided.

Testing was performed under ambient conditions at nominal voltage only.

Test configuration and setup used for the measurement was per the Conducted Test Set-up specified in this document.

Measure and sum the spectra across the outputs. With this technique, spectra are measured at each output of the device at the required resolution bandwidth. The individual spectra are then summed mathematically in linear power units. Unlike in-band power measurements, in which the sum involves a single measured value (output power) from each output, measurements for compliance with PSD limits involve summing entire spectra across corresponding frequency bins on the various outputs. Consistency is maintained for any device with multiple transmitter outputs to be certain the individual outputs are all aligned with the same span and same number of points. In this instance, the linear power spectrum value within the first spectral bin of output 0 is summed with that in the first spectral bin of output 1, and the first spectral bin of output 2, and so on up to the Nth output to obtain the true value for the first frequency bin of the summed spectrum. The summed spectrum value for each frequency bin is computed in this fashion. These summed spectral values were post processed and the resulting numerical and graphical data presented.

NOTE:

It may be observed that the spectrum in some antenna port plots break the limit line however this in itself does NOT constitute a failure. In all cases a spectrum summation plot is provided in order to prove compliance. A failure occurs only after the summation of all spectrum plots have been summed and are found to be greater than the limit line.

Supporting Information

Calculated Power = $A + 10 \log (1/x)$ dBm

$A = \text{Total Power Spectral Density} [10 \log_{10} (10^{a/10} + 10^{b/10} + 10^{c/10} + 10^{d/10})]$

$x = \text{Duty Cycle}$

Limits Power Spectral Density

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than +8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.



Title: Silver Spring Networks NIC 511-0303
To: FCC 15.247 & RSS 247 (DTS)
Serial #: SSNT113-U2_Conducted Rev A
Issue Date: 9th August 2016
Page: 15 of 31

Equipment Configuration for Power Spectral Density - Peak

| | | | |
|--------------------------------|----------------|-----------------------------------|----------------|
| Variant: | DSSS | Duty Cycle (%): | 99.0 |
| Data Rate: | 250 kbps | Antenna Gain (dBi): | 5.00 |
| Modulation: | OQPSK | Beam Forming Gain (Y)(dB): | Not Applicable |
| TPC: | Not Applicable | Tested By: | CC |
| Engineering Test Notes: | None | | |

Test Measurement Results

| Test Frequency | Measured Power Spectral Density | | | | Amplitude Summation | Limit | Margin |
|----------------|---------------------------------|----|----|----|-------------------------|----------|--------|
| | Port(s) (dBm/3KHz) | | | | | | |
| MHz | a | b | c | d | dBm/3KHz | dBm/3KHz | dB |
| 2405.0 | 7.675 | -- | -- | -- | 7.675 | 8.0 | -0.3 |
| 2440.0 | 7.569 | -- | -- | -- | 7.569 | 8.0 | -0.4 |
| 2480.0 | -14.042 | -- | -- | -- | -14.042 | 8.0 | -22.0 |

Traceability to Industry Recognized Test Methodologies

| | |
|--------------------------|----------------------------------|
| Work Instruction: | WI-03 MEASURING RF SPECTRUM MASK |
| Measurement Uncertainty: | ±2.81 dB |


Note: click the links in the above matrix to view the graphical image (plot).

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

A. APPENDIX - GRAPHICAL IMAGES

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.


A.1. 6 dB & 99% Bandwidth



| Analyzer Setup | Marker:Frequency:Amplitude | Test Results |
|---|---|--|
| Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD | M1 : 2404.168 MHz : 8.730 dBm M2 : 2405.431 MHz : 15.622 dBm Delta1 : 1.583 MHz : 1.403 dB T1 : 2403.888 MHz : 2.562 dBm T2 : 2406.092 MHz : 2.432 dBm OBW : 2.204 MHz | Measured 6 dB Bandwidth: 1.583 MHz Limit: \geq 500.0 kHz Margin: -1.08 MHz |

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



| Analyzer Setup | Marker:Frequency:Amplitude | Test Results |
|---|---|--|
| Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD | M1 : 2439.168 MHz : 8.728 dBm M2 : 2440.431 MHz : 15.604 dBm Delta1 : 1.583 MHz : 1.316 dB T1 : 2438.888 MHz : 2.596 dBm T2 : 2441.092 MHz : 2.452 dBm OBW : 2.204 MHz | Measured 6 dB Bandwidth: 1.583 MHz Limit: ≥ 500.0 kHz Margin: -1.08 MHz |

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




| Analyzer Setup | Marker:Frequency:Amplitude | Test Results |
|---|--|--|
| Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD | M1 : 2479.168 MHz : -6.954 dBm M2 : 2480.451 MHz : -0.188 dBm Delta1 : 1.583 MHz : 1.241 dB T1 : 2478.888 MHz : -13.064 dBm T2 : 2481.092 MHz : -13.326 dBm OBW : 2.204 MHz | Measured 6 dB Bandwidth: 1.583 MHz Limit: \geq 500.0 kHz Margin: -1.08 MHz |

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.


A.2. Conducted Output Power



| Analyzer Setup | Marker:Frequency:Amplitude | Test Results |
|---|--|--|
| Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW | M1 : 2402.886 MHz : 4.897 dBm M2 : 2404.509 MHz : 24.907 dBm Delta1 : 4.208 MHz : 0.551 dB | Channel Power: 27.37 dBm Limit: 30.00 dBm Margin: -2.63 dB |

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



| Analyzer Setup | Marker:Frequency:Amplitude | Test Results |
|---|--|--|
| Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW | M1 : 2437.886 MHz : 4.393 dBm M2 : 2439.489 MHz : 24.474 dBm Delta1 : 4.208 MHz : 0.612 dB | Channel Power: 26.92 dBm Limit: 30.00 dBm Margin: -3.08 dB |

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



| Analyzer Setup | Marker:Frequency:Amplitude | Test Results |
|---|---|--|
| Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW | M1 : 2477.906 MHz : -16.075 dBm M2 : 2479.529 MHz : 4.108 dBm Delta1 : 4.188 MHz : 0.895 dB | Channel Power: 6.53 dBm Limit: 30.00 dBm Margin: -23.47 dB |


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

A.3. Emissions

A.3.1. Conducted Emissions

A.3.1.1. Conducted Spurious Emissions




| Analyzer Setup | Marker:Frequency:Amplitude | Test Results |
|---|---|--------------------------------------|
| Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW | M1 : 2371.984 MHz : 20.087 dBm M2 : 22.565 GHz : -42.961 dBm | Limit: 0.09 dBm Margin: -43.05 dB |

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

CONDUCTED SPURIOUS EMISSIONS - PEAK

Variant: DSSS, Channel: 2440.00 MHz, Chain a, Temp: 20, Voltage: 4 Vdc




| Analyzer Setup | Marker:Frequency:Amplitude | Test Results |
|---|---|---------------------------------------|
| Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW | M1 : 2424.028 MHz : 19.026 dBm M2 : 22.045 GHz : -42.749 dBm | Limit: -0.97 dBm Margin: -41.78 dB |

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

CONDUCTED SPURIOUS EMISSIONS - PEAK

Variant: DSSS, Channel: 2480.00 MHz, Chain a, Temp: 20, Voltage: 4 Vdc




| Analyzer Setup | Marker:Frequency:Amplitude | Test Results |
|---|---|--|
| Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW | M1 : 2476.072 MHz : -1.916 dBm M2 : 6951.864 MHz : -50.453 dBm | Limit: -21.00 dBm Margin: -29.45 dB |

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

A.3.1.2. Conducted Band-Edge Emissions

Conducted Low Band-Edge Emissions



| Analyzer Setup | Marker:Frequency:Amplitude | Test Results |
|---|---|--------------------------------|
| Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW | M1 : 2400.000 MHz : -35.201 dBm M2 : 2403.531 MHz : -5.854 dBm M3 : 2404.541 MHz : 20.814 dBm | Channel Frequency: 2405.00 MHz |

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

Conducted High Band-Edge Emissions



CONDUCTED HIGH BAND-EDGE EMISSION - PEAK

Variant: DSSS, Channel: 2480.00 MHz, Chain a, Temp: 20, Voltage: 4 Vdc




| Analyzer Setup | Marker:Frequency:Amplitude | Test Results |
|---|--|--------------------------------|
| Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW | M1 : 2480.425 MHz : -0.390 dBm M2 : 2481.291 MHz : -17.361 dBm M3 : 2483.500 MHz : -47.686 dBm | Channel Frequency: 2480.00 MHz |

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

A.4. Power Spectral Density




| Analyzer Setup | Marker:Frequency:Amplitude | Test Results |
|---|-------------------------------|--|
| Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW | M1 : 2405.083 MHz : 7.675 dBm | Limit: ≤ 8.000 dBm Margin: -0.33 dB |

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

POWER SPECTRAL DENSITY - PEAK

Variant: DSSS, Channel: 2440.00 MHz, Chain a, Temp: 20, Voltage: 4 Vdc




| Analyzer Setup | Marker:Frequency:Amplitude | Test Results |
|---|-------------------------------|--|
| Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW | M1 : 2439.572 MHz : 7.569 dBm | Limit: ≤ 8.000 dBm Margin: -0.43 dB |

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

POWER SPECTRAL DENSITY - PEAK
 Variant: DSSS, Channel: 2480.00 MHz, Chain a, Temp: 20, Voltage: 4 Vdc



| Analyzer Setup | Marker:Frequency:Amplitude | Test Results |
|---|---------------------------------|--|
| Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW | M1 : 2480.564 MHz : -14.042 dBm | Limit: ≤ 8.000 dBm Margin: 22.04 dB |

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



575 Boulder Court
Pleasanton, California 94566, USA
Tel: +1 (925) 462 0304
Fax: +1 (925) 462 0306
www.micomlabs.com