

FCC §1.1307 (b) (1) & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE(MPE)**Applicable Standard**

According to subpart 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

MPE Calculated :

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

MPE Results

Tune-Up Power Including Tolerance:

Mode	Frequency band (MHz)	Antenna Gain		Max Tune-up Power (dBm)	Cable loss (dB)	Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)					
uplink	698-716	5	3.16	19.0	1.2	20	0.038	0.465
	776-787	5	3.16	20.0	1.2	20	0.048	0.517
	824-849	6	3.98	20.0	1.2	20	0.060	0.549
downlink	728-746	6	3.98	14.0	5.2	20	0.006	0.485
	746-757	6	3.98	14.0	5.3	20	0.006	0.497
	869-894	6	3.98	14.0	5.3	20	0.006	0.579

This EUT contains FCC ID: 2AC7Z-ESP32WROVERB, and the power density is
 Wi-Fi=0.1182mW/cm²,
 BLE=0.0007 mW/cm²,
 Bluetooth =0.0017 mW/cm²,

According to the MPE of FCC ID: 2AC7Z-ESP32WROVERB, Wi-Fi and Bluetooth can't transmit simultaneously, so consider the booster and Wi-Fi transmitting simultaneously is the worst case:
 The ratio= MPE/Limit_{Booster}+ MPE/Limit_{WIFI}=0.060/0.549+0.1182/1=0.2275<1.0

The maximum power density was calculated base on the maximum value of antenna gain and cable loss combination.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliance