



FCC RADIO TEST REPORT

FCC ID: OX6VB736

Product : Tablet PC

Trade Name : ViewSonic

Model Name : VB736

Serial Model : N/A

Report No. : NTEK- 2012NT0829744F

Prepared for

ViewMate Electronic Technology Limited

6F, BuildingL,SectionE,Block71, Baoan District, Shenzhen, China

Prepared by

NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community,Xixiang Street
Bao'an District, Shenzhen P.R. China

Tel.: +86-0755-61156588 Fax.: +86-0755-61156599

Website:www.ntek.org.cn

TEST RESULT CERTIFICATION

Applicant's name : ViewMate Electronic Technology Limited
Address : 6F, BuildingL,SectionE,Block71, Baoan District, Shenzhen, China
Manufacture's Name..... : ViewMate Electronic Technology Limited
Address : 6F, BuildingL,SectionE,Block71, Baoan District, Shenzhen, China

Product description

Product name : Tablet PC
Model and/or type reference : VB736
Serial Model : N/A

Standards : FCC Part15.247

Test procedure..... ANSI C63.4-2003

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personal only, and shall be noted in the revision of the document.

Date of Test.....:

Date (s) of performance of tests : 29 Aug. 2012 ~8 Sep. 2012

Date of Issue..... : 8 Sep. 2012

Test Result..... : **Pass**

Testing Engineer : Apple Huang
 (Apple Huang)

Technical Manager : Tom Zhang
 (Tom Zhang)

Authorized Signatory : Bovey Yang
 (Bovey Yang)

Table of Contents

	Page
1 . SUMMARY OF TEST RESULTS	5
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	6
2 . GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	9
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	11
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	12
3 . EMC EMISSION TEST	13
3.1 CONDUCTED EMISSION MEASUREMENT	13
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	13
3.1.2 TEST PROCEDURE	14
3.1.3 DEVIATION FROM TEST STANDARD	14
3.1.4 TEST SETUP	14
3.1.5 EUT OPERATING CONDITIONS	14
3.1.6 TEST RESULTS	15
3.2 RADIATED EMISSION MEASUREMENT	17
3.2.1 RADIATED EMISSION LIMITS	17
3.2.2 TEST PROCEDURE	18
3.2.3 DEVIATION FROM TEST STANDARD	18
3.2.4 TEST SETUP	19
3.2.5 EUT OPERATING CONDITIONS	20
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)	21
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	22
3.2.8 TEST RESULTS (ABOVE 1000 MHZ)	24
4 . POWER SPECTRAL DENSITY TEST	54
4.1 APPLIED PROCEDURES / LIMIT	54
4.1.1 TEST PROCEDURE	54
4.1.2 DEVIATION FROM STANDARD	54
4.1.3 TEST SETUP	54
4.1.4 EUT OPERATION CONDITIONS	54
4.1.5 TEST RESULTS	55
5 . BANDWIDTH TEST	61
5.1 APPLIED PROCEDURES / LIMIT	61
5.1.1 TEST PROCEDURE	61

Table of Contents

	Page
5.1.2 DEVIATION FROM STANDARD	61
5.1.3 TEST SETUP	61
5.1.4 EUT OPERATION CONDITIONS	61
5.1.5 TEST RESULTS	62
6 . PEAK OUTPUT POWER TEST	68
6.1 APPLIED PROCEDURES / LIMIT	68
6.1.1 TEST PROCEDURE	68
6.1.2 DEVIATION FROM STANDARD	68
6.1.3 TEST SETUP	68
6.1.4 EUT OPERATION CONDITIONS	68
6.1.5 TEST RESULTS	69
7 . ANTENNA REQUIREMENT	70
7.1 STANDARD REQUIREMENT	70
7.2 EUT ANTENNA	70
8 . EUT TEST PHOTO	71
APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b)	Peak Output Power	PASS	
15.247 (c)	Radiated Spurious Emission	PASS	
15.247 (d)	Power Spectral Density	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

1.1 TEST FACILITY

NTEK Testing Technology Co., Ltd

Add. : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.

FCC Registration No.:238937; IC Registration No.:9270A-1

CNAS Registration No.:L5516

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %** .

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power,conducted	$\pm 0.16\text{dB}$
3	Spurious emissions,conducted	$\pm 0.21\text{dB}$
4	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Tablet PC																
Trade Name	ViewSonic																
Model Name	VB736																
Serial Model	N/A																
Model Difference	N/A																
Product Description	The EUT is a Tablet PC <table> <tr> <td>Operation Frequency:</td><td>2412~2462 MHz</td></tr> <tr> <td>Modulation Type:</td><td>CCK/OFDM/DBPSK/DAPSK</td></tr> <tr> <td>Bit Rate of Transmitter</td><td>802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6 Mbps 802.11n:150/144.44/130/117/115.56/104/86.67/78/52/6.5 Mbps</td></tr> <tr> <td>Number Of Channel</td><td>11 CH, Please see Note 2.</td></tr> <tr> <td>Antenna Designation:</td><td>Please see Note 3.</td></tr> <tr> <td>Output Power(Conducted):</td><td>802.11b: 17.87 dBm (Max.) 802.11g: 16.79 dBm (Max.) 802.11n: 15.86 dBm (Max.)</td></tr> <tr> <td>Antenna Gain (dBi)</td><td>2.0 dBi</td></tr> <tr> <td>EIRP</td><td>802.11b: 17.87 dBm (Max.) 802.11g: 16.79 dBm (Max.) 802.11n: 15.86 dBm (Max.)</td></tr> </table> Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.	Operation Frequency:	2412~2462 MHz	Modulation Type:	CCK/OFDM/DBPSK/DAPSK	Bit Rate of Transmitter	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6 Mbps 802.11n:150/144.44/130/117/115.56/104/86.67/78/52/6.5 Mbps	Number Of Channel	11 CH, Please see Note 2.	Antenna Designation:	Please see Note 3.	Output Power(Conducted):	802.11b: 17.87 dBm (Max.) 802.11g: 16.79 dBm (Max.) 802.11n: 15.86 dBm (Max.)	Antenna Gain (dBi)	2.0 dBi	EIRP	802.11b: 17.87 dBm (Max.) 802.11g: 16.79 dBm (Max.) 802.11n: 15.86 dBm (Max.)
Operation Frequency:	2412~2462 MHz																
Modulation Type:	CCK/OFDM/DBPSK/DAPSK																
Bit Rate of Transmitter	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6 Mbps 802.11n:150/144.44/130/117/115.56/104/86.67/78/52/6.5 Mbps																
Number Of Channel	11 CH, Please see Note 2.																
Antenna Designation:	Please see Note 3.																
Output Power(Conducted):	802.11b: 17.87 dBm (Max.) 802.11g: 16.79 dBm (Max.) 802.11n: 15.86 dBm (Max.)																
Antenna Gain (dBi)	2.0 dBi																
EIRP	802.11b: 17.87 dBm (Max.) 802.11g: 16.79 dBm (Max.) 802.11n: 15.86 dBm (Max.)																
Channel List	Please refer to the Note 2.																
Power	DC 5V(USB) from PC																
Battery	Rated Voltage: 3.7V Charge Limit: 4.2V																
Connecting I/O Port(s)	Please refer to the User's Manual																

Note

:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

Channel List for 802.11b/g/n(20MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

3.

Table for Filed Antenna

Ant .	Brand	Model Name	Antenna Type	Connect or	Gain (dBi)	NOTE
A	N/A	N/A	FPCB antenna	N/A	2.0	N/A

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n CH1/ CH6/ CH11
Mode 4	Charge Mode

For Conducted Emission	
Final Test Mode	Description
Mode 4	Charge Mode


For Radiated Emission	
Final Test Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n CH1/ CH6/ CH11

Note:


- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission Test



Radiated Spurious Emission Test



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Tablet PC	N/S	VB736	N/A	EUT
E-2	Adapter	N/A	LA-520W	N/A	
E-3	Earphone	N/A	N/A	N/A	

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	0.8M	
C-2	NO	NO	0.8M	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	Agilent	E4407B	160400005	Jul. 06. 2013
2	Test Receiver	R&S	ESPI	101318	Jul. 06. 2013
3	Bilog Antenna	TESEQ	CBL6111D	31216	Jul. 06. 2013
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	Jul. 06. 2013
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	Jul. 06. 2013
6	Horn Antenna	EM	EM-AH-10180	2011071402	Jul. 06. 2013
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	Jul. 06. 2013
8	Amplifier	EM	EM-30180	060538	Jul. 06. 2013
9	Loop Antenna	ARA	PLA-1030/B	1029	Jul. 06. 2013
10	Power Meter	R&S	NRVS	100696	Jul. 06. 2013

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Test Receiver	R&S	ESCI	101160	Jul. 06. 2013
2	LISN	R&S	ENV216	101313	Jul. 06. 2013
3	LISN	EMCO	3816/2	00042990	Jul. 06. 2013
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	Jul. 06. 2013
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	Jul. 06. 2013
6	Absorbing clamp	R&S	MOS-21	100423	Jul. 06. 2013

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.


3.1.6 TEST RESULTS

EUT :	Tablet PC	Model Name. :	VB736
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 5.0V from Adapter AC 120V/60Hz	Test Mode :	Mode 4

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.2977	16.36	9.64	26	50.3	-24.3	AVG
0.3059	29.08	9.64	38.72	60.08	-21.36	QP
1.11	12.43	9.63	22.06	46	-23.94	AVG
1.1698	27.17	9.63	36.8	56	-19.2	QP
5.4579	11.88	9.69	21.57	50	-28.43	AVG
6.1337	27.29	9.71	37	60	-23	QP

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Tablet PC	Model Name. :	VB736
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 5.0V from Adapter AC 120V/60Hz	Test Mode :	Mode 4

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV)	Limits (dBμV)	Margin (dB)	Detector Type
0.2419	31.78	9.64	41.42	62.03	-20.61	QP
0.27	24.17	9.64	33.81	51.12	-17.31	AVG
1.2298	31.82	9.63	41.45	56	-14.55	QP
1.578	18.85	9.64	28.49	46	-17.51	AVG
5.7019	31.52	9.7	41.22	60	-18.78	QP
5.8258	20.68	9.71	30.39	50	-19.61	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class A (dBuV/m) (at 3M)		Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE	PEAK	AVERAGE
Above 1000	80	60	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz

**3.2.5 EUT OPERATING CONDITIONS**

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)

EUT:	Tablet PC	Model Name. :	VB736
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $20 \log (\text{specific distance/test distance})(\text{dB})$;

Limit line = specific limits(dBuv) + distance extrapolation factor.


3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)

EUT :	Tablet PC	Model Name :	VB736
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
66.0341	19.16	5.42	24.58	40	-15.42	QP
131.7576	23.48	11.94	35.42	40	-4.58	QP
219.8448	22.36	9.85	32.21	40	-7.79	QP

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Tablet PC	Model Name :	VB736
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
51.3004	12.82	7.56	20.38	40	-19.62	QP
126.7723	16.79	11.91	28.7	40	-11.3	QP
215.2677	23.73	9.46	33.19	40	-6.81	QP

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




3.2.8 TEST RESULTS (ABOVE 1000 MHZ)

EUT :	Tablet PC	Model Name :	VB736
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH1 (802.11b Mode)	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4824.152	52.09	10.44	62.53	74	-11.47	peak
4824.152	32.97	10.44	43.41	54	-10.59	AVG
7236.242	44.88	12.39	57.27	74	-16.73	peak
7236.242	30	12.39	42.39	54	-11.61	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Tablet PC	Model Name :	VB736
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH1 (802.11b Mode)	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4874.23	51.85	10.4	62.25	74	-11.75	peak
4874.23	33.12	10.4	43.52	54	-10.48	AVG
7311.341	42.02	12.75	54.77	74	-19.23	peak
7311.341	30.14	12.75	42.89	54	-11.11	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Tablet PC	Model Name :	VB736
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH6 (802.11b Mode)	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4874.382	49.93	10.4	60.33	74	-13.67	peak
4874.382	33.07	10.4	43.47	54	-10.53	AVG
7311.214	43.45	12.75	56.2	74	-17.8	peak
7311.214	29.52	12.75	42.27	54	-11.73	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Tablet PC	Model Name :	VB736
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH6 (802.11b Mode)	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4924.127	51.03	10.39	61.42	74	-12.58	peak
4934.127	32.43	10.44	42.87	54	-11.13	AVG
7386.219	43.59	12.68	56.27	74	-17.73	peak
7386.219	30.65	12.68	43.33	54	-10.67	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Tablet PC	Model Name :	VB736
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH11 (802.11b Mode)	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4924.457	51.05	10.39	61.44	74	-12.56	peak
4924.457	33.48	10.39	43.87	54	-10.13	AVG
7386.262	41.49	12.68	54.17	74	-19.83	peak
7386.262	28.68	12.68	41.36	54	-12.64	AVG

Remark:

- Factor = Antenna Factor + Cable Loss – Pre-amplifier.
- No emission detected above 18GHz




EUT :	Tablet PC	Model Name :	VB736
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH11 (802.11b Mode)	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4924.274	50.99	10.39	61.38	74	-12.62	peak
4924.274	32.1	10.39	42.49	54	-11.51	AVG
7386.338	42.14	12.68	54.82	74	-19.18	peak
7386.338	27.64	12.68	40.32	54	-13.68	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Tablet PC	Model Name :	VB736
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH1 (802.11g Mode)	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4824.418	47.92	10.44	58.36	74	-15.64	peak
4824.418	31.7	10.44	42.14	54	-11.86	AVG
7236.235	41.38	12.39	53.77	74	-20.23	peak
7236.235	27.72	12.39	40.11	54	-13.89	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Tablet PC	Model Name :	VB736
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH1 (802.11g Mode)	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4824.141	47.93	10.44	58.37	74	-15.63	peak
4824.141	31.08	10.44	41.52	54	-12.48	AVG
7236.218	42.26	12.39	54.65	74	-19.35	peak
7236.218	27.94	12.39	40.33	54	-13.67	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Tablet PC	Model Name :	VB736
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH6 (802.11g Mode)	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4874.385	50.42	10.4	60.82	74	-13.18	peak
4874.385	32.81	10.4	43.21	54	-10.79	AVG
7311.244	42.67	12.75	55.42	74	-18.58	peak
7311.244	28.93	12.75	41.68	54	-12.32	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Tablet PC	Model Name :	VB736
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH6 (802.11g Mode)	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4874.268	49.83	10.4	60.23	74	-13.77	peak
4874.268	31.77	10.4	42.17	54	-11.83	AVG
7311.482	42.55	12.75	55.3	74	-18.7	peak
7311.482	28.81	12.75	41.56	54	-12.44	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Tablet PC	Model Name :	VB736
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH11 (802.11g Mode)	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4924.374	49.43	10.39	59.82	74	-14.18	peak
4924.374	32.02	10.39	42.41	54	-11.59	AVG
7386.322	41.69	12.68	54.37	74	-19.63	peak
7386.322	29.8	12.68	42.48	54	-11.52	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Tablet PC	Model Name :	VB736
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH11(802.11g Mode)	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4924.369	50.09	10.39	60.48	74	-13.52	peak
4924.369	33.24	10.39	43.63	54	-10.37	AVG
7386.118	43.11	12.68	55.79	74	-18.21	peak
7386.118	31.15	12.68	43.83	54	-10.17	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Tablet PC	Model Name :	VB736
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH1 (802.11n Mode)	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4824.132	49.27	10.44	59.71	74	-14.29	peak
4824.132	32.97	10.44	43.41	54	-10.59	AVG
7236.249	43.44	12.39	55.83	74	-18.17	peak
7236.249	30.03	12.39	42.42	54	-11.58	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Tablet PC	Model Name :	VB736
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH1 (802.11n Mode)	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4824.326	49.79	10.44	60.23	74	-13.77	peak
4824.326	32.96	10.44	43.4	54	-10.6	AVG
7236.442	42.87	12.39	55.26	74	-18.74	peak
7236.442	29.86	12.39	42.25	54	-11.75	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Tablet PC	Model Name :	VB736
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH6 (802.11n Mode)	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4874.338	30.92	10.4	41.32	54	-12.68	AVG
4874.388	49.08	10.4	59.48	74	-14.52	peak
7311.247	44.02	12.75	56.77	74	-17.23	peak
7311.247	27.44	12.75	40.19	54	-13.81	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Tablet PC	Model Name :	VB736
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH6 (802.11n Mode)	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4874.136	48.26	10.4	58.66	74	-15.34	peak
4874.136	32.17	10.4	42.57	54	-11.43	AVG
7311.272	40.73	12.75	53.48	74	-20.52	peak
7311.272	26.74	12.75	39.49	54	-14.51	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Tablet PC	Model Name :	VB736
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH11 (802.11n Mode)	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4924.258	48.06	10.39	58.45	74	-15.55	peak
4924.258	32.23	10.39	42.62	54	-11.38	AVG
7386.23	41.56	12.68	54.24	74	-19.76	peak
7386.23	28.07	12.68	40.75	54	-13.25	AVG

Remark:

3. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

4. No emission detected above 18GHz




EUT :	Tablet PC	Model Name :	VB736
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH11 (802.11n Mode)	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4924.356	48.71	10.39	59.1	74	-14.9	peak
4924.356	31.64	10.39	42.03	54	-11.97	AVG
7386.271	41.52	12.68	54.2	74	-19.8	peak
7386.271	27.5	12.68	40.18	54	-13.82	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




Band Edge Emission:

EUT :	Tablet PC	Model Name :	VB736
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH1(802.11b Mode)	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2400	79.39	-12.99	66.4	74	-7.6	peak
2400	57.02	-12.99	44.03	54	-9.97	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Tablet PC	Model Name :	VB736
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH1(802.11b Mode)	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2400	78.69	-12.99	65.7	74	-8.3	peak
2400	59.54	-12.99	46.55	54	-7.45	AVG

Remark:


Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT :	Tablet PC	Model Name :	VB736
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH11(802.11b Mode)	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2483.5	61.21	-12.78	48.43	74	-25.57	peak

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Tablet PC	Model Name :	VB736
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH11(802.11b Mode)	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2483.5	47.11	-12.78	34.33	74	-39.67	peak

Remark:


Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT :	Tablet PC	Model Name :	VB736
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH1(802.11g Mode)	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2400	79.95	-12.99	66.96	74	-7.04	peak
2400	57.21	-12.99	44.22	54	-9.78	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Tablet PC	Model Name :	VB736
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH1(802.11gMode)	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2400	71.43	-12.99	58.44	74	-15.56	peak
2400	55.28	-12.99	42.29	54	-11.71	AVG

Remark:


Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT :	Tablet PC	Model Name :	VB736
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH11(802.11g Mode)	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2483.5	67.73	-12.78	54.95	74	-19.05	peak
2483.5	54.74	-12.78	41.96	54	-12.04	AVG


Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT :	Tablet PC	Model Name :	VB736
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH11(802.11g Mode)	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2483.5	57.27	-12.78	44.49	74	-29.51	peak

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Tablet PC	Model Name :	VB736
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH1(802.11n Mode)	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2400	75.46	-12.99	62.47	74	-11.53	peak
2400	54.48	-12.99	41.49	54	-12.51	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Tablet PC	Model Name :	VB736
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH1(802.11n Mode)	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2400	69.76	-12.99	56.77	74	-17.23	peak
2400	54.84	-12.99	41.85	54	-12.15	AVG

Remark:


Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT :	Tablet PC	Model Name :	VB736
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH11(802.11n Mode)	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2483.5	63.92	-12.78	51.14	74	-22.86	peak


Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT :	Tablet PC	Model Name :	VB736
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH11(802.11n Mode)	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2483.5	58.49	-12.78	45.71	74	-28.29	peak

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.



4. POWER SPECTRAL DENSITY TEST

4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS

4.1.1 TEST PROCEDURE

1. The testing follows Measurement Procedure PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v01.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable. The path loss was compensated to the results for each measurement.
3. Record the measurement data derived from spectrum analyzer.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 KHz. Video bandwidth (VBW) >= 300 KHz In order to make an accurate measurement, set the span to 5-30% greater than Emission Bandwidth (EBW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.
6. Scale the observed power level to an equivalent value in 3 kHz by adjusting (reducing) the measured power by a bandwidth correction factor (BWCF) where $BWCF = 10\log(3\text{ kHz}/100\text{ kHz}) = -15.2\text{ dB}$.

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP



4.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.


4.1.5 TEST RESULTS



EUT :	Tablet PC	Model Name :	VB736
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX b Mode /CH01, CH06, CH11		

Frequency	Power Density (dBm)	PSD/ 3KHz (dBm)	Limit (dBm)	Result
2412 MHz	9.63	-5.57	8	PASS
2437 MHz	8.76	-6.44	8	PASS
2462 MHz	8.51	-6.69	8	PASS

Note:

BWCF = $10\log(3\text{ kHz}/100\text{ kHz}) = -15.2\text{ dB}$.








EUT :	Tablet PC	Model Name :	VB736
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX g Mode /CH01, CH06, CH11		

Frequency	Power Density (dBm)	PSD/ 3KHz (dBm)	Limit (dBm)	Result
2412 MHz	5.16	-10.04	8	PASS
2437 MHz	4.41	-10.79	8	PASS
2462 MHz	3.84	-11.36	8	PASS

Note:

BWCF = $10\log(3\text{ kHz}/100\text{ kHz}) = -15.2\text{ dB}$.








EUT :	Tablet PC	Model Name :	VB736
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX n Mode /CH01, CH06, CH11		

Frequency	Power Density (dBm)	PSD/ 3KHz (dBm)	Limit (dBm)	Result
2412 MHz	5.41	-9.79	8	PASS
2437 MHz	4.57	-10.63	8	PASS
2462 MHz	4.01	-11.19	8	PASS

Note:

BWCF = $10\log(3\text{ kHz}/100\text{ kHz}) = -15.2\text{ dB}$.





5. BANDWIDTH TEST

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

5.1.1 TEST PROCEDURE


a.

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v01.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable. The path loss was compensated to the results for each measurement.
3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 1-5% of the emission bandwidth (EBW). Set the Video bandwidth (VBW) $\geq 3 * \text{RBW}$. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 KHz.
4. The marker-delta reading at this point is the 6 dB bandwidth of the emission.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP




5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


5.1.5 TEST RESULTS

EUT :	Tablet PC	Model Name :	VB736
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX bMode /CH01, CH06, CH11		


Frequency	6dB Bandwidth (MHz)	99% Occupied BW (MHz)	Channel Separation (MHz)	Result
2412 MHz	11.94	14.72	>=500KHz	PASS
2437 MHz	12.06	15.26	>=500KHz	PASS
2462 MHz	11.97	16.22	>=500KHz	PASS



TX CH 06




TX CH 11




EUT :	Tablet PC	Model Name :	VB736
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX g Mode /CH01, CH06, CH11		


Frequency	6dB Bandwidth (MHz)	99% Occupied BW (MHz)	Channel Separation (MHz)	Result
2412 MHz	16.51	16.60	>=500KHz	PASS
2437 MHz	16.46	16.54	>=500KHz	PASS
2462 MHz	16.89	16.88	>=500KHz	PASS



TX CH 06




TX CH 11




EUT :	Tablet PC	Model Name :	VB736
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX n Mode(20M) /CH01, CH06, CH11		


Frequency	6dB Bandwidth (MHz)	99% Occupied BW (MHz)	Channel Separation (MHz)	Result
2412 MHz	16.89	16.87	>=500KHz	PASS
2437 MHz	16.88	16.88	>=500KHz	PASS
2462 MHz	16.83	16.83	>=500KHz	PASS



TX CH 06



TX CH 11



6. PEAK OUTPUT POWER TEST

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

6.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the Power meter

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

6.1.5 TEST RESULTS

EUT :	Tablet PC	Model Name :	VB736
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX b/g/n(20M,40M) Mode /CH01, CH06, CH11		

TX 802.11b Mode					
Test Channel	Frequency	Peak output power. Antenna port	AV output power. Antenna port	Antenna Gain	LIMIT
	(MHz)	(dBm)	(dBm)	dBi	dBm
CH01	2412	17.87	14.67	2.0	30
CH06	2437	17.76	14.82	2.0	30
CH11	2462	17.57	14.32	2.0	30
TX 802.11g Mode					
CH01	2412	16.79	13.54	2.0	30
CH06	2437	16.55	13.66	2.0	30
CH11	2462	16.62	13.43	2.0	30
TX 802.11n Mode					
CH01	2412	15.86	13.46	2.0	30
CH06	2437	15.73	13.54	2.0	30
CH11	2462	15.64	13.42	2.0	30

7. ANTENNA REQUIREMENT

7.1 STANDARD REQUIREMENT



15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

7.2 EUT ANTENNA

The EUT antenna is FPCB antenna. It comply with the standard requirement.

8. EUT TEST PHOTO

Radiated Measurement Photos



Conducted Measurement Photos

