

RADIATED EMISSIONS
FCC Part 15, Sub-part B 15.109(a) (Class B)

File # 06056-1 Engr.: Clay Allred Date: Apr 04, 2000
 Site: 2 Distance: 3 meter Cables: 2.2
 Blcon: 187 Log: 10 Amp 1: 67 & 68

Freq. MHz	Meas'd (dBuV)	50% Duty Cycle Correction	Amp Factors (dB)	Cable Factors (dB)	Antenna Factors (dB)	Total Factors (dBuV/m)	Total (dBuV/m)	Limit (dBuV/m)	Delta (dB)	Azimuth (degree)	Height (m)	Hor/ Vert	HP/ R&S	Meas Type	Ave QP Peak	Comments
3.280	102.9	51.5	51.2	11.0	24.8	-15.4	38.05	94.0	-58.0	154	1.1	Vert	R&S	QP		Fundamental Field Strength
9.340	101.1	50.6	51.2	11.1	24.9	-15.2	35.35	94.0	-58.65	247	1.1	Vert	R&S	QP		Fundamental Field Strength
1.345	95.8	47.9	51.2	11.3	25.0	-14.9	33.00	94.0	-61.00	107	1.2	Vert	R&S	QP		Fundamental Field Strength
9.340	95.9	48.0	51.2	11.1	24.9	-15.2	32.75	94.0	-61.25	305	1	Hor/	R&S	QP		Fundamental Field Strength
3.290	92.9	48.5	51.2	11.0	24.8	-15.4	31.05	94.0	-62.95	300	1	Hor/	R&S	QP		Fundamental Field Strength
1.340	90.7	45.4	51.2	11.3	25.0	-14.9	30.45	94.0	-63.55	298	1	Hor/	R&S	QP		Fundamental Field Strength

Data not valid for report unless signed by DNB personnel