

# TEST REPORT

Ref. Report No.

00-341-003-01

Name and address of the applicant

AM Equipment  
P.O. BOX 790  
402 E. HAZEL JEFFERSON, OR 97352  
U.S.A.

Standard / Test regulation

FCC Part 15, Subpart B

Test result

Pass

**Incoming date : January 21, 2000**

**Test date : March 21, 2000**

Test item(s) ;

Superregenerative Receiver  
(RF Motor Control System)

Model/type ref. ;

MIDAS2

Manufacturer ;

SAM-M ELECTRON

Additional information ;

-Required Authorization : Certification  
-FCC ID. : O YT-3201219

**Issue date : April 14, 2000**

*This test report only responds to the tested sample and shall not be reproduced except in full without written approval of the Korea Testing Laboratory.*

Tested and reported by

*Jeong min Kim*

Jeong-Min Kim, Senior Engineer

Reviewed by

*S. J. Kim*

Seok-Jin Kim, EMC Team Leader

**KOREA TESTING  
LABORATORY**

## **TABLE OF CONTENTS**

I. GENERAL INFORMATION .....	3
1. Grantee Name and Mailing Address	
2. Manufacturer's Name and Mailing Address	
3. Equipment Descriptions	
4. Rules and Regulations	
5. Measuring Procedure	
6. Date of Measurement	
α. GENERAL REQUIREMENTS OF THE EUT .....	4
1. Labelling Requirement (Section 15.19)	
2. Information to User (Sections 15.21)	
3. Special Accessories (Section 15.27)	
β. CONDUCTED EMISSION MEASUREMENT (Section 15.107) .....	5-8
1. Test Procedure	
2. Photograph for the worst case configuration	
3. Sample Calculation	
4. Measurement Data	
χ. RADIATED EMISSION MEASUREMENT (Section 15.109) .....	9-12
1. Test Procedure	
2. Photograph for the worst case configuration	
3. Sample Calculation	
4. Measurement Data	
5. Reference Data	
δ. TEST EQUIPMENTS USED FOR MEASUREMENT.....	13

**. GENERAL INFORMATION**

1. Grantee Name and : AM Equipment  
Mailing Address P. O. Box 790, 402 E. HAZEL JEFFERSON, OR 97352 U.S.A.

2. Manufacturer's Name and : SAM-M ELECTRON  
Mailing Address 239-12 Gasan-Dong, Kumchon-Gu, Seoul, Korea 152-023

3. Equipment Descriptions

3.1 Tuning Frequency : 315.0MHz  
3.2 Detect Method : Superregenerative Detector  
3.3 Used Oscillator : 4MHz (Crystal)  
3.4 Power Supply : DC 12V (Battery or AC adapter)

4. Rules and Regulations : FCC Part 15, Subpart B

5. Measuring Procedure : ANSI C63.4-1992

6. Date of Measurement

6.1 Line Conducted : March 17, 2000  
6.2 Radiated Emission : March 21, 2000

**. GENERAL REQUIREMENTS OF THE EUT****1. Labelling Requirement (Section 15.19)**

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interface, and (2) this device must accept any interference received, including interference that may cause undesired operation.

1.1 Location of Label : Bottom side of EUT

1.2 How Applied : By ink-printing on adhesive label

**2. Information to User (Section 15.21)**

The following or similar statements were provided in the manual for user instruction.

Please refer page 1 of the attached manual for details.

**CAUTION** : Any changes or modifications in construction of this device which are not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

**3. Special Accessories (Section 15.27)**

3.1 Were the special Accessories provided? [    ] yes, [ x ] no

3.2 If yes, details for the special accessories are as follows :

3.3 If yes, were the appropriate instructions provided on the first page of the text concerned with the device?

[    ] yes, [    ] no

3.4 Are these accessories provided of the type which can be readily obtained from multiple retail outlets ?  
[    ] yes, [    ] no

And therefore does the manual specify what additional components or accessories are required to be used in order to comply with the Rules?

[    ] yes, [    ] no

**. CONDUCTED EMISSION MEASUREMENT (Section 15.107)****1. Test Procedure**

Conducted emission measurements on the EUT were performed by "AC Power Line Conducted Emissions Testing" procedure as per ANSI C63.4. The EUT was set up on a wooden table 0.8 meters height, 1.0 by 1.5 meters in size, placed in the shielded enclosed with a side of wall of which constituted a vertical conducting surface of 2.2m x 3.1m in size to maintain 40cm from the rear of EUT

LISN's(Line Impedance Stabilization Network, EMCO, 3825/2, 50ohm/50 $\omega$ H) were installed and electrically bonded to the conducting ground plane. The EUT was connected to the LISN.

One of two 50ohm output terminals of the LISN was connected to the Spectrum Analyzer(HP, 8566B, 10kHz to 22GHz) with the Quasi-Peak Adapter (HP, 85650A, 10kHz to 1.0GHz) and the other was terminated in 50 ohms. Measurements were again performed after interchanging such a connection oppositely.

The frequency range from 450kHz to 30MHz was examined and the peak values that are within 6dB of the limit would be compared to quasi-peak values using the Quasi-Peak instrument (ROHDE & SCHWARZ, ESH3, 9kHz to 30MHz : Detector Function CISPR Quasi-Peak) or HP Quasi-Peak adapter(85650A, 10kHz to 1.0GHz)

The voltage developed across the 50ohms port in LISN was measured by the Spectrum Analyzer and graphed by the Plotter(HP, 7470A). The 6dB bandwidth of the Spectrum Analyzer and Quasi-Peak Adapter was set to 9kHz with no post detector video filter.

The position of connecting cables of the EUT was changed to find the worst case configuration during measurements. The maximum emission level from the EUT occurred in such configuration as shown in the following photograph.

## 2. Photograph for the worst case configuration



## 3. Sample Calculation

The emission level measured in decibels above one microvolt ( $\text{dB}\delta$ ) was converted into microvolt ( $\delta$ ) as shown in following sample calculation.

For example :

Measured Value at 25.35MHz 32.1  $\text{dB}\delta$   
+ Cable Losses \* 0.0 dB

---

= Conducted Emission 32.1  $\text{dB}\delta$   
( = 40.3  $\delta$  )

\* In case of RG214/ RF cable 15Ft, the loss is about 0.17dB at the frequency of 30MHz which is negligible.

## 4. Measurement Data

- Resolution Bandwidth : x Peak (6dB Bandwidth : 9kHz)  
x CISPR Quasi-Peak (6dB Bandwidth : 9kHz)

Power Lead Tested	Frequency (MHz)	Measured Value		Emission Level		Limit (dB)	(*) Margin (dB)
		Peak (dB $\delta$ )	Q-Peak (dB $\delta$ )	(dB $\delta$ )	( $\delta$ )		
Live to Ground	0.48	28.9	17.7	17.7	7.7	250	-30.3
	25.35	32.2	32.1	32.1	40.3	250	-15.9
	27.04	32.1	32.0	32.0	39.8	250	-16.0
	-	-	-	-	-	-	-
Neutral to Ground	0.48	28.6	16.3	16.3	6.5	250	-31.7
	25.35	32.4	32.0	32.0	39.8	250	-16.0
	27.04	30.8	30.5	30.5	33.5	250	-17.5
	-	-	-	-	-	-	-

Note : The noise floor level of the spectrum analyzer was observed in 22dB $\delta$ .

Refer to measured graphs on next page.

\* Margin(dB) : Emission Level (dB) - Limit (dB)

