

Date: 2000-04-14

TEST REPORT

Page 1 of 10

No.: HM102399

APPLICANT: (Code: PAC007)

PACIFIC CANAAN LIMITED.

SUITE 1342, HITEC 1 TRADEMART DRIVE, KOWLOON BAY , HONG KONG

DATE OF SAMPLES RECEIVED: 2000-03-30

DATE OF TESTING: 2000-03-30 to 2000-04-11

DESCRIPTION OF SAMPLE(S):

A sample of product said to be:

Product: DIGITAL CAMERA WITH USB PORT

Manufacturer: PACIFIC CANAAN LIMITED.

Model Number: PCL8020

Brand Name: EC-CAM

Rating: 6.0V d.c. ("AAA" size battery x 4)

Origin: CHINA

INVESTIGATIONS REQUESTED:

Measurement to the relevant clauses of F.C.C. Rules and Regulations Part B - Unintentional Radiators. The results obtained are to compare with the class B digital device limit.

REMARK : This product was tested as a system using the Ancillary Equipment listed in Appendix B.

RESULTS: Please see attached sheet(s).

CONCLUSION:

From the measurement data obtained, the tested sample was considered to have COMPLIED with the requirement for the relevant clauses of Federal Communications Commission Rules for Class B digital device.

TEST EQUIPMENT AUDIT: Please see Appendix A.

Law Man Kit
Testing Engineer

Kitty Choy
Verify by

Patrick Wong
Patrick Wong
for Managing Director

Date: 2000-04-14

No.: HM102399

TEST REPORT

Page 2 of 10

TEST SUMMARY

(A) **Measurement of Radiated Emission**

Result -- Satisfactory
Data -- See the attached data

(B) **Measurement of Line-Conducted Voltage Test**

Result -- Satisfactory
Data -- See the attached data

Date: 2000-04-14

TEST REPORT

Page 3 of 10

No.: HM102399

(A) Measurement of Radiated Interference

TEST REFERENCE : FCC Rules Part 15 Subpart B Section 15.109(a)
: (Class B)
TEST CONDITION : Normal
TEST DATE : 2000-03-30

Emission Frequency	Meter Reading (including antenna factor)	Polarization	Field Strength (at 3m)	FCC Limited
MHz	dB(μ V)	H-V	μ V/m	μ V/m
132.005	23.2	V	14.45	150
132.019	28.4	H	26.30	150
180.027	30.8	H	34.67	150
203.984	26.1	V	20.18	150
204.035	29.4	H	29.51	150
276.041	32.7	H	43.15	200
300.036	32.7	H	43.15	200

- End -

SUMMARY

All data is within limits

Broad-band Antennas were used and both polarizations of emissions were measured.

polarizations at highest reading indicated as:

H -- Horizontal V -- Vertical

Quasi-peak measurements were performed if the maximised measurements

were less than 6dB below the quasi-peak limit line.

Quasi-peak measurements are denoted by * in the table above

NOTES FOR THE RADIATION MEASUREMENT

(1) Test site facility:

Open field test site located at Taipo (Hong Kong) with a metal ground plane in compliance with the requirements of ANSI C63.4:1992.

(2) Test Equipment:

HP 8572A EMI receiver was set to CISPR quasi-peak mode and the bandwidth of the receiver was set to 100KHz or 1MHz depending on the type of signal. A biconical log-Periodic antenna was used for frequency range from 30MHz to 1000MHz.

(3) Test Set-Up:

The EUT and support equipment are placed in accordance with ANSI C63.4.

(4) Measuring Procedure:

An initial pre-scan measurement was performed in a semi-anechoic chamber using a 25dB gain pre-amplifier. The receive antenna in the chamber was 1.5m above the groundplane and 3m from the sample. The sample was placed 0.8m above the groundplane. Measurements in both horizontal and vertical polarities were performed. All emissions recorded during the prescan were subsequently remeasured on the open field test site (described in 1 above) using the following procedure: The ambient noise scanning was made before powering on the EUT and support equipment to identify the emissions from the environment. During the test, each emission was maximized by: having the EUT continuously working, arranging, rotating turntable and manipulating interconnecting cables, rotating turntable and varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The frequency range tested is from 30MHz to 1000MHz and the worst-case emissions are shown in Test Results.

(5) Measuring Uncertainty:

The calculated uncertainty for measurement performed at 3M test distance are:-
30MHz to 300MHz = ± 3.7 dB, 300MHz to 1000MHz = $+3.0$ dB/- 2.7 dB.

Remark: Purpose of this test is to provide the Applicant with the necessary test data of their device for the submission to FCC with application for Equipment Authorization under FCC's Equipment Authorization Program. This test itself is not an Approval Test.

Date: 2000-04-14

TEST REPORT

Page 5 of 10

No.: HM102399

(B) Measurement of Line-Conducted Voltage onto AC Power Line

TEST REFERENCE : FCC Rules Part 15 Subpart B Section 15.107(a)
: (Class B)
TEST CONDITION : Normal
TEST DATE : 2000-04-11

(1) Between "Live" and "Ground"

Frequency Range of Emission			Maximum Measured Radio Noise		FCC Limit (Class B)	
	MHz		dB(µV)	µV	µV	
0.45	-	0.80	< 28.00	25.12	250.00	
0.80	-	1.60	28.20	25.70	250.00	
1.60	-	3.00	30.30	32.73	250.00	
3.00	-	5.00	32.20	40.74	250.00	
5.00	-	7.00	32.40	41.69	250.00	
7.00	-	9.00	33.30	46.24	250.00	
9.00	-	11.00	28.50	26.61	250.00	
11.00	-	13.00	< 28.80	27.54	250.00	
13.00	-	15.00	0.00	1.00	250.00	
15.00	-	17.00	< 29.10	28.51	250.00	
17.00	-	19.00	36.50	66.83	250.00	
19.00	-	21.00	0.00	1.00	250.00	
21.00	-	23.00	30.90	35.08	250.00	
23.00	-	25.00	0.00	1.00	250.00	
25.00	-	27.00	0.00	1.00	250.00	
27.00	-	30.00	< 18.80	8.71	250.00	=====

- End -

===== SUMMARY =====

All data is within limits

=====

Date: 2000-04-14

TEST REPORT

Page 6 of 10

No.: HM102399

(B) Measurement of Line-Conducted Voltage onto AC Power Line

TEST REFERENCE : FCC Rules Part 15 Subpart B Section 15.107(a)
: (Class B)
TEST CONDITION : Normal
TEST DATE : 2000-04-11

(1) Between "Neutral" and "Ground"

Frequency Range of Emission		Maximum Measured Radio Noise		FCC Limit (Class B)	
	MHz		dB(µV)	µV	µV
0.45	-	0.80	28.00	25.12	250.00
0.80	-	1.60	< 28.20	25.70	250.00
1.60	-	3.00	< 30.30	32.73	250.00
3.00	-	5.00	< 32.20	40.74	250.00
5.00	-	7.00	< 32.40	41.69	250.00
7.00	-	9.00	< 33.30	46.24	250.00
9.00	-	11.00	< 28.50	26.61	250.00
11.00	-	13.00	28.80	27.54	250.00
13.00	-	15.00	0.00	1.00	250.00
15.00	-	17.00	29.10	28.51	250.00
17.00	-	19.00	< 36.50	66.83	250.00
19.00	-	21.00	0.00	1.00	250.00
21.00	-	23.00	< 30.90	35.08	250.00
23.00	-	25.00	0.00	1.00	250.00
25.00	-	27.00	0.00	1.00	250.00
27.00	-	30.00	18.80	8.71	250.00

- End -

===== SUMMARY =====

All data is within limits

NOTES FOR THE CONDUCTED POWER-LINE MEASUREMENT

- (1) LISN (Line Impedance Stabilization Network) used :
50 μ H LISN in accordance with Section of ANSI C63.4:1992.
- (2) Measurement Instrumentations:
CISPR quasi-peak type radio noise meter (9 KHz - 30 MHz), 6 dB bandwidth set at 9 KHz for measurement between 150 KHz & 30MHz.
- (3) Frequency range scanned :
The frequency range from 450 KHz to 30 MHz had been searched. Reading of the highest emissions relating to the limit were reported as above.
- (4) Configuration of EUT:
Connection of equipment and operation conditions were same as those in the Radiation measurement.
- (5) Measurement procedure :
In accordance with the relevant sections of ANSI C63.4:1992 "FCC Methods of measurement of Radio Noise Emissions from Computing Devices".
- (6) Measuring Uncertainty:
The calculated uncertainty for conducted power-line measurement is = \pm 2.3dB.

Remark: Purpose of this test is to provide the Applicant with the necessary test data of their device for the submission to FCC with application for Equipment Authorization under FCC's Equipment Authorization Program. This test itself is not an Approval Test.

*** End of document ***

Date: 2000-04-14

TEST REPORT

Page 8 of 10

No.: HM102399

APPENDIX A

TEST EQUIPMENT AUDIT

Radiated Emission

EQP NO.	DESCRIPTION	MANUFACT URER	MODEL NO.	SERIAL NO.	LAST CAL.
EM007	SPECTRUM ANALYZER	HEWLETT PACKARD	HP85660B	3144A21192	11/06/99
EM008	SPECTRUM ANALYZER DISPLAY	HEWLETT PACKARD	HP85662A	3144A20514	11/06/99
EM009	QUASI PEAK ADAPTOR	HEWLETT PACKARD	HP85650A	3303A01702	11/06/99
EM010	RF PRESELECTOR	HEWLETT PACKARD	HP85685A	3221A01410	11/06/99
EM011	ATTENUATOR/SWITCH	HEWLETT PACKARD	HP11713A	2508A10595	11/06/99
EM012	PRE-AMPLIFIER	HEWLETT PACKARD	HP8449B	3008A00262	11/06/99
EM013	CONTROLLER (COMPUTER), COLOR MONITOR, KEYBOARD & MOUSE FLOPPY DRIVE	HEWLETT PACKARD HEWLETT PACKARD HEWLETT PACKARD	HP9000 HP A1097C HP9133L	6226A60314 3151J39517 2623A02468	CM
EM017	ANTENNA	ARA INC.	LPB-2513/A	1069	17/02/00
EM020	HORN ANTENNA	EMCO	3115	4032	30/06/97
EM072	SIGNAL GENERATOR	HEWLETT PACKARD	8640B	1948A11892	30/03/98
EM083	HKSTC OPEN AREA TEST SITE	HKSTC	N/A	N/A	15/01/00
EM145	EMI TEST RECEIVER	R & S	ESCS 30	830245/021	10/05/99

Date: 2000-04-14

TEST REPORT

Page 9 of 10

No.: HM102399

Line Conducted

EQP NO.	DESCRIPTION	MANUFACT URER	MODEL NO.	SERIAL NO.	LAST CAL
EM078	VARIAC	SHANGHAI VOLTAGE	TDGC-3/0.5	N/A	CM
EM081	SMALL SCREENED ROOM	MIKO INST HK	N/A	N/A	09/09/99
EM119	LISN	R & S	ESH3-Z5	0831.5518.52	09/08/98
EM120	EMI TEST RECEIVER	R&S	ESHS10	1004.0401.10	09/08/99
EM123	NOTEBOOK PC	ACER	350CX	P007865	N/A
EM127	ISOLATION TRANSFORMER 220 TO 300	WING SUN	N/A	N/A	01/09/97
EM142	PLUSE LIMITER	R & S	ESH3Z2	357.8810.52	29/01/99
EM145	EMI TEST RECEIVER	R & S	ESCS 30	830245/021	10/05/99

Remarks:-

CM Corrective Maintenance

N/A Not Applicable or Not Available

TBD To Be Determined

Date: 2000-04-14

TEST REPORT

Page 10 of 10

No.: HM102399

APPENDIX B

ANCILLARY EQUIPMENT

ITEM NO.	DESCRIPTION	MODEL NO.	FCC ID	REMARK
1	DELL COMPUTER	MMS	E2KTERMIND	N/A
2	AST AVGA MONITOR	CM6P	GDRCM6P	RESOLUTION:720*400(DURING TESTING) 1.0M UNSHIELDED POWER CORD CONNECTED TO THE COMPUTER 2.8M SHIELDED CABLE CONNECTED TO THE COMPUTER
3	AST KEYBOARD	KB-2923	LIAKWD-200	1.8M SHIELDED COILED CABLE CONNECTED TO THE COMPUTER
4	MOUSE	PS12	FSUGMZC8	2.4M UNSHIELDED CABLE CONNECTED TO THE COMPUTER
5	PARALLEL PRINTER	DMP3000	DE2850CDMP3000	1.8M UNSHIELDED POWER CORD 2.8M SHIELDED CABLE (BYNDLED TO 1M) CONNECTED TO THE COMPUTER