

Project No: TM-2505000232P  
Report No.: TMWK2505002042KR

FCC ID: P27K0402

Page: 1 / 46  
Rev.: 01

# RADIO TEST REPORT

## FCC 47 CFR PART 15 SUBPART C

<b>Test Standard</b>	<b>FCC Part 15.247</b>
<b>Product name</b>	<b>All-in-one Access Control Reader</b>
<b>Brand Name</b>	<b>Kisi Inc.</b>
<b>Model No.</b>	<b>K0402</b>
<b>Test Result</b>	<b>Pass</b>
<b>Statements of Conformity</b>	<b>Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.</b>

The test Result was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were given in ANSI C63.10: 2013 and compliance standards.

The test results of this report relate only to the tested sample (EUT) identified in this report.

The test Report of full or partial shall not copy. Without written approval of Compliance Certification Services Inc.( Wugu Laboratory)

Approved by:



---

Dally Hong  
Sr. Engineer

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

## Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	June 27, 2025	Initial Issue	ALL	Peggy Tsai
01	July 7, 2025	See the following Note Rev. (01)	P.5, 13	Peggy Tsai

**Note:**

**Rev. (01)**

1. Modify antenna gain in section 1.3.
2. Modify the worst mode of measurement in section 3.2.

## Table of contents

<b>1.</b>	<b>GENERAL INFORMATION .....</b>	<b>4</b>
1.1	<b>EUT INFORMATION .....</b>	4
1.2	<b>EUT CHANNEL INFORMATION .....</b>	5
1.3	<b>ANTENNA INFORMATION .....</b>	5
1.4	<b>MEASUREMENT UNCERTAINTY.....</b>	6
1.5	<b>FACILITIES AND TEST LOCATION .....</b>	6
1.6	<b>INSTRUMENT CALIBRATION .....</b>	7
1.7	<b>SUPPORT AND EUT ACCESSORIES EQUIPMENT .....</b>	9
1.8	<b>TEST SET UP DIAGRAM.....</b>	10
1.9	<b>TEST PROGRAM.....</b>	10
1.10	<b>TEST METHODOLOGY AND APPLIED STANDARDS .....</b>	10
<b>2.</b>	<b>TEST SUMMERY .....</b>	<b>11</b>
<b>3.</b>	<b>DESCRIPTION OF TEST MODES.....</b>	<b>12</b>
3.1	<b>THE WORST MODE OF OPERATING CONDITION .....</b>	12
3.2	<b>THE WORST MODE OF MEASUREMENT .....</b>	13
3.3	<b>EUT DUTY CYCLE.....</b>	14
<b>4.</b>	<b>TEST RESULT .....</b>	<b>15</b>
4.1	<b>AC POWER LINE CONDUCTED EMISSION .....</b>	15
4.2	<b>6DB BANDWIDTH AND OCCUPIED BANDWIDTH(99%) .....</b>	20
4.3	<b>OUTPUT POWER MEASUREMENT .....</b>	23
4.4	<b>POWER SPECTRAL DENSITY.....</b>	25
4.5	<b>CONDUCTED BAND EDGE AND SPURIOUS EMISSION .....</b>	28
4.6	<b>RADIATION BANDEDGE AND SPURIOUS EMISSION .....</b>	31
<b>APPENDIX 1 - PHOTOGRAPHS OF EUT</b>		

## 1. GENERAL INFORMATION

### 1.1 EUT INFORMATION

<b>Applicant</b>	Sercomm Corporation 8F, No. 3-1, YuanQu St., NanKang, Taipei 115, Taiwan
<b>Manufacturer</b>	Sercomm Corporation 8F, No. 3-1, YuanQu St., NanKang, Taipei 115, Taiwan
<b>Equipment</b>	All-in-one Access Control Reader
<b>Model No.</b>	K0402
<b>Model Discrepancy</b>	N/A
<b>Trade Name</b>	Kisi Inc.
<b>Received Date</b>	May 20, 2025
<b>Date of Test</b>	May 27 ~ 28, 2025
<b>Power Operation</b>	Powered from PoE (Not for sell) aruba / POE60U-1BT-5 I/P: 100-240Vac, 1.5A, 50-60Hz O/P: 56Vdc, 0.535A
<b>HW Version</b>	V10
<b>FW Version</b>	V3.1.02

**Remark:**

- For more details, please refer to the User's manual of the EUT.
- Disclaimer: Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received.

## 1.2 EUT CHANNEL INFORMATION

<b>Frequency Range</b>	2402MHz-2480MHz
<b>Modulation Type</b>	GFSK for BLE 1 Mbps
<b>Number of channel</b>	40 Channels

**Remark:**

Refer as ANSI C63.10: 2013 clause 5.6.1 Table 4 for test channels

Number of frequencies to be tested		
Frequency range in which device operates	Number of frequencies	Location in frequency range of operation
<input type="checkbox"/> 1 MHz or less	1	Middle
<input type="checkbox"/> 1 MHz to 10 MHz	2	1 near top and 1 near bottom
<input checked="" type="checkbox"/> More than 10 MHz	3	1 near top, 1 near middle, and 1 near bottom

## 1.3 ANTENNA INFORMATION

<b>Antenna Type</b>	<input type="checkbox"/> PIFA <input type="checkbox"/> PCB <input type="checkbox"/> Dipole <input checked="" type="checkbox"/> Chip Antenna
<b>Antenna Brand / Model</b>	PSA / RFECA3216060A4T
<b>Antenna Gain</b>	3.37 dBi

**Notes:**

1. The antenna(s) of the EUT are permanently attached and there are no provisions for connection to an external antenna. So the EUT complies with the requirements of §15.203.

## 1.4 MEASUREMENT UNCERTAINTY

PARAMETER	UNCERTAINTY
AC Powerline Conducted Emission	+/- 2.21 dB
Channel Bandwidth	+/- 2.79 dB
RF output power (Power Meter + Power sensor)	+/- 0.24 dB
Power Spectral density	+/- 2.74 dB
Conducted Bandedge	+/- 2.74 dB
Conducted Spurious Emission	+/- 2.74 dB
Radiated Emission_9kHz-30MHz	+/- 3.492 dB
Radiated Emission_30MHz-200MHz	+/- 3.62 dB
Radiated Emission_200MHz-1GHz	+/- 3.899 dB
Radiated Emission_1GHz-6GHz	+/- 5.063 dB
Radiated Emission_6GHz-18GHz	+/- 5.122 dB
Radiated Emission_18GHz-26GHz	+/- 3.032 dB
Radiated Emission_26GHz-40GHz	+/- 3.271 dB

**Remark:**

- 1.This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2
2. ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report.

## 1.5 FACILITIES AND TEST LOCATION

All measurement facilities used to collect the measurement data are located at

No.11, Wugong 6th Rd., Wugu Dist., New Taipei City, Taiwan.

CAB identifier: TW1309

Test site	Test Engineer	Remark
AC Conduction Room	Ben Yang	-
Radiation	Tony Chao	-
RF Conducted	David Li	-

**Remark:** The lab has been recognized as the FCC accredited lab. under the KDB 974614 D01 and is listed in the FCC pubic Access Link (PAL) database, FCC Registration No. :444940, the FCC Designation No.:TW1309

## 1.6 INSTRUMENT CALIBRATION

Conducted FCC/IC/NCC (All)					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
EXA Signal Analyzer	Keysight	N9010A	MY53400256	2024-11-19	2025-11-18
Power Sensor	Anritsu	MA2411B	1911387	2024-08-30	2025-08-29
Power Sensor	Anritsu	MA2411B	1911386	2024-07-19	2025-07-18
Power Meter	Anritsu	ML2496A	2136002	2024-07-19	2025-07-18
DC Blocks	Marvelous Microwave	MVE6411	MVE-001	2024-08-08	2025-08-07
<b>Software</b>	Radio Test Software Ver. 21				

966A Radiated					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Signal Analyzer	KEYSIGHT	N9010A	MY52220817	2025-03-05	2026-03-04
Active Loop Antenna	COM-POWER	AL-130	121051	2025-02-18	2026-02-17
Thermo-Hygro Meter	WISEWIND	1206	D07	2024-11-26	2025-11-25
Bi-Log Antenna	Sunol Sciences	JB3	A030105	2024-07-12	2025-07-11
Preamplifier	EMEC	EM330	060609	2025-02-20	2026-02-19
Cable	Huber+Suhner	104PEA	20995+21000+182330	2024-08-07	2025-08-06
Horn Antenna	ETC	MCTD 1209	DRH13M02003	2024-12-20	2025-12-19
Preamplifier	HP	8449B	3008A00965	2024-12-18	2025-12-17
Cable	EMCI	EMC101G	221012+230205+250412	2025-04-24	2026-04-23
Attenuator	Mini-Circuits	BW-S9W5	BWS9W5-09-966A-01	2025-02-06	2026-02-05
Site Validation	CCS	966A	N/A	2024-08-03	2025-08-02
High Pass Filters	Titan Microwave	T04H30001800070S01	22011402-4	2024-06-12	2025-06-11
Pre-Amplifier	EMCI	EMC184045SE	980860	2024-12-02	2025-12-01
Horn Antenna	SCHWARZBECK	BBHA9170	1047	2024-12-06	2025-12-05
Turn Table	CCS	CC-T-1F	N/A	N.C.R	N.C.R
Controller	CCS	CC-C-1F	N/A	N.C.R	N.C.R
Antenna Tower	CCS	CC-A-1F	N/A	N.C.R	N.C.R
<b>Software</b>	e3 V9-210616c				

**Remark:**

1. Each piece of equipment is scheduled for calibration once a year.
2. N.C.R. = No Calibration Required.

AC Mains Conduction					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
EMI Test Receiver	R&S	ESCI	100064	2024-06-14	2025-06-13
LISN	TESEQ	LN2-16N	22012	2025-02-23	2026-02-22
Cable	Woken	RFC-SMA-100-NMR-084SFL402	MFR-2Y194	2025-03-21	2026-03-20
Software	e3 V9-210616c				

**Remark:**

1. Each piece of equipment is scheduled for calibration once a year.
2. N.C.R. = No Calibration Required.

## 1.7 SUPPORT AND EUT ACCESSORIES EQUIPMENT


EUT Accessories Equipment					
No.	Equipment	Brand	Model	Series No.	FCC ID
	N/A				

Support Equipment (Conducted)					
No.	Equipment	Brand	Model	Series No.	FCC ID
1	NB(B)	Lenovo	X260	N/A	N/A
2	RJ 45	TEKSOURCE	142707-2	N/A	N/A
3	RJ 45	TEKSOURCE	142707-2	N/A	N/A
A	PoE	aruba	POE60U-1BT-5	N/A	N/A

Support Equipment (Conduction)					
No.	Equipment	Brand	Model	Series No.	FCC ID
1	NB(D)	Lenovo	ThinkPad X260	N/A	N/A
2	RJ 45	atake	AC6-FL10	202108270206	N/A
3	RJ 45	RASTO	R-PCC004	21070001	N/A
A	PoE	aruba	POE60U-1BT-5	N/A	N/A

Support Equipment (RSE)					
No.	Equipment	Brand	Model	Series No.	FCC ID
1	NB(D)	Lenovo	ThinkPad X260	N/A	N/A
2	Adapter	Lenovo	ADLX45DLC3A	N/A	N/A
3	RJ 45	atake	AC6-FL10	202108270206	N/A
4	RJ 45	RASTO	R-PCC004	21070001	N/A
A	PoE	aruba	POE60U-1BT-5	N/A	N/A

## 1.8 TEST SET UP DIAGRAM



## 1.9 TEST PROGRAM

The EUT connection corresponds to the surrounding fixture control board. This EUT uses background web page to load command to set the frequency, modulation, and power to allow the sample to continuously transmit.

## 1.10 TEST METHODOLOGY AND APPLIED STANDARDS

The test methodology, setups and results comply with all requirements in accordance with ANSI C63.10:2013, FCC Part 2, FCC Part 15.247, KDB 558074.

## 2. TEST SUMMERY

FCC Standard Section	Report Section	Test Item	Result
15.203	1.3	Antenna Requirement	Pass
15.207(a)	4.1	AC Conducted Emission	Pass
15.247(a)(2)	4.2	6 dB Bandwidth	Pass
-	4.2	Occupied Bandwidth (99%)	Pass
15.247(b)(3)	4.3	Output Power Measurement	Pass
15.247(e)	4.4	Power Spectral Density	Pass
15.247(d)	4.5	Conducted Band Edge	Pass
15.247(d)	4.5	Conducted Spurious Emission	Pass
15.247(d) 15.205, 15.209	4.6	Radiation Band Edge	Pass
15.247(d) 15.205, 15.209	4.6	Radiation Spurious Emission	Pass

### 3. DESCRIPTION OF TEST MODES

#### 3.1 THE WORST MODE OF OPERATING CONDITION

<b>Operation mode</b>	BLE Mode (1Mbps)
<b>Test Channel Frequencies</b>	1.Lowest Channel : 2402MHz 2.Middle Channel : 2442MHz 3.Highest Channel : 2480MHz

**Remark:**

1. EUT pre-scanned data rate of output power for each mode, the worst data rate were recorded in this report.

### 3.2 THE WORST MODE OF MEASUREMENT

AC Power Line Conduction Emission	
Test Condition	AC Power line conduction emission for line and neutral
Power supply Mode	Mode 1: EUT power by POE
Worst Mode	<input checked="" type="checkbox"/> Mode 1 <input type="checkbox"/> Mode 2 <input type="checkbox"/> Mode 3 <input type="checkbox"/> Mode 4

Radiated Emission Measurement Above 1G	
Test Condition	Radiated Emission Above 1G
Power supply Mode	Mode 1: EUT power by PoE
Worst Mode	<input checked="" type="checkbox"/> Mode 1 <input type="checkbox"/> Mode 2 <input type="checkbox"/> Mode 3 <input type="checkbox"/> Mode 4
Worst Position	<input type="checkbox"/> Placed in fixed position. <input type="checkbox"/> Placed in fixed position at X-Plane (E2-Plane) <input checked="" type="checkbox"/> Placed in fixed position at Y-Plane (E1-Plane) <input type="checkbox"/> Placed in fixed position at Z-Plane (H-Plane)

Radiated Emission Measurement Below 1G	
Test Condition	Radiated Emission Below 1G
Power supply Mode	Mode 1: EUT power by PoE
Worst Mode	<input checked="" type="checkbox"/> Mode 1 <input type="checkbox"/> Mode 2 <input type="checkbox"/> Mode 3 <input type="checkbox"/> Mode 4


**Remark:**

1. The worst mode was record in this test report.
2. AC power line conducted emission were performed the EUT transmit at the highest output power channel as worse case.
3. EUT pre-scanned in three axis ,X,Y, Z and two polarity, for radiated measurement. The worst case(Y-Plane) were recorded in this report

## 3.3 EUT DUTY CYCLE

Temperature: 26.1°C                      Test date: May 28, 2025  
 Humidity: 57% RH                        Tested by: David Li

Mode	Duty Cycle (%) = Ton / (Ton+Toff)	Duty Factor (dB) =10*log ( 1/Duty Cycle )	1/T (kHz)	VBW setting (kHz)
BLE 1M	100.00	0.00	0.00	0.01



## 4. TEST RESULT

### 4.1 AC POWER LINE CONDUCTED EMISSION

#### 4.1.1 Test Limit

According to §15.207(a),

Frequency Range (MHz)	Limits(dBμV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50


\* Decreases with the logarithm of the frequency.

#### 4.1.2 Test Procedure

Test method Refer as ANSI C63.10: 2013 clause 6.2,


1. The EUT was placed on a non-conducted table, which is 0.8m above horizontal ground plane and 0.4m above vertical ground plane.
2. EUT connected to the line impedance stabilization network (LISN)
3. Receiver set RBW of 9kHz and Detector Peak, and note as quasi-peak and average.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. Recorded Line for Neutral and Line.

#### 4.1.3 Test Setup



## 4.1.4 Test Result

Project No	: TM-2505000232P	Test Date	: 2025-05-27
Operation Band	: BLE	Temp./Humi.	: 25°C / 65%
Test Chamber	: Conduction	Engineer	: Ben.Yang
Probe	: Line	Test Voltage	: AC 120V/60Hz
Note	:		




Freq	Read Level	Factor	Actual FS	Limit	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV	dBuV	dB	PK/QP/AV
0.153	50.34	0.09	50.43	65.82	-15.39	QP
0.153	35.43	0.09	35.52	55.82	-20.30	Average
0.177	48.16	0.08	48.24	64.63	-16.39	QP
0.177	32.15	0.08	32.23	54.63	-22.40	Average
0.197	45.24	0.08	45.32	63.75	-18.43	QP
0.197	29.77	0.08	29.85	53.75	-23.90	Average
0.233	41.46	0.08	41.54	62.35	-20.81	QP
0.233	26.92	0.08	27.00	52.35	-25.35	Average
2.951	14.47	0.12	14.59	56.00	-41.41	QP
2.951	7.17	0.12	7.29	46.00	-38.71	Average
14.763	25.50	0.29	25.79	60.00	-34.21	QP
14.763	19.41	0.29	19.70	50.00	-30.30	Average

Note: 1. Actual FS= Spectrum Read Level + Factor

Note: 2. Margin= Actual FS - Limit

Project No	: TM-2505000232P	Test Date	: 2025-05-27
Operation Band	: BLE	Temp./Humi.	: 25°C / 65%
Test Chamber	: Conduction	Engineer	: Ben.Yang
Probe	: Neutral	Test Voltage	: AC 120V/60Hz
Note	:		




Freq	Read Level	Factor	Actual FS	Limit	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV	dBuV	dB	PK/QP/AV
0.154	50.12	0.10	50.22	65.80	-15.58	QP
0.154	34.75	0.10	34.85	55.80	-20.95	Average
0.185	45.28	0.10	45.38	64.26	-18.88	QP
0.185	30.21	0.10	30.31	54.26	-23.95	Average
0.209	43.05	0.10	43.15	63.26	-20.11	QP
0.209	28.84	0.10	28.94	53.26	-24.32	Average
0.511	19.93	0.08	20.01	56.00	-35.99	QP
0.511	7.47	0.08	7.55	46.00	-38.45	Average
3.494	18.29	0.15	18.44	56.00	-37.56	QP
3.494	8.00	0.15	8.15	46.00	-37.85	Average
17.220	27.30	0.32	27.62	60.00	-32.38	QP
17.220	18.73	0.32	19.05	50.00	-30.95	Average

Note: 1. Actual FS= Spectrum Read Level + Factor

Note: 2. Margin= Actual FS - Limit


Project No	: TM-2505000232P	Test Date	: 2025-05-27
Operation Band	: BLE	Temp./Humi.	: 25°C / 65%
Test Chamber	: Conduction	Engineer	: Ben.Yang
Probe	: Line	Test Voltage	: AC 230V/60Hz
Note	:		



Freq	Read Level	Factor	Actual FS	Limit	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV	dBuV	dB	PK/QP/AV
0.176	43.54	0.08	43.62	64.69	-21.07	QP
0.176	29.58	0.08	29.66	54.69	-25.03	Average
0.203	39.66	0.08	39.74	63.48	-23.74	QP
0.203	26.24	0.08	26.32	53.48	-27.16	Average
0.230	38.27	0.08	38.35	62.44	-24.09	QP
0.230	25.23	0.08	25.31	52.44	-27.13	Average
0.627	21.28	0.07	21.35	56.00	-34.65	QP
0.627	14.25	0.07	14.32	46.00	-31.68	Average
3.451	17.84	0.13	17.97	56.00	-38.03	QP
3.451	9.10	0.13	9.23	46.00	-36.77	Average
15.528	29.41	0.30	29.71	60.00	-30.29	QP
15.528	22.86	0.30	23.16	50.00	-26.84	Average

Note: 1. Actual FS= Spectrum Read Level + Factor  
 Note: 2. Margin= Actual FS - Limit

Project No : TM-2505000232P      Test Date : 2025-05-27  
 Operation Band : BLE      Temp./Humi. : 25°C / 65%  
 Test Chamber : Conduction      Engineer : Ben.Yang  
 Probe : Neutral      Test Voltage : AC 230V/60Hz  
 Note :



Freq	Read Level	Factor	Actual FS	Limit	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV	dBuV	dB	PK/QP/AV
0.168	43.30	0.10	43.40	65.06	-21.66	QP
0.168	28.71	0.10	28.81	55.06	-26.25	Average
0.208	39.75	0.10	39.85	63.29	-23.44	QP
0.208	26.77	0.10	26.87	53.29	-26.42	Average
0.257	35.34	0.09	35.43	61.52	-26.09	QP
0.257	21.88	0.09	21.97	51.52	-29.55	Average
0.492	21.41	0.08	21.49	56.14	-34.65	QP
0.492	13.98	0.08	14.06	46.14	-32.08	Average
3.541	20.18	0.15	20.33	56.00	-35.67	QP
3.541	10.40	0.15	10.55	46.00	-35.45	Average
15.630	29.97	0.31	30.28	60.00	-29.72	QP
15.630	23.11	0.31	23.42	50.00	-26.58	Average

Note: 1. Actual FS= Spectrum Read Level + Factor

Note: 2. Margin= Actual FS - Limit

## 4.2 6dB BANDWIDTH AND OCCUPIED BANDWIDTH(99%)

### 4.2.1 Test Limit

According to §15.247(a)(2),

#### 6 dB Bandwidth :

Limit	Shall be at least 500kHz
-------	--------------------------

Occupied Bandwidth(99%) : For reporting purposes only.

### 4.2.2 Test Procedure

Test method Refer as KDB 558074 D01 and ANSI C63.10: 2013 clause 6.9.2.

1. The EUT RF output connected to the spectrum analyzer by RF cable.
2. Setting maximum power transmit of EUT
3. SA set RBW = 100kHz, VBW = 300kHz and Detector = Peak, to measurement 6 dB Bandwidth.
4. SA set RBW = 1% ~ 5% OBW, VBW = three times the RBW and Detector = Peak, to measurement 99% Bandwidth
5. Measure and record the result of 6 dB Bandwidth and 99% Bandwidth. in the test report.


### 4.2.3 Test Setup

Refer to section 1.8.




## Test Data

### 6dB BANDWIDTH




OBW\_BLE 1M\_LowCH00-2402MHz


### BANDWIDTH 99%




IC OBW\_BLE 1M\_LowCH00-2402MHz




OBW\_BLE 1M\_MidCH20-2442MHz



IC OBW\_BLE 1M\_MidCH20-2442MHz



OBW\_BLE 1M\_HighCH39-2480MHz



IC OBW\_BLE 1M\_HighCH39-2480MHz

## 4.3 OUTPUT POWER MEASUREMENT

### 4.3.1 Test Limit

According to §15.247(b)(3),

**Peak output power** :

#### FCC

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.

Limit	<input checked="" type="checkbox"/> Antenna not exceed 6 dBi : 30dBm <input type="checkbox"/> Antenna with DG greater than 6 dBi [ Limit = 30 – (DG – 6) ] <input type="checkbox"/> Point-to-point operation
-------	---

**Average output power** : For reporting purposes only.

### 4.3.2 Test Procedure

Test method Refer as KDB 558074 D01

1. The EUT RF output connected to the power meter by RF cable.
2. Setting maximum power transmit of EUT.
3. The path loss was compensated to the results for each measurement.
4. Measure and record the result of Peak output power and Average output power. in the test report.

### 4.3.3 Test Setup

Refer to section 1.8.

### 4.3.4 Test Result

Temperature: 26.1°C

Test date: May 28, 2025

Humidity: 57% RH

Tested by: David Li

#### Peak & Average output power :

BLE 1M mode:

CH	Frequency (MHz)	Power Setting	Peak Output Power (dBm)	Required Limit (dBm)
0	2402	default	-1.64	30
20	2442	default	-1.86	30
39	2480	default	-2.07	30
CH	Frequency (MHz)	Power Setting	Avg. Output Power (dBm)	Required Limit (dBm)
0	2402	default	-1.72	30
20	2442	default	-1.94	30
39	2480	default	-2.14	30

**\*Note:**

**1. Measured by power meter, cable loss 0.5 dB + Duty cycle factor has been offsetted to the power meter for Avg. power and cable loss has been offsetted for Peak power measurement.**

## 4.4 POWER SPECTRAL DENSITY

### 4.4.1 Test Limit

According to §15.247(e),

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

Limit	<input checked="" type="checkbox"/> Antenna not exceed 6 dBi : 8dBm <input type="checkbox"/> Antenna with DG greater than 6 dBi [ Limit = 8 – (DG – 6) ] <input type="checkbox"/> Point-to-point operation :
-------	---

### 4.4.2 Test Procedure

Test method Refer as KDB 558074 D01

1. The EUT RF output connected to the spectrum analyzer by RF cable.
2. Setting maximum power transmit of EUT
3. SA set RBW = 3kHz, VBW = 10kHz, Span = 1.5 times DTS Bandwidth (6 dB BW), Detector = Peak, Sweep Time = Auto and Trace = Max hold.
4. The path loss was compensated to the results for each measurement by SA.
5. Mark the maximum level.
6. Measure and record the result of power spectral density. in the test report.

### 4.4.3 Test Setup

Refer to section 1.8.

#### 4.4.4 Test Result

Temperature: 26.1°C

Test date: May 28, 2025

Humidity: 57% RH

Tested by: David Li


##### BLE 1M mode

Frequency (MHz)	RF Power Density (dBm/3kHz)	Maximum Limit (dBm/3kHz)	Result
2402	-12.40	8	PASS
2442	-12.204	8	PASS
2480	-12.03	8	PASS

**\*Note:**

**1.cable loss as 0.5dB that offsets in the spectrum**

## Test Data



PSD\_BLE 1M\_LowCH00-2402MHz



PSD\_BLE 1M\_MidCH20-2442MHz



PSD\_BLE 1M\_HighCH39-2480MHz

## 4.5 CONDUCTED BAND EDGE AND SPURIOUS EMISSION

### 4.5.1 Test Limit

According to §15.247(d),

**FCC:** In any 100 kHz bandwidth outside the authorized frequency band, Non-restricted bands shall be attenuated at least 20 dB/30 dB relative to the maximum PSD level in 100 kHz by RF conducted or a radiated measurement which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

### 4.5.2 Test Procedure

Test method Refer as KDB 558074 D01

1. EUT RF output port connected to the SA by RF cable, and the path loss was compensated to result.
2. SA setting, RBW=100kHz, VBW=300kHz, Detector=Peak, Trace mode = max hold, SWT = Auto.
3. In any 100 kHz bandwidth outside the authorized frequency band, shall be attenuated at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when conducted power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

### 4.5.3 Test Setup

Refer to section 1.8.

### 4.5.4 Test Result

**Temperature:** 26.1°C


**Test date:** May 28, 2025

**Humidity:** 57% RH


**Tested by:** David Li



**Test Data**




Reference Level\_BLE 1M\_LowCH00-2402MHz




Band Edge\_BLE 1M\_LowCH00-2402MHz



Reference Level\_BLE 1M\_MidCH20-2442MHz




Band Edge\_BLE 1M\_HighCH39-2480MHz




Reference Level\_BLE 1M\_HighCH39-2480MHz


## Spurious Emission



Spurious Emission\_BLE 1M\_LowCH00-2402MHz



Spurious Emission\_BLE 1M\_MidCH20-2442MHz



Spurious Emission\_BLE 1M\_HighCH39-2480MHz

## 4.6 RADIATION BANDEDGE AND SPURIOUS EMISSION

### 4.6.1 Test Limit

FCC according to §15.247(d), §15.209 and §15.205,

In any 100 kHz bandwidth outside the authorized frequency band, all harmonic and spurious must be least 20 dB below the highest emission level with the authorized frequency band. Radiation emission which fall in the restricted bands must also follow the FCC section 15.209 as below limit in table.

#### Below 30 MHz

Frequency	Field Strength (microvolts/m)	Magnetic H-Field (microamperes/m)	Measurement Distance (metres)
9-490 kHz	2,400/F (F in kHz)	2,400/F (F in kHz)	300
490-1,705 kHz	24,000/F (F in kHz)	24,000/F (F in kHz)	30
1.705-30 MHz	30	N/A	30

#### Above 30 MHz

Frequency (MHz)	Field Strength microvolts/m at 3 metres (watts, e.i.r.p.)	
	Transmitters	Receivers
30-88	100 (3 nW)	100 (3 nW)
88-216	150 (6.8 nW)	150 (6.8 nW)
216-960	200 (12 nW)	200 (12 nW)
Above 960	500 (75 nW)	500 (75 nW)

**Remark:**

Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open area test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

## 4.6.2 Test Procedure

1. The EUT is placed on a turntable, Above 1 GHz is 1.5m and below 1 GHz is 0.8m above ground plane. The EUT Configured un accordance with ANSI C63.10: 2013, and the EUT set in a continuous mode.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level. And EUT is set 3m away from the receiving antenna, which is scanned from 1m to 4m above the ground plane to find out the highest emissions. Measurement are made polarized in both the vertical and the horizontal positions with antenna.
3. Span shall wide enough to full capture the emission measured. The SA from 9KHz to 26.5GHz set to the low, Mid and High channels with the EUT transmit.
4. No emission found between lowest internal used/generated frequency to 30MHz (9KHz~30MHz).

Radiated emission below 30MHz is measured in a 9m\*6m\*6m semi-ane choic chamber, the measurements correspond to those obtained at an open-field test site. There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

5. The SA setting following :

- (1) Below 30MHz :

(1.1) 9KHz-490KHz : RBW=200Hz / VBW=1kHz / Sweep=AUTO

(1.2) 490KHz-30MHz : RBW=10kHz / VBW=30kHz / Sweep=AUTO

- (2) 30MHz to 1GHz : RBW = 100kHz, VBW  $\geq$  3\*RBW, Sweep = Auto,

Detector = Peak, Trace = Max hold.

- (3) Above 1GHz :

(3.1) For Peak measurement : RBW = 1MHz, VBW  $\geq$  3 RBW, Sweep = Auto,  
Detector = Peak, Trace = Max hold.

(3.2) For Average measurement : RBW = 1MHz, VBW

·If Duty Cycle  $\geq$  98%, VBW=10Hz.

·If Duty Cycle < 98%, VBW=1/T.


6. Data result :

Actual FS=Spectrum Reading Level + Factor


Margin=Actual FS- Limit

## 4.6.3 Test Setup


### 9kHz ~ 30MHz



### 30MHz ~ 1GHz




## Above 1 GHz



## 4.6.4 Test Result

### Band Edge Test Data


Project No	: TM-2505000232P	Test Date	: 2025-05-27
Operation Band	: BLE_1M	Temp./Humi.	: 24.5/58
Frequency	: 2402 MHz	Antenna Pol.	: Vertical
Operation Mode	: Bandedge	Engineer	: Tony.Chao
EUT Pol	: E1	Test Chamber	: 966A
Setting	:		



Trace: 1

Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
2344.97	43.40	6.13	49.53	74.00	-24.47	Peak
2389.43	32.91	6.32	39.23	54.00	-14.77	Average
2402.00	89.08	6.38	95.46	--	--	Peak
2402.00	88.75	6.38	95.13	--	--	Average
2488.35	43.15	6.81	49.96	74.00	-24.04	Peak
2498.34	33.06	6.81	39.87	54.00	-14.13	Average


Project No	: TM-2505000232P	Test Date	: 2025-05-27
Operation Band	: BLE_1M	Temp./Humi.	: 24.5/58
Frequency	: 2402 MHz	Antenna Pol.	: HORIZONTAL
Operation Mode	: Bandedge	Engineer	: Tony.Chao
EUT Pol	: E1	Test Chamber	: 966A
Setting	:		



Trace: 1

Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
2321.99	43.01	6.26	49.27	74.00	-24.73	Peak
2388.93	33.08	6.32	39.40	54.00	-14.60	Average
2402.00	87.06	6.38	93.44	--	--	Peak
2402.00	86.75	6.38	93.13	--	--	Average
2487.85	32.92	6.81	39.73	54.00	-14.27	Average
2497.84	43.14	6.81	49.95	74.00	-24.05	Peak


Project No	: TM-2505000232P	Test Date	: 2025-05-27
Operation Band	: BLE_1M	Temp./Humi.	: 24.5/58
Frequency	: 2480 MHz	Antenna Pol.	: VERTICAL
Operation Mode	: Bandedge	Engineer	: Tony.Chao
EUT Pol	: E1	Test Chamber	: 966A
Setting	:		



Trace: 1

Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
2311.00	32.82	6.38	39.20	54.00	-14.80	Average
2389.43	42.97	6.32	49.29	74.00	-24.71	Peak
2480.00	87.80	6.73	94.53	--	--	Peak
2480.00	87.57	6.73	94.30	--	--	Average
2483.85	34.21	6.77	40.98	54.00	-13.02	Average
2491.85	43.18	6.82	50.00	74.00	-24.00	Peak

Project No	: TM-2505000232P	Test Date	: 2025-05-27
Operation Band	: BLE_1M	Temp./Humi.	: 24.5/58
Frequency	: 2480 MHz	Antenna Pol.	: HORIZONTAL
Operation Mode	: Bandedge	Engineer	: Tony.Chao
EUT Pol	: E1	Test Chamber	: 966A
Setting	:		




Trace: 1

Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
2311.00	32.83	6.38	39.21	54.00	-14.79	Average
2327.99	43.31	6.24	49.55	74.00	-24.45	Peak
2480.00	87.18	6.73	93.91	--	--	Peak
2480.00	86.93	6.73	93.66	--	--	Average
2483.85	34.04	6.77	40.81	54.00	-13.19	Average
2486.85	43.05	6.80	49.85	74.00	-24.15	Peak


## TX Test Data

Project No	: TM-2505000232P	Test Date	: 2025-05-27
Operation Band	: BLE_1M	Temp./Humi.	: 24.5/58
Frequency	: 2442 MHz	Antenna Pol.	: VERTICAL
Operation Mode	: TX	Engineer	: Tony.Chao
EUT Pol	: E1	Test Chamber	: 966A
Setting	:		




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
34.20	42.35	-5.82	36.53	40.00	-3.47	Peak
48.20	50.21	-15.17	35.04	40.00	-4.96	Peak
149.00	38.41	-11.04	27.37	43.50	-16.13	Peak
221.20	42.60	-12.51	30.09	46.00	-15.91	Peak
297.00	43.89	-9.45	34.44	46.00	-11.56	Peak
525.00	35.73	-4.22	31.51	46.00	-14.49	Peak

Project No	: TM-2505000232P	Test Date	: 2025-05-27
Operation Band	: BLE_1M	Temp./Humi.	: 24.5/58
Frequency	: 2442 MHz	Antenna Pol.	: HORIZONTAL
Operation Mode	: TX	Engineer	: Tony.Chao
EUT Pol	: E1	Test Chamber	: 966A
Setting	:		




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
47.30	46.16	-14.88	31.28	40.00	-8.72	Peak
151.00	41.30	-10.94	30.36	43.50	-13.14	Peak
270.40	45.49	-9.68	35.81	46.00	-10.19	Peak
408.40	40.16	-6.48	33.68	46.00	-12.32	Peak
567.90	35.74	-3.34	32.40	46.00	-13.60	Peak
891.00	40.49	1.46	41.95	46.00	-4.05	Peak

Project No	: TM-2505000232P	Test Date	: 2025-05-27
Operation Band	: BLE_1M	Temp./Humi.	: 24.5/58
Frequency	: 2402 MHz	Antenna Pol.	: VERTICAL
Operation Mode	: TX	Engineer	: Tony.Chao
EUT Pol	: E1	Test Chamber	: 966A
Setting	:		




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4804.00	46.10	2.40	48.50	74.00	-25.50	Peak
4804.00	42.33	2.40	44.73	54.00	-9.27	Average
7206.00	35.73	8.96	44.69	74.00	-29.31	Peak
7206.00	26.50	8.96	35.46	54.00	-18.54	Average

Project No	: TM-2505000232P	Test Date	: 2025-05-27
Operation Band	: BLE_1M	Temp./Humi.	: 24.5/58
Frequency	: 2402 MHz	Antenna Pol.	: HORIZONTAL
Operation Mode	: TX	Engineer	: Tony.Chao
EUT Pol	: E1	Test Chamber	: 966A
Setting	:		




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4804.00	42.58	2.40	44.98	74.00	-29.02	Peak
4804.00	37.41	2.40	39.81	54.00	-14.19	Average
7206.00	35.17	8.96	44.13	74.00	-29.87	Peak
7206.00	26.52	8.96	35.48	54.00	-18.52	Average

Project No	: TM-2505000232P	Test Date	: 2025-05-27
Operation Band	: BLE_1M	Temp./Humi.	: 24.5/58
Frequency	: 2442 MHz	Antenna Pol.	: VERTICAL
Operation Mode	: TX	Engineer	: Tony.Chao
EUT Pol	: E1	Test Chamber	: 966A
Setting	:		




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4884.00	46.48	2.70	49.18	74.00	-24.82	Peak
4884.00	43.53	2.70	46.23	54.00	-7.77	Average
7326.00	35.98	9.39	45.37	74.00	-28.63	Peak
7326.00	26.54	9.39	35.93	54.00	-18.07	Average

Project No	: TM-2505000232P	Test Date	: 2025-05-27
Operation Band	: BLE_1M	Temp./Humi.	: 24.5/58
Frequency	: 2442 MHz	Antenna Pol.	: HORIZONTAL
Operation Mode	: TX	Engineer	: Tony.Chao
EUT Pol	: E1	Test Chamber	: 966A
Setting	:		




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4884.00	40.43	2.70	43.13	74.00	-30.87	Peak
4884.00	37.29	2.70	39.99	54.00	-14.01	Average
7326.00	35.35	9.39	44.74	74.00	-29.26	Peak
7326.00	26.49	9.39	35.88	54.00	-18.12	Average

Project No	: TM-2505000232P	Test Date	: 2025-05-27
Operation Band	: BLE_1M	Temp./Humi.	: 24.5/58
Frequency	: 2480 MHz	Antenna Pol.	: VERTICAL
Operation Mode	: TX	Engineer	: Tony.Chao
EUT Pol	: E1	Test Chamber	: 966A
Setting	:		



Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4960.00	44.60	3.52	48.12	74.00	-25.88	Peak
4960.00	39.75	3.52	43.27	54.00	-10.73	Average
7440.00	35.47	9.46	44.93	74.00	-29.07	Peak
7440.00	26.32	9.46	35.78	54.00	-18.22	Average

Project No	: TM-2505000232P	Test Date	: 2025-05-27
Operation Band	: BLE_1M	Temp./Humi.	: 24.5/58
Frequency	: 2480 MHz	Antenna Pol.	: HORIZONTAL
Operation Mode	: TX	Engineer	: Tony.Chao
EUT Pol	: E1	Test Chamber	: 966A
Setting	:		



Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4960.00	42.97	3.52	46.49	74.00	-27.51	Peak
4960.00	37.40	3.52	40.92	54.00	-13.08	Average
7440.00	35.27	9.46	44.73	74.00	-29.27	Peak
7440.00	26.33	9.46	35.79	54.00	-18.21	Average

**- End of Test Report -**