

FCC TEST REPORT

according to

FCC Rules and Regulations

Part 15 Subpart C

Applicant	: SerComm Corporation
Address	: 8F, No. 3-1, YuanQu St., NanKang, Taipei 115, Taiwan, R.O.C.
Equipment	: Pre-N Wireless USB Dongle
Model No.	: UB801Rn
FCC ID	: P27UB801RN
Trade Name	: SerComm

Laboratory Accreditation



- The test result refers exclusively to the test presented test model / sample.,
- Without written approval of **Exclusive Certification Corp.** the test report shall not be reproduced except in full.
- The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

Contents

1.	Report of Measurements and Examinations.....	5
1.1	List of Measurements and Examinations	5
2.	Test Configuration of Equipment under Test.....	6
2.1	Feature of Equipment under Test.....	6
2.2	RF Specifications	7
2.3	Test Mode & Test Software	8
2.4	Description of Test System.....	8
2.5	Connection Diagram of Test System.....	9
2.6	General Information of Test.....	10
2.7	Measurement Uncertainty	10
2.8	History of this test report	11
3.	Antenna Requirements.....	12
3.1	Standard Applicable	12
3.2	Antenna Construction and Directional Gain.....	12
4.	Test of Conducted Emission.....	13
4.1	Test Limit.....	13
4.2	Test Procedures.....	13
4.3	Typical Test Setup	14
4.4	Measurement equipment	14
4.5	Test Result and Data.....	15
4.6	Test Photographs	21
5.	Test of Radiated Emission	22
5.1	Test Limit.....	22
5.2	Test Procedures.....	23
5.3	Typical Test Setup	24
5.4	Measurement equipment	24
5.5	Test Result and Data.....	25
5.6	Test Photographs	61
6.	6dB Bandwidth Measurement Data.....	62
6.1	Test Limit	62
6.2	Test Procedures	62
6.3	Test Setup Layout	62
6.4	Measurement equipment	62
6.5	Test Result and Data.....	62
7.	Maximum Peak Output Power	72
7.1	Test Limit	72
7.2	Test Procedures	72
7.3	Test Setup Layout	72
7.4	Measurement equipment	72
7.5	Test Result and Data.....	72
8.	Band Edges Measurement.....	82
8.1	Test Limit	82
8.2	Test Procedure :	82
8.3	Test Setup Layout	82
8.4	Measurement equipment	82
8.5	Test Result and Data.....	82

8.6	Restrict band emission Measurement Data	95
9.	Power Spectral Density	97
9.1	Test Limit	97
9.2	Test Procedures	97
9.3	Test Setup Layout :	97
9.4	List of Measuring Equipment Used	97
9.5	Test Result and Data	97
10.	Restricted Bands of Operation	108
10.1	Labeling Requirement	108
Appendix A. Photographs of EUT.....		A1 ~ A5

CERTIFICATE OF COMPLIANCE

according to

FCC Rules and Regulations

Part 15 Subpart C


Applicant	: SerComm Corporation
Address	: 8F, No. 3-1, YuanQu St., NanKang, Taipei 115, Taiwan, R.O.C.
Equipment	: Pre-N Wireless USB Dongle
Model No.	: UB801Rn
FCC ID	: P27UB801RN

I **HEREBY** CERTIFY THAT :

The measurements shown in this test report were made in accordance with the procedures given in **ANSI C63.4** The equipment was **passed** the test performed according to **FCC Rules and Regulations Part 15 Subpart C (2005)**.

The test was carried out on Sep. 28, 2007 at **Exclusive Certification Corp.**

Signature


Anson Chou / Manager

1. Report of Measurements and Examinations

1.1 List of Measurements and Examinations

FCC Rule	Description of Test	Result
15.203	. Antenna Requirement	Pass
15.207	. Conducted Emission	Pass
15.209 15.247(d)	. Radiated Emission	Pass
15.247(a)(2)	. 6dB Bandwidth	Pass
15.247(b)	. Maximum Peak Output Power	Pass
15.247(d)	. 100kHz Bandwidth of Frequency Band Edges	Pass
15.247(e)	. Power Spectral Density	Pass
1.1307 1.1310 2.1091 2.1093	. RF Exposure Compliance	Pass

2. Test Configuration of Equipment under Test

2.1 Feature of Equipment under Test

Model	UB801Rn	
Chipset:	Ralink RT2870	
RF Chip:	Ralink RT2820	
Bus Type:	USB 2.0	
Data Rates:	20 MHz BW: 130, 117, 104, 78, 52, 39, 26, 13 (802.11n)	
	40 MHz BW: 300, 270, 243, 216, 162, 108, 81, 54, 27	
	54, 48, 36, 24, 18, 12, 9, and 6 Mbps (802.11g)	
	11, 5.5, 2, 1 Mbps (802.11b)	
Frequency Band:	2.4GHz to 2.5GHz	
Wireless Medium:	DSSS and OFDM	
Media Access Protocol:	CSMA/CA	
Operating Channels:	1-11	
Wireless Medium:	Draft 802.11n	BPSK, QPSK, 16-QAM, 64-QAM
	802.11g	OFDM
	802.11b	CCK, QPSK, BPSK
Media Access Protocol:	CSMA/CA	
Transmit Power:	802.11n:	20±1 dBm
	802.11g:	16±1 dBm
	802.11b:	16±1 dBm
Security:	WPA/WPA2; 128-bit TKIP/AES encryption, 40/64-, 128-bit WEP shared-key encryption 802.1x, and EAP-TLS, and PEAP authentication WPS	
Standards Conformance:	WPA certified, IEEE 802.11g, IEEE 802.11b, IEEE 802.11n	
EMI:	FCC, CE	
Environmental Range:	Operating temperature:	0° to 40°C (32° to 104°F)
	Operating humidity:	0 to 90% non-condensing

2.2 RF Specifications

Spreading 802.11b: DSSS, CCK, QPSK, BPSK 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11n, 20MHz: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11n, 40MHz: OFDM (64QAM, 16QAM, QPSK, BPSK)
Frequency Range 2.4 ~ 2.472 GHz
Number of Channels USA, Canada and Taiwan: 1 ~ 11 Most European Countries: 1 ~ 13
Data Rate 802.11b: 11, 5.5, 2, 1Mbps 802.11g: 54, 48, 36, 24, 18, 12, 9, 6 Mbps 802.11n, 20MHz: 130, 117, 104, 78, 52, 39, 26, 13 Mbps 802.11n, 40MHz: 300, 270, 243, 216, 162, 108, 81, 54, 27 Mbps
Modulation 802.11b: DSSS, CCK, QPSK, BPSK 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11n, 20MHz: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11n, 40MHz: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna PIFA Antenna 22MM-1 (Peak gain): 1.810dBi 22MM-2 (Peak gain): 1.779dBi
Transmit Power FCC: 802.11b: 16 ± 1 dBm 802.11g: 16 ± 1 dBm 802.11n, 20MHz: 20 ± 1 dBm 802.11n, 40MHz: 20 ± 1 dBm ETSI: (EIRP) 802.11b: 14.81dBm 802.11g: 14.81dBm 802.11n, 20MHz: 17.81dBm 802.11n, 40MHz: 17.81dBm

2.3 Test Mode & Test Software

- a. During testing, the interface cables and equipment positions were varied according to ANSI C63.4
- b. The complete test system included IBM PC, Monitor, Keyboard, Mouse, Modem, Printer and EUT for EMI test.
- c. An executive program, EMITEST.exe under WIN XP, which generates a complete line of continuously repeating "H" pattern was used as the test software.


The program was executed as follows:

1. Turn on the power of all equipment.
 2. The PC reads the test program from the hard disk drive and runs it.
 3. The PC sends "H" messages to the monitor, and the monitor displays "H" patterns on the screen.
 4. The PC sends "H" messages to the modem.
 5. The PC sends "H" messages to the printer.
 6. The PC sends "H" messages to the internal Hard Disk, and the Hard Disk reads and writes the message.
 7. Repeat the steps from 2 to 6.
- d. An executive program, RT2870QA.exe under WIN XP, which generates a continuous signal by the following frequency to test.
 - 802.11b (CH 01: 2412MHz) • 802.11b (CH 06: 2437MHz) • 802.11b (CH 11: 2462MHz)
 - 802.11g (CH 01: 2412MHz) • 802.11g (CH 06: 2437MHz) • 802.11g (CH 11: 2462MHz)

2.4 Description of Test System

Device	Manufacturer	Model No.	Description
PC	IBM	IGV	Power Cable, Unshielding 1.8 m
Monitor	SlimAGE	510A	Power Cable, Adapter Unshielding 1.8 m Data Cable, VGA Shielding 1.35 m
Keyboard	IBM	KB-0225	Data Cable, PS2 Shielding 1.85 m
Mouse	IBM	MO28VO	Data Cable, USB Shielding 1.85 m
Modem	ACEXX	DM-1414	Power Cable, Adapter Unshielding 1.8 m Data Cable, RS232 Shielding 1.35 m
Printer	hp	Desk Jet 400	Power Cable, Adapter Unshielding 1.8 m Data Cable, PRINT Shielding 1.6 m

2.5 Connection Diagram of Test System



1. The PS2 cable is connected from PC to the Keyboard.
2. The USB cable is connected from PC to the Mouse.
3. The VGA cable is connected from PC to the Monitor.
4. The PRINT cable is connected from PC to the Printer.
5. The RS232 cable is connected from PC to the Modem.

2.6 General Information of Test

Test Site :	Exclusive Certification Corp. 4F-2, No. 28, Lane 78, Xing-Ai Rd. Nei-hu, Taipei City 114 Taiwan R.O.C.
Test Site Location (OATS1-SD):	No.68-1, Shihbachongsi, shihding Township, Taipei City 223, Taiwan, R.O.C. Registration Number: 632249.
FCC Registration Number :	632249
IC Registration Number :	6597A-1
VCCI Registration Number :	T-182 for Telecommunication Test C-2188 for Conducted emission test R-1902 for Radiated emission test
Test Voltage:	AC 120V/ 60Hz
Test in Compliance with:	ANSI C63.4-2003 FCC Part 15 Subpart C
Frequency Range Investigated:	Conducted: from 150kHz to 30 MHz Radiation: from 30 MHz to 24620MHz
Test Distance:	The test distance of radiated emission from antenna to EUT is 3 M.

2.7 Measurement Uncertainty

Measurement Item	Measurement Frequency	Polarization	Uncertainty
Conducted Emission	9 kHz ~ 30 MHz	LINE/NEUTRAL	2.71 dB
Radiated Emission	30 MHz ~ 1GHz	Vertical	4.11 dB
		Horizontal	4.10 dB
6 dB Bandwidth	---	---	7500 Hz
Maximum Peak Output Power	---	---	1.4 dB
100kHz Bandwidth of Frequency Band Edges	---	---	2.2 dB
Power Spectral Density	---	---	2.2 dB

2.8 History of this test report

■ ORIGINAL.

☐ Additional attachment as following record:

[illegible]

3. Antenna Requirements

3.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

3.2 Antenna Construction and Directional Gain

Antenna 1 (22MM-1):

Antenna type: PIFA Antenna

Antenna Gain: 1.810 dBi.

Antenna 2 (22MM-2):

Antenna type: PIFA Antenna

Antenna Gain: 1.779 dBi.

4. Test of Conducted Emission

4.1 Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz on the 120 VAC power and return leads of the EUT according to the methods defined in ANSI C63.4-2003 Section 3.1. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in section 2.2. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.


Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50

*Decreases with the logarithm of the frequency.

4.2 Test Procedures

- The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- Connect EUT to the power mains through a line impedance stabilization network (LISN).
- All the support units are connecting to the other LISN.
- The LISN provides 50 ohm coupling impedance for the measuring instrument.
- The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
- Both sides of AC line were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched.
- Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

4.3 Typical Test Setup




4.4 Measurement equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date.
Receiver	R&S	ESCI	100443	2007/09/27	2008/09/26
LISN	NNB-2/16Z	MESS TEC	02/10191	2007/05/14	2008/05/13
LISN	NNB-2/16Z	ROLF HEINE	03/10058	2007/04/19	2008/04/18

4.5 Test Result and Data

Power	: DC 5V from PC	Pol/Phase	: LINE
Test Mode	: 802.11g CH1	Temperature	: 26 °C
Memo	:	Humidity	: 60 %




Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark
	MHz	dBuV	dB	dBuV	dBuV	dBuV	
1	0.15	51.50	0.10	51.60	65.99	-14.39	QP
2	0.15	22.48	0.10	22.58	55.99	-33.41	AVERAGE
3	0.17	49.33	0.10	49.43	64.82	-15.40	QP
4	0.17	30.81	0.10	30.91	54.82	-23.91	AVERAGE
5	0.22	46.53	0.11	46.64	62.71	-16.06	QP
6	0.22	38.96	0.11	39.07	52.71	-13.64	AVERAGE
7	0.27	43.15	0.12	43.27	61.01	-17.74	QP
8	0.27	17.18	0.12	17.29	51.01	-33.71	AVERAGE
9	0.32	42.90	0.12	43.02	59.62	-16.61	QP
10	0.32	23.76	0.12	23.88	49.62	-25.74	AVERAGE
11	0.37	44.64	0.12	44.76	58.45	-13.70	QP
12	0.37	29.33	0.12	29.45	48.45	-19.01	AVERAGE

Remarks: 1. Level = Read Level + Factor
 2. Factor = LISN(ISN) Factor + Cable Loss
 3. All emission below 1GHz at 802.11b/g mode are all the same,so the 802.11g mode chosen as representative in final test.
 4. According to technical experiences,all spurious emission of 802.11g mode at channel 1,6,11 are almost the same below 1GHz,so that the channel 1 was chosen as representative in final test.
 5. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: NEUTRAL
Test Mode	: 802.11g CH1	Temperature	: 26 °C
Memo	:	Humidity	: 60 %



Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark
	MHz	dBuV	dB	dBuV	dBuV	dBuV	
1	0.19	47.93	0.09	48.02	64.22	-16.20	QP
2	0.19	18.72	0.09	18.81	54.22	-35.42	AVERAGE
3	0.22	46.64	0.09	46.73	62.79	-16.05	QP
4	0.22	39.14	0.09	39.23	52.79	-13.55	AVERAGE
5	0.28	44.58	0.10	44.68	60.80	-16.12	QP
6	0.28	25.44	0.10	25.54	50.80	-25.26	AVERAGE
7	0.33	44.33	0.10	44.44	59.54	-15.10	QP
8	0.33	32.08	0.10	32.18	49.54	-17.36	AVERAGE
9	0.37	44.30	0.11	44.40	58.40	-14.00	QP
10	0.37	25.32	0.11	25.42	48.40	-22.98	AVERAGE
11	0.43	44.10	0.11	44.21	57.28	-13.07	QP
12	0.43	18.44	0.11	18.55	47.28	-28.73	AVERAGE
13	0.51	44.50	0.12	44.62	56.00	-11.38	QP
14	0.51	17.61	0.12	17.73	46.00	-28.27	AVERAGE

Remarks: 1. Level = Read Level + Factor

2. Factor = LISN(ISN) Factor + Cable Loss

24 0.44 37.50 0.11 37.61 57.02 -19.41 QP

Remarks: 1. Level = Read Level + Factor


2. Factor = LISN(ISN) Factor + Cable Loss

3. All emission below 1GHz at 802.11b/g mode are all the same,so the 802.11g mode chosen as representative in final test.

4. According to technical experiences,all spurious emission of 802.11g mode at channel 1,6,11 are almost the same below 1GHz,so that the channel 1 was chosen as representative in final test.

5. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: LINE
Test Mode	: 802.11n, 20MHz BW CH1	Temperature	: 26 °C
Memo	:	Humidity	: 60 %




Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark
	MHz	dBuV	dB	dBuV	dBuV	dBuV	
1	0.15	34.48	0.10	34.58	56.00	-21.42	AVERAGE
2	0.15	55.52	0.10	55.62	66.00	-10.38	QP
3	0.16	24.10	0.10	24.20	55.54	-31.34	AVERAGE
4	0.16	49.69	0.10	49.79	65.54	-15.74	QP
5	0.22	45.37	0.11	45.48	62.99	-17.52	QP
6	0.22	32.36	0.11	32.47	52.99	-20.52	AVERAGE
7	0.26	42.78	0.12	42.90	61.28	-18.38	QP
8	0.26	16.55	0.12	16.67	51.28	-34.62	AVERAGE
9	0.32	42.52	0.12	42.64	59.80	-17.16	QP
10	0.32	26.46	0.12	26.58	49.80	-23.22	AVERAGE
11	0.36	41.89	0.12	42.01	58.66	-16.64	QP
12	0.36	24.88	0.12	25.00	48.66	-23.65	AVERAGE

Remarks:

1. Level = Read Level + Factor
2. Factor = LISN(ISN) Factor + Cable Loss
3. According to technical experiences, all spurious emission of 802.11MIMO mode at channel 1,6,11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
4. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: NEUTRAL
Test Mode	: 802.11n, 20MHz BW CH1	Temperature	: 26 °C
Memo	:	Humidity	: 60 %




Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark
	MHz	dBuV	dB	dBuV	dBuV	dBuV	
1	0.16	50.00	0.09	50.09	65.41	-15.32	QP
2	0.16	24.11	0.09	24.20	55.41	-31.21	AVERAGE
3	0.21	47.62	0.09	47.71	63.17	-15.46	QP
4	0.21	19.86	0.09	19.95	53.17	-33.22	AVERAGE
5	0.26	45.27	0.10	45.37	61.56	-16.19	QP
6	0.26	24.49	0.10	24.59	51.56	-26.97	AVERAGE
7	0.30	43.70	0.10	43.81	60.14	-16.34	QP
8	0.30	16.92	0.10	17.02	50.14	-33.12	AVERAGE
9	0.36	43.81	0.11	43.91	58.80	-14.89	QP
10	0.36	19.92	0.11	20.03	48.80	-28.77	AVERAGE
11	0.52	45.30	0.12	45.43	56.00	-10.57	QP
12	0.52	18.95	0.12	19.07	46.00	-26.93	AVERAGE

Remarks:

1. Level = Read Level + Factor
2. Factor = LISN(ISN) Factor + Cable Loss
3. According to technical experiences, all spurious emission of 802.11MIMO mode at channel 1,6,11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
4. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: LINE
Test Mode	: 802.11n, 40MHz BW CH3	Temperature	: 26 °C
Memo	:	Humidity	: 60 %




Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark
	MHz	dBuV	dB	dBuV	dBuV	dBuV	
1	0.16	50.54	0.10	50.64	65.58	-14.94	QP
2	0.16	25.26	0.10	25.36	55.58	-30.22	AVERAGE
3	0.21	48.11	0.11	48.21	63.16	-14.95	QP
4	0.21	19.77	0.11	19.88	53.16	-33.28	AVERAGE
5	0.26	46.53	0.12	46.64	61.28	-14.64	QP
6	0.26	18.33	0.12	18.45	51.28	-32.83	AVERAGE
7	0.31	44.79	0.12	44.91	59.91	-14.99	QP
8	0.31	22.65	0.12	22.77	49.91	-27.13	AVERAGE
9	0.36	44.29	0.12	44.41	58.64	-14.23	QP
10	0.36	27.12	0.12	27.24	48.64	-21.40	AVERAGE
11	0.52	45.30	0.13	45.43	56.00	-10.57	QP
12	0.52	18.60	0.13	18.73	46.00	-27.27	AVERAGE

Remarks:

1. Level = Read Level + Factor
2. Factor = LISN(ISN) Factor + Cable Loss
3. According to technical experiences, all spurious emission of 802.11MIMO mode at channel 3, 6, 9 are almost the same below 1GHz, so that the channel 3 was chosen as representative in final test.
4. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: NEUTRAL
Test Mode	: 802.11n, 40MHz BW CH3	Temperature	: 26 °C
Memo	:	Humidity	: 60 %



Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark
	MHz	dBuV	dB	dBuV	dBuV	dBuV	
1	0.20	48.12	0.09	48.21	63.75	-15.54	QP
2	0.20	18.66	0.09	18.75	53.75	-35.00	AVERAGE
3	0.24	45.01	0.10	45.10	62.07	-16.97	QP
4	0.24	22.87	0.10	22.97	52.07	-29.10	AVERAGE
5	0.33	44.95	0.10	45.05	59.33	-14.28	QP
6	0.33	32.86	0.10	32.97	49.33	-16.36	AVERAGE
7	0.39	45.70	0.11	45.81	58.12	-12.30	QP
8	0.39	19.47	0.11	19.58	48.12	-28.53	AVERAGE
9	0.53	35.56	0.12	35.68	56.00	-20.32	QP
10	0.53	14.58	0.12	14.71	46.00	-31.29	AVERAGE
11	0.62	33.99	0.13	34.12	56.00	-21.88	QP
12	0.62	9.85	0.13	9.97	46.00	-36.03	AVERAGE
13	1.58	31.24	0.18	31.42	56.00	-24.58	QP
14	1.58	12.28	0.18	12.46	46.00	-33.54	AVERAGE

Remarks:

1. Level = Read Level + Factor
2. Factor = LISN(ISN) Factor + Cable Loss
3. According to technical experiences, all spurious emission of 802.11MIMO mode at channel 3,6,9 are almost the same below 1GHz, so that the channel 3 was chosen as representative in final test.
4. The data is worse case.

Test engineer: Ben

5. Test of Radiated Emission

5.1 Test Limit

Radiated emissions from 30 MHz to 25 GHz were measured according to the methods defines in ANSI C63.4-2003. The EUT was placed, 0.8 meter above the ground plane, as shown in section 5.6.3. The interface cables and equipment positions were varied within limits of reasonable applications to determine the positions producing maximum radiated emissions. For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency (MHz)	Distance Meters	Radiated (μ V / M)	Radiated (dB μ V / M)
30-88	3	100	40.0
88-216	3	150	43.5
216-960	3	200	46.0
Above 960	3	500	54.0


For unintentional device, according to CISPR PUB.22, for Class B digital devices, the general requirement of field strength of radiated emissions from intentional radiators at a distance of 10 meters shall not exceed the below table.

Frequency (MHz)	Distance Meters	Radiated (dB μ V / M)
30-230	10	30
230-1000	10	37

5.2 Test Procedures

- a. The EUT was placed on a rotatable table top 0.8 meter above ground.
- b. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- f. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
- h. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

5.3 Typical Test Setup




5.4 Measurement equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date
EMI Receiver	85460A	HP	3807A00454	2007/06/05	2008/06/04
Spectrum Analyzer	FSP40	R&S	10047	2007/01/23	2008/01/22
Horn Antenna	3115	EMCO	31589	2007/03/05	2008/03/04
Horn Antenna	3116	EMCO	31970	2007/03/06	2008/03/05
Bilog Antenna	CBL6112B	Schaffner	2840	2007/04/26	2008/04/25
Amplifier	8449B	Agilent	3008A01954	2007/01/12	2008/01/11
Amplifier	8447D	Agilent	2944A10531	2007/09/26	2008/09/25

5.5 Test Result and Data


Power	: DC 5V from PC	Pol/Phase	: VERTICAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 1	Humidity	: 65 %
Modulation Type	: 802.11g	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 24 Mbps



Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g mode are all the same, so the 802.11g mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g mode at channel 1, 6, 11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
6. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: VERTICAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 1	Humidity	: 65 %
Modulation Type	: 802.11g	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 24 Mbps




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	503.00	43.60	-4.57	39.02	46.00	-6.98	Peak	100	85
2	534.50	40.05	-2.90	37.15	46.00	-8.85	Peak	100	167
3	568.10	42.47	-4.48	37.99	46.00	-8.01	Peak	100	0
4	666.10	40.36	-4.54	35.82	46.00	-10.18	Peak	100	10
5	736.10	43.29	-3.38	39.91	46.00	-6.09	Peak	100	241
6	761.30	38.30	-2.77	35.53	46.00	-10.47	Peak	100	314

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g mode are all the same, so the 802.11g mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g mode at channel 1, 6, 11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
6. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: HORIZONTAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 1	Humidity	: 65 %
Modulation Type	: 802.11g	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 24 Mbps




Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	196.93	50.83	-20.20	30.63	43.50	-12.87	Peak	200	124
2	224.43	53.25	-19.15	34.11	46.00	-11.89	Peak	200	174
3	232.13	55.57	-18.36	37.21	46.00	-8.79	Peak	200	222
4	249.45	49.61	-16.83	32.78	46.00	-13.22	Peak	200	314
5	265.95	52.58	-15.13	37.45	46.00	-8.55	Peak	200	323
6	274.75	49.95	-14.37	35.58	46.00	-10.42	Peak	200	0

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g mode are all the same, so the 802.11g mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g mode at channel 1, 6, 11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
6. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: HORIZONTAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 1	Humidity	: 65 %
Modulation Type	: 802.11g	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 24 Mbps




Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	363.00	54.03	-11.87	42.16	46.00	-3.84	QP	200	24
2	402.90	51.08	-8.86	42.22	46.00	-3.78	QP	200	165
3	435.80	48.69	-7.87	40.81	46.00	-5.19	QP	200	324
4	503.00	47.57	-6.48	41.09	46.00	-4.91	QP	200	0
5	568.10	46.60	-4.55	42.05	46.00	-3.95	QP	200	44
6	601.70	37.28	-2.36	34.91	46.00	-11.09	Peak	100	0
7	637.40	45.76	-4.83	40.93	46.00	-5.07	QP	200	12
8	668.20	41.09	-4.37	36.72	46.00	-9.28	Peak	200	50

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g mode are all the same, so the 802.11g mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g mode at channel 1, 6, 11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
6. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: VERTICAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 1	Humidity	: 65 %
Modulation Type	: 802.11b	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 11 Mbps




Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4824.10	30.16	8.64	38.80	54.00	-15.20	Average	100	149
2	4824.10	41.82	8.64	50.46	74.00	-23.54	Peak	100	149

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: HORIZONTAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 1	Humidity	: 65 %
Modulation Type	: 802.11b	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 11 Mbps




Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4824.10	41.76	8.64	50.40	74.00	-23.60	Peak	100	177
2	4824.10	30.24	8.64	38.88	54.00	-15.12	Average	100	177

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: VERTICAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 6	Humidity	: 65 %
Modulation Type	: 802.11b	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 11 Mbps




Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4874.50	41.47	8.78	50.25	74.00	-23.75	Peak	100	149
2	4874.50	30.10	8.78	38.88	54.00	-15.12	Average	100	149

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: HORIZONTAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 6	Humidity	: 65 %
Modulation Type	: 802.11b	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 11 Mbps




Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4875.90	43.06	8.79	51.84	74.00	-22.16	Peak	100	177
2	4875.90	31.59	8.79	40.37	54.00	-13.63	Average	100	177

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.


Power	: DC 5V from PC	Pol/Phase	: VERTICAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 11	Humidity	: 65 %
Modulation Type	: 802.11b	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 11 Mbps



Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: HORIZONTAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 11	Humidity	: 65 %
Modulation Type	: 802.11b	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 11 Mbps




Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4924.30	30.60	8.93	39.53	54.00	-14.47	Average	100	177
2	4924.30	42.63	8.93	51.55	74.00	-22.45	Peak	100	177

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.


Power	: DC 5V from PC	Pol/Phase	: VERTICAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 1	Humidity	: 65 %
Modulation Type	: 802.11g	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 24 Mbps



Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: HORIZONTAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 1	Humidity	: 65 %
Modulation Type	: 802.11g	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 24 Mbps




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4824.00	30.27	8.64	38.91	54.00	-15.09	Average	100	177
2	4824.00	41.73	8.64	50.37	74.00	-23.63	Peak	100	177

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: VERTICAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 6	Humidity	: 65 %
Modulation Type	: 802.11g	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 24 Mbps




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4874.20	41.19	8.78	49.97	74.00	-24.03	Peak	100	149
2	4874.20	29.97	8.78	38.75	54.00	-15.25	Average	100	149

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: HORIZONTAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 6	Humidity	: 65 %
Modulation Type	: 802.11g	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 24 Mbps




Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4874.60	42.30	8.78	51.08	74.00	-22.92	Peak	100	177
2	4874.60	31.10	8.78	39.89	54.00	-14.11	Average	100	177

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: VERTICAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 11	Humidity	: 65 %
Modulation Type	: 802.11g	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 24 Mbps




Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4923.70	41.63	8.92	50.55	74.00	-23.45	Peak	100	149
2	4923.70	30.18	8.92	39.10	54.00	-14.90	Average	100	149

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: HORIZONTAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 11	Humidity	: 65 %
Modulation Type	: 802.11g	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 24 Mbps




Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4923.80	41.74	8.92	50.66	74.00	-23.34	Peak	100	177
2	4923.80	30.40	8.92	39.32	54.00	-14.68	Average	100	177

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.


Power	: DC 5V from PC	Pol/Phase	: VERTICAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 1	Humidity	: 65 %
Modulation Type	: 802.11n, 20MHz BW	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 130 Mbps



Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. According to technical experiences, all spurious emission of 802.11MIMO mode at channel 1,6,11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
5. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: VERTICAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 1	Humidity	: 65 %
Modulation Type	: 802.11n, 20MHz BW	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 130 Mbps




Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	503.70	46.17	-4.46	41.71	46.00	-4.29	QP	100	84
2	534.50	43.91	-2.90	41.01	46.00	-4.99	QP	100	0
3	568.10	44.41	-4.48	39.92	46.00	-6.08	Peak	100	214
4	657.70	44.20	-4.67	39.54	46.00	-6.46	Peak	100	257
5	735.40	43.99	-3.45	40.54	46.00	-5.46	QP	100	41
6	817.30	39.92	-1.16	38.76	46.00	-7.24	Peak	100	0

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. According to technical experiences, all spurious emission of 802.11MIMO mode at channel 1,6,11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
5. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: HORIZONTAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 1	Humidity	: 65 %
Modulation Type	: 802.11n, 20MHz BW	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 130 Mbps




Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	197.75	54.96	-20.04	34.93	43.50	-8.57	Peak	200	74
2	232.13	57.29	-18.36	38.93	46.00	-7.07	Peak	200	0
3	249.45	50.31	-16.83	33.47	46.00	-12.53	Peak	200	70
4	265.40	49.47	-15.12	34.35	46.00	-11.65	Peak	200	352
5	274.75	50.14	-14.37	35.77	46.00	-10.23	Peak	200	58
6	299.50	44.42	-14.99	29.43	46.00	-16.57	Peak	200	0

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. According to technical experiences, all spurious emission of 802.11MIMO mode at channel 1, 6, 11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
5. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: HORIZONTAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 1	Humidity	: 65 %
Modulation Type	: 802.11n, 20MHz BW	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 130 Mbps




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	503.00	45.10	-6.48	38.62	46.00	-7.38	Peak	200	0
2	570.20	47.41	-4.97	42.44	46.00	-3.56	QP	200	74
3	603.80	41.96	-2.54	39.42	46.00	-6.58	Peak	200	62
4	636.00	44.48	-4.76	39.72	46.00	-6.28	Peak	200	99
5	701.80	42.68	-7.69	34.99	46.00	-11.01	Peak	200	298
6	724.90	44.66	-6.67	37.99	46.00	-8.01	Peak	200	0
7	960.10	36.03	7.24	43.27	54.00	-10.73	Peak	200	200

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. According to technical experiences, all spurious emission of 802.11MIMO mode at channel 1,6,11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
5. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: VERTICAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 1	Humidity	: 65 %
Modulation Type	: 802.11n, 20MHz BW	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 130 Mbps




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4824.20	41.83	8.64	50.47	74.00	-23.53	Peak	100	149
2	4824.20	29.99	8.64	38.63	54.00	-15.37	Average	100	149

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: HORIZONTAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 1	Humidity	: 65 %
Modulation Type	: 802.11n, 20MHz BW	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 130 Mbps




Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4824.10	42.08	8.64	50.72	74.00	-23.28	Peak	100	177
2	4824.10	30.13	8.64	38.77	54.00	-15.23	Average	100	177

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: VERTICAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 6	Humidity	: 65 %
Modulation Type	: 802.11n, 20MHz BW	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 130 Mbps




Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4875.00	41.45	8.79	50.23	74.00	-23.77	Peak	100	149
2	4875.00	30.13	8.79	38.91	54.00	-15.09	Average	100	149

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.


Power	: DC 5V from PC	Pol/Phase	: HORIZONTAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 6	Humidity	: 65 %
Modulation Type	: 802.11n, 20MHz BW	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 130 Mbps



Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: VERTICAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 11	Humidity	: 65 %
Modulation Type	: 802.11n, 20MHz BW	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 130 Mbps




Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4924.00	41.96	8.92	50.89	74.00	-23.11	Peak	100	149
2	4924.00	30.17	8.92	39.10	54.00	-14.90	Average	100	149

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: HORIZONTAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 11	Humidity	: 65 %
Modulation Type	: 802.11n, 20MHz BW	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 130 Mbps




Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4925.10	42.46	8.93	51.38	74.00	-22.62	Peak	100	177
2	4925.10	30.48	8.93	39.41	54.00	-14.59	Average	100	177

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: VERTICAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 3	Humidity	: 65 %
Modulation Type	: 802.11n, 40MHz BW	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 270 Mbps




Trace: (Discrete)									
Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	124.33	44.87	-12.26	32.60	43.50	-10.90	Peak	100	42
2	156.23	47.33	-13.73	33.59	43.50	-9.91	Peak	100	0
3	166.13	49.78	-15.55	34.23	43.50	-9.27	Peak	100	86
4	197.75	45.63	-13.55	32.08	43.50	-11.42	Peak	100	333
5	232.95	47.94	-13.76	34.18	46.00	-11.82	Peak	100	74
6	274.75	41.78	-14.29	27.49	46.00	-18.51	Peak	100	88

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. According to technical experiences, all spurious emission of 802.11MIMO mode at channel 3,6,9 are almost the same below 1GHz, so that the channel 3 was chosen as representative in final test.
5. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: VERTICAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 3	Humidity	: 65 %
Modulation Type	: 802.11n, 40MHz BW	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 270 Mbps




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	357.40	51.96	-10.42	41.53	46.00	-4.47	QP	100	77
2	500.90	46.22	-4.91	41.31	46.00	-4.69	QP	100	360
3	657.70	46.65	-4.67	41.98	46.00	-4.02	QP	100	89
4	668.90	47.39	-5.27	42.13	46.00	-3.87	QP	100	342
5	735.40	45.46	-3.45	42.01	46.00	-3.99	QP	100	333
6	777.40	45.32	-3.74	41.58	46.00	-4.42	QP	100	252
7	817.30	43.20	-1.16	42.04	46.00	-3.96	QP	100	155

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. According to technical experiences, all spurious emission of 802.11MIMO mode at channel 3,6,9 are almost the same below 1GHz, so that the channel 3 was chosen as representative in final test.
5. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: HORIZONTAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 3	Humidity	: 65 %
Modulation Type	: 802.11n, 40MHz BW	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 270 Mbps




Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	159.25	49.60	-20.39	29.21	43.50	-14.29	Peak	200	360
2	199.95	52.51	-19.60	32.91	43.50	-10.59	Peak	200	360
3	209.85	47.02	-19.28	27.75	43.50	-15.75	Peak	200	35
4	214.80	47.23	-18.70	28.53	43.50	-14.97	Peak	200	222
5	232.13	52.99	-18.36	34.63	46.00	-11.37	Peak	200	136
6	265.13	47.04	-15.12	31.92	46.00	-14.08	Peak	200	52

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. According to technical experiences, all spurious emission of 802.11MIMO mode at channel 3,6,9 are almost the same below 1GHz, so that the channel 3 was chosen as representative in final test.
5. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: HORIZONTAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 3	Humidity	: 65 %
Modulation Type	: 802.11n, 40MHz BW	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 270 Mbps




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	363.70	50.36	-11.84	38.51	46.00	-7.49	Peak	200	360
2	435.80	46.21	-7.87	38.34	46.00	-7.66	Peak	200	77
3	503.70	47.17	-6.38	40.79	46.00	-5.21	QP	200	178
4	568.10	47.02	-4.55	42.46	46.00	-3.54	QP	200	210
5	603.80	43.88	-2.54	41.34	46.00	-4.66	QP	200	137
6	960.10	36.72	7.24	43.96	54.00	-10.04	Peak	200	360

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. According to technical experiences, all spurious emission of 802.11MIMO mode at channel 3, 6, 9 are almost the same below 1GHz, so that the channel 3 was chosen as representative in final test.
5. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: VERTICAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 3	Humidity	: 65 %
Modulation Type	: 802.11n, 40MHz BW	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 270 Mbps




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4844.00	42.10	8.70	50.79	74.00	-23.21	Peak	100	149
2	4844.00	30.03	8.70	38.72	54.00	-15.28	Average	100	149

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: HORIZONTAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 3	Humidity	: 65 %
Modulation Type	: 802.11n, 40MHz BW	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 270 Mbps




Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4843.80	42.33	8.70	51.03	74.00	-22.97	Peak	100	177
2	4843.80	30.31	8.70	39.00	54.00	-15.00	Average	100	177

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: VERTICAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 6	Humidity	: 65 %
Modulation Type	: 802.11n, 40MHz BW	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 270 Mbps




Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4874.00	41.63	8.78	50.41	74.00	-23.59	Peak	100	149
2	4874.00	30.03	8.78	38.81	54.00	-15.19	Average	100	149

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: HORIZONTAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 6	Humidity	: 65 %
Modulation Type	: 802.11n, 40MHz BW	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 270 Mbps




Trace: (Discrete)									
Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4874.80	42.46	8.78	51.24	74.00	-22.76	Peak	100	177
2	4874.80	30.46	8.78	39.25	54.00	-14.75	Average	100	177

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: VERTICAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 9	Humidity	: 65 %
Modulation Type	: 802.11n, 40MHz BW	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 270 Mbps




Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4904.00	41.83	8.87	50.70	74.00	-23.30	Peak	100	149
2	4904.00	30.06	8.87	38.93	54.00	-15.07	Average	100	149

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.

Power	: DC 5V from PC	Pol/Phase	: HORIZONTAL
Test Mode	: Transmit / Receive	Temperature	: 26 °C
Operation Channel	: 9	Humidity	: 65 %
Modulation Type	: 802.11n, 40MHz BW	Atmospheric Pressure	: 1010 hPa
Memo	:	Rate	: 270 Mbps



Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4904.60	42.37	8.87	51.24	74.00	-22.76	Peak	100	177
2	4904.60	30.31	8.87	39.18	54.00	-14.82	Average	100	177

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.

Test engineer:

Ben

6. 6dB Bandwidth Measurement Data


6.1 Test Limit

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

6.2 Test Procedures

- The transmitter output was connected to the spectrum analyzer.
- Set RBW of spectrum analyzer to 100 KHz and VBW to 100 KHz.
- The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.

6.3 Test Setup Layout



6.4 Measurement equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Valid Date.
Spectrum Analyzer	FSP40	R&S	100047	2007/01/16

6.5 Test Result and Data

- (1) Modulation Standard: IEEE 802.11b (11Mbps)

Test Date: Sep. 20, 2007 Temperature: 26 Humidity: 62% Atmospheric pressure: 1010 hPa

Channel	Frequency (MHz)	6dB Bandwidth (MHz)
01	2412	12.0
06	2437	12.2
11	2462	12.3

- (2) Modulation Standard: IEEE 802.11g (24Mbps)

Test Date: Sep. 20, 2007 Temperature: 26 Humidity: 62% Atmospheric pressure: 1010 hPa

Channel	Frequency (MHz)	6dB Bandwidth (MHz)
01	2412	16.6
06	2437	16.6
11	2462	16.7

- (3) Modulation Standard: 802.11n, 20MHz BW (130Mbps)

Test Date: Sep. 20, 2007 Temperature: 26 Humidity: 62% Atmospheric pressure: 1010 hPa


Channel	Frequency (MHz)	6dB Bandwidth of TX0 (MHz)	6dB Bandwidth of TX1 (MHz)
01	2412	17.8	17.8
06	2437	17.7	17.9
11	2462	17.7	17.8

- (4) Modulation Standard: IEEE 802.11n, 40MHz BW (270Mbps)

Test Date: Sep. 21, 2007 Temperature: 25 Humidity: 62% Atmospheric pressure: 1010 hPa


Channel	Frequency (MHz)	6dB Bandwidth of TX0 (MHz)	6dB Bandwidth of TX1 (MHz)
03	2422	36.6	36.6
06	2437	36.4	36.6
09	2452	36.6	36.4

Modulation Standard: 802.11b (11Mbps)
Channel: 01




Date: 20.SEP.2007 11:54:40

Channel:06




Date: 20.SEP.2007 11:56:41

Channel:11




Date: 20.SEP.2007 12:01:35

Modulation Standard:802.11g (24Mbps)
Channel:01


Date: 20.SEP.2007 13:16:14

Channel:06




Date: 20.SEP.2007 13:18:36

Channel:11




Date: 20.SEP.2007 13:21:24

Modulation Standard: 802.11n, 20MHz BW (130Mbps) – TX0
Channel:01




Date: 20.SEP.2007 17:51:45

Channel:06



Date: 20.SEP.2007 17:57:47


Channel:11



Date: 20.SEP.2007 18:00:30


Modulation Standard: 802.11n, 20MHz BW (130Mbps) – TX1

Channel:01




Date: 20.SEP.2007 17:48:28

Channel:06




Date: 20.SEP.2007 17:54:43

Channel:11




Date: 20.SEP.2007 18:02:38

Modulation Standard: 802.11n, 40MHz BW (270Mbps) – TX0
Channel:03




Date: 21.SEP.2007 17:51:58

Channel:06



Date: 21.SEP.2007 17:48:49


Channel:09



Date: 21.SEP.2007 17:42:57


Modulation Standard: 802.11n, 40MHz BW (270Mbps) – TX1

Channel:03




Date: 21.SEP.2007 17:13:20

Channel:06



Date: 21.SEP.2007 17:30:43

Channel:09



Date: 21.SEP.2007 17:40:05

7. Maximum Peak Output Power


7.1 Test Limit

The Maximum Peak Output Power Measurement is 30dBm.

7.2 Test Procedures

The antenna port(RF output)of the EUT was connected to the input(RF input)of a power meter. Power was read directly from the meter and cable loss connection was added to the reading to obtain power at the EUT antenna terminal. The EUT Output Power was set to maximum to produce the worse case test result.

7.3 Test Setup Layout



7.4 Measurement equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date.
Spectrum Analyzer	FSP40	R&S	100047	2007/01/23	2008/01/22

7.5 Test Result and Data

(1) Modulation Standard: IEEE 802.11b (11Mbps)

Test Date: Sep. 20, 2007 Temperature: 26 Humidity: 62% Atmospheric pressure: 1010 hPa

Channel	Frequency (MHz)	Peak Power Output (dBm)	Peak Power Output (mW)
01	2412	15.85	38.5
06	2437	16.66	46.3
11	2462	17.12	51.5

(2) Modulation Standard: IEEE 802.11g (24Mbps)

Test Date: Sep. 20, 2007 Temperature: 26 Humidity: 62% Atmospheric pressure: 1010 hPa

Channel	Frequency (MHz)	Peak Power Output (dBm)	Peak Power Output (mW)
01	2412	16.09	40.6
06	2437	16.60	45.7
11	2462	17.31	53.8

(3) Modulation Standard: IEEE 802.11n, 20MHz BW (130Mbps)

Test Date: Sep. 20, 2007 Temperature: 26 Humidity: 62% Atmospheric pressure: 1010 hPa


Channel	Frequency (MHz)	Peak Power Output Of TX0 (dBm)	Peak Power Output Of TX1 (dBm)	Peak Power Output Of Total (dBm)	Peak Power Output Of Total (mW)
01	2412	16.53	17.76	20.20	104.68
06	2437	17.71	18.46	21.11	129.17
11	2462	18.43	19.30	21.90	154.78

(4) Modulation Standard: IEEE 802.11n, 40MHz BW (270Mbps)

Test Date: Sep. 21, 2007 Temperature: 25 Humidity: 62% Atmospheric pressure: 1010 hPa


Channel	Frequency (MHz)	Peak Power Output Of TX0 (dBm)	Peak Power Output Of TX1 (dBm)	Peak Power Output Of Total (dBm)	Peak Power Output Of Total (mW)
03	2422	16.33	18.32	20.45	110.87
06	2437	16.80	18.85	20.96	124.60
09	2452	17.37	19.24	21.42	138.52

Modulation Standard: 802.11b (11Mbps)
Channel: 01




Date: 20.SEP.2007 11:30:10

Channel:06




Date: 20.SEP.2007 11:31:33

Channel: 11




Date: 20.SEP.2007 11:32:34

Modulation Standard: 802.11g (24Mbps)
Channel: 01


Date: 20.SEP.2007 11:16:05

Channel: 06




Date: 20.SEP.2007 11:17:04

Channel:11




Date: 20.SEP.2007 11:18:20

Modulation Standard: 802.11n, 20MHz BW (130Mbps) - TX0
Channel:01


Date: 20.SEP.2007 16:18:34

Channel:06




Date: 20.SEP.2007 16:22:55

Channel:11




Date: 20.SEP.2007 16:24:32

Modulation Standard: 802.11n, 20MHz BW (130Mbps) - TX1
Channel:01




Date: 20.SEP.2007 16:19:57

Channel:06




Date: 20.SEP.2007 16:20:58

Channel:11




Date: 20.SEP.2007 16:26:15

Modulation Standard: 802.11n, 40MHz BW (270Mbps) - TX0
Channel:03




Date: 21.SEP.2007 16:58:36

Channel:06



Date: 21.SEP.2007 17:02:23


Channel:09



Date: 21.SEP.2007 17:03:59


Modulation Standard: 802.11n, 40MHz BW (270Mbps) - TX1

Channel:03




Date: 21.SEP.2007 17:09:20

Channel:06



Date: 21.SEP.2007 17:07:08

Channel:09



Date: 21.SEP.2007 17:05:56

8. Band Edges Measurement


8.1 Test Limit

Below -20dB of the highest emission level of operating band
(In 100 kHz Resolution Bandwidth)

8.2 Test Procedure :

- 1.The transmitter output was connected to the spectrum analyzer via a low lose cable.
- 2.Set both RBW and VBW of spectrum analyzer to 100 KHz with convenient frequency span including 100 KHz bandwidth from band edge.
- 3.The band edges was measured and recorded.

8.3 Test Setup Layout



8.4 Measurement equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date.
Spectrum Analyzer	FSP40	R&S	100047	2007/01/23	2008/01/22

8.5 Test Result and Data

(1) Modulation Standard: IEEE 802.11b (11Mbps)

Test Date: Sep. 20, 2007 Temperature: 26 Humidity: 62% Atmospheric pressure: 1010 hPa

Channel	Frequency	maximum value in frequency (MHz)	maximum value is (dBm)
01	2412	2396.2	-39.56
11	2462	2484.1	-48.97

(2) Modulation Standard: IEEE 802.11g (24Mbps)

Test Date: Sep. 20, 2007 Temperature: 26 Humidity: 62% Atmospheric pressure: 1010 hPa

Channel	Frequency	maximum value in frequency (MHz)	maximum value is (dBm)
01	2412	2399.8	-36.93
11	2462	2483.4	-47.20

(3) Modulation Standard: IEEE 802.11n, 20MHz BW (130Mbps)

Test Date: Sep. 20, 2007 Temperature: 26 Humidity: 62% Atmospheric pressure: 1010 hPa

Channel Frequency		maximum value in frequency and measurement value			
		TX0		TX1	
		MHz	dBm	MHz	dBm
01	2412	2399.8	-38.90	2399.8	-37.17
11	2462	2484.5	-45.45	2483.7	-49.53


(4) Modulation Standard: IEEE 802.11n, 40MHz BW (270Mbps)

Test Date: Sep. 21, 2007 Temperature: 25 Humidity: 62% Atmospheric pressure: 1010 hPa


Channel Frequency		maximum value in frequency and measurement value			
		TX0		TX1	
		MHz	dBm	MHz	dBm
03	2422	2398.6	-40.13	2399.8	-40.59
09	2452	2485.5	-45.00	2487.1	-43.18

Modulation Standard: 802.11b (11Mbps)

Channel: 01




Date: 20.SEP.2007 13:53:44




Date: 20.SEP.2007 13:55:17

Channel: 11




Date: 20.SEP.2007 14:06:04




Date: 20.SEP.2007 14:07:13

Modulation Standard: 802.11g (24Mbps)

Channel: 01




Date: 20.SEP.2007 13:32:17




Date: 20.SEP.2007 13:39:48

Channel: 11




Date: 20.SEP.2007 13:44:06




Date: 20.SEP.2007 13:46:00

Modulation Standard: 802.11n, 20MHz BW (130Mbps) – TX0

Channel: 01




Date: 20.SEP.2007 18:33:44




Date: 20.SEP.2007 18:35:11

Channel: 11




Date: 20.SEP.2007 18:27:48




Date: 20.SEP.2007 18:31:25

Modulation Standard: 802.11n, 20MHz BW (130Mbps) – TX1

Channel: 01




Date: 20.SEP.2007 18:12:13




Date: 20.SEP.2007 18:14:50

Channel: 11




Date: 20.SEP.2007 18:20:49




Date: 20.SEP.2007 18:22:23

Modulation Standard: 802.11n, 40MHz BW (270Mbps) – TX0

Channel: 03




Date: 21.SEP.2007 17:56:02




Date: 21.SEP.2007 17:57:37

Channel: 09




Date: 21.SEP.2007 18:00:31




Date: 21.SEP.2007 18:02:08

Modulation Standard: 802.11n, 40MHz BW (270Mbps) – TX1

Channel: 03




Date: 21.SEP.2007 18:04:36




Date: 21.SEP.2007 18:06:13

Channel: 09



Date: 21.SEP.2007 18:08:57



Date: 21.SEP.2007 18:10:23

8.6 Restrict band emission Measurement Data

Modulation Standard: IEEE 802.11b (11Mbps)

Test Date: Sep. 28, 2007 Temperature: 26 Humidity: 65% Atmospheric pressure: 1010 hPa

a) Channel 1

Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2372.73	H	58.34	-0.21	58.13	Peak	74	54	-15.87	182	1.1
2389.97	H	43.41	-0.14	43.27	Ave	74	54	-10.73	182	1.1
2368.55	V	55.21	-0.23	54.98	Peak	74	54	-19.02	148	1.0
2389.97	V	40.00	-0.14	39.86	Ave	74	54	-14.14	148	1.0

b) Channel 11

Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2483.51	H	59.15	0.23	59.39	Peak	74	54	-14.61	182	1.1
2483.55	H	44.80	0.23	45.03	Ave	74	54	-8.97	182	1.1
2484.31	V	56.98	0.24	57.22	Peak	74	54	-16.78	148	1.0
2483.51	V	41.72	0.23	41.95	Ave	74	54	-12.05	148	1.0

Modulation Standard: 802.11g (24Mbps)

Test Date: Sep. 28, 2007 Temperature: 26 Humidity: 65% Atmospheric pressure: 1010 hPa

a) Channel 1

Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2384.87	H	58.33	-0.16	58.17	Peak	74	54	-15.83	182	1.1
2330.71	H	44.07	-0.38	43.69	Ave	74	54	-10.31	182	1.1
2336.42	V	54.94	-0.35	54.59	Peak	74	54	-19.41	148	1.0
2389.87	V	40.43	-0.14	40.29	Ave	74	54	-13.71	148	1.0

b) Channel 11

Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2483.96	H	58.67	0.24	58.91	Peak	74	54	-15.09	182	1.1
2483.51	H	44.02	0.23	44.26	Ave	74	54	-9.74	182	1.1
2483.55	V	58.28	0.23	58.51	Peak	74	54	-15.49	148	1.0
2483.51	V	42.30	0.23	42.53	Ave	74	54	-11.47	148	1.0

Notes:

1. Result = Meter Reading + Factor
2. Factor = Antenna Factor + Cable Loss – Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3 MHz for Peak detection at frequency above 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz

Modulation Standard: IEEE 802.11n, 20MHz BW (130Mbps)

Test Date: Sep. 28, 2007 Temperature: 26 Humidity: 65% Atmospheric pressure: 1010 hPa

c) Channel 1

Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2314.28	H	58.28	-0.44	57.83	Peak	74	54	-16.17	182	1.1
2389.87	H	43.51	-0.14	43.37	Ave	74	54	-10.63	182	1.1
2312.65	V	54.89	-0.45	54.44	Peak	74	54	-19.56	148	1.0
2389.87	V	39.74	-0.14	39.60	Ave	74	54	-14.40	148	1.0

d) Channel 11

Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2483.51	H	56.53	0.23	56.77	Peak	74	54	-17.23	182	1.1
2483.51	H	44.06	0.23	44.30	Ave	74	54	-9.70	182	1.1
2492.63	V	55.85	0.27	56.12	Peak	74	54	-17.88	148	1.0
2483.51	V	40.80	0.23	41.04	Ave	74	54	-12.96	148	1.0

Modulation Standard: IEEE 802.11n, 40MHz BW (270Mbps)

Test Date: Sep. 28, 2007 Temperature: 26 Humidity: 65% Atmospheric pressure: 1010 hPa

e) Channel 3

Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2388.13	H	57.90	-0.15	57.75	Peak	74	54	-16.25	182	1.1
2389.87	H	44.63	-0.14	44.49	Ave	74	54	-9.51	182	1.1
2389.97	V	61.21	-0.14	61.47	Peak	74	54	-12.53	148	1.0
2389.97	V	48.36	-0.14	48.22	Ave	74	54	-5.78	148	1.0

f) Channel 09

Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2484.88	H	60.94	0.24	61.18	Peak	74	54	-12.82	182	1.1
2483.51	H	46.42	0.23	46.66	Ave	74	54	-7.34	182	1.1
2487.35	V	57.53	0.25	57.78	Peak	74	54	-16.22	148	1.0
2484.27	V	44.02	0.24	44.26	Ave	74	54	-9.74	148	1.0

9. Power Spectral Density


9.1 Test Limit

The Maximum of Power Spectral Density Measurement is 8dBm.

9.2 Test Procedures

- The transmitter output was connected to spectrum analyzer.
- The spectrum analyzer's resolution bandwidth were set at 3KHz RBW and 30KHz VBW as that of the fundamental frequency. Set the sweep time=span/3KHz.
- The power spectral density was measured and recorded.
- The Sweep time is allowed to be longer than span/3KHz for a full response of the mixer in the spectrum analyzer.

9.3 Test Setup Layout :



9.4 List of Measuring Equipment Used

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Valid Date.
Spectrum Analyzer	FSP40	R&S	100047	2007/01/16

9.5 Test Result and Data

(1) Modulation Standard: IEEE 802.11b (11Mbps)

Test Date: Sep. 20, 2007 Temperature: 26 Humidity: 62% Atmospheric pressure: 1010 hPa

Channel	Frequency	Maximum Power Density of 3 kHz Bandwidth (dBm)
01	2412	-15.61
06	2437	-14.73
11	2462	-13.88

(2) Modulation Standard: IEEE 802.11g (24Mbps)

Test Date: Sep. 20, 2007 Temperature: 26 Humidity: 62% Atmospheric pressure: 1010 hPa

Channel	Frequency	Maximum Power Density of 3 kHz Bandwidth (dBm)
01	2412	-18.45
06	2437	-17.69
11	2462	-16.91

(3) Modulation Standard: IEEE 802.11n, 20MHz BW (130Mbps)

Test Date: Sep. 20, 2007 Temperature: 26 Humidity: 62% Atmospheric pressure: 1010 hPa


Channel	Frequency	Maximum Power Density of 3 kHz Bandwidth (dBm)		
		TX0	TX1	Total
01	2412	-22.43	-19.87	-17.95
06	2437	-21.41	-19.07	-17.07
11	2462	-20.46	-18.32	-16.25

(4) Modulation Standard: IEEE 802.11n, 40MHz BW (270Mbps)

Test Date: Sep. 21, 2007 Temperature: 25 Humidity: 62% Atmospheric pressure: 1010 hPa


Channel	Frequency	Maximum Power Density of 3 kHz Bandwidth (dBm)		
		TX0	TX1	Total
03	2422	-26.48	-21.06	-19.96
06	2437	-25.93	-16.71	-16.21
09	2452	-25.28	-16.10	-15.60

Modulation Standard: 802.11b (11Mbps)
Channel: 01




Date: 20.SEP.2007 14:19:30

Channel:06




Date: 20.SEP.2007 14:32:25

Channel: 11




Date: 20.SEP.2007 14:42:20

Modulation Standard: 802.11g (24Mbps)
Channel: 01


Date: 20.SEP.2007 15:04:33

Channel: 06




Date: 20.SEP.2007 15:16:39

Channel:11




Date: 20.SEP.2007 15:27:24

Modulation Standard: 802.11n, 20MHz BW (130Mbps) – TX0
Channel:01




Date: 20.SEP.2007 19:17:41

Channel:06



Date: 20.SEP.2007 19:27:41


Channel:11



Date: 20.SEP.2007 19:38:32


Modulation Standard: 802.11n, 20MHz BW (130Mbps) – TX1

Channel:01




Date: 20.SEP.2007 20:14:17

Channel:06




Date: 20.SEP.2007 20:04:08

Channel:11




Date: 20.SEP.2007 19:49:43

Modulation Standard: 802.11n, 40MHz BW (270Mbps) – TX0
Channel:03




Date: 21.SEP.2007 18:54:40

Channel:06



Date: 21.SEP.2007 19:05:23


Channel:09



Date: 21.SEP.2007 19:14:52


Modulation Standard: 802.11n, 40MHz BW (270Mbps) – TX1

Channel:03




Date: 21.SEP.2007 18:43:39

Channel:06



Date: 21.SEP.2007 18:33:52

Channel:09



Date: 21.SEP.2007 18:24:16

10. Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.09000 – 0.11000	16.42000 – 16.42300	399.9 – 410.0	4.500 – 5.250
0.49500 – 0.505**	16.69475 – 16.69525	608.0 – 614.0	5.350 – 5.460
2.17350 – 2.19050	16.80425 – 16.80475	960.0 – 1240.0	7.250 – 7.750
4.12500 – 4.12800	25.50000 – 25.67000	1300.0 – 1427.0	8.025 – 8.500
4.17725 – 4.17775	37.50000 – 38.25000	1435.0 – 1626.5	9.000 – 9.200
4.20725 – 4.20775	73.00000 – 74.60000	1645.5 – 1646.5	9.300 – 9.500
6.21500 – 6.21800	74.80000 – 75.20000	1660.0 – 1710.0	10.600 – 12.700
6.26775 – 6.26825	108.00000 – 121.94000	1718.8 – 1722.2	13.250 – 13.400
6.31175 – 6.31225	123.00000 – 138.00000	2200.0 – 2300.0	14.470 – 14.500
8.29100 – 8.29400	149.90000 – 150.05000	2310.0 – 2390.0	15.350 – 16.200
8.36200 – 8.36600	156.52475 – 156.52525	2483.5 – 2500.0	17.700 – 21.400
8.37625 – 8.38675	156.70000 – 156.90000	2655.0 – 2900.0	22.010 – 23.120
8.41425 – 8.41475	162.01250 – 167.17000	3260.0 – 3267.0	23.600 – 24.000
12.29000 – 12.29300	167.72000 – 173.20000	3332.0 – 3339.0	31.200 – 31.800
12.51975 – 12.52025	240.00000 – 285.00000	3345.8 – 3358.0	36.430 – 36.500
12.57675 – 12.57725	322.00000 – 335.40000	3600.0 – 4400.0	Above 38.6
13.36000 – 13.41000			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

10.1 Labeling Requirement

The device shall bear the following statement in a conspicuous location on the device:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.