

## 1.1. Test Result of RF Exposure Evaluation

- . Product: Wireless Network Camera
- . Test Item: RF Exposure Evaluation Data
- . Test site: OATSI-SD
- . Test Mode: Normal Operation

### 1.1.1. Antenna Gain

The maximum Gain is 1.8 dBi.

### 1.1.2. EUT Operation condition

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

### 1.1.3. Output Power into Antenna & RF Exposure Evaluation Distance

(1) Modulation Standard: IEEE 802.11b(11Mbps)

Test Date: Jul. 16, 2008      Temperature: 20      Humidity: 60%

Channel	Channel Frequency (MHz)	Output Power to Antenna (dBm)	Power Density (S) (mW/cm <sup>2</sup> )
01	2412	24.87	0.092
06	2437	24.74	0.090
11	2462	24.85	0.092

(2) Modulation Standard: IEEE 802.11g(24Mbps)

Test Date: Jan. 04, 2008      Temperature: 22      Humidity: 60%

Channel	Channel Frequency (MHz)	Output Power to Antenna (dBm)	Power Density (S) (mW/cm <sup>2</sup> )
01	2412	23.93	0.074
06	2437	23.94	0.075
11	2462	23.91	0.074

The MPE is calculated as  $0.092 \text{ mW} / \text{cm}^2 < \text{limit } 1 \text{ mW} / \text{cm}^2$ . So, RF exposure limit warning or SAR test are not required.

For 2412-2462 MHz, the EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47CFR2.1091 (b).

The RF Exposure Information page from the manual is included here for reference.