



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2016SZ0817087F
- Page 1 of 24 -

FCC RADIO TEST REPORT

FCC ID: P348709WS

Product : Weather station

Trade Name : OCHO

Model Name : MLG-8709WS

Serial Model : MLG-8710WS, MLG-8711WS, MLG-8712WS,
MLG-8713WS

Prepared for

MAJOR LEAGUE GLOBAL CO., LTD.

3A22(4/F), Baoyuan Huafeng Headquarters Economic B Bao'an District,
Shenzhen, P.R.C

Prepared by

Shenzhen Asia Test Technology Co.,Ltd.

7 / F, Xinwei Building, Gushu Village, Xixiang Town, Baoan District,
Shenzhen, China



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2016SZ0817087F
- Page 2 of 24 -

TEST RESULT CERTIFICATION

Applicant's name : MAJOR LEAGUE GLOBAL CO., LTD.

Address : 3A22(4/F), Baoyuan Huafeng Headquarters Economic B Bao'an District, Shenzhen, P.R.C

Manufacture's Name : MAJOR LEAGUE GLOBAL CO., LTD.

Address : 3A22(4/F), Baoyuan Huafeng Headquarters Economic B Bao'an District, Shenzhen, P.R.C

Product description

Product Name : Weather station

Model and/or type reference : MLG-8709WS

Serial Model : MLG-8710WS, MLG-8711WS, MLG-8712WS,
MLG-8713WS

Standards : FCC Part15.231:2016

Test procedure ANSI C63.10-2013

This device described above has been tested by ATT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

Date of Test

Date (s) of performance of tests Aug. 16 2016 ~Aug. 24 2016

Date of Issue Aug. 24 2016

Test Result **Pass**

Testing Engineer:

A handwritten signature in black ink, appearing to read "Jack Xie".

(Jack xie)

A handwritten signature in black ink, appearing to read "James Liu".

Technical Manager :

(James liu)

A handwritten signature in black ink, appearing to read "Amanda Mei".

(Amanda mei)

Authorized Signatory :



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2016SZ0817087F
- Page 3 of 24 -

Table of Contents	Page
1 . SUMMARY OF TEST RESULTS	5
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	6
2 . GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	8
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	9
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	10
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	11
3 . ANTENNA REQUIREMENT	12
3.1 STANDARD REQUIREMENT	12
3.2 EUT ANTENNA	12
3.3 CONDUCTED EMISSION MEASUREMENT	13
3.3.1 POWER LINE CONDUCTED EMISSION LIMITS	13
3.3.2 TEST PROCEDURE	14
3.3.3 DEVIATION FROM TEST STANDARD	14
3.3.4 TEST SETUP	14
3.3.5 TEST RESULT	15
3.4 RADIATED EMISSION MEASUREMENT	16
3.4.1 RADIATED EMISSION LIMITS	16
3.4.2 TEST PROCEDURE	17
3.4.3 DEVIATION FROM TEST STANDARD	17
3.4.4 TEST SETUP	18
3.4.5 TEST RESULTS (BELOW 30MHZ)	20
3.4.6 TEST RESULTS (BETWEEN 30 – 5000 MHZ)	21
4 . BANDWIDTH TEST	22
4.1 TEST PROCEDURE	22
4.2 DEVIATION FROM STANDARD	22
4.3 TEST SETUP	22
4.4 TEST RESULTS	23



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2016SZ0817087F
- Page 4 of 24 -

Table of Contents	Page
5 . TRANSMITTER TIMEOUT	24
5.1 REQUIREMENTS	24
6 . EUT TEST PHOTO	
APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2016SZ0817087F
- Page 5 of 24 -

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15, Subpart C (15.231)			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	N/A	
15.203	Antenna Requirement	Pass	
15.231	Radiated Spurious Emission	Pass	
15.231	Occupied Bandwidth	Pass	
15.231	Transmitter Timeout	Pass	

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2016SZ0817087F
- Page 6 of 24 -

1.1 TEST FACILITY

Shenzhen Asia Test Technology Co.,Ltd.

7 / F, Xinwei Building, Gushu Village, Xixiang Town, Baoan District, Shenzhen, China

FCC Registration No.: 348715

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$ · where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$ · providing a level of confidence of approximately 95 % .

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power,conducted	$\pm 0.16\text{dB}$
3	Spurious emissions,conducted	$\pm 0.21\text{dB}$
4	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^\circ\text{C}$
7	Humidity	$\pm 2\%$



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2016SZ0817087F
- Page 7 of 24 -

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Weather station	
Model Name	MLG-8709WS	
Serial Model	MLG-8710WS, MLG-8711WS, MLG-8712WS, MLG-8713WS	
Model Difference	All models are the same circuit and RF module, except model name and colours.	
Product Description	The EUT is a Weather station Transmitter	
	Product Type	Weather station
	Operation Frequency:	433.92MHz
	Modulation Type:	FSK
	Number Of Channel	1CH.
	Antenna Designation:	extension cord antenna
	Antenna Gain(Peak)	0 dBi
	Field strength:	75.68 dBuV/m (PK Max.)
Channel List	N/A	
Adapter	N/A	
HW	TX_20160215	
SW	V1.0	
Battery	DC 3V	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

Table for Filed Antenna

Ant .	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	extension cord	N/A	0	Antenna



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2016SZ0817087F
- Page 8 of 24 -

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX

For Conducted Emission	
Final Test Mode	Description
Mode 1	N/A

For Radiated Emission	
Final Test Mode	Description
Mode 1	TX

Note:

- (1) The EUT used new battery during the measurement.
- (2) EUT continuous transmission during the test.
- (3) There are three type Match Code(CH1,CH2,CH3) in the TX,All operating mode has been tested, only the worst case(CH1) reported.




Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2016SZ0817087F
- Page 9 of 24 -

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2016SZ0817087F
- Page 10 of 24 -

2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Weather station	OCHO	MLG-8709WS	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) For detachable type I/O cable should be specified the length in cm in «Length» column.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2016SZ0817087F
- Page 11 of 24 -

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Equipment No.	Instrument	Manufacturer	Model Name	Serial Number	Specification	Cal. Data
1	Semi-anechoic chamber	Changzhou Chengyu	EC3088	N/A	9*6*6m	10/25/2015
2	Broadband antenna	R&S	VULB 9160	VULB91 60-516	30MHz-1500 MHz	10/25/2015
3	Horn antenna	R&S	BBHA 9120D	10087	1GHz-18GHz	06/05/2016
4	Test receiver	R&S	ESCI	101686	9KHz-3GHz	10/25/2015
5	EMI Measuring Receiver	R&S	ESR	101660	9KHz-40GHz	10/25/2015
6	Multi-device controller	MF	MF-7868	MF78680 8762	N/A	10/25/2015
7	Amplifier	EM	EM-30180	060538	1GHz-18GHz	10/25/2015
8	Amplifier	Schwarzbeck	BBV 9475	BBV 9475-663	1GHz-18GHz	06/05/2016
9	Radiated Cable 1#	FUJIKURA	5D-2W	01	30MHz-1GHz	10/25/2015
10	Radiated Cable 2#	FUJIKURA	10D2W	02	1GHz -25GHz	10/25/2015
11	SMA Antenna connector	Dosin	Dosin-SMA	N/A	N/A	10/25/2015
Note: The SMA antenna connector is soldered on the PCB board in order to perform conducted tests and this SMA antenna connector is listed in the equipment list. The Cal.Interval was one year						



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2016SZ0817087F
- Page 12 of 24 -

3. ANTENNA REQUIREMENT

3.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

3.2 EUT ANTENNA

The EUT antenna is soldered on the PCB board extension cord Antenna. It comply with the standard requirement.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2016SZ0817087F
- Page 13 of 24 -

3.3 CONDUCTED EMISSION MEASUREMENT

3.3.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5			66 - 56 *	56 - 46 *	CISPR
0.50 -5.0			56.00	46.00	CISPR
5.0 -30.0			60.00	50.00	CISPR

0.15 -0.5			66 - 56 *	56 - 46 *	LP002.
0.50 -5.0			56.00	46.00	LP002.
5.0 -30.0			60.00	50.00	LP002.

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2016SZ0817087F
- Page 14 of 24 -


3.3.2 TEST PROCEDURE

- a. The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.3.3 DEVIATION FROM TEST STANDARD

No deviation

3.3.4 TEST SETUP



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2016SZ0817087F
- Page 15 of 24 -

3.2.5 TEST RESULT

N/A

Note : Due to this EUT is powered by batteries only, this test item is not applicable.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2016SZ0817087F
- Page 16 of 24 -

3.4 RADIATED EMISSION MEASUREMENT

3.4.1 Radiated Emission Limits (FCC 15.209)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RADIATED EMISSION MEASUREMENT (FCC 15.231)

Fundamental Frequency (MHz)	Field Strength of fundamental (microvolts/meter)	Field Strength of Unwanted Emissions (microvolts/meter)
40.66 - 40.70	2250.00	225.00
70 - 130	1250.00	125.00
130 - 174	1,250 to 3,750 **	125 to 375 **
174 - 260	3750.00	375.00
260 - 470	3,750 to 12,500 **	375 to 1,250 **
Above 470	12500.00	1250.00

Notes:

- (1) ** linear interpolations
[Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows: for the band 130-174 MHz, uV/m at 3 meters = $56.81818(F) - 6136.3636$; for the band 260-470 MHz, uV/m at 3 meters = $41.6667(F) - 7083.3333$. The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.]
The limits on the field strength of the spurious emissions in the above table are based on the fundamental frequency of the intentional radiator. Spurious emissions shall be attenuated to the average (or, alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in 93 Section 15.209, whichever limit permits a higher field strength.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2016SZ0817087F
- Page 17 of 24 -

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1MHz / 1MHz for Peak

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.4.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3m meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note: For radiated meissont test above 1GHz

EUT was placed upon a wooden test table which was placed on the turn table 1.5m above the horizontal metal ground plane, and operating in the mode as mentioned above. Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.


3.4.3 DEVIATION FROM TEST STANDARD

No deviation




3.4.4 TEST SETUP

(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz






Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2016SZ0817087F
- Page 19 of 24 -

(C) Radiated Emission Test-Up Frequency Above 1GHz





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2016SZ0817087F
- Page 20 of 24 -

3.4.5 TEST RESULTS (BELOW 30MHz)

EUT :	Weather station	Model Name. :	MLG-8709WS
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3V
Test Mode :	TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log(\text{specific distance}/\text{test distance})$ (dB);
Limit line = specific limits(dBuv) + distance extrapolation factor.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2016SZ0817087F
- Page 21 of 24 -

3.4.6 TEST RESULTS (BETWEEN 30 – 5000 MHZ)

Operation Mode:	433.92MHz	Test Date :	Aug. 17, 2016
Frequency Range:	30~5000MHz	Temperature :	24°C
Test Result:	PASS	Humidity :	55 %
Measured Distance:	3m	Test By:	Jack

Frequency (MHz)	Reading Level(PK) (dBuV)	Correct Factor (dB)	Field Strength (PK) (dBuV/m)	Limit(PK) (dBuV/m)	Limit(AV) (dBuV/m)	Ant.Pol. H/V
433.92	65.02	8.47	73.49	100.82	80.82	H
867.84	40.11	11.76	51.87	80.82	60.82	H
1301.76	52.23	-5.88	46.35	74	54	H
1735.68	48.33	-4.67	43.66	74	54	H
2169.6	43.24	-2.05	41.19	74	54	H
--	--	--	--	74	54	H
433.92	67.21	8.47	75.68	100.82	80.82	V
867.84	42.05	11.76	53.81	80.82	60.82	V
1301.76*	54.57	-5.88	48.69	74	54	V
1735.68	49.18	-4.67	44.51	74	54	V
2169.6	44.38	-2.05	42.33	74	54	V
--	--	--	--	74	54	V

NOTE:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. *: Denotes restricted band of operation.
Measurements were made using a peak detector and average detector. Any emission falling within the restricted bands of FCC Part 15 Section 15.205 were compliance with the emission limit of FCC Part 15 Section 15.209.
3. FCC Limit for Average Measurement = $41.6667(433.92)-7083.3333=80.82$ dBuV/m
4. $1/PW = 1/1.64ms = 0.61 < RBW(120KHz)$, PDCF is not needed
5. Field Strength= measured reading+ Correct Factor
Correct Factor= Antenna Factor + Cable Loss–Pre-amplifier



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2016SZ0817087F
- Page 22 of 24 -

4. BANDWIDTH TEST

4.1 TEST PROCEDURE

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

Limit: $433.92\text{MHz} \times 0.25\% = 1084.8\text{KHz}$

4.2 DEVIATION FROM STANDARD

No deviation.

4.3 TEST SETUP






Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2016SZ0817087F
- Page 23 of 25 -

4.4 TEST RESULTS

EUT :	Weather station	Model Name :	MLG-8709WS
Temperature :	26 °C	Relative Humidity :	53%
Pressure :	1020 hPa	Test Power :	DC 3V
Test Mode :	TX		

Test Channel	Frequency (MHz)	20 dBc Bandwidth (kHz)	Limit (kHz)
CH01	433.92	57.225	1084.8



Date: 20.AUG.2016 15:47:24



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2016SZ0817087F
- Page 24 of 25 -

5. TRANSMITTER TIMEOUT

5.1 REQUIREMENTS

1 A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

Result: The EUT does not have a manually operated transmitter.

2 A transmitter activated automatically shall cease transmission within 5 seconds after activation.

Result: The EUT has a activated automatically transmitter, please refer to below detail data.

3 Periodic transmissions at regular predetermined intervals are not permitted. However, polling or supervision transmissions, including data, to determine system integrity of transmitters used in security or safety applications are allowed if the total duration of transmissions does not exceed more than two seconds per hour for each transmitter. There is no limit on the number of individual transmissions, provided the total transmission time does not exceed two seconds per hour


Result: The EUT does not employ periodic transmission.

4 Intentional radiators which are employed for radio control purposes during emergencies involving fire, security, and safety of life, when activated to signal an alarm, may operate during the pendency of the alarm condition.

Result: The section is not applicable to EUT.

This EUT is a AUTO operated transmitter which will automatically deactivate the transmitter. the EUT transmits data (0.826 ms) in a Random time intervals but not exceed interval 66.4s.

Test data



Date: 20.AUG.2016 15:25:47

THE DURATION OF EACH TRANSMISSION	LIMIT	RESULT
0.826s	<5s	PASS