

ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR FCC CERTIFICATION

Test Report No. : E067R-041

AGR No. : A067A-109

Applicant : KI RYUNG ELECTRONICS CO., LTD.
Address : 219-6, Gasan-Dong, Kumchun-Ku, Seoul, 153-023, Korea

Manufacturer : KI RYUNG ELECTRONICS CO., LTD.
Address : 219-6, Gasan-Dong, Kumchun-Ku, Seoul, 153-023, Korea

Type of Equipment : Digital Satellite Radio (FM Transmitter)

FCC ID. : P3HNSPHR2

Model Name : SP-R2

Serial number : N/A

Total page of Report : 19 pages (including this page)


Date of Incoming : July 18, 2006


Date of Issuing : July 26, 2006

SUMMARY

The equipment complies with the regulation of *FCC CRF 47 PART 15, SUBPART C, SECTION 15.239*.

This test report contains only the results of a single test of the sample supplied for the examination. It is not a general valid assessment of the features of the respective products of the mass-production.

Prepared by: 
Young-Min, Choi / Project Engineer
EMC Div.
ONETECH Corp.

Reviewed by: 
Y. K. Kwon / Director
EMC Div.
ONETECH Corp.

CONTENTS

	Page
1. VERIFICATION OF COMPLIANCE.....	3
2. GENERAL INFORMATION.....	4
2.1 PRODUCT DESCRIPTION.....	4
2.2 MODEL DIFFERENCES.....	4
2.3 RELATED SUBMITTAL(S) / GRANT(S)	4
2.4 TEST SYSTEM DETAILS	4
2.5 TEST METHODOLOGY	4
2.6 TEST FACILITY	4
3. SYSTEM TEST CONFIGURATION.....	5
3.1 JUSTIFICATION	5
3.2 EUT EXERCISE SOFTWARE.....	5
3.3 CABLE DESCRIPTION	5
3.4 EQUIPMENT MODIFICATIONS	5
3.5 CONFIGURATION OF TEST SYSTEM.....	6
3.6 ANTENNA REQUIREMENT	6
4. PRELIMINARY TEST.....	6
4.1 AC POWER LINE CONDUCTED EMISSION TEST	6
4.2 RADIATED EMISSION TEST	6
5. FINAL RESULT OF MEASUREMENT	7
5.1 CONDUCTED EMISSION TEST.....	7
5.2 RADIATED EMISSION TEST (WITHIN THE PERMITTED 200 KHZ BAND).....	9
5.2.1 Operating Condition: AC/DC Adaptor Mode	9
5.2.2 Operating Condition: Car Adaptor Mode.....	10
5.3 RADIATED EMISSION TEST (OUTSIDE OF THE SPECIFIED 200 KHZ BAND).....	11
5.3.1 Operating Condition: AC/DC Adaptor Mode	11
5.3.2 Operating Condition: Car Adaptor Mode.....	12
5.4 BANDWIDTH OF THE OPERATING FREQUENCY	13
6. FIELD STRENGTH CALCULATION	18
7. LIST OF TEST EQUIPMENT.....	19

1. VERIFICATION OF COMPLIANCE

- APPLICANT : KI RYUNG ELECTRONICS CO., LTD.
- ADDRESS : 219-6, Gasan-Dong, Kumchun-Ku, Seoul, 153-023, Korea
- CONTACT PERSON : Mr. Won-Kyu, Choi / Q.C. Assistant Manager
- TELEPHONE NO : +82-2-3282-2261
- BRAND NAME : SIRIUS
- FCC ID : P3HNSPHR2
- MODEL NAME : SP-R2
- SERIAL NUMBER : N/A
- DATE : July 26, 2006

DEVICE TYPE	Low Power Communication Device Transmitter
E.U.T. DESCRIPTION	Digital Satellite Radio (FM Transmitter)
THIS REPORT CONCERNS	ORIGINAL GRANT
MEASUREMENT PROCEDURES	Charter 7 and 13 of ANSI C63.4: 2003
TYPE OF EQUIPMENT TESTED	PRE-PRODUCTION
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	CERTIFICATION
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SECTION 15.239
MODIFICATIONS ON THE EQUIPMENT TO ACHIEVE COMPLIANCE	Yes
FINAL TEST WAS CONDUCTED ON	3 METER OPEN AREA TEST SITE

- The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. GENERAL INFORMATION

2.1 Product Description

The KI RYUNG ELECTRONICS CO., LTD., Model SP-R2 (referred to as the EUT in this report) is a Digital Satellite Radio that has the FM transmitter from 88.1 MHz to 107.9 MHz for audio signal of FM radio receiver. Product specification described herein was obtained from product data sheet or user's manual.

CHASSIS TYPE	Plastic
LIST OF EACH OSC. OR CRY. FREQ.(FREQ.>=1MHz)	Main Board : 7.3728 MHz and 7.6 MHz SSM Module: 17 MHz and 12.288 MHz
POWER REQUIREMENT	DC 12V from an AC/DC Adaptor or Car Adaptor
TX FREQUENCY RANGE	88.1 MHz ~ 107.9 MHz (range into 200 kHz Step)
NUMBER OF LAYERS	Main Board : 6 Layers, PM2.5 Module Board : 8 Layers, Cradle Board: 4 Layers
EXTERNAL CONNECTOR	DC In, Antenna In, Audio Out, FM Out

2.2 Model Differences

-. The difference(s) compared to the EUT is as follows: None

2.3 Related Submittal(s) / Grant(s)

-. Original submittal only

2.4 Test System Details

The model numbers for all the equipments which were used in the tested system is:

Model	Manufacturer	FCC ID	Description	Connected to
SP-R2	KI RYUNG ELECTRONICS	P3HNSPHR2	Digital Satellite Radio(EUT)	-
DSA-0131F-12	DVE	N/A	AC/DC Adaptor	EUT
ISGSRA733	SIRIUS	N/A	Satellite Radio Antenna	EUT

2.5 Test Methodology

The radiated testing was performed according to the procedures in chapter 7, 13 of ANSI C63.4: 2003 and performed at a distance of 3 meters from EUT to the antenna.

2.6 Test Facility

The open area test site and conducted measurement facilities are located on at 307-51 Daessangryung-Ri, Chowol-Eup, Kwangju-City, Kyunggi-Do, 464-080, Korea. Description details of test facilities were submitted to the Commission on August 30, 2005. (Registration Number: 340658)

3. SYSTEM TEST CONFIGURATION

3.1 Justification

This device was configured for testing in a typical way as a normal customer is supposed to be used. During the test, the following components were installed inside of the EUT.

DEVICE TYPE	MANUFACTURER	MODEL/PART NUMBER	FCC ID
Main Board	Ki Ryung Electronics	Sportster_REV.0	N/A
RF Module Board	Ki Ryung Electronics	Pulsar-M2.5 REV.0	N/A
Cradle Board	Ki Ryung Electronics	X3 CRADLE REV.C	N/A
Adapter Board	N/A	N/A	N/A

3.2 EUT exercise Software

The Model, SP-R2 is included a FM transmitter designed to operate on function in the 88.1 ~ 107.9 MHz. The EUT does not have an audio input port, so the internal 1 kHz modulation signal was transmitted with maximum audio level.

3.3 Cable Description

Ports Name	Shielded	Ferrite Bead	Metal Hood	Length (m)	Connected to
Audio Out	N	N	BOTH END	1.5	Terminator Resistor (10 Kohm)
DC In	N	EUT END	EUT END	1.2	AC/DC Adaptor or Car Adaptor
FM Out	N	N	EUT END	1.2	-
Antenna In	N	N	EUT END	1.2	External GPS Antenna

3.4 Equipment Modifications

It is acknowledged by Ki Ryung Electronics Co., Ltd.. that the modifications below will be installed to the Model SP-R2 in order to comply with FCC Rules as a Low Power Communication Device Transmitter.

1. R331(820ohm) change to 750ohm. For attenuate FM transmitter level.
2. Cut the pattern between C339(1000pF) and FM_OUT, and add 1000pF between FM_OUT and R332(1000pF)
3. Cut the pattern line comes from I2S clock.

3.5 Configuration of Test System

Line Conducted Test: The EUT was connected to AC/DC adaptor and AC/DC adaptor was connected to LISN. All supporting equipments were connected to another LISN. Preliminary Power line Conducted Emission test was performed by using the procedure in ANSI C63.4: 2003 7.2.3 to determine the worse operating conditions.

Radiated Emission Test: Preliminary radiated emissions test were conducted using the procedure in ANSI C63.4: 2003 8.3.1.1 and 13.1.4.1 to determine the worse operating conditions. Final radiated emission tests were conducted at 3 meter open area test site.

Occupied Bandwidth Measurement:

This measurement is performed with the antenna located close enough to give a full-scale deflection of the modulated carrier on the spectrum analyzer.

3.6 Antenna Requirement

For intentional device, according to section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna Construction:

FM transmitter antenna of the EUT is fixed inside the EUT, no consideration of replacement by the user.

4. PRELIMINARY TEST

4.1 AC Power line Conducted Emission Test

During Preliminary Test, the following operating mode was investigated

Operation Mode	The Worse operating condition (Please check one only)
Transmit the RF Signal continuously	X

4.2 Radiated Emission Test

During Preliminary Test, the following operating mode was investigated

Operation Mode	The Worse operating condition (Please check one only)
Transmit the RF Signal continuously	X

5. FINAL RESULT OF MEASUREMENT

Preliminary test was done in normal operation mode. And the final measurement was selected for the maximized emission level

5.1 Conducted Emission Test

Humidity Level : 60 % Temperature: 20 °C

Limits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.207 (a)

Type of Test : Low Power Communication Device Transmitter

Result : PASSED BY -7.16 dB at 0.71 MHz under peak detector mode

EUT : Digital Satellite Radio Date: July 21, 2006

Operating Condition : Transmit the RF signal.

Detector : CISPR Quasi-Peak (6 dB Bandwidth: 9 kHz)

Frequency (MHz)	Line	Peak (dBuV)		Margin (dB)
		Emission level	Q.P Limits	
0.47	H	48.31	56.43	-8.12
0.71	H	48.84	56.00	-7.16
1.67	H	47.96	56.00	-8.04
1.68	N	48.27	56.00	-7.73
4.44	H	45.76	56.00	-10.24
4.64	N	47.83	56.00	-8.17
Frequency (MHz)	Line	Average (dBuV)		Margin (dB)
		Emission level	Limits	
0.47	H	32.81	46.43	-13.62
0.71	H	31.41	46.00	-14.59
1.67	H	28.84	46.00	-17.16
1.68	N	29.59	46.00	-16.41
4.44	H	26.51	46.00	-19.49
4.64	N	27.36	46.00	-18.64


Line Conducted Emission Tabulated Data

Remark : "H": Hot Line, "N": Neutral line


See next page for an overview sweep performed with peak and average detector.



Tested by: Sue-Yong, Lee / Test Engineer



HOT LINE



NEUTRAL LINE

It should not be reproduced except in full, without the written approval of ONETECH.

EMC-002 (Rev.0)

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Kyunggi-Do, 462-705, Korea
(TEL: +82-31-746-8500, FAX: +82-31-746-8700)

EMC Testing Dept : 307-51 Daessangryung-Ri, Chowol-Eup, Kwangju-City, Kyunggi-Do, 464-860, Korea. (TEL: +82-31-765-8289, FAX: +82-31-766-2904)

5.2 Radiated Emission Test (Within the permitted 200 kHz band)

The following table shows the highest levels of radiated emission on both polarizations of horizontal and vertical.

5.2.1 Operating Condition: AC/DC Adaptor Mode

Humidity Level : 50 %

Temperature: 21 °C

Limits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.239 (b)

Type of Test : Low Power Communication Device Transmitter

Result : PASSED BY – 4.14 dB at 97.90 MHz

EUT : Digital Satellite Radio

Date: July 20, 2006

Distance : 3 Meter

Radiated Emission			Ant	Correction Factors		Total	Limit (dBuV/m)	Margin (dB)
Freq. (MHz)	Amp. (dBuV)	Detect Mode	Pol.	Ant. (dBuV/m)	Cable (dB)	Amp. (dBuV/m)		
88.10	31.00	Peak	H	7.89	1.74	40.63	48.00	-7.37
88.10	29.70	Peak	V	7.89	1.74	39.33	48.00	-8.67
97.90	32.30	Peak	H	9.66	1.90	43.86	48.00	-4.14
97.90	30.50	Peak	V	9.66	1.90	42.06	48.00	-5.94
107.90	20.00	Peak	H	11.07	1.90	32.97	48.00	-15.03
107.90	22.40	Peak	V	11.07	1.90	35.37	48.00	-12.63

Radiated Emission Tabulated Data

Remark: Per 15.31(m), three channels (near top, near middle and near bottom) were tested because the EUT's frequency range is more than 10 MHz.

Tested by: Sue-Young, Lee/ Test Engineer

5.2.2 Operating Condition: Car Adaptor ModeHumidity Level : 50 %Temperature: 21 °CLimits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.239 (b)Type of Test : Low Power Communication Device TransmitterResult : PASSED BY -4.27 dB at 88.10 MHz

EUT : Digital Satellite Radio


Date: July 20, 2006

Distance : 3 Meter

Radiated Emission			Ant	Correction Factors		Total	Limit (dBuV/m)	Margin (dB)
Freq. (MHz)	Amp. (dBuV)	Detect Mode	Pol.	Ant. (dBuV/m)	Cable (dB)	Amp. (dBuV/m)		
88.10	34.10	Peak	H	7.89	1.74	43.73	48.00	-4.27
88.10	33.50	Peak	V	7.89	1.74	43.13	48.00	-4.87
97.90	30.40	Peak	H	9.66	1.90	41.96	48.00	-6.04
97.90	29.10	Peak	V	9.66	1.90	40.66	48.00	-7.34
107.90	22.90	Peak	H	11.07	1.90	35.87	48.00	-12.13
107.90	24.30	Peak	V	11.07	1.90	37.27	48.00	-10.73

Radiated Emission Tabulated Data

Remark: Per 15.31(m), three channels (near top, near middle and near bottom) were tested because the EUT's frequency range is more than 10 MHz.



Tested by: Sue-Young, Lee/ Test Engineer

5.3 Radiated Emission Test (Outside of the specified 200 kHz band)

The following table shows the highest levels of radiated emission on both polarizations of horizontal and vertical.

5.3.1 Operating Condition: AC/DC Adaptor Mode

Humidity Level : 50 % Temperature: 21 °C

Limits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.209 (a)

Type of Test : Low Power Communication Device Transmitter

Result : PASSED BY -14.79 dB at 155.00 MHz

EUT : Digital Satellite Radio Date: July 20, 2006

Frequency range : 30MHz – 1000MHz

Detector : CISPR Quasi-Peak (6 dB Bandwidth: 120 kHz)

Distance : 3 Meter

Remark : Other emissions

Radiated Emission		Ant	Correction Factors		Total	FCC	
Freq. (MHz)	Amp. (dBuV)	Pol.	Ant. (dBuV/m)	Cable (dB)	Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
56.20	14.50	H	8.63	1.40	24.53	40.00	-15.47
71.20	12.20	V	5.66	1.52	19.38	43.52	-24.14
155.00	11.20	V	15.18	2.35	28.73	43.52	-14.79
169.20	9.50	V	15.61	2.40	27.51	46.02	-18.51
220.10	7.10	H	16.47	2.96	26.53	46.02	-19.49


Tested by: Sue-Young, Lee/ Test Engineer

5.3.2 Operating Condition: Car Adaptor Mode

Humidity Level : 50 % Temperature: 21 °C
 Limits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.209 (a)
 Type of Test : Low Power Communication Device Transmitter
 Result : PASSED BY -10.46 dB at 140.00 MHz

EUT : Digital Satellite Radio Date: July 20, 2006
 Frequency range : 30MHz – 1000MHz
 Detector : CISPR Quasi-Peak (6 dB Bandwidth: 120 kHz)
 Distance : 3 Meter
 Remark : Other emissions

Radiated Emission		Ant	Correction Factors		Total	FCC	
Freq. (MHz)	Amp. (dBuV)	Pol.	Ant. (dBuV/m)	Cable (dB)	Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
74.5	17.50	V	6.09	1.59	25.18	40.00	-14.82
46.47	14.22	H	11.87	1.64	27.73	43.52	-15.79
140	15.90	H	14.76	2.40	33.06	43.52	-10.46
230.2	7.50	V	16.68	3.08	27.26	46.02	-18.76
305.1	9.20	H	13.81	3.84	26.85	46.02	-19.17
521.2	6.50	H	17.74	5.42	29.66	46.02	-16.36




Tested by: Sue-Young, Lee/ Test Engineer

5.4 Bandwidth of the operating frequency


Humidity Level : 50 % Temperature: 21 °C
Limits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.239 (a)
Result : PASSED

EUT : Digital Satellite Radio Date: July 20, 2006
Operating Condition : Transmit the RF signal.
Minimum Resolution
Bandwidth : 10 kHz
Remark : Refer to test data in next page.




Tested by: Sue-Young, Lee/ Test Engineer


Operating Condition: AC/DC Adaptor Mode




Bottom Frequency (88.1MHz)




Middle Frequency (97.9MHz)




Operating Condition: Car Adaptor Mode



Bottom Frequency (88.1MHz)



Middle Frequency (97.9MHz)

**Top Frequency(107.9 MHz)**

6. FIELD STRENGTH CALCULATION

Meter readings are compared to the specification limit correcting for antenna and cable losses

+ Meter reading (dBuV)

+ Cable Loss (dB)

+ Antenna Factor (Loss) (dB/meter)

= Corrected Reading (dBuV/meter)

- Specification Limit (dBuV/meter)

= dB Relative to Spec (+/- dB)

7. LIST OF TEST EQUIPMENT

No.	EQUIPMENTS	MFR.	MODEL	SER. NO.	LAST CAL	DUE CAL	USE
1.	Test receiver	R/S	ESVS10	827864/005	DEC/05	12MONTH	■
2.	Test receiver	R/S	ESHS 10	834467/007	MAY/06	12MONTH	■
3.	Spectrum analyzer	HP	8566B	3407A08547	JUL/05	12MONTH	■
4.	TRILOG Broadband Antenna	Schwarzbeck	VULB9163	VULB9163 166	MAY/06	12MONTH	
5.	Biconical antenna	EMCO	3110	9003-1121	FEB/06	12MONTH	
		Schwarzbeck	VHA9103	91031852	FEB/06		■
6.	Log Periodic antenna	EMCO	3146	9001-2614	FEB/06	12MONTH	
		Schwarzbeck	9108-A(494)	62281001	FEB/06		■
7.	LISN	EMCO	3825/2	9109-1867	JUL/05	12MONTH	■
				9109-1869	JUL/05		
		Schwarzbeck	NSLK 8126	8126-404	AUG/05		■
8.	Position Controller	HD GmbH	HD100	N/A	N/A	N/A	■
9.	Turn Table	HD GmbH	DS420S	N/A	N/A	N/A	■
10.	Antenna Master	HD GmbH	MA240	N/A	N/A	N/A	■