

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.249)

COMPANY	NU-DEVICES, INC.	DATE	2/6/02
EUT	MOUSE-NET COMPANION 101 TOUCHPAD SYSTEM - TX	DUTY CYCLE	N/A
MODEL	MOUSE-NET COMPANION 101	PEAK TO AVG	N/A
S/N	3	TEST DIST.	3 METERS
TEST ENGINEER	KYLE FUJIMOTO	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments
903.3000	65.9	65.8 QP	H	1.0	0	X	LOW	22.8	5.1	0.0	93.7	-0.3	94.0	
903.3000	64.9	64.8 QP	H	1.0	0	Y	LOW	22.8	5.1	0.0	92.7	-1.3	94.0	
903.3000	54.4	54.3 QP	H	1.0	90	Z	LOW	22.8	5.1	0.0	82.2	-11.8	94.0	
903.3000	56.8	56.7 QP	V	2.0	270	X	LOW	22.8	5.1	0.0	84.6	-9.4	94.0	
903.3000	52.6	52.5 QP	V	1.0	90	Y	LOW	22.8	5.1	0.0	80.4	-13.6	94.0	
903.3000	65.5	65.4 QP	V	1.0	0	Z	LOW	22.8	5.1	0.0	93.3	-0.7	94.0	
912.3000	65.0	64.9 QP	H	1.0	0	X	HIGH	23.2	5.2	0.0	93.3	-0.7	94.0	
912.3000	64.4	64.3 QP	H	1.0	0	Y	HIGH	23.2	5.2	0.0	92.7	-1.3	94.0	
912.3000	54.4	54.3 QP	H	2.0	0	Z	HIGH	23.2	5.2	0.0	82.7	-11.3	94.0	
912.3000	56.4	56.3 QP	V	1.0	0	X	HIGH	23.2	5.2	0.0	84.7	-9.3	94.0	
912.3000	57.2	57.1 QP	V	2.0	0	Y	HIGH	23.2	5.2	0.0	85.5	-8.5	94.0	
912.3000	64.3	64.2 QP	V	2.0	0	Z	HIGH	23.2	5.2	0.0	92.6	-1.4	94.0	
921.3000	63.7	63.6 QP	H	1.0	0	X	HIGH	23.5	5.4	0.0	92.5	-1.5	94.0	
921.3000	63.5	63.4 QP	H	1.0	0	Y	HIGH	23.5	5.4	0.0	92.3	-1.7	94.0	
921.3000	52.2	52.1 QP	H	1.0	45	Z	HIGH	23.5	5.4	0.0	81.0	-13.0	94.0	
921.3000	51.9	51.8 QP	V	1.0	225	X	HIGH	23.5	5.4	0.0	80.7	-13.3	94.0	
921.3000	52.2	52.1 QP	V	1.0	0	Y	HIGH	23.5	5.4	0.0	81.0	-13.0	94.0	
921.3000	63.3	63.2 QP	V	1.0	0	Z	HIGH	23.5	5.4	0.0	92.1	-1.9	94.0	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN

** DELTA = SPEC LIMIT - CORRECTED READING

PAGE 1