



**TEST REPORT CONCERNING THE COMPLIANCE
OF AN INDUCTIVE E-DOCUMENT READER
OPERATING ON 13.56 MHZ,
BRAND INTEGRATED ENGINEERING,
MODEL SMARTREADER/EXTA
WITH 47 CFR PART 15 (2004-10-01).**

FCC listed : 90828
Industry Canada : IC3501
VCCI registered : R-1518, C-1598

TNO Electronic Products & Services (EPS) B.V.
P.O. Box 15
9822 ZG Niekerk (NL)
Smidshornerweg 18
9822 TL Niekerk (NL)

Telephone: +31 594 505005
Telefax: +31 594 504804

E-mail: info@eps.tno.nl



Test specification(s): 47 CFR Part 15 (2004-10-01))
Description of EUT: 13.56 MHz inductive e-document reader
Manufacturer: Integrated Engineering
Brand mark: Integrated Engineering
Model: Smartreader/extA
FCC ID: P4E-SMARTPIN-3

MEASUREMENT/TECHNICAL REPORT

Integrated Engineering B.V.

Model : Smartreader/extA

FCC ID: P4E-SMARTPIN-3

January 30, 2006

This report concerns:	Original grant/certification	Class 2 change	Verification
Equipment type:	Intelligent Substation		
Deferred grant requested per 47 CFR 0.457(d)(1)(ii) ?	Yes	No	n.a.
Report prepared by:	Name	: J. Schuurmans, B.Sc.E.E.	
	Company name	: TNO Electronic Products & Services (EPS) B.V.	
	Address	: Smidshornerweg 18	
	Postal code/city	: 9822 ZG Niekerk	
	Mailing address	: P.O. Box 15	
	Postal code/city	: 9822 TL Niekerk	
	Country	: The Netherlands	
	Telephone number	: + 31 594 505 005	
	Telefax number	: + 31 594 504 804	
	E-mail	: info@eps.tno.nl	

The data taken for this test and report herein was done in accordance with 47 CFR Part 15 and the measurement procedures of ANSI C63.4-1992. TNO Electronic Products & Services (EPS) B.V. at Niekerk, The Netherlands, certifies that the data is accurate and contains a true representation of the emission profile of the Equipment Under Test (EUT) on the date of the test as noted in the test report. I have reviewed the test report and find it to be an accurate description of the test(s) performed and the EUT so tested.

Date: January 30, 2006

Signature:

P.A.J.M. Robben, B.Sc.E.E.
TNO Electronic Products & Services (EPS) B.V.



Test specification(s): 47 CFR Part 15 (2004-10-01))
Description of EUT: 13.56 MHz inductive e-document reader
Manufacturer: Integrated Engineering
Brand mark: Integrated Engineering
Model: Smartreader/extA
FCC ID: P4E-SMARTPIN-3

Description of test item

Test item : 13.56 MHz inductive e-document reader
Manufacturer : Integrated Engineering B.V.
Brand : Integrated Engineering
Model : Smartreader/extA, model no. 800-8250
Serial number(s) : 05.25 2000
Revision : Not applicable
Receipt date : November 15, 2005

Applicant information

Applicant's representative : Ir. R. Holslag
Company : Integrated Engineering B.V.
Address : Paasheuvelweg 20
Postal code : 1105 BJ
City : Amsterdam
PO-box : -
Postal code : -
City : -
Country : The Netherlands
Telephone number : +31 (0) 20 46 20 755
Telefax number : +31 (0) 20 46 20 756

Test(s) performed

Location : Niekerk
Test(s) started : November 15, 2005
Test(s) completed : December 23, 2005
Purpose of test(s) : Equipment Authorisation (Certification).

Test specification(s) : 47 CFR Part 15 (2004-01-10)

Test engineers : J. Schuurmans, B.Sc.E.E. 

Report written by : J. Schuurmans, B.Sc.E.E.

Report date : January 30, 2006

This report is in conformity with NEN-EN-ISO/IEC 17025: 2000.

This report shall not be reproduced, except in full, without the written permission of TNO Electronic Products & Services (EPS) B.V.
The test results relate only to the item(s) tested.



Table of contents

1	General information.	5
1.1	Product description.	5
1.1.1	Introduction.	5
1.2	Related submittal(s) and/or Grant(s).	5
1.3	Tested system details.	5
1.3.1	Description of input and output ports.	6
1.4	Test methodology.	6
1.5	Test facility.	6
1.6	Product labeling.	6
2	System test configuration.	7
2.1	Justification.	7
2.2	EUT mode of operation.	7
2.3	Special accessories.	7
2.4	Equipment modifications.	7
2.5	Block diagram of the EUT.	8
2.6	Schematics of the EUT.	8
2.7	Part list of the EUT.	8
3	Radiated emission data.	9
3.1	Radiated field strength measurements (30 MHz – 1 GHz, H-field).	9
3.2	Radiated field strength measurements (frequency range of 0.009-30 MHz, H-field).	11
4	Conducted emission data.	12
4.1	Conducted emission data of the EUT.	12
5	Operation in the band 13.110 – 14010 MHz.	13
5.1	Field strength near the carrier frequency.	13
6	List of utilized test equipment.	14



Test specification(s): 47 CFR Part 15 (2004-10-01))
Description of EUT: 13.56 MHz inductive e-document reader
Manufacturer: Integrated Engineering
Brand mark: Integrated Engineering
Model: Smartreader/extA
FCC ID: P4E-SMARTPIN-3

1 General information.

1.1 Product description.

1.1.1 Introduction.

The EUT is an inductive e-document reader intended to be read the inductive tags used in certain documents.

1.2 Related submittal(s) and/or Grant(s).

Not applicable.

1.3 Tested system details.

Details and an overview of the system and all of its components, as it has been tested, may be found below.

Test item 1	:	13.56 MHz Inductive e-document reader
Manufacturer	:	Integrated Engineering B.V.
Brand	:	Integrated Engineering
Model	:	SmartReader/extA
Model number	:	800-8250
Serial number	:	05.45.2000
Voltage input rating	:	+5 V DC through USB connector
Auxiliary equipment 1	:	Laptop
Manufacturer	:	Dell Computer Corporation
Brand	:	Dell
Model	:	C600
Serial number	:	TW-0791UH-12800-155-4387
Voltage input rating	:	100-240 VAC, 50-60 Hz
Current input rating	:	3.5 Amps max.
Remarks	:	used on USB port.



Test specification(s): 47 CFR Part 15 (2004-10-01))
Description of EUT: 13.56 MHz inductive e-document reader
Manufacturer: Integrated Engineering
Brand mark: Integrated Engineering
Model: Smartreader/extA
FCC ID: P4E-SMARTPIN-3

1.3.1 Description of input and output ports.

Number	Ports	From	To	Shielding	Remarks
1	AC mains	AC mains	AE1	yes / no	None
2	USB port	AE1	EUT	yes no	None

AE = Auxiliary equipment

1.4 Test methodology.

The test methodology used is based on the requirements of 47 CFR Part 15 (2004-10-01), sections 15.207 and 15.209, and 15.225.

The test methods, which have been used, are based on ANSI C63.4: 2003.

Radiated emission tests above 30 MHz were performed at a measurement distance of 3 meters.

Radiated emission tests below 30 MHz were performed at a measurement distance of 3 meters and 10 meters. To calculate the field strength level from these results to the appropriate distance at which the limit is specified, the calculation in appendix 1 has been applied.

The receivers are switching automatically to the right bandwidth in accordance with CISPR 16. This is implemented in the receiver. The antenna factors are programmed in the test receiver. The receiver automatically calculates the appropriate correction factor for the utilized antenna and also the appropriate antenna factor for the cable loss. The total correction is automatically added to the measured value.

1.5 Test facility.

The Federal Communications Commission has reviewed the technical characteristics of the test facilities at TNO Electronic Products & Services (EPS) B.V., located in Niekerk, 9822 TL Smidshornerweg 18, The Netherlands, and has found these test facilities to be in compliance with the requirements of 47 CFR Part 15, section 2.948, per October 23, 2000.

The description of the test facilities has been filed at the Office of the Federal Communications Commission under registration number 90828. The facility has been added to the list of laboratories performing these test services for the public on a fee basis.

The list of all public test facilities is available on the Internet at <http://www.fcc.gov>.

1.6 Product labeling.

In accordance with 47 CFR Part 15.19 (a)(3) the following text shall be placed on a label, which is attached to the EUT:

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

A label, in accordance with 47 CFR Part 15.19 (b)(1)(i), shall be attached to the EUT.

For further details about the labeling requirements (size, legibility, etc.) as set by the Federal Communications Commission see 47 CFR Part 15.19 (a)(3), 47 CFR Part 15.19 (b)(1), 47 CFR Part 15.19 (b)(2) and 47 CFR Part 15.19 (b)(4).



Test specification(s):	47 CFR Part 15 (2004-10-01))
Description of EUT:	13.56 MHz inductive e-document reader
Manufacturer:	Integrated Engineering
Brand mark:	Integrated Engineering
Model:	Smartreader/extA
FCC ID:	P4E-SMARTPIN-3

2 System test configuration.

2.1 Justification.

The system was configured for testing in a typical fashion (as a customer would normally use it).

The justification and manipulation of cables and equipment in order to simulate a worst-case behavior of the test setup has been carried out as prescribed in ANSI C63.4: 2003.

2.2 EUT mode of operation.

The EUT has been tested in active mode, i.e. the EUT is ready to detect an e-document. To assess the behavior of the EUT while reading the e-document, the EUT is tested with a e-document presented such that it continuously reads the e-document, and continuously sends data to the USB port of the EUT, connected to AE1.

2.3 Special accessories.

No special accessories are used and/or needed to achieve compliance with the appropriate sections of 47 CFR Part 15.

2.4 Equipment modifications.

No modifications have been made to the equipment in order to achieve compliance with the appropriate sections of 47 CFR Part 15.



Test specification(s):	47 CFR Part 15 (2004-10-01))
Description of EUT:	13.56 MHz inductive e-document reader
Manufacturer:	Integrated Engineering
Brand mark:	Integrated Engineering
Model:	Smartreader/extA
FCC ID:	P4E-SMARTPIN-3

2.5 Block diagram of the EUT.

The block diagram is available in the technical documentation package which will be submitted to the Commission.

2.6 Schematics of the EUT.

The schematics are available in the technical documentation package which will be submitted to the Commission.

2.7 Part list of the EUT.

The part list is available in the technical documentation package which will be submitted to the Commission.



Test specification(s): 47 CFR Part 15 (2004-10-01))
Description of EUT: 13.56 MHz inductive e-document reader
Manufacturer: Integrated Engineering
Brand mark: Integrated Engineering
Model: Smartreader/extA
FCC ID: P4E-SMARTPIN-3

3 Radiated emission data.

3.1 Radiated field strength measurements (30 MHz – 1 GHz, H-field).

Frequency (MHz)	Measurement results dB(μV)/m @ 3 metres Quasi-peak		Limits dB(μV)/m @ 3 metres Quasi-peak	Margin (dB) Quasi-peak		Result
	Vertical	Horizontal		Vertical	Horizontal	
43.81	21.4	12.5	40.0	-18.6	-27.5	PASS
47.94	27.4	10.4	40.0	-12.6	-29.6	PASS
50.44	20.5	9.4	40.0	-19.5	-30.6	PASS
54.25	30.3	32.0	40.0	-9.7	-8.0	PASS
67.81	22.9	22.9	40.0	-17.1	-17.1	PASS
81.37	25.0	24.8	40.0	-15.0	-15.2	PASS
86.43	26.3	18.4	40.0	-13.7	-21.6	PASS
108.50	26.3	26.8	43.5	-17.2	-16.7	PASS
115.13	31.8	28.6	43.5	-11.8	-15.0	PASS
120.00	25.2	25.0	43.5	-18.3	-18.5	PASS
120.69	31.8	21.9	43.5	-11.7	-21.6	PASS
135.63	27.5	19.9	43.5	-16.0	-23.6	PASS
149.18	24.7	26.9	43.5	-18.8	-16.6	PASS
162.75	30.7	34.2	43.5	-12.8	-9.3	PASS
170.00	20.6	23.8	43.5	-22.9	-19.7	PASS
176.31	33.2	37.0	43.5	-10.3	-6.5	PASS
180.00	24.8	27.9	43.5	-18.7	-15.6	PASS
189.88	36.4	38.5	43.5	-7.1	-5.0	PASS
190.00	22.7	29.4	43.5	-20.8	-14.1	PASS
200.00	19.8	24.8	43.5	-23.7	-18.7	PASS
200.00	19.8	24.8	43.5	-23.7	-18.7	PASS
203.43	25.3	27.3	43.5	-18.2	-16.2	PASS
221.18	27.0	21.2	46.0	-19.0	-24.8	PASS
230.55	25.2	31.0	46.0	-20.8	-15.0	PASS
233.50	14.4	23.9	46.0	-31.6	-22.1	PASS
244.13	24.7	36.5	46.0	-21.3	-9.5	PASS
257.68	27.6	29.6	46.0	-18.4	-16.4	PASS
260.00	26.6	26.1	46.0	-19.4	-19.9	PASS
271.24	23.7	16.9	46.0	-22.3	-29.1	PASS
280.00	26.0	26.0	46.0	-20.0	-20.0	PASS
300.00	26.7	28.6	46.0	-19.3	-17.4	PASS
311.93	34.3	34.0	46.0	-11.7	-12.0	PASS
474.67	29.0	23.5	46.0	-17.0	-22.5	PASS

Table 1: Radiated emission of the EUT.



Test specification(s): 47 CFR Part 15 (2004-10-01))
Description of EUT: 13.56 MHz inductive e-document reader
Manufacturer: Integrated Engineering
Brand mark: Integrated Engineering
Model: Smartreader/extA
FCC ID: P4E-SMARTPIN-3

The results of the radiated emission tests, carried out in accordance with 47 CFR Part 15, section 15.209, with the EUT tested in active mode and while detecting a card are depicted in table 1.

Notes:

1. Field strength values of radiated emissions at frequencies not listed in the table above are more than 20 dB below the applicable limit.

Test engineer

A handwritten signature in blue ink, appearing to read 'J. Schuurmans', is written over a horizontal line.

Signature :

Name : J. Schuurmans

Date : December 12, 2005



Test specification(s): 47 CFR Part 15 (2004-10-01))
 Description of EUT: 13.56 MHz inductive e-document reader
 Manufacturer: Integrated Engineering
 Brand mark: Integrated Engineering
 Model: Smartreader/extA
 FCC ID: P4E-SMARTPIN-3

3.2 Radiated field strength measurements (frequency range of 0.009-30 MHz, H-field).

Frequency (MHz)	Measurement results dB μ V Quasi-peak		Antenna factor dB	Cable loss dB	Measurement results dB(μ V)/m Quasi-peak (calculated) 30 meters	Limits Part 15.209 & 225 dB(μ V)/m
	3 meters	10 meters				
0.009 - 0.490	<10.0	n.a.	20.5	1	-	28.5 – 13.8 (300 m)
0.490 - 1.705	<10.0	n.a.	19.5	1	-	33.8 - 22.9 (30 m)
1.705 – 13.56	< 10.0	n.a.	19.5	1	-	29.5 (30 m)
13.110-13.410	<10	n.a.	19.5	1	-	40.5 (30 m)
13.410-13.553	<10	n.a.	19.5	1	-	50.5 (30 m)
13.553-13.567	57.7	37.5	19.5	1	40.6	84.0 (30m)
13.567-13.710	<10	n.a.	19.5	1	-	50.5 (30m)
13.710—14.010	<10	n.a.	19.5	1	-	40.5 (30m)
27.124	12.0	<10.0	19.7	1	<12.0	29.5 (30m)

Table 2 Radiated emissions of the EUT.

The results of the radiated emission tests, carried out in accordance with 47 CFR Part 15, sections 15.205 and 15.209, with the EUT operating in continuous transmit mode on 13.56 kHz, are depicted in table 2.

- Notes:**
- A total work out of the calculated measurement result can be found in the Appendix 1.
 - Frequency range: 9-90 kHz Average detector used during measurements
110-490 kHz Average detector used during measurements
 - The radiated field strengths were measured at a distance of 3 and 10 meters. Measured field strengths at a distance of 10 meters were already below the limit of 30/300 meters
 - n.a. indicates that no field strength values could be measured on the listed frequencies or in the listed frequency range
 - Field strength values of radiated emissions at frequencies not listed in table 2 are more than 20 dB below the applicable limit
 - The EUT was varied in three positions, the loop antenna was varied in two orientations. The reported value is the worst case found at the reported frequency.
 - The EUT was tested in both normal mode (i.e. without a label in its proximity) and in activated mode (i.e. with a label in its proximity).

Test engineer

Signature

Name : J. Schuurmans

Date : December 19, 2005



Test specification(s): 47 CFR Part 15 (2004-10-01))
Description of EUT: 13.56 MHz inductive e-document reader
Manufacturer: Integrated Engineering
Brand mark: Integrated Engineering
Model: Smartreader/extA
FCC ID: P4E-SMARTPIN-3

4 Conducted emission data.

4.1 Conducted emission data of the EUT.

Frequency (MHz)	Measurement results dB(μ V) Neutral		Measurement results dB(μ V) Line 1		Limits dB(μ V)		Margin (dB) Neutral		Margin (dB) Line 1		Result
	QP	AV	QP	AV	QP	AV	QP	AV	QP	AV	
0.15	43.3	10.8	42.8	10.9	66.0	56.0	-22.7	-45.2	-23.2	-45.1	PASS
0.19	50.8	32.5	50.2	32.9	64.2	54.2	-13.4	-21.7	-14.0	-21.3	PASS
0.30	37.1	26.9	36.9	28.7	60.2	50.2	-23.1	-23.3	-23.3	-21.5	PASS
0.20	33.5	32.1	32.8	24.7	63.8	53.8	-30.3	-21.7	-31.0	-29.1	PASS
0.50	31.2	23.0	28.9	21.4	56.1	46.1	-24.9	-23.1	-27.2	-24.7	PASS
0.82	31.5	26.7	32.3	28.0	56.0	46.0	-24.5	-19.3	-23.7	-18.0	PASS
2.50	33.3	26.6	33.1	27.2	56.0	46.0	-22.7	-19.4	-22.9	-18.8	PASS
13.56	33.3	32.5	34.2	32.4	60.0	50.0	-26.7	-17.5	-25.8	-17.6	PASS
27.12	31.2	21.0	21.0	14.3	60.0	50.0	-28.8	-29.0	-39.0	-35.7	PASS

Table 3: Conducted emission measurements.

The results of the conducted emission tests, carried out in accordance with 47 CFR Part 15, section 15.207, at the 110 Volts AC mains connection terminals of the AC/DC power supply which was connected to the EUT, are depicted in table 5. A dummy load was attached to replace the internal antenna.

Notes:

1. The conducted emissions on frequencies which are not listed in the table above were found to be below 25 dB μ V on both line 1 and line 2.

Test engineer

Signature : 

Name : J. Schuurmans, B.Sc.E.E.

Date : December 8, 2005

5 Operation in the band 13.110 – 14010 MHz.

5.1 Field strength near the carrier frequency




Figure 1: Fieldstrength near the carrier frequency.

Notes:

1. The peak level in figure 1 corresponds to the value at 30 m in Table 2.
2. The temperature dependence and AC mains voltage (85%-115%) dependence have been found to be less than +/- 0.01% of the operating frequency

Test engineer

Signature : 

Name : J. Schuurmans, B.Sc.E.E.

Date : December 19, 2005



Test specification(s): 47 CFR Part 15 (2004-10-01))
Description of EUT: 13.56 MHz inductive e-document reader
Manufacturer: Integrated Engineering
Brand mark: Integrated Engineering
Model: Smartreader/extA
FCC ID: P4E-SMARTPIN-3

6 List of utilized test equipment.

Inventory number	Description	Brand	Model
12476	Antenna mast	EMCO	TR3
12477	Antenna mast 1-4 mtr	Poelstra	--
12491	Measuring receiver	R&S	ESH3
12493	Spectrum monitor ESH3	R&S	EZM
12512	LISN FCC	Emco	3725/2
12605	calibrated dipole 28MHz-1GHz	Emco	3121c
12636	Polyester chamber	Polyforce	--
13313	Pulse limiter	R&S	ESH3-Z2
13886	Open Area testsite	Comtest	--
14051	Anechoic room	Comtest	--
15633	Biconilog Testantenna	Chase	CBL 6111B
15667	Measuring receiver	R&S	ESCS 30
99055	Non-conducting support	NMi	--
99061	Non-conducting support 150cm	NMi	--
99077	Regulating trafo	RFT	LTS006
99112	Tripod	Chase	--



Appendix 1

Calculated measurements results radiated field strength, H-Field

General Formula:

d_1 = short distance

d_2 = long distance

$$(d_1/d_2))^n = H_{d2}/H_{d1}$$

$$n \log(d_1/d_2) = \log(H_{d2}/H_{d1})$$

Measured field strength at 13.56 MHz:

$$H_{3m} = 79.2 \text{ dB}\mu\text{V/m} = 9120 \text{ }\mu\text{V/m}$$

$$H_{10m} = 59.0 \text{ dB}\mu\text{V/m} = 891.3 \text{ }\mu\text{V/m}$$

$$n = \log(H_{d2}/H_{d1}) / \log(d_1/d_2)$$

$$n = \log(891.3/9120) / \log(3/10)$$

$$n = 1.93$$

Calculated field strength at 13.56 MHz (10m --> 30m):

$$H_{30m} = H_{d2}, H_{10m} = H_{d1}$$

$$n \log(d_1/d_2) = \log(H_{d2}/H_{d1}) \Rightarrow H_{d2} = H_{d1} (d_1/d_2)^n$$

$$H_{30} = 106.75 \mu\text{V/m} = 40.6 \text{ dB}\mu\text{V/m}$$