

**TEST REPORT CONCERNING THE COMPLIANCE
OF A 13.56 MHZ INDUCTIVE PROXIMITY CARD
READER, OPERATING ON 13.56 MHZ, BRAND
INTEGRATED ENGINEERING,
MODEL SMARTREADERII/8PIN V01.01, WITH
47 CFR PART 15 (AUGUST 14, 2006).**

FCC listed : 90828
Industry Canada : IC3501
R&TTE, LVD, EMC Notified Body : 1856

**TNO Electronic Products & Services (EPS) B.V.
P.O. Box 15
9822 ZG Niekerk (NL)
Smidshornerweg 18
9822 TL Niekerk (NL)**

Telephone: +31 594 505005
Telefax: +31 594 504804

E-mail: info@tno-eps.com
Web: www.tno-eps.com



Test specification(s): 47 CFR Part 15 (2006-02-01)
Description of EUT: 13.56 MHz Inductive Proximity Card Reader
Manufacturer: Integrated Engineering
Brand mark: Integrated Engineering
Model: SmartreaderII/8pin V01.01
FCC ID: P4E-SMARTPIN-8

MEASUREMENT/TECHNICAL REPORT

Integrated Engineering B.V.

Model : SmartreaderII/8pin V01.01

FCC ID: P4E-SMARTPIN-8

August 22, 2007

This report concerns:	Original grant/certification	Class 2 change	Verification
Equipment type:	13.56 MHz Inductive Proximity Card Reader for (DesFire PIV/Mifare) cards		
Deferred grant requested per 47 CFR 0.457(d)(1)(ii) ?	Yes	No	n.a.
Report prepared by:	Name	: Ties E.T. Koning	
	Company name	: TNO Electronic Products & Services (EPS) B.V.	
	Address	: Smidshornerweg 18	
	Postal code/city	: 9822 ZG Niekerk	
	Mailing address	: P.O. Box 15	
	Postal code/city	: 9822 TL Niekerk	
	Country	: The Netherlands	
	Telephone number	: + 31 594 505 005	
	Telefax number	: + 31 594 504 804	
	E-mail	: info@tno-eps.com	

The data taken for this test and report herein was done in accordance with 47 CFR Part 15 (August 14, 2006) and the measurement procedures of ANSI C63.4-2003. TNO Electronic Products & Services (EPS) B.V. at Niekerk, The Netherlands, certifies that the data is accurate and contains a true representation of the emission profile of the Equipment Under Test (EUT) on the date of the test as noted in the test report. I have reviewed the test report and find it to be an accurate description of the test(s) performed and the EUT so tested.

Date: August 22, 2007

Signature:

H.J. Pieters
Project Manager TNO Electronic Products & Services (EPS) B.V.

Description of test item

Test item : 13.56 MHz Inductive Proximity Card Reader
 Manufacturer : Integrated Engineering B.V.
 Brand : Integrated Engineering
 Model : SmartreaderII/8pin V01.01
 Serial number(s) : n.a.
 Revision : n.a.
 Receipt date : July 12, 2007

Applicant information

Applicant's representative : Ir. R. Holslag
 Company : Integrated Engineering B.V.
 Address : Paasheuvelweg 20
 Postal code : 1105 BJ
 City : Amsterdam
 PO-box : -
 Postal code : -
 City : -
 Country : The Netherlands
 Telephone number : +31 (0) 20 46 20 755
 Telefax number : +31 (0) 20 46 20 756


Test(s) performed

Location : Niekerk
 Test(s) started : July 17, 2007
 Test(s) completed : August 17, 2007
 Purpose of test(s) : Equipment Authorization (Original grant/certification)

Test specification(s) : 47 CFR Part 15 (August 14, 2006)

Test engineers : Ties E.T. Koning

Report written by : Ties E.T. Koning.



Report date : August 22, 2007

This report is in conformity with NEN-EN-ISO/IEC 17025: 2005

This report shall not be reproduced, except in full, without the written permission of TNO Electronic Products & Services (EPS) B.V.
The test results relate only to the item(s) tested.

Table of contents

1	General information.	5
1.1	Product description.	5
1.1.1	Introduction.	5
1.2	Related submittal(s) and/or Grant(s).	5
1.2.1	General.	5
1.2.2	FCC ID P4E-SMARTPIN-8.	5
1.3	Tested system details.	5
1.3.1	Description of input and output ports.	6
1.4	Test methodology.	6
1.5	Test facility.	6
1.6	Product labeling.	6
2	System test configuration.	7
2.1	Justification.	7
2.2	EUT mode of operation.	7
2.3	Special accessories.	7
2.4	Equipment modifications.	7
2.5	Block diagram of the EUT.	7
2.6	Schematics of the EUT.	7
2.7	Part list of the EUT.	7
3	Radiated emission data.	8
3.1	Radiated field strength measurements (FCC 15-209: 30 MHz – 1 GHz, E-field).	8
3.2	Radiated field strength measurements (frequency range of 0.009-30 MHz, H-field).	9
3.3	Carrier stability under special conditions.	10
3.3.1	Frequency stability (on 13.56 MHz) in accordance with 47 CFR Part 15, section 15.225 (e) at –20 °C and +50 °C: 10	
3.3.2	Frequency stability in accordance with 47 CFR Part 15, sections 15.225 (e): Temperature = 20 °C 10	
4	Conducted emission data.	12
4.1	Conducted emission data of the EUT.	12
5	List of utilized test equipment.	13

1 General information.

1.1 Product description.

1.1.1 Introduction.

The EUT is an inductive proximity card reader intended to be used in access control systems, parking systems and other applications using RFID readers. It is capable of reading 13.56 MHz inductive tags.

The content of this report and measurement results have not been changed other than the way of presenting the data.

1.2 Related submittal(s) and/or Grant(s).

1.2.1 General.

This test report supports the original grant/certification in equipment authorization files under FCC ID P4E-SMARTPIN-8.

1.2.2 FCC ID P4E-SMARTPIN-8.

This report supports the results of the 13.56 MHz Inductive Card Reader (FCC ID P4E-SMARTPIN-8).

1.3 Tested system details.

Details and an overview of the system and all of its components, as it has been tested, may be found below.

EUT	:	13.56 MHz Inductive Card Reader
Manufacturer	:	Integrated Engineering B.V.
Brand	:	Integrated Engineering
Model	:	SmartreaderII/8pin V01.01
Serial number	:	n.a.
Voltage input rating	:	+4 - +12 VDC (any DC power supply) and 100-240 VAC *)
Current input rating	:	700 mAmps
Remarks	:	All testing with +4 and +12 V DC and 110 V AC achieving maximum radiation

*) Applying an AC adaptor (Auxiliary equipment 1)

Auxiliary equipment 1	:	AC/DC power adapter
Manufacturer	:	FWGB
Brand	:	FRIWO
Model	:	QO2867
Serial number	:	n.a.
Voltage input rating	:	100-240 VAC, 50-60 Hz
Current input rating	:	400 mAmps max.
Voltage output rating	:	+5 VDC
Current output rating	:	2.4 Amps
Remarks	:	-

1.3.1 Description of input and output ports.

Number	Ports	From	To	Shielding	Remarks
1	AC mains	AC mains	AE1	yes / no	None
2	DC power input port	AE1	EUT	yes / no	None
3	Serial port	EUT	--	yes no	None

AE = Auxiliary equipment

1.4 Test methodology.

The test methodology used is based on the requirements of 47 CFR Part 15 (August 14, 2006), sections 15.207, 15.209 and 15.225.

The test methods, which have been used, are based on ANSI C63.4: 2003.

Radiated emission tests above 30 MHz were performed at a measurement distance of 3 meters.

Radiated emission tests below 30 MHz were performed at a measurement distance of 3 meters and 10 meters. To calculate the field strength level from these results to the appropriate distance at which the limit is specified, the calculation in appendix 1 has been applied.

The receivers are switching automatically to the right bandwidth in accordance with CISPR 16. This is implemented in the receiver. The antenna factors are programmed in the test receiver. The receiver automatically calculates the appropriate correction factor for the utilized antenna and also the appropriate antenna factor for the cable loss. The total correction is automatically added to the measured value.

1.5 Test facility.

The Federal Communications Commission has reviewed the technical characteristics of the test facilities at TNO Electronic Products & Services (EPS) B.V., located in Niekerk, 9822 TL Smidshornerweg 18, The Netherlands, and has found these test facilities to be in compliance with the requirements of 47 CFR Part 15, section 2.948, per October 23, 2000.

The description of the test facilities has been filed at the Office of the Federal Communications Commission under registration number 90828. The facility has been added to the list of laboratories performing these test services for the public on a fee basis.

The list of all public test facilities is available on the Internet at <http://www.fcc.gov>.

1.6 Product labeling.

In accordance with 47 CFR Part 15.19 (a)(3) the following text shall be placed on a label, which is attached to the EUT:

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

A label, in accordance with 47 CFR Part 15.19 (b)(1)(i), shall be attached to the EUT.

For further details about the labeling requirements (size, legibility, etc.) as set by the Federal Communications Commission see 47 CFR Part 15.19 (a)(3), 47 CFR Part 15.19 (b)(1), 47 CFR Part 15.19 (b)(2) and 47 CFR Part 15.19 (b)(4).

2 System test configuration.

2.1 Justification.

The system was configured for testing in a typical fashion (as a customer would normally use it).

The justification and manipulation of cables and equipment in order to simulate a worst-case behavior of the test setup has been carried out as prescribed in ANSI C63.4: 2003.

2.2 EUT mode of operation.

The EUT has been tested in active mode, i.e. the EUT is ready to detect a card. To assess the behavior of the EUT while reading the card, the EUT is tested with a card presented such that it continuously reads the card, and continuously sends data to the serial port of the EUT.

The intentional radiator tests (47 CFR Part 15 sections, 15.207, 15.209 and 15.225) have been performed with a complete functioning EUT and interconnections.

2.3 Special accessories.

No special accessories are used and/or needed to achieve compliance with the appropriate sections of 47 CFR Part 15.

2.4 Equipment modifications.

No modifications have been made to the equipment in order to achieve compliance with the appropriate sections of 47 CFR Part 15.

2.5 Block diagram of the EUT.

The block diagram is available in the technical documentation package, which will be submitted to the Commission.

2.6 Schematics of the EUT.

The schematics are available in the technical documentation package, which will be submitted to the Commission.

2.7 Part list of the EUT.

The part list is available in the technical documentation package, which will be submitted to the Commission.

3 Radiated emission data.

3.1 Radiated field strength measurements (FCC 15-209: 30 MHz – 1 GHz, E-field).

Frequency (MHz)	Measurement results dB(μV)/m @ 3 metres Quasi-peak		Limits dB(μV)/m @ 3 metres Quasi-peak	Result PASS/FAIL
	Vertical	Horizontal		
30.0-88.0	< 20.0	<<	40.0	PASS
except for:				
40.68	38.5	<<	40.0	PASS
54.20	18.0	<<	40.0	PASS
67.81	20.9	<<	40.0	PASS
81.37	16.0	<<	40.0	PASS
88.0-216.0	< 20.0	<<	43.5	PASS
except for:				
108.49	29.0	<<	43.5	PASS
122.00	28.9	<<	43.5	PASS
149.19	33.0	<<	43.5	PASS
176.30	39.7	<<	43.5	PASS
216.0-950.0	< 25.0	<<	46.0	PASS
except for:				
256.68	22.0	<<	46.0	PASS
> 950.0	< 30.0	<<	54.0	PASS

Table 1


Radiated emissions of the EUT. The results of the radiated emission tests, carried out in accordance with 47 CFR Part 15, section 15.209, with the EUT tested in active mode and while detecting a card are depicted in table 1.

Notes:

- Field strength values of radiated emissions at frequencies not listed in the table above are more than 20 dB below the applicable limit.
- "<<" means that measurement values are much lower than the value determined for the other polarization.

Test engineer

Signature :



Name : Ties E.T. Koning

Date : August 17, 2007

3.2 Radiated field strength measurements (frequency range of 0.009-30 MHz, H-field).

Frequency (MHz)	Measurement results dB μ V		Antenna factor dB	Cable loss dB	Measurement results dB(μ V)/m for 30 m (calculated)	Limits Part 15.209 & Part 15.225 dB(μ V)/m
	3 meters	10 meters				
0.009 - 0.490	<10.0	n.i.	20.5	1	n.i	48.5 – 13.8 (300 m)
0.490 - 1.705	<10.0	n.i.	19.5	1	n.i	33.8 - 22.9 (30 m)
1.705 – 30.0	< 10.0	n.i.	19.5	1	n.i	29.5 (30 m)
13.562	42.7	19.7	19.6	1	20.1	24.0 (30m) (FCC 15.225-(a))

Table 2

Radiated emissions of the EUT. The results of the radiated emission tests, carried out in accordance with 47 CFR Part 15, sections 15.205, 15.209 and 15.225 with the EUT operating in continuous transmit mode on 13.562 MHz, are depicted in table 2.

- Notes:**
- An example of a calculated measurement result can be found in Appendix 1.
 - Frequency range: 9-90 kHz Average detector used during measurements
110-490 kHz Average detector used during measurements
 - n.i. indicates that no field strength values could be measured on the listed frequencies or in the listed frequency range.
 - Field strength values of radiated emissions at frequencies not listed in table 3 are more than 20 dB below the applicable limit

The EUT was varied in three positions, the loop antenna was varied in two orientations. The reported value is the worst case found at the reported frequency.


The EUT was tested in both normal mode (i.e. without a label in its proximity) and in activated mode (i.e. with a label in its proximity).

Test engineer

Signature :

Name : T.E.T. Koning

Date : August 17, 2007



3.3 Carrier stability under special conditions.

3.3.1 Frequency stability (on 13.56 MHz) in accordance with 47 CFR Part 15, section 15.225 (e) at -20 °C and +50 °C:

- 1) The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% of the operating frequency over a temperature variation of -20 °C to +50 °C at normal supply voltage (see table 3).

Stability under special conditions Temperature (°C)	Measured frequency (MHz)	Frequency deviation (limit $\pm 0.01\%$) (%)	PASS/FAIL
21.0	13.562 (reference)	N.A.	N.A.
-20.0	13.562	< 0.01	PASS
50.0	13.562	< 0.01	PASS

Table 3.

3.3.2 Frequency stability in accordance with 47 CFR Part 15, sections 15.225 (e): Temperature = 20 °C

3.3.2.1 At 85% and 115% of rated voltage supply level

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% of the operating frequency at 85% and at 115% of the rated power supply voltage at 20 °C environmental temperature. The results are stated in Table 4.

Stability under special conditions % variation U	Measured frequency (MHz)	Frequency deviation limit (%)	PASS/FAIL
100.0	13.562 (reference)	N.A.	N.A.
85.0	13.562	< 0.01	PASS
115.0	13.562	< 0.01	PASS


Table 4

Test engineer

Signature :

Name : T.E.T. Koning

Date : August 17, 2007



Amplitude stability in accordance with 47 CFR Part 15, sections 15.31 (e).

EUT amplitude stability measured at 3 different power supply voltages determined at 21 °C (see table 5).

Stability under special conditions % variation U	Amplitude deviation (dB)	PASS/FAIL
100.0	Reference	N.A.
85.0	0.0	PASS
115.0	0.0	PASS


Table 5

Test engineer

Signature :

Name : T.E.T. Koning

Date : August 17, 2007



4 Conducted emission data.

4.1 Conducted emission data of the EUT.

Frequency (MHz)	Measurement results dB(μV) Neutral		Measurement results dB(μV) Line 1		Limits dB(μV)		Result
	QP	AV	QP	AV	QP	AV	
0.15-0.5	< 30.0	< 15.0	<<	<<	66.0-56.0	56.0-46.0	PASS
except for: 0.175	33.5	18.0	<<	<<	65.2	55.2	PASS
0.5-5.0	< 25.0	< 15.0	<<	<<	56.0	46.0	PASS
except for: 2.995	21.3	12.5	<<	<<	56.0	46.0	PASS
5.0-30.0	< 30.0	< 20.0	<<	<<	60.0	50.0	PASS
except for: 13.562	45.0	42.3	<<	<<	60.0	50.0	PASS
27.125	37.6	34.0	<<	<<	60.0	50.0	PASS

Table 6


Conducted emission measurements. The results of the conducted emission tests, carried out in accordance with 47 CFR Part 15, section 15.207, at the 110 Volts AC mains connection terminals of the AC/DC power supply which was connected to the EUT, are depicted in table 6. The EUT was tested in both active mode, and while detecting a card. Maximum values recorded.

Test engineer

Signature :

Name : Ties E.T. Koning

Date : August 17, 2007





Test specification(s): 47 CFR Part 15 (2006-02-01)
 Description of EUT: 13.56 MHz Inductive Proximity Card Reader
 Manufacturer: Integrated Engineering
 Brand mark: Integrated Engineering
 Model: SmartreaderII/8pin V01.01
 FCC ID: P4E-SMARTPIN-8

5 List of utilized test equipment.

Inventory number	Description	Brand	Model	Last cal.	Next cal.
12476	Antenna mast	EMCO	TR3	-	-
12477	Antenna mast 1-4 mtr	Poelstra	--	-	-
12482	Loop antenna	EMCO	6507	04/2007	04/2008
12483	Guidehorn	EMCO	3115	03/2007	03/2008
12484	Guidehorn	EMCO	3115	03/2007	03/2008
12533	Signalgenerator	MARCONI	2032	03/2007	03/2008
12605	Calibrated dipole 28MHz-1GHz	EMCO	3121c	09/2002	09/2007
12640	Temperature chamber	Heraeus	VEM03/500	01/2007	01/2008
13664	Spectrum analyzer	HP	HP8593E	08/2006	08/2007
13886	Open Area testsite	Comtest	--	09/2006	09/2009
14051	Anechoic room	Comtest	--	-	-
15633	Biconilog Testantenna	Chase	CBL 6111B	02/2007	02/2008
15667	Measuring receiver	R&S	ESCS 30	04/2007	04/2008
99596	Preamplifier 0.5 GHz - 18 GHz	Miteq	AMF-5D-005180-28-13p	07/2006	07/2008

Appendix 1

Calculated measurements results radiated field strength, H-Field

General Formula:

d_1 = short distance

d_2 = long distance

So: $(d_1/d_2)^n = H_{d2}/H_{d1}$

$$n \log(d_1/d_2) = \log(H_{d2}/H_{d1})$$

Measured field strength at 13.562 MHz:

$$H_{3m} = 63.3 \text{ dB}\mu\text{V/m} = 1462 \text{ }\mu\text{V/m}$$

$$H_{10m} = 40.3 \text{ dB}\mu\text{V/m} = 103.5 \text{ }\mu\text{V/m}$$

$$n = \log(H_{d2}/H_{d1}) / \log(d_1/d_2)$$

$$n = \log(103.5/1462) / \log(3/10)$$

$$n = 2.12$$

Calculated field strength at 13.562 MHz (10m --> 30m):

$$H_{30m} = H_{d2}, H_{10m} = H_{d1}$$

$$n \log(d_1/d_2) = \log(H_{d2}/H_{d1}) \Rightarrow H_{d2} = H_{d1} (d_1/d_2)^n$$

$$H_{30} = 10.1 \text{ }\mu\text{V/m} = 20.1 \text{ dB}\mu\text{V/m}$$