

FCC TEST REPORT

(PART 24)

REPORT NO.: RF140410C13-1

MODEL NO.: N450

FCC ID: P4Q-N450

RECEIVED: Apr. 10, 2014

TESTED: Apr. 28, 2014 ~ May 13, 2014

ISSUED: May 19, 2014

APPLICANT: MITAC International Corp.

ADDRESS: Building B, No. 209, Sec. 1, Nan Gang Rd., Nan Gang Dist.,
Taipei 11568, Taiwan, R.O.C.

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist., New
Taipei City, Taiwan (R.O.C.)

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim
product certification, approval, or endorsement by TAF or
any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1 CERTIFICATION	4
2 SUMMARY OF TEST RESULTS.....	5
2.1 MEASUREMENT UNCERTAINTY	5
2.2 TEST SITE AND INSTRUMENTS	6
3 GENERAL INFORMATION	7
3.1 GENERAL DESCRIPTION OF EUT.....	7
3.2 CONFIGURATION OF SYSTEM UNDER TEST	9
3.3 DESCRIPTION OF SUPPORT UNITS.....	9
3.4 TEST ITEM AND TEST CONFIGURATION	10
3.5 EUT OPERATING CONDITIONS.....	11
3.6 GENERAL DESCRIPTION OF APPLIED STANDARDS	11
4 TEST TYPES AND RESULTS.....	12
4.1 OUTPUT POWER MEASUREMENT	12
4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT	12
4.1.2 TEST PROCEDURES	12
4.1.3 TEST SETUP	13
4.1.4 TEST RESULTS	14
4.2 FREQUENCY STABILITY MEASUREMENT	17
4.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT	17
4.2.2 TEST PROCEDURE	17
4.2.3 TEST SETUP	17
4.2.4 TEST RESULTS	18
4.3 OCCUPIED BANDWIDTH MEASUREMENT	19
4.3.1 TEST PROCEDURES.....	19
4.3.2 TEST SETUP	19
4.3.3 TEST RESULTS	20
4.4 PEAK TO AVERAGE RATIO.....	21
4.4.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT	21
4.4.2 TEST SETUP	21
4.4.3 TEST PROCEDURES.....	21
4.4.4 TEST RESULTS	22
4.5 BAND EDGE MEASUREMENT	23
4.5.1 LIMITS OF BAND EDGE MEASUREMENT	23
4.5.2 TEST SETUP	23
4.5.3 TEST PROCEDURES.....	23
4.5.4 TEST RESULTS	24
4.6 CONDUCTED SPURIOUS EMISSIONS.....	25
4.6.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT.....	25
4.6.2 TEST PROCEDURE	25
4.6.3 TEST SETUP	25
4.6.4 TEST RESULTS	26
4.7 RADIATED EMISSION MEASUREMENT	27
4.7.1 LIMITS OF RADIATED EMISSION MEASUREMENT	27
4.7.2 TEST PROCEDURES.....	27
4.7.3 DEVIATION FROM TEST STANDARD	27
4.7.4 TEST SETUP	28
4.7.5 TEST RESULTS	29
5 PHOTOGRAPHS OF THE TEST CONFIGURATION	49
6 INFORMATION ON THE TESTING LABORATORIES	50
7 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB.....	51



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF140410C13-1	Original release	May 19, 2014



A D T

1 CERTIFICATION

PRODUCT: Tablet

MODEL: N450

BRAND: Mio, Mitac

APPLICANT: MITAC International Corp.

TESTED: Apr. 28, 2014 ~ May 13, 2014

TEST SAMPLE: Production Unit

STANDARDS: FCC Part 24, Subpart E

The above equipment (model: N450) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Vera Huang , **DATE** : May 19, 2014

Vera Huang / Specialist

APPROVED BY : Sam chen , **DATE** : May 19, 2014

Sam Chen / Senior Project Engineer

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 24 & Part 2			
STANDARD SECTION	TEST TYPE	RESULT	REMARK
2.1046 24.232	Equivalent Isotropically Radiated Power	PASS	Meet the requirement of limit.
2.1055 24.235	Frequency Stability	PASS	Meet the requirement of limit.
2.1049 24.238(b)	Occupied Bandwidth	PASS	Meet the requirement of limit.
24.232(d)	Peak to average ratio	PASS	Meet the requirement of limit.
24.238(b)	Band Edge Measurements	PASS	Meet the requirement of limit.
2.1051 24.238	Conducted Spurious Emissions	PASS	Meet the requirement of limit.
2.1053 24.238	Radiated Spurious Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -21.84dB at 46.20MHz.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	150kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	2.93 dB
	200MHz ~1000MHz	2.95 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2.2 TEST SITE AND INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCI	100412	Sep. 13, 2013	Sep. 12, 2014
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 21, 2013	Dec. 20, 2014
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Feb. 27, 2014	Feb. 26, 2015
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D- 209	Sep. 12, 2013	Sep. 11, 2014
HORN Antenna SCHWARZBECK	BBHA 9170	9170-480	Dec. 18, 2013	Dec. 17, 2014
Preamplifier EMCI	EMC 012645	980115	Dec. 26, 2013	Dec. 25, 2014
Preamplifier EMCI	EMC 184045	980116	Jan. 13, 2014	Jan. 12, 2015
Preamplifier EMCI	EMC 330H	980112	Dec. 27, 2013	Dec. 26, 2014
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	309219/4 2950114	Oct. 18, 2013	Oct. 17, 2014
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250130/4	Oct. 18, 2013	Oct. 17, 2014
RF signal cable Worken	RG-213	NA	Nov. 07, 2013	Nov. 06, 2014
Software BV ADT	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA
Mini-Circuits Power Splitter	ZN2PD-9G	NA	Jul. 18, 2013	Jul. 17, 2014
JFW 20dB attenuation	50HF-020-SMA	NA	NA	NA
Communications Tester-Wireless	E5515C	MY52102544	Sep. 05, 2012	Sep. 04, 2014
Radio Communication Analyzer	MT8820C	6201300640	Aug. 01, 2013	Jul. 31, 2014

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Chamber 10.
3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 690701.
5. The IC Site Registration No. is IC 7450F-10.



A D T

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	Tablet	
MODEL NO.	N450	
POWER SUPPLY	12Vdc (adapter or host equipment) 3.7Vdc (Li-ion battery)	
MODULATION TYPE	GPRS	GMSK
	EDGE	GMSK, 8PSK
	WCDMA	BPSK
FREQUENCY RANGE	GPRS/EDGE	1850.2MHz ~ 1909.8MHz
	WCDMA	1852.4MHz ~ 1907.6MHz
MAX. EIRP POWER	GPRS	899.70mW
	EDGE	179.23mW
	WCDMA	172.35mW
EMISSION DESIGNATOR	GPRS	246KGXW
	EDGE	255KG7W
	WCDMA	4M08F9W
ANTENNA TYPE	Fixed Internal Antenna	
I/O PORTS	Refer to users' manual	
DATA CABLE	Refer to NOTE as below	
ACCESSORY DEVICES	Refer to NOTE as below	

NOTE:


1. The EUT contains following accessory devices.

ITEM	BRAND	MODEL	SPECIFICATION
Adapter 1	SINO-AMERICAN	SA142B-12U	I/P: 110-240Vac, 1.2A O/P: 12Vdc, 3A
Adapter 2	SINPRO	HPU63A-105	I/P: 100-240Vac, 1.62-0.72A O/P: 12Vdc, 5.25A
Battery 1	GETAC	BP-TKS-12/3360 SN	3.7Vdc, 6720mAh
Battery 2	Tian Yu	BK-N450X-510KNX-01	3.7Vdc, 510mAh
USB Cable	EMINENCE	JU-57405040525	0.9m cable
BCR-1 (1D)	Opticon	MDL2001	--
BCR-2 (2D)	HoneyWell	5680	--
BCR-3 (2D)	Code	CR8012	--
CPU	TI	44705GPCBS	1.5G Hz
eMMC	N/A	N/A	16GB
LCD Panel	N/A	N/A	10.1 inch
Front Camera	Liteon	10P2SF130	--
Rear Camera	Liteon	10P2SA511	--
WWAN Module	Ublox	LISA-U200	--
WLAN,BT Module	Jorjin	WG7833-B0 & WX7833-B0	--


2. The above EUT information is declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 CONFIGURATION OF SYSTEM UNDER TEST

FOR RADIATION EMISSION TEST



FOR E.I.R.P. TEST



3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Earphone	N/A	N/A	N/A	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA

NOTE:

1. All power cords of the above support units are non shielded (1.8m).

3.4 TEST ITEM AND TEST CONFIGURATION

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case was found and listed as below table. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	DESCRIPTION	AXIS	
		EIRP	RADIATED EMISSION
A	Tablet w/o Bar Code Scanner + Adapter 1	X	X
B	Tablet w/ 1D Opticon Scanner + Adapter 1	Y	Y
C	Tablet w/ 2D HoneyWell Scanner + Adapter 1	Y	Z
D	Tablet w/ 2D Code Scanner + Adapter 1	Y	Z
E	Tablet w/o Bar Code Scanner + Adapter 2	-	X
F	Tablet w/ 1D Opticon Scanner + Adapter 2	-	Y
G	Tablet w/ 2D HoneyWell Scanner + Adapter 2	-	Z
H	Tablet w/ 2D Code Scanner + Adapter 2	-	Z

GSM MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
A	EIRP	512 to 810	512, 661, 810	GPRS, EDGE
B, C, D	EIRP	512 to 810	512, 661, 810	GPRS
A	FREQUENCY STABILITY	512 to 810	661	GPRS, EDGE
A	OCCUPIED BANDWIDTH	512 to 810	512, 661, 810	GPRS, EDGE
A	PEAK TO AVERAGE RATIO	512 to 810	512, 661, 810	GPRS, EDGE
A	BAND EDGE	512 to 810	512, 810	GPRS, EDGE
A	CONDCUDED EMISSION	512 to 810	661	GPRS, EDGE
A	RADIATED EMISSION	512 to 810	661	GPRS, EDGE
B, C, D, E, F, G, H	RADIATED EMISSION	512 to 810	661	GPRS



A D T

WCDMA MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
A	EIRP	9262 to 9538	9262, 9400, 9538	WCDMA
A	FREQUENCY STABILITY	9262 to 9538	9400	WCDMA
A	OCCUPIED BANDWIDTH	9262 to 9538	9262, 9400, 9538	WCDMA
A	PEAK TO AVERAGE RATIO	9262 to 9538	9262, 9400, 9538	WCDMA
A	BAND EDGE	9262 to 9538	9262, 9538	WCDMA
A	CONDCUDED EMISSION	9262 to 9538	9400	WCDMA
A	RADIATED EMISSION	9262 to 9538	9400	WCDMA

Test CONDITION:

TEST ITEM	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
EIRP	26deg. C, 58%RH	3.8Vdc	Howard Kao
FREQUENCY STABILITY	26deg. C, 58%RH	3.8Vdc	Howard Kao
OCCUPIED BANDWIDTH	26deg. C, 58%RH	3.8Vdc	Howard Kao
PEAK TO AVERAGE RATIO	26deg. C, 58%RH	3.8Vdc	Howard Kao
BAND EDGE	26deg. C, 58%RH	3.8Vdc	Howard Kao
CONDCUDED EMISSION	26deg. C, 58%RH	3.8Vdc	Howard Kao
RADIATED EMISSION	25deg. C, 65%RH	120Vac, 60Hz	Johnson Liao / Peter Weng

3.5 EUT OPERATING CONDITIONS

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.6 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 24

ANSI/TIA/EIA-603-C 2004

NOTE: All test items have been performed and recorded as per the above standards.

4 TEST TYPES AND RESULTS

4.1 OUTPUT POWER MEASUREMENT

4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

Mobile and portable stations are limited to 2 watts EIRP.

4.1.2 TEST PROCEDURES

EIRP MEASUREMENT:


- a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 1MHz for GSM, GPRS & EDGE, 5MHz for CDMA & WCDMA, and 10MHz for LTE mode.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step b. Record the power level of S.G
- d. $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}.$

CONDUCTED POWER MEASUREMENT:


The EUT was set up for the maximum power with GSM, GPRS, EDGE & WCDMA link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

4.1.3 TEST SETUP

EIRP / ERP MEASUREMENT:



CONDUCTED POWER MEASUREMENT:



4.1.4 TEST RESULTS

CONDUCTED OUTPUT POWER (dBm)

Band	GSM1900		
Channel	512	661	810
Frequency (MHz)	1850.2	1880.0	1909.8
GPRS 8 (GMSK, 1 slot)	28.53	28.61	28.21
GPRS 10 (GMSK, 2 slot)	28.44	28.52	28.12
GPRS 11 (GMSK, 3 slot)	27.32	27.50	27.27
GPRS 12 (GMSK, 4 slot)	26.37	26.45	26.05
EDGE 8 (GMSK, 1 Uplink)	28.44	28.50	28.12
EDGE 10 (GMSK, 2 Uplink)	26.54	26.62	26.22
EDGE 11 (GMSK, 3 Uplink)	25.70	25.78	25.38
EDGE 12 (GMSK, 4 Uplink)	24.47	24.55	24.15
EDGE 8 (8PSK, 1 Uplink)	22.50	22.58	22.18
EDGE 10 (8PSK, 2 Uplink)	22.46	22.54	22.14
EDGE 11 (8PSK, 3 Uplink)	21.64	21.72	21.32
EDGE 12 (8PSK, 4 Uplink)	20.58	20.66	20.26

Band	WCDMA II		
Channel	9262	9400	9538
Frequency (MHz)	1852.4	1880.0	1907.6
RMC 12.2K	22.48	22.53	22.50
HSDPA Subtest-1	22.37	22.42	22.39
HSDPA Subtest-2	21.68	21.73	21.70
HSDPA Subtest-3	21.47	21.52	21.49
HSDPA Subtest-4	21.11	21.16	21.13
HSUPA Subtest-1	21.72	21.77	21.74
HSUPA Subtest-2	19.96	20.00	19.98
HSUPA Subtest-3	20.66	20.71	20.68
HSUPA Subtest-4	20.18	20.23	20.20
HSUPA Subtest-5	21.96	22.01	21.98

EIRP POWER (dBm)

MODE A

GPRS							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
X	512	1850.2	-8.44	36.57	28.13	650.43	H
	661	1880.0	-8.71	37.22	28.51	710.23	H
	810	1909.8	-9.15	37.18	28.03	635.62	H
	512	1850.2	-14.73	37.65	22.92	195.93	V
	661	1880.0	-14.64	37.58	22.94	196.92	V
	810	1909.8	-15.23	37.48	22.25	167.88	V

EDGE							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
X	512	1850.2	-14.46	36.57	22.11	162.63	H
	661	1880.0	-14.69	37.22	22.53	179.23	H
	810	1909.8	-15.23	37.18	21.95	156.75	H
	512	1850.2	-19.71	37.65	17.94	62.24	V
	661	1880.0	-19.89	37.58	17.69	58.79	V
	810	1909.8	-20.13	37.48	17.35	54.33	V

WCDMA							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
X	9262	1852.4	-14.58	36.57	21.99	158.20	H
	9400	1880.0	-14.86	37.22	22.36	172.35	H
	9538	1907.6	-15.13	37.18	22.05	160.40	H
	9262	1852.4	-21.43	37.65	16.22	41.89	V
	9400	1880.0	-21.07	37.58	16.51	44.80	V
	9538	1907.6	-21.36	37.48	16.12	40.93	V

MODE B

GPRS							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Y	512	1850.2	-14.02	36.57	22.55	179.97	H
	661	1880.0	-14.53	37.22	22.69	185.95	H
	810	1909.8	-14.67	37.18	22.51	178.32	H
	512	1850.2	-9.36	37.65	28.29	674.68	V
	661	1880.0	-9.22	37.58	28.36	685.96	V
	810	1909.8	-9.29	37.48	28.19	659.17	V

MODE C

GPRS							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Y	512	1850.2	-15.15	36.57	21.42	138.74	H
	661	1880.0	-16.32	37.22	20.90	123.14	H
	810	1909.8	-15.77	37.18	21.41	138.42	H
	512	1850.2	-10.98	37.65	26.67	464.62	V
	661	1880.0	-10.10	37.58	27.48	560.14	V
	810	1909.8	-9.88	37.48	27.60	575.44	V

MODE D

GPRS							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Y	512	1850.2	-13.43	36.57	23.14	206.16	H
	661	1880.0	-14.00	37.22	23.22	210.09	H
	810	1909.8	-14.14	37.18	23.04	201.47	H
	512	1850.2	-8.11	37.65	29.54	899.70	V
	661	1880.0	-8.31	37.58	29.27	845.86	V
	810	1909.8	-8.28	37.48	29.20	831.76	V

4.2 FREQUENCY STABILITY MEASUREMENT

4.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT


The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

4.2.2 TEST PROCEDURE

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the $\pm 0.5^{\circ}\text{C}$ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

4.2.3 TEST SETUP



4.2.4 TEST RESULTS

FREQUENCY ERROR vs. VOLTAGE

VOLTAGE (Volts)	FREQUENCY ERROR (ppm)			LIMIT (ppm)
	GPRS	EDGE	WCDMA	
3.8	-0.003	-0.004	-0.001	2.5
3.4	-0.001	-0.003	-0.004	2.5
4.2	-0.002	-0.004	-0.003	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.4Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE

TEMP. (°C)	FREQUENCY ERROR (ppm)			LIMIT (ppm)
	GPRS	EDGE	WCDMA	
-10	0.005	-0.004	-0.002	2.5
0	-0.001	-0.005	-0.003	2.5
10	0.003	-0.003	-0.001	2.5
20	0.004	-0.002	0.003	2.5
30	0.001	0.002	-0.001	2.5
40	0.002	0.001	-0.001	2.5
50	0.003	-0.004	-0.003	2.5

Note:


1. The applicant declared that the normal operating temperature of the EUT is from -10°C to 50°C.
2. The EUT would shut down automatically as below -10°C.

4.3 OCCUPIED BANDWIDTH MEASUREMENT

4.3.1 TEST PROCEDURES


The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

4.3.2 TEST SETUP



4.3.3 TEST RESULTS

CHANNEL	FREQUENCY	99% OCCUPIED BANDWIDTH (kHz)		CHANNEL	FREQUENCY	99% OCCUPIED BANDWIDTH (MHz)
		GPRS	EDGE			
512	1850.2	243.19	248.38	9262	1852.4	4.0772
661	1880.0	245.45	249.86	9400	1880.0	4.0766
810	1909.8	246.39	254.50	9538	1907.6	4.0736
CHANNEL	FREQUENCY	26dB BANDWIDTH (kHz)		CHANNEL	FREQUENCY	26dB BANDWIDTH (MHz)
		GPRS	EDGE			
512	1850.2	305.70	312.70	9262	1852.4	4.662
661	1880.0	313.90	317.00	9400	1880.0	4.669
810	1909.8	315.70	323.00	9538	1907.6	4.669




4.4 PEAK TO AVERAGE RATIO

4.4.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB.

4.4.2 TEST SETUP




4.4.3 TEST PROCEDURES

1. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1%.

4.4.4 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)		CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
		GPRS	EDGE			WCDMA
512	1850.2	0.11	2.93	9262	1852.4	2.69
661	1880.0	0.11	2.75	9400	1880.0	2.67
810	1909.8	0.11	2.69	9538	1907.6	2.58




4.5 BAND EDGE MEASUREMENT

4.5.1 LIMITS OF BAND EDGE MEASUREMENT

Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

4.5.2 TEST SETUP




4.5.3 TEST PROCEDURES

- All measurements were done at low and high operational frequency range.
- The center frequency of spectrum is the band edge frequency and span is 1MHz. RB of the spectrum is 3kHz and VB of the spectrum is 10kHz (GSM/GPRS/EDGE).
- The center frequency of spectrum is the band edge frequency and span is 5MHz. RB of the spectrum is 100kHz and VB of the spectrum is 300kHz (WCDMA/LTE).
- Record the max trace plot into the test report.



A D T

4.5.4 TEST RESULTS



4.6 CONDUCTED SPURIOUS EMISSIONS


4.6.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit is equal to -13dBm.


4.6.2 TEST PROCEDURE

- The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- Measuring frequency range is from 30 MHz to 19.1GHz. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz is used for conducted emission measurement.

4.6.3 TEST SETUP



4.6.4 TEST RESULTS



4.7 RADIATED EMISSION MEASUREMENT

4.7.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit is equal to -13dBm.

4.7.2 TEST PROCEDURES


- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G
- c. $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$.
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, $E.R.P \text{ power} = E.I.R.P \text{ power} - 2.15\text{dBi}$.

NOTE: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.

4.7.3 DEVIATION FROM TEST STANDARD

No deviation

4.7.4 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.7.5 TEST RESULTS

MODE A


GPRS:



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 15



Site : 966 Chamber 5
Condition: PART22/24 3m HORIZONTAL
Remark : GPRS1900 Link
Tested by: Johnson Liao
Plane : X

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	pp	42.69	-51.89	-50.56	-13.00	-38.89	-1.33 Peak
2		144.21	-54.74	-48.76	-13.00	-41.74	-5.98 Peak
3		201.99	-59.38	-51.52	-13.00	-46.38	-7.86 Peak
4		390.30	-70.40	-64.69	-13.00	-57.40	-5.71 Peak
5		666.80	-64.16	-65.00	-13.00	-51.16	0.84 Peak
6		947.50	-62.10	-65.74	-13.00	-49.10	3.64 Peak
7		3760.00	-56.99	-48.69	-13.00	-43.99	-8.30 Peak



A D T




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 16

Date: 2014-05-07



Site : 966 Chamber 5
Condition: PART22/24 3m VERTICAL
Remark : GPRS1900 Link
Tested by: Johnson Liao
Plane : X

		Read	Limit	Over			
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	pp	87.24	-45.25	-34.76	-13.00	-32.25	-10.49 Peak
2		152.04	-47.48	-41.09	-13.00	-34.48	-6.39 Peak
3		209.01	-57.12	-49.61	-13.00	-44.12	-7.51 Peak
4		382.60	-69.49	-63.73	-13.00	-56.49	-5.76 Peak
5		656.30	-63.97	-64.63	-13.00	-50.97	0.66 Peak
6		920.90	-62.14	-65.24	-13.00	-49.14	3.10 Peak
7		3760.00	-56.19	-47.89	-13.00	-43.19	-8.30 Peak



A D T

EDGE:




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 11

Date: 2014-05-07



Site : 966 Chamber 5
Condition: PART22/24 3m HORIZONTAL
Remark : EDGE1900 Link
Tested by: Johnson Liao
Plane : X

Freq	Level	Read	Limit	Over	Factor	Remark
		Level	Line	Limit		
MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 pp 3760.00	-56.24	-47.94	-13.00	-43.24	-8.30	Peak



A D T




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 12

Date: 2014-05-07



Site : 966 Chamber 5
Condition: PART22/24 3m VERTICAL
Remark : EDGE1900 Link
Tested by: Johnson Liao
Plane : X

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	pp	3760.00	-57.22	-48.92	-13.00	-44.22	-8.30 Peak



A D T


WCDMA:



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 11



Site : 966 Chamber 5
Condition: PART22/24 3m HORIZONTAL
Remark : Band II Link
Tested by: Johnson Liao
Plane : X

Freq	Level	Read	Limit	Over	Factor	Remark
		Level	Line	Limit		
MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 pp 3760.00	-57.07	-48.77	-13.00	-44.07	-8.30	Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 12



Site : 966 Chamber 5
Condition: PART22/24 3m VERTICAL
Remark : Band II Link
Tested by: Johnson Liao
Plane : X

Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 pp 3760.00	-56.26	-47.96	-13.00	-43.26	-8.30	Peak



A D T

MODE B


GPRS:



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 15



Site : 966 Chamber 5
Condition: PART22/24 3m HORIZONTAL
Remark : GPRS1900 Link
Tested by: Johnson Liao
Plane : Y


		Read	Limit	Over			
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	pp	41.88	-55.00	-53.61	-13.00	-42.00	-1.39 Peak
2		141.51	-58.65	-52.85	-13.00	-45.65	-5.80 Peak
3		203.88	-60.86	-53.08	-13.00	-47.86	-7.78 Peak
4		550.60	-69.23	-67.52	-13.00	-56.23	-1.71 Peak
5		587.00	-66.53	-65.81	-13.00	-53.53	-0.72 Peak
6		696.90	-65.66	-67.06	-13.00	-52.66	1.40 Peak
7		3760.00	-56.64	-48.34	-13.00	-43.64	-8.30 Peak



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 16



Site : 966 Chamber 5
Condition: PART22/24 3m VERTICAL
Remark : GPRS1900 Link
Tested by: Johnson Liao
Plane : Y

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	43.23	-50.69	-49.43	-13.00	-37.69	-1.26	Peak
2 pp	86.70	-48.25	-37.79	-13.00	-35.25	-10.46	Peak
3	206.85	-58.75	-51.11	-13.00	-45.75	-7.64	Peak
4	496.70	-69.77	-66.58	-13.00	-56.77	-3.19	Peak
5	632.50	-66.37	-66.60	-13.00	-53.37	0.23	Peak
6	796.30	-65.09	-67.19	-13.00	-52.09	2.10	Peak
7	3760.00	-56.87	-48.57	-13.00	-43.87	-8.30	Peak



A D T

MODE C


GPRS:



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 13



Site : 966 Chamber 5
Condition: PART22/24 3m HORIZONTAL
Remark : GPRS1900 Link
Tested by: PeterWeng
Plane : Z

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	43.77	-53.49	-52.23	-13.00	-40.49	-1.26	Peak
2	83.19	-60.20	-49.84	-13.00	-47.20	-10.36	Peak
3	146.37	-57.96	-51.85	-13.00	-44.96	-6.11	Peak
4	360.20	-71.01	-65.08	-13.00	-58.01	-5.93	Peak
5	465.20	-69.66	-65.69	-13.00	-56.66	-3.97	Peak
6	794.20	-64.77	-66.86	-13.00	-51.77	2.09	Peak
7 pp	3760.00	-39.58	-31.28	-13.00	-26.58	-8.30	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 14

Date: 2014-05-13



Site : 966 Chamber 5
Condition: PART22/24 3m VERTICAL
Remark : GPRS1900 Link
Tested by: PeterWeng
Plane : Z

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	42.42	-51.20	-49.87	-13.00	-38.20	-1.33	Peak
2	84.27	-49.39	-39.00	-13.00	-36.39	-10.39	Peak
3	153.93	-54.85	-48.43	-13.00	-41.85	-6.42	Peak
4	461.70	-69.28	-65.21	-13.00	-56.28	-4.07	Peak
5	730.50	-65.33	-66.98	-13.00	-52.33	1.65	Peak
6	923.70	-62.65	-65.81	-13.00	-49.65	3.16	Peak
7 pp	3760.00	-40.58	-32.28	-13.00	-27.58	-8.30	Peak



A D T

MODE D


GPRS:



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 13



Site : 966 Chamber 5
Condition: PART22/24 3m HORIZONTAL
Remark : GPRS1900 Link
Tested by: PeterWeng
Plane : Z

		Read	Limit	Over			
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	pp	44.04	-54.61	-53.35	-13.00	-41.61	-1.26 Peak
2		133.68	-58.47	-51.25	-13.00	-45.47	-7.22 Peak
3		203.88	-60.86	-53.08	-13.00	-47.86	-7.78 Peak
4		454.00	-70.40	-66.13	-13.00	-57.40	-4.27 Peak
5		766.90	-64.19	-66.10	-13.00	-51.19	1.91 Peak
6		930.00	-62.43	-65.72	-13.00	-49.43	3.29 Peak
7		3760.00	-55.42	-47.12	-13.00	-42.42	-8.30 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 14



Site : 966 Chamber 5
Condition: PART22/24 3m VERTICAL
Remark : GPRS1900 Link
Tested by: PeterWeng
Plane : Z

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 pp	84.00	-50.15	-39.76	-13.00	-37.15	-10.39	Peak
2	152.85	-53.64	-47.23	-13.00	-40.64	-6.41	Peak
3	205.77	-58.47	-50.78	-13.00	-45.47	-7.69	Peak
4	689.20	-65.31	-66.57	-13.00	-52.31	1.26	Peak
5	762.70	-64.92	-66.79	-13.00	-51.92	1.87	Peak
6	850.90	-63.96	-66.38	-13.00	-50.96	2.42	Peak
7	3760.00	-56.96	-48.66	-13.00	-43.96	-8.30	Peak



A D T

MODE E


GPRS:



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 5



Site : 966 Chamber 5
Condition: PART22/24 3m HORIZONTAL
Remark : GPRS1900 Link
Tested by: Johnson Liao
Plane : X
Remark : Metical

		Read	Limit	Over			
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 pp	46.20	-39.31	-36.98	-13.00	-26.31	-2.33	Peak
2	145.56	-61.77	-55.72	-13.00	-48.77	-6.05	Peak
3	207.39	-61.37	-53.77	-13.00	-48.37	-7.60	Peak
4	327.30	-67.29	-61.11	-13.00	-54.29	-6.18	Peak
5	540.10	-67.01	-65.01	-13.00	-54.01	-2.00	Peak
6	724.20	-62.90	-64.52	-13.00	-49.90	1.62	Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 6



Site : 966 Chamber 5
Condition: PART22/24 3m VERTICAL
Remark : GPRS1900 Link
Tested by: Johnson Liao
Plane : X
Remark : Metical

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 pp	46.20	-34.84	-32.51	-13.00	-21.84	-2.33	Peak
2	106.14	-59.19	-48.66	-13.00	-46.19	-10.53	Peak
3	206.31	-62.79	-55.15	-13.00	-49.79	-7.64	Peak
4	358.80	-70.03	-64.09	-13.00	-57.03	-5.94	Peak
5	555.50	-66.84	-65.27	-13.00	-53.84	-1.57	Peak
6	726.30	-63.31	-64.94	-13.00	-50.31	1.63	Peak



A D T

MODE F


GPRS:



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 5



Site : 966 Chamber 5
Condition: PART22/24 3m HORIZONTAL
Remark : GPRS1900 Link
Tested by: Johnson Liao
Plane : Y
Remark : Metical

		Read	Limit	Over			
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 pp	45.66	-40.52	-38.76	-13.00	-27.52	-1.76	Peak
2	146.91	-63.25	-57.08	-13.00	-50.25	-6.17	Peak
3	204.15	-63.09	-55.36	-13.00	-50.09	-7.73	Peak
4	337.10	-69.25	-63.15	-13.00	-56.25	-6.10	Peak
5	593.30	-66.28	-65.74	-13.00	-53.28	-0.54	Peak
6	764.10	-64.17	-66.06	-13.00	-51.17	1.89	Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 6



Site : 966 Chamber 5
Condition: PART22/24 3m VERTICAL
Remark : GPRS1900 Link
Tested by: Johnson Liao
Plane : Y
Remark : Metical

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 pp	45.66	-36.77	-35.01	-13.00	-23.77	-1.76	Peak
2	100.20	-64.45	-54.05	-13.00	-51.45	-10.40	Peak
3	210.90	-64.96	-57.49	-13.00	-51.96	-7.47	Peak
4	323.10	-70.98	-64.77	-13.00	-57.98	-6.21	Peak
5	643.00	-63.43	-63.85	-13.00	-50.43	0.42	Peak
6	748.70	-63.96	-65.74	-13.00	-50.96	1.78	Peak



A D T

MODE G


GPRS:



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 5



Site : 966 Chamber 5
Condition: PART22/24 3m HORIZONTAL
Remark : GPRS1900 Link
Tested by: Johnson Liao
Plane : Z
Remark : Metical

		Read	Limit	Over			
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 pp	43.23	-38.78	-37.52	-13.00	-25.78	-1.26	Peak
2	143.67	-62.80	-56.88	-13.00	-49.80	-5.92	Peak
3	210.09	-63.04	-55.57	-13.00	-50.04	-7.47	Peak
4	328.00	-67.80	-61.63	-13.00	-54.80	-6.17	Peak
5	558.30	-67.23	-65.74	-13.00	-54.23	-1.49	Peak
6	713.70	-63.94	-65.48	-13.00	-50.94	1.54	Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 6



Site : 966 Chamber 5
Condition: PART22/24 3m VERTICAL
Remark : GPRS1900 Link
Tested by: Johnson Liao
Plane : Z
Remark : Metical

		Read	Limit	Over			
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 pp	46.47	-37.57	-35.24	-13.00	-24.57	-2.33	Peak
2	204.96	-64.31	-56.58	-13.00	-51.31	-7.73	Peak
3	240.60	-68.64	-62.52	-13.00	-55.64	-6.12	Peak
4	442.10	-69.48	-64.92	-13.00	-56.48	-4.56	Peak
5	617.80	-66.17	-66.13	-13.00	-53.17	-0.04	Peak
6	769.00	-64.54	-66.46	-13.00	-51.54	1.92	Peak



A D T

MODE H


GPRS:



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 5



Site : 966 Chamber 5
Condition: PART22/24 3m HORIZONTAL
Remark : GPRS1900 Link
Tested by: Johnson Liao
Plane : Z
Remark : Metical

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 pp	46.74	-39.63	-37.30	-13.00	-26.63	-2.33	Peak
2	101.82	-69.95	-59.51	-13.00	-56.95	-10.44	Peak
3	211.98	-63.29	-55.91	-13.00	-50.29	-7.38	Peak
4	379.10	-71.01	-65.22	-13.00	-58.01	-5.79	Peak
5	633.20	-65.44	-65.68	-13.00	-52.44	0.24	Peak
6	775.30	-64.27	-66.23	-13.00	-51.27	1.96	Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 6



Site : 966 Chamber 5
Condition: PART22/24 3m VERTICAL
Remark : GPRS1900 Link
Tested by: Johnson Liao
Plane : Z
Remark : Metical

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 pp	45.66	-36.77	-35.01	-13.00	-23.77	-1.76	Peak
2	106.95	-61.10	-50.55	-13.00	-48.10	-10.55	Peak
3	214.41	-64.23	-56.93	-13.00	-51.23	-7.30	Peak
4	335.70	-71.70	-65.59	-13.00	-58.70	-6.11	Peak
5	550.60	-67.72	-66.01	-13.00	-54.72	-1.71	Peak
6	833.40	-63.78	-66.10	-13.00	-50.78	2.32	Peak

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

6 INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.



A D T

7 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications were made to the EUT by the lab during the test.

---END---