

# FCC Report

**Applicant:** Mitac International Corporation

**Address of Applicant:** Building B, No.209, Sec.1, Nan Gang Rd., Nan Gang Taipei, 11568 Taiwan

## Equipment Under Test (EUT)

**Product Name:** GPS Portable Navigation Device

**Model No.:** N515

**Trade Mark:** Mitac, Magellan, Mio

**FCC ID:** P4Q-N515

**Applicable standards:** FCC CFR Title 47 Part 15 Subpart B:2015

**Date of sample receipt:** August 10, 2016

**Date of Test:** August 11-15, 2016

**Date of report issue:** August 16, 2016

**Test Result :** PASS \*

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

A handwritten signature of Robinson Lo is written over a circular blue official seal. The seal contains the text "UNITED TECHNOLOGY SERVICES" around the perimeter, "GTS" in the center, "GLOBAL TESTING CO." below it, and the year "2015" at the bottom. The signature is written in black ink and appears to read "Robinson Lo" followed by "August".

**Robinson Lo**  
**Laboratory Manager**

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the GTS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of GTS or testing done by GTS in connection with, distribution or use of the product described in this report must be approved by GTS in writing.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

## 2 Version

Version No.	Date	Description
00	August 16, 2016	Original

**Prepared By:**

*Edward Pan*

**Date:**

August 16, 2016

**Project Engineer**

**Check By:**

*Andy Wu*

**Date:**

August 16, 2016

**Reviewer**

### 3 Contents

	Page
<b>1 COVER PAGE</b>	1
<b>2 VERSION</b>	2
<b>3 CONTENTS</b>	3
<b>4 TEST SUMMARY</b>	4
4.1 MEASUREMENT UNCERTAINTY	4
<b>5 GENERAL INFORMATION</b>	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF EUT	5
5.3 TEST MODE	5
5.4 TEST FACILITY	6
5.5 TEST LOCATION	6
5.6 DESCRIPTION OF SUPPORT UNITS	6
5.7 DEVIATION FROM STANDARDS	6
5.8 ABNORMALITIES FROM STANDARD CONDITIONS	6
5.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
<b>6 TEST INSTRUMENTS LIST</b>	7
<b>7 TEST RESULTS AND MEASUREMENT DATA</b>	9
7.1 CONDUCTED EMISSIONS	9
7.2 RADIATED EMISSION	12
<b>8 TEST SETUP PHOTO</b>	22
<b>9 EUT CONSTRUCTIONAL DETAILS</b>	23

## 4 Test Summary

Test Item	Section in CFR 47	Result
Conducted Emission	Part15.107	PASS
Radiated Emissions	Part15.109	PASS

PASS: The EUT complies with the essential requirements in the standard.

Remark : Test according to ANSI C63.4:2014.

### 4.1 Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz ~ 30MHz	± 4.34dB	(1)
Radiated Emission	30MHz ~ 1000MHz	± 4.24dB	(1)
Radiated Emission	1GHz ~ 26.5GHz	± 4.68dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	± 3.45dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

## 5 General Information

### 5.1 Client Information

Applicant:	Mitac International Corporation
Address of Applicant:	Building B, No.209, Sec.1, Nan Gang Rd., Nan Gang Taipei, 11568 Taiwan
Manufacturer:	Dongguan Yuanfeng Technology Co., Ltd
Address of Manufacturer:	No. 18, Industrial East Road, Songshan Lake Hi-Tech Industrial Development Zone, Dongguan, Guangdong, 523808, China

### 5.2 General Description of EUT

Product Name:	GPS Portable Navigation Device
Model No.:	N515
Power Supply:	Adapter 1: Model:MIL050200I Input: AC 100-240V~50/60Hz, 0.6A Output: DC 5V ,2A Adapter 2: Model:CA-052-00U-09 Input: DC 12/24V, 1300mA Output: DC 5V ,2A Adapter 3: Model:TCV10100 Input: DC 12-24V Output: DC 5V ,2A Or DC 3.7V 4000mAh Li-ion Battery
Remark: All of adapters were tested. And found radiated emission of adapter 3 was the worst case. Conducted emission of adapter 1 was the worst. So only the worst case was recorded in the report.	

### 5.3 Test mode

Test mode:	
PC mode	Keep the EUT in data exchange with PC mode.
REC mode	Keep the EUT in video recording mode.
USB playing mode	Keep the EUT in video playing via USB flash disk mode.
TF card playing mode	Keep the EUT in TF card playing mode.

## 5.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC —Registration No.: 600491**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 600491, June 22, 2016.

- **Industry Canada (IC) —Registration No.: 9079A-2**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, August 15, 2016..

## 5.5 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

No. 301-309, 3/F., Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102

Tel: 0755-27798480

Fax: 0755-27798960

## 5.6 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC Approval
Apple	PC	A1278	C1MN99ERDTY3	FCC DoC
DELTA	ADAPTER	ADP-60ADT	N/A	FCC DoC
DELL	KEYBOARD	SK-8115	N/A	FCC DoC
DELL	MOUSE	N/A	N/A	FCC DoC
GS	Lead-Acid battery	S5D26R-MFZ	9442804454	FCC DoC

## 5.7 Deviation from Standards

Biconical, log.per. antenna and horn antenna were used instead of dipole antenna.

Semi-anechoic Chamber was used as alternation of open air test sites, and all test suites were performed with radiated method in it.

## 5.8 Abnormalities from Standard Conditions

None.

## 5.9 Other Information Requested by the Customer

None.

## 6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.0(L)*6.0(W)* 6.0(H)	GTS250	July. 03 2015	July. 02 2020
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	ESU EMI Test Receiver	R&S	ESU26	GTS203	June. 29 2016	June. 28 2017
4	Loop Antenna	Zhinan	ZN30900A	GTS534	June. 29 2016	June. 28 2017
5	BiConiLog Antenna	SCHWARZBECK	VULB9163	GTS214	June. 29 2016	June. 28 2017
6	Double-ridged horn antenna	SCHWARZBECK	9120D	GTS208	June. 29 2016	June. 28 2017
7	Horn Antenna	ETS-LINDGREN	3160-09	GTS218	June. 29 2016	June. 28 2017
8	RF Amplifier	HP	8347A	GTS204	June. 29 2016	June. 28 2017
9	RF Amplifier	HP	8349B	GTS206	June. 29 2016	June. 28 2017
10	Broadband Preamplifier	SCHWARZBECK	BBV9718	GTS535	June. 29 2016	June. 28 2017
11	PSA Series Spectrum Analyzer	Agilent	E4440A	GTS536	June. 29 2016	June. 28 2017
12	Universal Radio Communication tester	ROHDE&SCHWARZ	CMU 200	GTS538	June. 29 2016	June. 28 2017
13	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
14	Coaxial Cable	GTS	N/A	GTS210	June. 29 2016	June. 28 2017
15	Coaxial Cable	GTS	N/A	GTS211	June. 29 2016	June. 28 2017
16	Coaxial Cable	GTS	N/A	GTS210	June. 29 2016	June. 28 2017
17	Coaxial Cable	GTS	N/A	GTS212	June. 29 2016	June. 28 2017
18	Thermo meter	N/A	N/A	GTS256	June. 29 2016	June. 28 2017
19	D.C. Power Supply	Insteck	PS-3030	GTS232	June. 29 2016	June. 28 2017


Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	May.16 2014	May.15 2019
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 29 2016	June. 28 2017
3	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June. 29 2016	June. 28 2017
4	Artificial Mains Network	SCHWARZBECK MESS	NSLK8127	GTS226	June. 29 2016	June. 28 2017
5	High voltage probe	SCHWARZBECK	TK9420	GTS537	June. 29 2016	June. 28 2017
6	ISN	SCHWARZBECK	NTFM 8158	GTS565	June. 29 2016	June. 28 2017
7	Coaxial Cable	GTS	N/A	GTS227	June. 29 2016	June. 28 2017
8	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
9	Thermo meter	KTJ	TA328	GTS233	June. 29 2016	June. 28 2017
10	10dB Pulse Limiter	Rohde & Schwarz	N/A	GTS224	June. 29 2016	June. 28 2017

General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Barometer	ChangChun	DYM3	GTS255	June. 29 2016	June. 28 2017

## 7 Test Results and Measurement Data


### 7.1 Conducted Emissions

Test Requirement:	FCC Part15 B Section 15.107																
Test Method:	ANSI C63.4:2014																
Test Frequency Range:	150KHz to 30MHz																
Class / Severity:	Class B																
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto																
Limit:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>			Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)																
	Quasi-peak	Average															
0.15-0.5	66 to 56*	56 to 46*															
0.5-5	56	46															
5-30	60	50															
	<p>* Decreases with the logarithm of the frequency.</p>																
Test setup:	<p>Reference Plane</p> <p>LISN</p> <p>AUX Equipment</p> <p>E.U.T</p> <p>Test table/Insulation plane</p> <p>LISN</p> <p>Filter</p> <p>AC power</p> <p>EMI Receiver</p> <p>40cm</p> <p>80cm</p> <p>Test table height=0.8m</p>																
Test procedure:	<ol style="list-style-type: none"> <li>1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</li> <li>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</li> <li>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2014 on conducted measurement.</li> </ol>																
Test Instruments:	Refer to section 6 for details																
Test mode:	Refer to section 5.3 for details																
Test results:	Pass																

**Measurement Data**
**Line:**


Site : Shielded room  
 Condition : FCC PART15 CLASSB QP LISN-2013 LINE  
 Job No. : 0100  
 Test mode : PC mode  
 Test Engineer: Sky

Freq	Read	LISN		Cable	Limit	Over	Remark
	Freq	Level	Level Factor	Loss	Line	Limit	
	MHz	dBuV	dBuV	dB	dB	dBuV	dB
1	0.156	47.35	47.62	0.15	0.12	65.65	-18.03 QP
2	0.202	42.77	43.04	0.14	0.13	63.54	-20.50 QP
3	0.627	29.73	29.98	0.13	0.12	56.00	-26.02 QP
4	0.716	29.22	29.49	0.14	0.13	56.00	-26.51 QP
5	4.158	31.81	32.16	0.20	0.15	56.00	-23.84 QP
6	19.740	26.38	27.19	0.59	0.22	60.00	-32.81 QP

**Neutral:**


Site : Shielded room  
 Condition : FCC PART15 CLASSB QP LISN-2013 NEUTRAL  
 Job No. : 0100  
 Test mode : PC mode  
 Test Engineer: Sky


Freq	Read	LISN	Cable	Limit	Over	Remark
	MHz	dBuV	Level Factor	Loss	Line	
1	0.161	48.29	48.48	0.07	0.12	65.43 -16.95 QP
2	0.213	42.03	42.22	0.06	0.13	63.10 -20.88 QP
3	0.627	31.42	31.61	0.07	0.12	56.00 -24.39 QP
4	0.716	29.50	29.70	0.07	0.13	56.00 -26.30 QP
5	4.574	32.54	32.84	0.15	0.15	56.00 -23.16 QP
6	19.740	31.83	32.56	0.51	0.22	60.00 -27.44 QP

**Notes:**


1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

## 7.2 Radiated Emission

Test Requirement:	FCC Part15 B Section 15.109																									
Test Method:	ANSI C63.4:2014																									
Test Frequency Range:	30MHz to 25GHz																									
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)																									
Receiver setup:	<table border="1"> <thead> <tr> <th>Frequency</th><th>Detector</th><th>RBW</th><th>VBW</th><th>Remark</th></tr> </thead> <tbody> <tr> <td>30MHz-1GHz</td><td>Quasi-peak</td><td>120kHz</td><td>300kHz</td><td>Quasi-peak Value</td></tr> <tr> <td>Above 1GHz</td><td>Peak</td><td>1MHz</td><td>3MHz</td><td>Peak Value</td></tr> <tr> <td></td><td>Peak</td><td>1MHz</td><td>10Hz</td><td>Average Value</td></tr> </tbody> </table>					Frequency	Detector	RBW	VBW	Remark	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value	Above 1GHz	Peak	1MHz	3MHz	Peak Value		Peak	1MHz	10Hz	Average Value	
Frequency	Detector	RBW	VBW	Remark																						
30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value																						
Above 1GHz	Peak	1MHz	3MHz	Peak Value																						
	Peak	1MHz	10Hz	Average Value																						
Limit:	<table border="1"> <thead> <tr> <th>Frequency</th><th>Limit (dBuV/m @3m)</th><th>Remark</th></tr> </thead> <tbody> <tr> <td>30MHz-88MHz</td><td>40.00</td><td>Quasi-peak Value</td></tr> <tr> <td>88MHz-216MHz</td><td>43.50</td><td>Quasi-peak Value</td></tr> <tr> <td>216MHz-960MHz</td><td>46.00</td><td>Quasi-peak Value</td></tr> <tr> <td>960MHz-1GHz</td><td>54.00</td><td>Quasi-peak Value</td></tr> <tr> <td>Above 1GHz</td><td>54.00</td><td>Average Value</td></tr> <tr> <td></td><td>74.00</td><td>Peak Value</td></tr> </tbody> </table>					Frequency	Limit (dBuV/m @3m)	Remark	30MHz-88MHz	40.00	Quasi-peak Value	88MHz-216MHz	43.50	Quasi-peak Value	216MHz-960MHz	46.00	Quasi-peak Value	960MHz-1GHz	54.00	Quasi-peak Value	Above 1GHz	54.00	Average Value		74.00	Peak Value
Frequency	Limit (dBuV/m @3m)	Remark																								
30MHz-88MHz	40.00	Quasi-peak Value																								
88MHz-216MHz	43.50	Quasi-peak Value																								
216MHz-960MHz	46.00	Quasi-peak Value																								
960MHz-1GHz	54.00	Quasi-peak Value																								
Above 1GHz	54.00	Average Value																								
	74.00	Peak Value																								
Test Procedure:	<ol style="list-style-type: none"> <li>1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> </ol>																									
Test setup:	Below 1GHz																									



Above 1GHz



Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1 012mbar
Measurement Record:	Uncertainty: $\pm 4.5\text{dB}$					
Test Instruments:	Refer to section 6 for details					
Test mode:	Refer to section 5.3 for details					
Test results:	Pass					

**Note:**

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:


Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

## Measurement Data

### PC mode:

Below 1GHz

Horizontal:



Site : 3m chamber

Condition : FCC PART15 CLASS B VULB9163-2013M HORIZONTAL


Job No. : 0100

Test Mode : PC mode

Test Engineer: Sky

Freq	Read	Antenna	Cable	Preamp	Limit	Over	Remark
	Level	Factor	Loss	Factor	Level	Line	
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	66.499	37.79	12.02	0.91	29.88	20.84	40.00 -19.16 QP
2	163.755	39.30	10.77	1.65	29.34	22.38	43.50 -21.12 QP
3	211.527	42.84	12.93	1.91	29.31	28.37	43.50 -15.13 QP
4	321.061	40.45	15.40	2.47	29.88	28.44	46.00 -17.56 QP
5	552.883	37.21	19.62	3.53	29.30	31.06	46.00 -14.94 QP
6	721.726	29.54	21.10	4.17	29.20	25.61	46.00 -20.39 QP

Vertical:




Site : 3m chamber  
 Condition : FCC PART15 CLASS B VULB9163-2013M VERTICAL  
 Job No. : 0100  
 Test Mode : PC mode  
 Test Engineer: Sky

Freq	Read	Antenna	Cable	Preamp	Limit	Over	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	66.967	34.65	11.89	0.92	29.87	17.59	40.00	-22.41 QP
2	153.739	39.50	10.42	1.59	29.39	22.12	43.50	-21.38 QP
3	327.887	40.21	15.66	2.51	29.84	28.54	46.00	-17.46 QP
4	410.383	35.62	17.26	2.91	29.48	26.31	46.00	-19.69 QP
5	492.469	36.67	18.39	3.27	29.32	29.01	46.00	-16.99 QP
6	798.980	35.91	22.06	4.45	29.20	33.22	46.00	-12.78 QP

**REC mode with adapter 3 data :**

Below 1GHz


Horizontal:



Site : 3m chamber  
 Condition : FCC PART15 CLASS B VULB9163-2013M HORIZONTAL  
 Job No. : 0100  
 Test Mode : REC mode  
 Test Engineer: Sky  
 Remark : DC 24V

	Read	Antenna	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
MHz	dBuV	dB/m		dB	dBuV/m	dBuV/m	dB	
1	66.034	41.79	12.30	0.91	29.88	25.12	40.00	-14.88 QP
2	87.112	52.29	13.03	1.09	29.76	36.65	40.00	-3.35 QP
3	153.739	49.74	10.42	1.59	29.39	32.36	43.50	-11.14 QP
4	319.937	42.33	15.33	2.47	29.88	30.25	46.00	-15.75 QP
5	552.883	48.17	19.62	3.53	29.30	42.02	46.00	-3.98 QP
6	562.662	46.39	19.83	3.57	29.30	40.49	46.00	-5.51 QP

Vertical:




Site : 3m chamber  
 Condition : FCC PART15 CLASS B VULB9163-2013M VERTICAL  
 Job No. : 0100  
 Test Mode : REC mode  
 Test Engineer: Sky  
 Remark : DC 24V

Freq	ReadAntenna		Cable Preamp		Limit Level	Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB				
1	38.888	31.31	15.30	0.65	30.05	17.21	40.00	-22.79 QP
2	54.071	34.43	15.06	0.81	29.97	20.33	40.00	-19.67 QP
3	85.898	42.02	12.60	1.08	29.77	25.93	40.00	-14.07 QP
4	153.200	40.61	10.39	1.59	29.39	23.20	43.50	-20.30 QP
5	554.825	40.58	19.67	3.54	29.30	34.49	46.00	-11.51 QP
6	566.622	40.51	19.88	3.59	29.30	34.68	46.00	-11.32 QP

Above 1GHz

**PC mode:**

Horizontal:




Site : 3m chamber  
 Condition : FCC PART 15 (PK) BBHA9120D ANT(>1GHZ) HORIZONTAL  
 Job No. : 0100  
 Test Mode : PC mode  
 Test Engineer: Sky

Freq	ReadAntenna	Cable	Preamp	Limit	Over	Remark		
	Level	Factor	Loss					
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	-----
1 1070.000	38.60	24.67	4.35	32.87	34.75	74.00	-39.25	Peak
2 2285.000	36.96	27.99	5.28	34.13	36.10	74.00	-37.90	Peak
3 3430.000	37.70	28.72	6.82	32.83	40.41	74.00	-33.59	Peak
4 4770.000	32.56	31.73	8.58	32.07	40.80	74.00	-33.20	Peak
5 5885.000	30.04	32.74	10.04	32.20	40.62	74.00	-33.38	Peak

Remark: No emission found from 6GHz to 25GHz. So this band was not display on the report.

Vertical:



Site : 3m chamber  
 Condition : FCC PART 15 (PK) BBHA9120D ANT(>1GHZ) VERTICAL

Job No. : 0100

Test Mode : PC mode


Test Engineer: Sky

Freq	ReadAntenna		Cable		Preamp		Limit Level	Over Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV/m	dBuV/m				
1	1370.000	37.88	25.66	4.59	33.39	34.74	74.00	-39.26	Peak	
2	2355.000	37.19	27.69	5.34	34.05	36.17	74.00	-37.83	Peak	
3	3415.000	37.44	28.67	6.80	32.85	40.06	74.00	-33.94	Peak	
4	4150.000	33.67	30.06	8.01	32.01	39.73	74.00	-34.27	Peak	
5	4695.000	33.19	31.65	8.51	32.03	41.32	74.00	-32.68	Peak	
6	5645.000	30.52	32.36	9.72	32.35	40.25	74.00	-33.75	Peak	

Remark: No emission found from 6GHz to 25GHz. So this band was not display on the report.

**REC mode with adapter 3 data :**

Horizontal:




Site : 3m chamber  
 Condition : FCC PART 15 (PK) BBHA9120D ANT(>1GHZ) HORIZONTAL  
 Job No. : 0100  
 Test Mode : REC mode  
 Test Engineer: Sky  
 Remark : DC 24V

Freq	ReadAntenna		Cable		Preamp	Limit	Over	Remark
	Level	Factor	Loss	Factor				
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	-----
1 1230.000	38.03	25.47	4.49	33.16	34.83	74.00	-39.17	Peak
2 2310.000	37.04	27.91	5.30	34.11	36.14	74.00	-37.86	Peak
3 3410.000	37.42	28.64	6.78	32.85	39.99	74.00	-34.01	Peak
4 4170.000	33.89	30.10	8.03	32.00	40.02	74.00	-33.98	Peak
5 4640.000	32.63	31.57	8.46	32.01	40.65	74.00	-33.35	Peak
6 5095.000	31.64	32.03	8.90	32.23	40.34	74.00	-33.66	Peak

Remark: No emission found from 6GHz to 25GHz. So this band was not display on the report.

Vertical:



Site : 3m chamber

Condition : FCC PART 15 (PK) BBHA9120D ANT(>1GHZ) VERTICAL

Job No. : 0100

Test Mode : REC mode

Test Engineer: Sky

Remark : DC 24V

Freq	ReadAntenna		Cable		Preamp Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB				
1	1325.000	37.72	25.67	4.56	33.30	34.65	74.00	-39.35 Peak
2	2325.000	37.48	27.84	5.32	34.09	36.55	74.00	-37.45 Peak
3	3405.000	37.52	28.64	6.78	32.87	40.07	74.00	-33.93 Peak
4	4345.000	32.88	30.88	8.19	31.86	40.09	74.00	-33.91 Peak
5	5185.000	31.48	32.00	9.03	32.27	40.24	74.00	-33.76 Peak
6	5795.000	29.86	32.63	9.93	32.25	40.17	74.00	-33.83 Peak

Remark: No emission found from 6GHz to 25GHz. So this band was not display on the report.

## 8 Test Setup Photo

Radiated Emission(PC mode)



## Conducted Emission



## 9 EUT Constructional Details

Reference to the test report No. GTS201608000100E01

----- End-----