



# FCC RF Test Report

**APPLICANT** : MiTAC Digital Technology Corporation  
**EQUIPMENT** : Tablet  
**BRAND NAME** : Mitac, Magellan  
**MODEL NAME** : N536B  
**FCC ID** : P4Q-N536B  
**STANDARD** : FCC Part 15 Subpart C §15.225  
**CLASSIFICATION** : (DXX) Low Power Communication Device Transmitter

The product was received on Mar. 23, 2018 and testing was completed on Apr. 21, 2018. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



No. 52, Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.



## TABLE OF CONTENTS

<b>REVISION HISTORY.....</b>	<b>3</b>
<b>SUMMARY OF THE TEST RESULT .....</b>	<b>4</b>
<b>1. GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1    Applicant.....	5
1.2    Manufacturer .....	5
1.3    Product Feature of Equipment Under Test.....	5
1.4    Modification of EUT .....	6
1.5    Testing Location .....	6
1.6    Applicable Standards.....	6
<b>2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....</b>	<b>7</b>
2.1    Descriptions of Test Mode.....	7
2.2    Connection Diagram of Test System.....	7
2.3    Table for Supporting Units.....	8
2.4    EUT Operation Test Setup .....	8
<b>3. TEST RESULTS.....</b>	<b>9</b>
3.1    AC Power Line Conducted Emissions Measurement .....	9
3.2    20dB and 99% OBW Spectrum Bandwidth Measurement.....	11
3.3    Frequency Stability Measurement .....	12
3.4    Field Strength of Fundamental Emissions and Mask Measurement.....	13
3.5    Radiated Emissions Measurement.....	15
3.6    Antenna Requirements.....	18
<b>4. LIST OF MEASURING EQUIPMENT .....</b>	<b>19</b>
<b>5. UNCERTAINTY OF EVALUATION .....</b>	<b>20</b>
<b>APPENDIX A. TEST RESULTS OF CONDUCTED EMISSION TEST</b>	
<b>APPENDIX B. TEST RESULTS OF CONDUCTED TEST ITEMS</b>	
B1. Test Result of 20dB Spectrum Bandwidth	
B2. Test Result of Frequency Stability	
<b>APPENDIX C. TEST RESULTS OF RADIATED TEST ITEMS</b>	
C1. Test Result of Field Strength of Fundamental Emissions	
C2. Results of Radiated Emissions (9 kHz~30MHz)	
C3. Results of Radiated Emissions (30MHz~1GHz)	
<b>APPENDIX D. SETUP PHOTOGRAPHS</b>	



## REVISION HISTORY



## SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C §15.225				
Part	FCC Rule	Description of Test	Result	Remark
3.1	15.207	AC Power Line Conducted Emissions	Complies	Under limit 5.76 dB at 3.671MHz
3.2	15.215(c)	20dB Spectrum Bandwidth	Complies	-
	-	99% OBW Spectrum Bandwidth	Complies	-
3.3	15.225(e)	Frequency Stability	Complies	-
3.4	15.225(a)(b)(c)	Field Strength of Fundamental Emissions	Complies	Max level 62.64 dB $\mu$ V/m at 13.560 MHz
3.5	15.225(d) & 15.209	Radiated Spurious Emissions	Complies	Under limit 4.53 dB at 45.930MHz
3.6	15.203	Antenna Requirements	Complies	-



## 1. General Description

### 1.1 Applicant

**MiTAC Digital Technology Corporation**

No.200, Wen Hua 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)

### 1.2 Manufacturer

**MITAC Computer (Kunshan) Co., Ltd.**

No. 269, 2nd Avenue, District A, Comprehensive Free Trade Zone, 300 Kunshan, China

### 1.3 Product Feature of Equipment Under Test

WCDMA/LTE, Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n, Wi-Fi 5GHz 802.11a/n, NFC, and GNSS

Product Specification subjective to this standard	
<b>Sample 1</b>	EUT with SKU 3
<b>Sample 2</b>	EUT with SKU 4
<b>Integrated WLAN Module</b>	Brand Name: Qualcomm Model Name: WCN3660B
<b>Antenna Type</b>	WWAN: PIFA Antenna WLAN: Holder with FPC Antenna Bluetooth: Holder with FPC Antenna NFC : Loop Antenna GPS / Glonass : PATCH Antenna

Remark: All the tests were performed with Sample 1.

### <Sample Information>

Sample List		
SKU	SKU 3	SKU 4
<b>Model name</b>	N536B	N536B
<b>WLAN</b>	Support	Support
<b>WWAN</b>	Support (with voice)	Support (with voice)
<b>RFID(13.56MHz)</b>	Support	Support
<b>Barcode</b>	Support(SR)	Support(MR)
<b>GPS</b>	Support	Support



## 1.4 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.5 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1190 and TW0007 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

<b>Test Site</b>	SPORTON INTERNATIONAL INC.	
<b>Test Site Location</b>	No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-3273456 / FAX: +886-3-3284978	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	TH03-HY	CO05-HY
<b>Test Engineer</b>	Louis Chung	
<b>Temperature</b>	22~24°C	
<b>Relative Humidity</b>	53~55%	
<b>Note:</b> The test site complies with ANSI C63.4 2014 requirement.		

<b>Test Site</b>	SPORTON INTERNATIONAL INC.	
<b>Test Site Location</b>	No.58, Aly. 75, Ln. 564, Wenhua 3rd Rd. Guishan Dist, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 / FAX: +886-3-327-0855	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	03CH11-HY	
<b>Test Engineer</b>	Jacky Hung and Lance Chiang	
<b>Temperature</b>	21~25°C	
<b>Relative Humidity</b>	52~57%	
<b>Note:</b> The test site complies with ANSI C63.4 2014 requirement.		

## 1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.225
- ♦ ANSI C63.10-2013

## 2. Test Configuration of Equipment Under Test

### 2.1 Descriptions of Test Mode

Investigation has been done on all the possible configurations.


The following table is a list of the test modes shown in this test report.

Test Items	
AC Power Line Conducted Emissions	Field Strength of Fundamental Emissions
20dB Spectrum Bandwidth	Frequency Stability
Radiated Emissions 9kHz~30MHz	Radiated Emissions 30MHz~1GHz

The EUT pre-scanned in four NFC type, A, B, F, V. The worst type (type F) was recorded in this report. Pre-scanned tests, X, Y, Z in three orthogonal panels to determine the final configuration (Z plane as worst plane) from all possible combinations.

Test Cases	
AC Conducted Emission	Mode 1 : WCDMA Band V Idle + Bluetooth Link + WLAN (2.4GHz) Link + NFC Link + Earphone + USB Cable (Charging from Adapter)

### 2.2 Connection Diagram of Test System





## 2.3 Table for Supporting Units

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
3.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8m
4.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A
5.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
6.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A
7.	NFC Card	Metro Taipei	Easy Card	N/A	N/A	N/A

## 2.4 EUT Operation Test Setup

The EUT was programmed to be in continuously transmitting mode.

The ancillary equipment, NFC card, is used to make the EUT (NFC) continuously transmit at 13.56MHz and is placed around 1 cm gap to the EUT.



### 3. Test Results

#### 3.1 AC Power Line Conducted Emissions Measurement

##### 3.1.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


##### 3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

##### 3.1.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

### 3.1.4 Test setup



### 3.1.5 Test Result of AC Conducted Emission

Please refer to Appendix A.

## 3.2 20dB and 99% OBW Spectrum Bandwidth Measurement

### 3.2.1 Limit

Intentional radiators must be designed to ensure that the 20dB and 99% emission bandwidth in the specific band 13.553~13.567MHz.


### 3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

### 3.2.3 Test Procedures

1. The spectrum analyzer connected via a receive antenna placed near the EUT in peak Max hold mode.
2. The resolution bandwidth of 1 kHz and the video bandwidth of 3 kHz were used.
3. Measured the spectrum width with power higher than 20dB below carrier.
4. Measured the 99% OBW.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Conducted Test Items

Please refer to Appendix B.

### 3.3 Frequency Stability Measurement

#### 3.3.1 Limit

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% (100ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.


#### 3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.3.3 Test Procedures

1. The spectrum analyzer connected via a receive antenna placed near the EUT.
2. EUT have transmitted signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire emissions bandwidth.
4. Set RBW = 1 kHz, VBW = 3 kHz with peak detector and maxhold settings.
5. The fc is declaring of channel frequency. Then the frequency error formula is  $(fc-f)/fc \times 10^6$  ppm and the limit is less than  $\pm 100$  ppm.
6. Extreme temperature rule is -20°C~50°C.

#### 3.3.4 Test Setup



#### 3.3.5 Test Result of Conducted Test Items

Please refer to Appendix B.



### 3.4 Field Strength of Fundamental Emissions and Mask Measurement

#### 3.4.1 Limit

Rules and specifications	FCC CFR 47 Part 15 section 15.225			
Description	Compliance with the spectrum mask is tested with RBW set to 9kHz.			
Freq. of Emission (MHz)	Field Strength ( $\mu$ V/m) at 30m	Field Strength (dB $\mu$ V/m) at 30m	Field Strength (dB $\mu$ V/m) at 10m	Field Strength (dB $\mu$ V/m) at 3m
1.705~13.110	30	29.5	48.58	69.5
13.110~13.410	106	40.5	59.58	80.5
13.410~13.553	334	50.5	69.58	90.5
13.553~13.567	15848	84.0	103.08	124.0
13.567~13.710	334	50.5	69.58	90.5
13.710~14.010	106	40.5	59.58	80.5
14.010~30.000	30	29.5	48.58	69.5

#### 3.4.2 Measuring Instruments

See list of measuring instruments of this test report.


### 3.4.3 Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the loop receiving antenna mounted antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the receiving antenna was fixed at one meter above ground to find the maximum emissions field strength.
4. For Fundamental emissions, use the receiver to measure QP reading.
5. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
6. Compliance with the spectrum mask is tested with RBW set to 9kHz.

Note: Emission level (dB $\mu$ V/m) = 20 log Emission level ( $\mu$ V/m).

### 3.4.4 Test Setup

For radiated emissions below 30MHz



### 3.4.5 Test Result of Field Strength of Fundamental Emissions and Mask

Please refer to Appendix C.



## 3.5 Radiated Emissions Measurement

### 3.5.1 Limit

The field strength of any emissions which appear outside of 13.110 ~14.010MHz band shall not exceed the general radiated emissions limits.

Frequencies (MHz)	Field Strength ( $\mu$ V/m)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

### 3.5.3 Measuring Instrument Setting

The following table is the setting of receiver.

Receiver Parameter	Setting
Attenuation	Auto
Frequency Range: 9kHz~150kHz	RBW 200Hz for QP
Frequency Range: 150kHz~30MHz	RBW 9kHz for QP
Frequency Range: 30MHz~1000MHz	RBW 120kHz for Peak

**Note:** The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.




### 3.5.4 Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
7. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. Antenna Requirements

### 3.5.5 Test Setup

For radiated emissions below 30MHz



For radiated emissions above 30MHz



### 3.5.6 Test Result of Radiated Emissions Measurement

Please refer to Appendix C.

**Remark:** There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.



## 3.6 Antenna Requirements

### 3.6.1 Standard Applicable

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

### 3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.



## 4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	AC POWER	AFC-500W	F1040700 11	50Hz~60Hz	Mar. 21, 2018	Apr. 14, 2018	Mar. 20, 2019	Conducted (TH03-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP30	101329	9kHz~30GHz	Jun. 26, 2017	Apr. 14, 2018	Jun. 25, 2018	Conducted (TH03-HY)
Temperature Chamber	ESPEC	SU-641	92013721	-30°C ~70°C	Dec. 06, 2017	Apr. 14, 2018	Dec. 05, 2019	Conducted (TH03-HY)
AC Power Source	ChainTek	APC-1000 W	N/A	N/A	N/A	Apr. 21, 2018	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	3.6GHz	Dec. 08, 2017	Apr. 21, 2018	Dec. 07, 2018	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 30, 2017	Apr. 21, 2018	Nov. 29, 2018	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Dec. 08, 2017	Apr. 21, 2018	Dec. 07, 2018	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Apr. 21, 2018	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 03, 2018	Apr. 21, 2018	Jan. 02, 2019	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 03, 2018	Apr. 21, 2018	Jan. 02, 2019	Conduction (CO05-HY)
Software	Audix	E3 6.2009-8-2 4	RK-00104 2	N/A	N/A	Apr. 10, 2018 ~ Apr. 11, 2018	N/A	Radiation (03CH11-HY)
Amplifier	SONOMA	310N	187312	9kHz~1GHz	Jan. 16, 2018	Apr. 10, 2018 ~ Apr. 11, 2018	Jan. 15, 2019	Radiation (03CH11-HY)
Bilog Antenna	TESEQ	CBL 6111D&N-6 -06	35414&AT- N0602	30MHz~1GHz	Oct. 14, 2017	Apr. 10, 2018 ~ Apr. 11, 2018	Oct. 13, 2018	Radiation (03CH11-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Nov. 23, 2017	Apr. 10, 2018 ~ Apr. 11, 2018	Nov. 22, 2018	Radiation (03CH11-HY)
Spectrum Analyzer	Keysight	N9010A	MY542004 86	10Hz ~ 44GHz	Oct. 19, 2017	Apr. 10, 2018 ~ Apr. 11, 2018	Oct. 18, 2018	Radiation (03CH11-HY)
Antenna Mast	EMEC	AM-BS-450 0-B	N/A	1~4m	N/A	Apr. 10, 2018 ~ Apr. 11, 2018	N/A	Radiation (03CH11-HY)
Turn Table	EMEC	TT 2000	N/A	0~360 Degree	N/A	Apr. 10, 2018 ~ Apr. 11, 2018	N/A	Radiation (03CH11-HY)
EMI Test Receiver	Keysight	N9038A(M XE)	MY554201 70	N/A	Mar. 06, 2018	Apr. 10, 2018 ~ Apr. 11, 2018	Mar. 05, 2019	Radiation (03CH11-HY)
Filter	Wainwright	WHK20/10 00C7/40SS	SN2	20M High Pass	Sep. 18, 2017	Apr. 10, 2018 ~ Apr. 11, 2018	Sep. 17, 2018	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLE X 104	MY9837/4	9K-30M	Mar. 20, 2017	Apr. 10, 2018 ~ Apr. 11, 2018	May 15, 2018	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLE X 104	MY9837/4	30M-18G	Mar. 15, 2017	Apr. 10, 2018 ~ Apr. 11, 2018	May 15, 2018	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLE X 102	MY2589/2	30M-18G	Mar. 15, 2017	Apr. 10, 2018 ~ Apr. 11, 2018	May 15, 2018	Radiation (03CH11-HY)



## 5. Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.70
--	------

### Uncertainty of Radiated Emission Measurement (9 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.45
--	------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.20
--	------




## **Appendix A. Test Results of Conducted Emission Test**

## EUT Information

Report NO : 720610-10  
 Test Mode : Mode 1  
 Test Voltage : 120Vac/60Hz  
 Phase : Line

Full Spectrum



## Final Result


Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	39.38	55.88	16.50	L1	OFF	19.5
0.152250	57.99	---	65.88	7.89	L1	OFF	19.5
0.228750	---	31.45	52.50	21.05	L1	OFF	19.5
0.228750	49.58	---	62.50	12.92	L1	OFF	19.5
0.318750	---	27.35	49.74	22.39	L1	OFF	19.5
0.318750	41.26	---	59.74	18.48	L1	OFF	19.5
0.424500	---	27.66	47.36	19.70	L1	OFF	19.5
0.424500	42.62	---	57.36	14.74	L1	OFF	19.5
0.514500	---	26.16	46.00	19.84	L1	OFF	19.5
0.514500	42.34	---	56.00	13.66	L1	OFF	19.5
0.534750	---	24.80	46.00	21.20	L1	OFF	19.5
0.534750	37.47	---	56.00	18.53	L1	OFF	19.5
0.685500	---	26.66	46.00	19.34	L1	OFF	19.5
0.685500	39.95	---	56.00	16.05	L1	OFF	19.5
0.771000	---	27.72	46.00	18.28	L1	OFF	19.5
0.771000	42.67	---	56.00	13.33	L1	OFF	19.5
0.834000	---	25.79	46.00	20.21	L1	OFF	19.5
0.834000	40.99	---	56.00	15.01	L1	OFF	19.5
1.027500	---	26.88	46.00	19.12	L1	OFF	19.5
1.027500	42.02	---	56.00	13.98	L1	OFF	19.5
1.119750	---	26.15	46.00	19.85	L1	OFF	19.5

<b>1.119750</b>	<b>41.75</b>	<b>---</b>	<b>56.00</b>	<b>14.25</b>	<b>L1</b>	<b>OFF</b>	<b>19.5</b>
<b>1.284000</b>	<b>---</b>	<b>27.02</b>	<b>46.00</b>	<b>18.98</b>	<b>L1</b>	<b>OFF</b>	<b>19.6</b>
<b>1.284000</b>	<b>41.88</b>	<b>---</b>	<b>56.00</b>	<b>14.12</b>	<b>L1</b>	<b>OFF</b>	<b>19.6</b>
<b>1.376250</b>	<b>---</b>	<b>27.84</b>	<b>46.00</b>	<b>18.16</b>	<b>L1</b>	<b>OFF</b>	<b>19.6</b>
<b>1.376250</b>	<b>43.02</b>	<b>---</b>	<b>56.00</b>	<b>12.98</b>	<b>L1</b>	<b>OFF</b>	<b>19.6</b>
<b>1.542750</b>	<b>---</b>	<b>29.04</b>	<b>46.00</b>	<b>16.96</b>	<b>L1</b>	<b>OFF</b>	<b>19.6</b>
<b>1.542750</b>	<b>42.17</b>	<b>---</b>	<b>56.00</b>	<b>13.83</b>	<b>L1</b>	<b>OFF</b>	<b>19.6</b>
<b>1.896000</b>	<b>---</b>	<b>28.27</b>	<b>46.00</b>	<b>17.73</b>	<b>L1</b>	<b>OFF</b>	<b>19.6</b>
<b>1.896000</b>	<b>43.28</b>	<b>---</b>	<b>56.00</b>	<b>12.72</b>	<b>L1</b>	<b>OFF</b>	<b>19.6</b>
<b>2.413500</b>	<b>---</b>	<b>28.18</b>	<b>46.00</b>	<b>17.82</b>	<b>L1</b>	<b>OFF</b>	<b>19.5</b>
<b>2.413500</b>	<b>43.08</b>	<b>---</b>	<b>56.00</b>	<b>12.92</b>	<b>L1</b>	<b>OFF</b>	<b>19.5</b>
<b>3.790500</b>	<b>---</b>	<b>33.33</b>	<b>46.00</b>	<b>12.67</b>	<b>L1</b>	<b>OFF</b>	<b>19.6</b>
<b>3.790500</b>	<b>48.61</b>	<b>---</b>	<b>56.00</b>	<b>7.39</b>	<b>L1</b>	<b>OFF</b>	<b>19.6</b>
<b>7.017000</b>	<b>---</b>	<b>28.76</b>	<b>50.00</b>	<b>21.24</b>	<b>L1</b>	<b>OFF</b>	<b>19.6</b>
<b>7.017000</b>	<b>40.58</b>	<b>---</b>	<b>60.00</b>	<b>19.42</b>	<b>L1</b>	<b>OFF</b>	<b>19.6</b>
<b>13.560000</b>	<b>---</b>	<b>34.06</b>	<b>50.00</b>	<b>15.94</b>	<b>L1</b>	<b>OFF</b>	<b>19.7</b>
<b>13.560000</b>	<b>44.87</b>	<b>---</b>	<b>60.00</b>	<b>15.13</b>	<b>L1</b>	<b>OFF</b>	<b>19.7</b>

## EUT Information

Report NO : 720610-10  
 Test Mode : Mode 1  
 Test Voltage : 120Vac/60Hz  
 Phase : Neutral

Full Spectrum





## Final Result

Frequency (MHz)	QuasiPeak (dB $\mu$ V)	CAverage (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	36.49	55.88	19.39	N	OFF	19.5
0.152250	53.27	---	65.88	12.61	N	OFF	19.5
0.231000	---	31.85	52.41	20.56	N	OFF	19.5
0.231000	46.17	---	62.41	16.24	N	OFF	19.5
0.309750	---	28.04	49.98	21.94	N	OFF	19.5
0.309750	40.89	---	59.98	19.09	N	OFF	19.5
0.431250	---	26.21	47.23	21.02	N	OFF	19.5
0.431250	43.69	---	57.23	13.54	N	OFF	19.5
0.516750	---	26.30	46.00	19.70	N	OFF	19.5
0.516750	43.97	---	56.00	12.03	N	OFF	19.5
0.530250	---	25.38	46.00	20.62	N	OFF	19.5
0.530250	42.16	---	56.00	13.84	N	OFF	19.5
0.609000	---	25.95	46.00	20.05	N	OFF	19.5
0.609000	42.21	---	56.00	13.79	N	OFF	19.5
0.764250	---	29.11	46.00	16.89	N	OFF	19.5
0.764250	44.40	---	56.00	11.60	N	OFF	19.5
0.834000	---	27.99	46.00	18.01	N	OFF	19.5
0.834000	44.78	---	56.00	11.22	N	OFF	19.5
1.034250	---	26.23	46.00	19.77	N	OFF	19.5
1.034250	41.46	---	56.00	14.54	N	OFF	19.5
1.538250	---	29.09	46.00	16.91	N	OFF	19.6

<b>1.538250</b>	<b>44.75</b>	---	<b>56.00</b>	<b>11.25</b>	<b>N</b>	<b>OFF</b>	<b>19.6</b>
<b>2.445000</b>	---	<b>30.04</b>	<b>46.00</b>	<b>15.96</b>	<b>N</b>	<b>OFF</b>	<b>19.5</b>
<b>2.445000</b>	<b>44.68</b>	---	<b>56.00</b>	<b>11.32</b>	<b>N</b>	<b>OFF</b>	<b>19.5</b>
<b>3.671250</b>	---	<b>34.79</b>	<b>46.00</b>	<b>11.21</b>	<b>N</b>	<b>OFF</b>	<b>19.6</b>
<b>3.671250</b>	<b>50.24</b>	---	<b>56.00</b>	<b>5.76</b>	<b>N</b>	<b>OFF</b>	<b>19.6</b>
<b>4.812000</b>	---	<b>29.10</b>	<b>46.00</b>	<b>16.90</b>	<b>N</b>	<b>OFF</b>	<b>19.6</b>
<b>4.812000</b>	<b>42.21</b>	---	<b>56.00</b>	<b>13.79</b>	<b>N</b>	<b>OFF</b>	<b>19.6</b>
<b>4.960500</b>	---	<b>30.00</b>	<b>46.00</b>	<b>16.00</b>	<b>N</b>	<b>OFF</b>	<b>19.6</b>
<b>4.960500</b>	<b>41.80</b>	---	<b>56.00</b>	<b>14.20</b>	<b>N</b>	<b>OFF</b>	<b>19.6</b>
<b>7.194750</b>	---	<b>28.82</b>	<b>50.00</b>	<b>21.18</b>	<b>N</b>	<b>OFF</b>	<b>19.7</b>
<b>7.194750</b>	<b>41.02</b>	---	<b>60.00</b>	<b>18.98</b>	<b>N</b>	<b>OFF</b>	<b>19.7</b>
<b>13.560000</b>	---	<b>34.40</b>	<b>50.00</b>	<b>15.60</b>	<b>N</b>	<b>OFF</b>	<b>19.8</b>
<b>13.560000</b>	<b>45.46</b>	---	<b>60.00</b>	<b>14.54</b>	<b>N</b>	<b>OFF</b>	<b>19.8</b>

## Appendix B. Test Results of Conducted Test Items

### B1. Test Result of 20dB Spectrum Bandwidth

Test mode	NFC Tx	Test Frequency (MHz)	13.56
	 <p>Ref E 10 dBm Att 30 dB SWT 20 ms</p> <p>RBW 1 kHz Marker 1 [T1] -13.16 dBm</p> <p>RBW 3 kHz Marker 2 [T1] 13.559860000 MHz</p> <p>Temp 1 [T1] ndb -32.99 dBm</p> <p>Temp 2 [T1] 13.558500000 MHz</p> <p>Temp 3 [T1] 13.561140000 MHz</p> <p>Temp 4 [T1] -33.12 dBm</p> <p>Span 10 kHz</p>	 <p>Ref E 10 dBm Att 30 dB SWT 20 ms</p> <p>RBW 1 kHz Marker 1 [T1] -13.16 dBm</p> <p>RBW 3 kHz Marker 2 [T1] 13.559860000 MHz</p> <p>OBW 2.640000000 kHz Temp 1 [T1 OBW] -27.86 dBm</p> <p>Temp 2 [T1 OBW] 13.558700000 MHz</p> <p>Temp 3 [T1 OBW] -28.23 dBm</p> <p>Temp 4 [T1 OBW] 13.560940000 MHz</p> <p>Span 10 kHz</p>	
Date: 14.APR.2018 09:14:03		Date: 14.APR.2018 09:13:34	
20dB Bandwidth (kHz)	2.640	99% OccupiedBW(kHz)	2.240
Frequency range (MHz)	<b>f<sub>L</sub> &gt; 13.553</b> <b>f<sub>H</sub> &lt; 13.567</b>	13.55850	<b>Test Result</b> <b>Complies</b>

**Remark:** Because the measured signal is CW adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW.



## B2. Test Result of Frequency Stability



B3. Voltage vs. Frequency Stability		Temperature vs. Frequency Stability		
Voltage (Vac)	Measurement Frequency (MHz)	Temperature (°C)	Time	Measurement Frequency (MHz)
120	13.559820	-20	0	13.559810
102	13.559820		2	13.559820
138	13.559820		5	13.559860
			10	13.559900
		-10	0	13.559900
			2	13.559900
			5	13.559910
			10	13.559910
		0	0	13.559920
			2	13.559910
			5	13.559900
			10	13.559900
		10	0	13.559900
			2	13.559900
			5	13.559900
			10	13.559880
		20	0	13.559820
			2	13.559820
			5	13.559820
			10	13.559820
		30	0	13.559840
			2	13.559820
			5	13.559830
			10	13.559820
		40	0	13.559800
			2	13.559800
			5	13.559800
			10	13.559800



Voltage vs. Frequency Stability		Temperature vs. Frequency Stability		
Voltage (Vac)	Measurement Frequency (MHz)	Temperature (°C)	Time	Measurement Frequency (MHz)
		50	0	13.559800
			2	13.559780
			5	13.559780
			10	13.559780
Max.Deviation (MHz)	-0.000180	Max.Deviation (MHz)		-0.000220
Max.Deviation (ppm)	-13.2743	Max.Deviation (ppm)		-16.2242
Limit	FS < ±100 ppm	Limit		FS < ±100 ppm
Test Result	PASS	Test Result		PASS

## Appendix C. Test Results of Radiated Test Items


### C1. Test Result of Field Strength of Fundamental Emissions

Test Mode :	NFC Tx	Test Frequency (MHz)	13.56																											
			Date: 2018-04-10																											
Site : 03CH11-HY Condition : 15.225 3m LOOP_AN(H) HORIZONTAL : RBW:9.000KHz VBW:9.000KHz SWT:Auto Project : 720610-10																														
<table><thead><tr><th>Freq</th><th>Over Level</th><th>Limit</th><th>Limit Line</th><th>ReadAntenna Level</th><th>Cable Factor</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>13.56</td><td>62.64</td><td>-61.36</td><td>124.00</td><td>41.36</td><td>21.02</td><td>0.26</td><td>100 181 QP</td></tr></tbody></table>			Freq	Over Level	Limit	Limit Line	ReadAntenna Level	Cable Factor	A/Pos	T/Pos	Remark	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg	1	13.56	62.64	-61.36	124.00	41.36	21.02	0.26	100 181 QP	
Freq	Over Level	Limit	Limit Line	ReadAntenna Level	Cable Factor	A/Pos	T/Pos	Remark																						
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg																						
1	13.56	62.64	-61.36	124.00	41.36	21.02	0.26	100 181 QP																						
			Date: 2018-04-10																											
Site : 03CH11-HY Condition : 15.225 3m LOOP_AN(V) VERTICAL : RBW:9.000KHz VBW:9.000KHz SWT:Auto Project : 720610-10																														
<table><thead><tr><th>Freq</th><th>Over Level</th><th>Limit</th><th>Limit Line</th><th>ReadAntenna Level</th><th>Cable Factor</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>13.56</td><td>58.15</td><td>-65.85</td><td>124.00</td><td>36.87</td><td>21.02</td><td>0.26</td><td>100 99 QP</td></tr></tbody></table>			Freq	Over Level	Limit	Limit Line	ReadAntenna Level	Cable Factor	A/Pos	T/Pos	Remark	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg	1	13.56	58.15	-65.85	124.00	36.87	21.02	0.26	100 99 QP	
Freq	Over Level	Limit	Limit Line	ReadAntenna Level	Cable Factor	A/Pos	T/Pos	Remark																						
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg																						
1	13.56	58.15	-65.85	124.00	36.87	21.02	0.26	100 99 QP																						



## C2. Results of Radiated Spurious Emissions (9 kHz~30MHz)

Test Mode :	NFC Tx		Polarization :	Horizontal													
<b>Frequency (MHz)</b> <b>Level (dB<math>\mu</math>V/m)</b> <b>Over Limit (dB)</b> <b>Limit Line (dB<math>\mu</math>V/m)</b> <b>Read Level (dB<math>\mu</math>V)</b> <b>Antenna Factor (dB)</b> <b>Cable Loss (dB)</b> <b>Ant Pos (cm)</b> <b>Table Pos (deg)</b> <b>Remark</b>																	
0.0192	53.74	-68.2	121.94	34.03	19.7	0.01	-	-	Average								
0.06249	47.22	-64.47	111.69	27.41	19.8	0.01	-	-	Average								
0.09378	39.86	-68.3	108.16	20.25	19.6	0.01	-	-	QP								
0.125	36.09	-69.58	105.67	16.51	19.57	0.01	-	-	Average								
0.16224	49.83	-53.57	103.4	30.29	19.53	0.01	-	-	Average								
1.384	48.1	-16.68	64.78	28.67	19.32	0.11	100	0	QP								
13.344	39.01	-30.49	69.5	17.76	21	0.25	-	-	QP								
13.56	61.62	-7.88	69.5	40.34	21.02	0.26	-	-	QP								
21.895	37.73	-31.77	69.5	15.82	21.64	0.27	-	-	QP								
28.12	39.01	-30.49	69.5	17.01	21.76	0.24	-	-	QP								


**Note:**

1. 13.56 MHz is fundamental signal which can be ignored.
2. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
3. Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB);
4. Limit line = specific limits (dB $\mu$ V) + distance extrapolation factor.



## C3. Results of Radiated Spurious Emissions (30MHz~1GHz)

Test Mode :	NFC Tx		Polarization :		Horizontal															
Level (dB $\mu$ V/m)																				
Date: 2018-04-11																				
Frequency (MHz)	Level (dB $\mu$ V/m)	Over Limit (dB)	Limit Line (dB $\mu$ V/m)	Read Level (dB $\mu$ V)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark										
84.54	30.49	-9.51	40	48.01	13.7	1.22	32.48	100	0	Peak										
189.84	28.13	-15.37	43.5	44.09	14.59	1.69	32.4	-	-	Peak										
200.1	27.79	-15.71	43.5	43.43	14.87	1.72	32.39	-	-	Peak										
850.2	31.99	-14.01	46	30.15	28.8	3.67	31.92	-	-	Peak										
867	32.34	-13.66	46	30.29	29.06	3.67	31.83	-	-	Peak										
954.5	34.09	-11.91	46	29.61	30.81	3.9	31.16	-	-	Peak										

**Note:**

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Emission level (dB $\mu$ V/m) = 20 log Emission level ( $\mu$ V/m).
3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor= Level.