

TEST REPORT For FCC

Test Report No. : CTK-2015-00376
Date of Issue : 2015-03-25
FCC ID : P4Y365PLUS
Model/Type No. : 365plus
Variant Model/Type No. : -
Kind of Product : Digital door lock
Applicant : Samsung SDS Co., Ltd.
Applicant Address : 125, Olympic-ro 35-gil, Songpa-gu, Seoul, Korea
Manufacturer : Meta Networks Co., Ltd.
Manufacturer Address : 55, Galmachi-ro 281beon-gil, Jungwon-gu, Seongnam-si, Gyeonggi-do, Korea
Contact Person : Yu Seungkwan / Advisory Engineer
Telephone : +82-2-6155-5105
Received Date : 2015-03-12
Test period : Start : 2015-03-17 End : 2015-03-25


The test results presented in this report relate only to the object tested.

Tested by



Won-Jae, Hwang
Test Engineer
Date: 2015-03-25

Reviewed by



Young-Joon, Park
Technical Manager
Date: 2015-03-25



CTK Co., Ltd.

CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-624-9501
www.e-ctk.com

REPORT REVISION HISTORY

Date	Revision	Page No
2015-03-25	Issued (CTK-2015-00376)	All

This report shall not be reproduced except in full, without the written approval of CTK Co., Ltd. This document may be altered or revised by CTK Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by CTK Co., Ltd. will constitute fraud and shall nullify the document.



CTK Co., Ltd.

CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-624-9501
www.e-ctk.com

TABLE OF CONTENTS

REPORT REVISION HISTORY	2
1.0 General Product Description	4
1.1 Tested Frequency	4
1.2 Model Differences	5
1.3 Device Modifications	5
1.4 Peripheral Devices	5
1.5 Calibration Details of Equipment Used for Measurement	5
1.6 Test Facility.....	5
1.7 Laboratory Accreditations and Listings	6
2 Summary of tests.....	7
2.1 Technical Characteristic Test	8
2.1.1 6dB Bandwidth	8
2.1.2 Maximum peak Conducted Output Power.....	12
2.1.3 Power Spectral Density	16
2.1.4 Band - edge	20
2.1.5 Field Strength of Emissions	25
2.1.6 AC Conducted Emissions.....	31
APPENDIX A – Test Equipment Used For Tests	34



CTK Co., Ltd.

CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-624-9501
www.e-ctk.com

1.0 General Product Description

Kind of Product	Digital door lock	
Model/Type No.	365plus	
Variant Model/Type No.	-	
Serial number	Prototype	
EUT condition	Pre-production, not damaged	
Frequency Range	2405 MHz - 2480 MHz	
RF output power	11.36 dBm	
Number of channels	16	
Transfer Rate	250 Kbps	
Type of Modulation	DSSS	
Channel Spacing	5 MHz	
Duty cycle TX power	1.0	
Power Source	6 Vdc (4 AA Alkaline 1.5 V Batteries (LR6))	
Antenna Type	Wire antenna	Gain : 3.14 dBi

1.1 Tested Frequency

	CH11	CH15	CH19	CH20	CH25	CH26
Frequency (MHz)	2405	2425	2445	2450	2475	2480

1.2 Model Differences

Not applicable

1.3 Device Modifications

The following modifications were necessary for compliance:

Not applicable

1.4 Peripheral Devices

Device	Manufacturer	Model No.	Serial No.
Note Computer	DELL INC.	Inspiron 6400	-
Switching Adapter2	DDongguang Lite Power 2nd Plant	LA65NS0-00	-

1.5 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less. All test equipment calibrations are traceable to the Korea Research Institute of Standards and Science (KRISS), therefore, all test data recorded in this report is traceable to KRISS.

1.6 Test Facility

The measurement facility is located at (Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea. The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.



CTK Co., Ltd.
The Prime Leader of Global Regulatory Certification

CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-624-9501
www.e-ctk.com

1.7 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Logo
USA	FCC	3 m & 10 m SAC and Conducted Test Site to perform FCC Part 15/18 measurements	 805871
JAPAN	VCCI	3 m & 10 m SAC and Conducted Test Site	 R-948, C-986, T-1843
KOREA	MSIP	EMI (Electromagnetic Interference / Emission) EMS (Electromagnetic Susceptibility / Immunity)	 No. 51, KR0025
International	KOLAS	EMC	



CTK Co., Ltd.

CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-624-9501
www.e-ctk.com

2 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
15.247(a)	6 dB Bandwidth	> 500 kHz	Conducted	C
15.247(b)	Maximum Output Power	< 1 Watt		C
15.247(d)	Conducted Spurious emission	> 20 dBc		C
15.247(d)	Band Edge	> 20 dBc		C
15.247(e)	Transmitter Power Spectral Density	< 8 dBm @ 3 kHz		C
15.209	Field Strength of Harmonics	15.209(a)	Radiated	C
15.207	AC Conducted Emissions	15.207(a)	Line Conducted	NA

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

Note 2: The data in this test report are traceable to the national or international standards.

The sample was tested according to the following specification:

- FCC Part 15.247, ANSI C63.4-2003

The tests were performed according to the method of measurements prescribed in

KDB No.558074



CTK Co., Ltd.

CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-624-9501
www.e-ctk.com

2.1 Technical Characteristic Test

2.1.1 6dB Bandwidth

Procedure:

The bandwidth at 6dB below the highest in-band spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate frequencies.

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 6dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 6 dB bandwidth of the emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 100 kHz Span = 40 MHz

VBW = 100 kHz (VBW \geq RBW) Sweep = auto

Trace = max hold Detector function = peak

Measurement Data:

Frequency (MHz)	Channel No.	Test Results		
		6dB Bandwidth (MHz)	Occupied Bandwidth (MHz)	Result
2405	11	1.632	2.471	Complies
2425	15	1.626	2.474	Complies
2445	19	1.619	2.467	Complies
2450	20	1.620	2.473	Complies
2475	25	1.624	2.456	Complies
2480	26	1.635	2.491	Complies

Minimum Standard:


6 dB Bandwidth > 500kHz


See next pages for actual measured spectrum plots.




CTK Co., Ltd.

CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-624-9501
www.e-ctk.com








2.1.2 Maximum peak Conducted Output Power

Test Location

RF Test Room

Test Procedures

The transmitter output is connected to a spectrum analyzer and the analyzer's internal channel power integration function is used to integrate the power over a bandwidth greater than or equal to the 99% bandwidth.



Limit

< 1 W

Test Results

Cable loss : 0.4 dB

Frequency (MHz)	Channel No.	Measurement data (dBm)	Total Power (dBm)	Limit	Result
2405	11	9.56	9.96	30dBm	Complies
2425	15	10.71	11.11		Complies
2445	19	11.36	11.76		Complies
2450	20	11.30	11.70		Complies
2475	25	10.82	11.22		Complies
2480	26	4.09	4.49		Complies



CTK Co., Ltd.
The Prime Leader of Global Regulatory Certification

CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-624-9501
www.e-ctk.com



CH11



CH15









CTK Co., Ltd.

CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-624-9501
www.e-ctk.com

2.1.3 Power Spectral Density

Procedure:

The peak power density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

The spectrum analyzer is set to:

RBW = 3 kHz	VBW = (VBW \geq RBW)
Sweep = Auto	Span = 5 MHz
Detector function = peak	Trace = max hold

Test Results

Frequency (MHz)	Ch.	Test Results	
		dBm	Result
2405	11	-6.036	Complies
2425	15	-5.174	Complies
2445	19	-4.616	Complies
2450	20	-5.164	Complies
2475	25	-5.482	Complies
2480	26	-12.649	Complies

Minimum Standard:

Power Spectral Density	< 8dBm @ 3 kHz BW
------------------------	-------------------

See next pages for actual measured spectrum plots.

Power Density Measurement

CH11



CH15



CH19

CH20




CTK Co., Ltd.
The Prime Leader of Global Regulatory Certification

CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-624-9501
www.e-ctk.com

CH25



CH26



2.1.4 Band - edge

Procedure:

The bandwidth at 20dB down from the highest inband spectral density is measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate frequencies.

After the trace being stable, Use the marker-to-peak function to measure 20 dB down both sides of the intentional emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 100 kHz VBW = 100 kHz

Span = 20 MHz Detector function = peak

Trace = max hold Sweep = auto

Measurement Data: Complies


- All conducted emission in any 100 kHz bandwidth outside of the spread spectrum band was at least 20dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.

Minimum Standard:	> 20 dBc
--------------------------	----------


See next pages for actual measured spectrum plots.

Band-edge Measurements


CH11




CH26



Band – edge (at 20 dB blow) – CH11
Frequency Range = 30 MHz ~ 10th harmonic




Band – edge (at 20 dB blow) – CH15
Frequency Range = 30 MHz ~ 10th harmonic




Band – edge (at 20 dB blow) – CH19


Frequency Range = 30 MHz ~ 10th harmonic




Band – edge (at 20 dB blow) – CH20
Frequency Range = 30 MHz ~ 10th harmonic



Band – edge (at 20 dB blow) – CH25
Frequency Range = 30 MHz ~ 10th harmonic



Band – edge (at 20 dB blow) – CH26
Frequency Range = 30 MHz ~ 10th harmonic



2.1.5 Field Strength of Emissions

Test Location

10 m SAC (test distance : 10 m, 3 m)
 3 m SAC (test distance : 3 m)

Test Procedures

- 1) In the frequency range of 9 kHz to 30 MHz, magnetic field is measured with Loop Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
- 2) In the frequency range above 30 MHz, Bi-Log Test Antenna(30 MHz to 1 GHz) and Horn Test Antenna(above 1 GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is carried from 1m to 4m above the ground to determine the maximum value of the field strength. The emissions levels at both horizontal and vertical polarizations should be tested.

The spectrum analyzer is set to:

Frequency Range = 9 kHz ~ 25 GHz (2.4 GHz 10th harmonic)

RBW = 1 MHz for f ≥ 1 GHz, 100 kHz for f < 1 GHz, 9 kHz for f < 30 MHz

VBW ≥ RBW

Sweep = auto

Limit

- 15.209(a)



Frequency(MHz)	Field Strength uV/m@3m	Field Strength dBuV/m@3m	Deasurement Distance (meters)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	30
1.705-30	30	-	30
30-88	100**	40	3
88-216	150**	43.5	3
216-960	200**	46	3
Above 960	500	54	3

** Except as provided in 15.209(g).fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72MHz, 76-88MHz, 174-216MHz, 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g.15.231 and 15.241.


Note :

- 1) For above 1 GHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.
- 2) For above 1 GHz, limit field strength of harmonics : 54 dBuV/m@3m (AV) and 74 dBuV/m@3m (PK)

Test Setup:

1) For field strength of emissions from 9 kHz to 30 MHz

2) For field strength of emissions from 30 MHz to 1 GHz


3) For field strength of emissions above 1 GHz



Test Results

1) 9 kHz to 30 MHz

EUT	Digital door lock	Measurement Detail	
Model	365plus	Frequency Range	9 kHz – 30 MHz
Test mode	Ch.19 (Worst Case)	Detector function	Quasi-Peak

The requirements are:

Complies

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
-	-	-	See note

Note :

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB)

Test Results


EUT	Digital door lock	Measurement Detail	
Model	365plus	Frequency Range	Below 1000MHz
Mode	Ch.19 (Worst Case)	Detector function	Quasi-Peak

The requirements are:

Complies

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
902.394	40.5	5.5	Quasi-peak

Test Data



Final Result

No.	Frequency [MHz]	(P) V	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]
1	902.394	V	35.6	4.9	40.5	46.0	5.5	100.0	0.0
2	902.394	H	29.5	4.9	34.4	46.0	11.6	100.0	157.0

Remark :

1. The field strength of spurious emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in stand-up position(X axis) and the worst case was recorded.



CTK Co., Ltd.

CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-624-9501
www.e-ctk.com

Test Results

EUT	Digital door lock	Measurement Detail	
Model	365plus	Frequency Range	1-25GHz

Remarks

We have tested three mode (X, Y, Z). The worst mode (X axis) for final test.

The requirements are:

Complies

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
2483.5	52.3	1.7	Average

Test Data

Ch.11

Frequency [MHz]	(P)	Reading AV [dB(uV)]	Reading PK [dB(uV)]	Factor [dB(1/m)]	Level AV [dB(uV/m)]	Level PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Limit PK [dB(uV/m)]	Margin AV [dB]	Margin PK [dB]

No emissions were detected at a level greater than 20dB below limit.

Ch.15

Frequency [MHz]	(P)	Reading AV [dB(uV)]	Reading PK [dB(uV)]	Factor [dB(1/m)]	Level AV [dB(uV/m)]	Level PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Limit PK [dB(uV/m)]	Margin AV [dB]	Margin PK [dB]

No emissions were detected at a level greater than 20dB below limit.

Ch.19

Frequency [MHz]	(P)	Reading AV [dB(uV)]	Reading PK [dB(uV)]	Factor [dB(1/m)]	Level AV [dB(uV/m)]	Level PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Limit PK [dB(uV/m)]	Margin AV [dB]	Margin PK [dB]

No emissions were detected at a level greater than 20dB below limit.

Ch.20

Frequency [MHz]	(P)	Reading AV [dB(uV)]	Reading PK [dB(uV)]	Factor [dB(1/m)]	Level AV [dB(uV/m)]	Level PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Limit PK [dB(uV/m)]	Margin AV [dB]	Margin PK [dB]

No emissions were detected at a level greater than 20dB below limit.



Ch.25

Frequency [MHz]	(P)	Reading AV [dB(uV)]	Reading PK [dB(uV)]	Factor [dB(1/m)]	Level AV [dB(uV/m)]	Level PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Limit PK [dB(uV/m)]	Margin AV [dB]	Margin PK [dB]
--------------------	-----	------------------------	------------------------	---------------------	---------------------------	---------------------------	---------------------------	---------------------------	----------------------	----------------------

No emissions were detected at a level greater than 20dB below limit.

Ch.26

Frequency [MHz]	(P)	Reading AV [dB(uV)]	Reading PK [dB(uV)]	Factor [dB(1/m)]	Level AV [dB(uV/m)]	Level PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Limit PK [dB(uV/m)]	Margin AV [dB]	Margin PK [dB]
--------------------	-----	------------------------	------------------------	---------------------	---------------------------	---------------------------	---------------------------	---------------------------	----------------------	----------------------

No emissions were detected at a level greater than 20dB below limit.

Restricted band edge test data

Measured frequency range : 2310-2390 MHz, 2483.5-2500 MHz

Frequency [MHz]	(P)	Reading AV [dB(uV)]	Reading PK [dB(uV)]	Factor [dB(1/m)]	Level AV [dB(uV/m)]	Level PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Limit PK [dB(uV/m)]	Margin AV [dB]	Margin PK [dB]
2483.5	V	37.8	52.1	8.3	46.1	60.4	54.0	74.0	7.9	13.6
2483.5	H	44.0	59.4	8.3	52.3	67.7	54.0	74.0	1.7	6.3

2.1.6 AC Conducted Emissions

Test Location

Shielded Room

Frequency Range of Measurement

150 kHz to 30 MHz

Instrument Settings

IF Band Width: 9 kHz

Test Procedures

The EUT was placed on a non-metallic table 0.8m above the metallic, grounded floor and 0.4m from the reference ground plane wall. The distance to other metallic surfaces was at least 0.8m.

Amplitude measurements were performed with a quasi-peak detector and an average detector.

Limit

- 15.207(a)

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56*	56 to 46*
0.5 ~ 5	56	46
5 ~ 30	60	50

* Decreases with the logarithm of the frequency.

Test Results

The requirements are:

Not Applicable (Battery Power)

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
-	-	-	-



CTK Co., Ltd.

CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-624-9501
www.e-ctk.com

Test Data

[HOT]

Not Applicable

Not Applicable



CTK Co., Ltd.

CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-624-9501
www.e-ctk.com

[NEUTRAL]

Not Applicable

Not Applicable

**APPENDIX A – Test Equipment Used For Tests**

	Name of Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	Signal Analyzer	Agilent	N9020A	MY48011598	2014-11-07	2015-11-07
2	Spectrum Analyzer	Rohde & Schwarz	FSP-30	100994	2014-11-07	2015-11-07
3	EMI Test Receiver	Rohde & Schwarz	ESCI7	100814	2014-12-05	2015-12-05
4	EMI Test Receiver	Rohde & Schwarz	ESCI7	100816	2014-12-05	2015-12-05
5	Active Loop Antenna	SCHWARZBECK	FMZB 1513	1513-126	2014-05-19	2016-05-19
6	Attenuator	HP	8498A	1801A06913	2014-11-11	2015-11-11
7	EPM Series Power Meter	HP	E4418A	GB38272734	2014-11-17	2015-11-17
8	Power Sensor	HP	8487A	3318A03524	2015-02-06	2016-02-06
9	Audio Analyzer	HP	8903B	2747A03432	2014-11-10	2015-11-10
10	ESG-D Series Signal Generator	Agilent	E4432B	US40054094	2014-11-12	2015-11-12
11	SYNTHEZIZED SWEEPER	HP	8341B	2819A01563	2014-11-14	2015-11-14
12	Attenuator	HP	8494A	3308A33351	2014-11-07	2015-11-07
13	Temp&Humi Chamber	Kunpoong	JT-TH-556-1	9QE5-002	2015-01-16	2016-01-16
14	Temp&Humi Chamber	Kunpoong	JT-TH-556-2	9QE5-003	2015-01-16	2016-01-16
15	Temp&Humi Chamber	ESPEC CORP.	SH-241	92000872	2014-08-18	2015-08-18
16	DC POWER SUPPLY	Agilent	E3632A	MY40011638	2014-11-07	2015-11-07
17	Horn Antenna	ETS-Lindgren	3115	00078894	2013-05-13	2015-05-13
18	Horn Antenna	ETS-Lindgren	3116	00062504	2013-05-27	2015-05-27
19	Horn Antenna	ETS-Lindgren	3117	00154525	2013-07-03	2015-07-03
20	OPT H64 AMPLIFIER	HP	8447F	3113A06814	2015-02-06	2016-02-06
21	PREAMPLIFIER	Agilent	8449B	3008A02307	2014-10-24	2015-10-24
22	Radio Communication Tester	Rohde & Schwarz	CMU200	106765	2015-02-02	2016-02-02
23	LISN	Rohde & Schwarz	ENV216	101235	2014-07-30	2015-07-30
24	LISN	Rohde & Schwarz	ENV216	101236	2014-07-30	2015-07-30
25	LISN	Rohde & Schwarz	ENV216	101151	2014-11-07	2015-11-07
26	DC POWER SUPPLY	Agilent	E3632A	MY40011638	2014-11-07	2015-11-07
27	EMI Test Receiver	Rohde & Schwarz	ESCI3	100032	2015-02-02	2016-02-02
28	6dB Attenuator	R&S	DNF	272.4110.50	2014-11-07	2015-11-07
29	AMPLIFIER	Sonoma Instrument Co.	310	291721	2015-02-02	2016-02-02
30	EMI Test Receiver	Rohde & Schwarz	ESU40	100336	2014-05-15	2015-05-15
31	Signal Generator	Rohde & Schwarz	SMBV100A	258008	2014-08-21	2015-08-21
32	Bilog Antenna	Schaffner	CBL6111C	2551	2014-05-08	2016-05-08