



RF EXPOSURE REPORT



Report No.: 18020638-FCC-H

Supersede Report No.: N/A

Applicant	Shanghai MXCHIP Information Technology Co., Ltd.		
Product Name	BLE module		
Model No.	EMB1061		
Serial Model	EMB1061-P,EMB1061-E		
Test Standard	FCC 2.1091		
Issue Date	June 27, 2017		
Test Result	<input checked="" type="checkbox"/> Pass	<input type="checkbox"/> Fail	
Equipment complied with the specification		<input checked="" type="checkbox"/>	
Equipment did not comply with the specification		<input type="checkbox"/>	
			
Peter Wei Test Engineer		Amos Xia Engineer Reviewer	
<p style="text-align: center;">This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only</p>			

Issued by:

SIEMIC (Nanjing-China) Laboratories

2-1 Longcang Avenue Yuhua Economic and
Technology Development Park, Nanjing, China

Tel:+86(25)86730128/86730129 Fax:+86(25)86730127 Email: China@siemic.com.cn



Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report No.	18020638-FCC-H
Page	3 of 8

This page has been left blank intentionally.

CONTENTS

1	REPORT REVISION HISTORY.....	5
2	CUSTOMER INFORMATION	5
3	TEST SITE INFORMATION.....	5
4	EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5	FCC §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	7

1 Report Revision History

Report No.	Report Version	Description	Issue Date
18020638-FCC-H	NONE	Original	June 27, 2017

2 Customer information

Applicant Name	Shanghai MXCHIP Information Technology Co., Ltd.
Applicant Add	9thFloor, No.5 Lane2145JinshaJiangRoad,Putuo District,ShangHai(200333)
Manufacturer	Shanghai MXCHIP Information Technology Co., Ltd.
Manufacturer Add	9thFloor, No.5 Lane2145JinshaJiangRoad,Putuo District,ShangHai(200333)

3 Test site information

Lab performing tests	SIEMIC (Nanjing-China) Laboratories
Lab Address	2-1 Longcang Avenue Yuhua Economic and Technology Development Park, Nanjing, China
FCC Test Site No.	694825
IC Test Site No.	4842B-1
Test Software	EZ_EMU

4 Equipment under Test (EUT) Information

Description of EUT: BLE module

Main Model: EMB1061

Serial Model: EMB1061-P,EMB1061-E

Date EUT received: June 20, 2018

Output power 5.547 dBm

Antenna Gain: 2 dBi

Type of Modulation: BLE:GFSK

RF Operating Frequency (ies): BLE: 2402-2480 MHz

Number of Channels: BLE: 40CH

Port: N/A

Input Power: 3~3.6V

Trade Name : MXCHIP

FCC ID: P53-EMB1061

5 FCC §2.1091 - Maximum Permissible exposure (MPE)

Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Test Data

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

Where: S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Type	Test mode	CH	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)
Output power	GFSK	Low	2402	4.839	5±1
	π/4DQPSK	Low	2440	5.121	
	8DPSK	Low	2480	5.547	

For the antenna manufacturer provide only used limited to ERP/EIRP or radiated spurious emission test. The MPE evaluation as below:

GFSK

The maximum peak output power (turn-up power) in low channel of BLE is 6 dBm

Maximum peak output power (turn-up power) at antenna input terminal: 1 (mW)

Prediction distance: >20 (cm)

Predication frequency: 2402(MHz) lowest frequency

Antenna Gain (typical): 2 (dBi)

Antenna Gain (typical): 1.58 (numeric)

The worst case is power density at predication frequency at 20 cm: 0.0013 (mW/cm²)

MPE limit for general population exposure at prediction frequency: 1 (mW/cm²)

0.0013 (mW/cm²) < 1(mW/cm²)

The maximum peak output power (turn-up power) in low channel of BLE is 6 dBm

Maximum peak output power (turn-up power) at antenna input terminal: 1 (mW)

Prediction distance: >20 (cm)

Predication frequency: 2440(MHz) lowest frequency

Antenna Gain (typical): 2 (dBi)

Antenna Gain (typical): 1.58 (numeric)

The worst case is power density at predication frequency at 20 cm: 0.0013 (mW/cm²)

MPE limit for general population exposure at prediction frequency: 1 (mW/cm²)

0.0013 (mW/cm²) < 1(mW/cm²)

The maximum peak output power (turn-up power) in low channel of BLE is 6 dBm

Maximum peak output power (turn-up power) at antenna input terminal: 1 (mW)

Prediction distance: >20 (cm)

Predication frequency: 2480(MHz) lowest frequency

Antenna Gain (typical): 2 (dBi)

Antenna Gain (typical): 1.58 (numeric)

The worst case is power density at predication frequency at 20 cm: 0.0013 (mW/cm²)

MPE limit for general population exposure at prediction frequency: 1 (mW/cm²)

0.0013 (mW/cm²) < 1(mW/cm²)