

TEST REPORT

Product Name : Embedded Wi-Fi/BLE Module
Model Number : EMC3080-P, EMC3080-E
FCC ID : P53-EMC3080

Prepared for : Shanghai MXCHIP Information Technology Co., Ltd.
Address : 9th Floor, No.5, Lane2145 JinshaJiang Road, Putuo District, ShangHai, China (200333)

Prepared by : EMTEK (SHENZHEN) CO., LTD.
Address : Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China

Tel: (0755) 26954280
Fax: (0755) 26954282

Report Number : ES210118062W02
Date(s) of Tests : June 10, 2020 to August 03, 2020
January 20, 2021 to February 23, 2021
Date of issue : March 4, 2021

Table of Contents

1	TEST RESULT CERTIFICATION	3
2	EUT TECHNICAL DESCRIPTION	4
3	SUMMARY OF TEST RESULT	5
4	TEST METHODOLOGY	6
4.1	GENERAL DESCRIPTION OF APPLIED STANDARDS	6
4.2	MEASUREMENT EQUIPMENT USED	6
4.3	DESCRIPTION OF TEST MODES	7
4.4	TEST SOFTWARE	7
5	FACILITIES AND ACCREDITATIONS.....	8
5.1	FACILITIES.....	8
5.2	LABORATORY ACCREDITATIONS AND LISTINGS	8
6	TEST SYSTEM UNCERTAINTY.....	9
7	SETUP OF EQUIPMENT UNDER TEST	10
7.1	RADIO FREQUENCY TEST SETUP 1.....	10
7.2	RADIO FREQUENCY TEST SETUP 2.....	10
7.3	CONDUCTED EMISSION TEST SETUP	12
7.4	BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM.....	13
7.5	SUPPORT EQUIPMENT.....	13
8	TEST REQUIREMENTS.....	14
8.1	DTS 6DB BANDWIDTH	14
8.2	MAXIMUM PEAK CONDUCTED OUTPUT POWER	17
8.3	MAXIMUM POWER SPECTRAL DENSITY	20
8.4	UNWANTED EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS.....	23
8.5	RADIATED SPURIOUS EMISSION	28
8.6	CONDUCTED EMISSIONS TEST	50
8.7	ANTENNA APPLICATION	51

1 TEST RESULT CERTIFICATION

Applicant : Shanghai MXCHIP Information Technology Co., Ltd.

Address : 9th Floor, No.5, Lane2145 JinshaJiang Road, Putuo District, ShangHai, China (200333)

Manufacturer : Shanghai MXCHIP Information Technology Co., Ltd.

Address : 9th Floor, No.5, Lane2145 JinshaJiang Road, Putuo District, ShangHai, China (200333)

Trade Mark : **MXCHIP®**

EUT : Embedded Wi-Fi/BLE Module

Model Number : EMC3080-P, EMC3080-E

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 2 , Subpart J FCC 47 CFR Part 15, Subpart C	PASS

The above equipment was tested by EMTEK(SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2 and Part 15.247

The test results of this report relate only to the tested sample identified in this report

Date of Test : June 10, 2020 to August 03, 2020
January 20, 2021 to February 23, 2021

Prepared by : 
Sewen Guo /Editor

Reviewer : 
Joe Xia/Editor

Approve & Authorized Signer : 
Lisa Wang/Manager

2 EUT TECHNICAL DESCRIPTION

Characteristics	Description
Product:	Embedded Wi-Fi/BLE Module
Model Number:	EMC3080-P, EMC3080-E (Two models are identical in circuitry and electrical, mechanical and physical construction; the only difference is EMC3080-P model with PCB antenna; EMC3080-E model with IPEX antenna connector)
Sample:	2#
Device Type:	Bluetooth V4.2
Data Rate :	1Mbps for GFSK modulation
Modulation:	Bluetooth DTS: GFSK
Operating Frequency Range:	2402-2480MHz
Number of Channels:	40 Channels for Bluetooth DTS;
Transmit Power Max:	8.45 dBm
Antenna Gain:	EMC3080-P (Antenna 1): PCB Antenna; Max Antenna Gain 2dBi EMC3080-E (Antenna 2): IPEX connector; Max Support Antenna Gain 2dBi
Power Supply:	DC 2.7V to 3.3V
Test Power:	DC 3.3V via R&D board (R&D board power supply via USB Port 5V)
Date of Received:	January 20, 2021
Temperature Range:	-20°C ~ 85°C

Note:

- 1) For more details, please refer to the User's manual of the EUT.
- 2) Based on the original report ES200605008W02, add the model EMC3080-E and update the product name; Two models are identical in circuitry and electrical, mechanical and physical construction; the only difference is EMC3080-P model with PCB antenna; EMC3080-E model with IPEX antenna connector. Only the radiation difference test is carried out, and other data refers to the data of the original report (ES200605008W02).

3 SUMMARY OF TEST RESULT

FCC Part Clause	Test Parameter	Verdict	Remark
15.247(a)(2)	DTS (6dB) Bandwidth	PASS	
15.247(b)(3)	Maximum Peak Conducted Output Power	PASS	
15.247(e)	Maximum Power Spectral Density Level	PASS	
15.247(d)	Unwanted Emission Into Non-Restricted Frequency Bands	PASS	
15.247(d) 15.209	Unwanted Emission Into Restricted Frequency Bands (conducted)	PASS	
15.247(d) 15.209	Radiated Spurious Emission	PASS	
15.207	Conducted Emission Test	N/A	
15.247(b)	Antenna Application	PASS	
	NOTE1: N/A (Not Applicable) NOTE2: According to FCC OET KDB 558074, the report use radiated measurements in the restricted frequency bands. In addition, the radiated test is also performed to ensure the emissions emanating from the device cabinet also comply with the applicable limits.		

RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for FCC ID: P53-EMC3080 filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

4 TEST METHODOLOGY

4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards:

FCC 47 CFR Part 2, Subpart J

FCC 47 CFR Part 15, Subpart C

FCC KDB 558074 D01 15.247 Meas Guidance v05r02

4.2 MEASUREMENT EQUIPMENT USED

4.2.1 Conducted Emission Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LASTCAL.	DUE CAL.
Test Receiver	Rohde & Schwarz	ESCI	101384	2020/5/16	2021/5/15
L.I.S.N.	Rohde & Schwarz	ENV216	5	2020/5/16	2021/5/15
L.I.S.N.	Kyoritsu	KNW-407	8-1492-9	2020/5/16	2021/5/15
Absorbing Clamp	Rohde & Schwarz	MDS-21	833711/025	2020/7/4	2021/7/3
Loop antenna	Laplace	RF300	8006	2020/6/30	2021/6/29
Van der Hoofden test-head	Schwarzbeck	VDHH 9502	9502-054	2020/5/16	2021/5/15
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100107	2020/5/17	2021/5/16

4.2.2 Radiated Emission Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	DUE CAL.
Pre-Amplifier	HP	8447F	2944A07999	2020/5/16	2021/5/15
EMI Test Receiver	Rohde & Schwarz	ESCI	101414	2020/5/16	2021/5/15
Bilog Antenna	Schwarzbeck	VULB9163	712	2019/9/22	2021/9/21
Horn antenna	Schwarzbeck	BBHA9120D	9120D-1178	2020/7/4	2021/7/3
Pre-Amplifie	Lunar EM	LNA1G18-48	J1011131010001	2020/5/16	2021/5/15
Spectrum Analyzer	Rohde & Schwarz	FSV40	100967	2020/5/16	2021/5/15
Horn antenna	Schwarzbeck	BBHA9170	9170-399	2019/6/16	2021/6/15
Loop Antenna	Schwarzbeck	FMZB1519	1519-012	2019/7/14	2021/7/13
Cable	Schwarzbeck	AK9513	ACRX1	2020/5/16	2021/5/15
Cable	Rosenberger	N/A	FP2RX2	2020/5/16	2021/5/15
Cable	Schwarzbeck	AK9513	CRPX1	2020/5/16	2021/5/15
Cable	Schwarzbeck	AK9513	CRRX2	2020/5/16	2021/5/15

4.2.3 Radio Frequency Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LASTCAL.	DUE CAL.
Signal Analyzer	Agilent	N9010A	MY53470879	2020/5/16	2021/5/15
Spectrum Analyzer	Rohde & Schwarz	FSV40	100967	2020/5/16	2021/5/15
Spectrum Analyzer	Agilent	E4407B	88156318	2020/5/16	2021/5/15
DC Power	Manson	HCS-3202	G431609656	2020/8/29	2021/8/28
Power Meter	\	PS-X10-100	\	2020/5/16	2021/5/15
Power Splitter	MiNi-circuits	ZAPD-30-S+	\	2020/5/17	2021/5/16
Thermometer	Hegao	HTC-1	\	2020/7/8	2021/7/7
Temp. / Humidity Chamber	ESPEC	EL-02KA	12107166	2020/6/30	2021/6/29

Remark: Each piece of equipment is scheduled for calibration once a year.

4.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (Bluetooth V4.2 DTS :1Mbps) were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list for Bluetooth V4.2 DTS:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	19	2440	...	...
1	2404	20	2442	37	2476
2	2406	21	2444	38	2478
...	...	...	...	39	2480
Note: $fc=2402\text{MHz}+k \times 2\text{MHz}$ $k=1$ to 39					

Test Frequency and channel for Bluetooth V4.2 DTS:

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	19	2440	39	2480

4.4 TEST SOFTWARE

Item	Software
RF conducted:	ETSI Certification of Regulations Test Solution(V1.04.01)
Radiated Emission:	EMTEK(Ver.RA-03A1)-Shenzhen

5 FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

Building 69, Majialong Industry Zone District, Nanshan District, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

5.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

EMC Lab.

: **Accredited by CNAS**

The Certificate Registration Number is L2291.

The Laboratory has been assessed and proved to be in compliance with CNAS-CL01 (identical to ISO/IEC 17025:2017)

Accredited by FCC

Designation Number: CN1204

Test Firm Registration Number: 882943

Accredited by A2LA

The Certificate Number is 4321.01.

Accredited by Industry Canada

The Conformity Assessment Body Identifier is CN0008

Name of Firm

: EMTEK (SHENZHEN) CO., LTD.

Site Location


: Building 69, Majialong Industry Zone,
Nanshan District, Shenzhen, Guangdong, China

6 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Parameter	Measurement Uncertainty
RF Output Power	±1.0%
Power Spectral Density	±0.9%
Duty Cycle and Tx-Sequence and Tx-Gap	±1.3%
Medium Utilisation Factor	±1.5%
Occupied Channel Bandwidth	±2.3%
Transmitter Unwanted Emission in the Out-of Band	±1.2%
Transmitter Unwanted Emissions in the Spurious Domain	±2.7%
Receiver Spurious Emissions	±2.7%
Temperature	±3.2%
Humidity	±2.5%


Measurement Uncertainty for a level of Confidence of 95%



7 SETUP OF EQUIPMENT UNDER TEST

7.1 RADIO FREQUENCY TEST SETUP 1

The Bluetooth V4.2 DTS component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



7.2 RADIO FREQUENCY TEST SETUP 2

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

Below 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.


30MHz-1GHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


Above 1GHz:

The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


(a) Radiated Emission Test Set-Up, Frequency Below 30MHz



(b) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(c) Radiated Emission Test Set-Up, Frequency above 1000MHz




7.3 CONDUCTED EMISSION TEST SETUP


The mains cable of the EUT (maybe per AC/DC Adapter) must be connected to LISN. The LISN shall be placed 0.8 m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.

Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.1 m.

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.



7.4 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM



7.5 SUPPORT EQUIPMENT

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
/	/	/	/

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

8 TEST REQUIREMENTS

8.1 DTS 6DB BANDWIDTH

8.1.1 Applicable Standard

According to FCC Part 15.247(a)(2) and KDB 558074 D01 15.247 Meas Guidance v05r02

8.1.2 Conformance Limit

The minimum -6 dB bandwidth shall be at least 500 kHz.

8.1.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.1.4 Test Procedure

The EUT was operating in Bluetooth V4.2 DTS mode and controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 100 kHz.

Set the video bandwidth (VBW) =300 kHz.

Set Span=2 times OBW

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Measure and record the results in the test report.

Test Results

Temperature:	24.5° C
Relative Humidity:	55%
ATM Pressure:	1011 mbar

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Bandwidth (kHz)	Limit (kHz)	Verdict
Bluetooth V4.2 DTS	0	2402	642.778	>500	PASS
	19	2440	632.911	>500	PASS
	39	2480	633.328	>500	PASS

Test Model	DTS (6dB) Bandwidth	
	BluetoothV4.2 DTS	
	Channel 0: 2402MHz	GFSK modulation

Agilent 17:39:16 Jul 26, 2020		Freq/Channel
Ch Freq 2.402 GHz Trig Free		Center Freq 2.40200000 GHz
Occupied Bandwidth		Start Freq 2.40050000 GHz
		Stop Freq 2.40350000 GHz
		CF Step 300.000000 kHz Auto Man
		Freq Offset 0.00000000 Hz
		Signal Track On Off
		Scale Type Log Lin

Ref 15 dBm #Atten 20 dB Mkr1 2.4019925 GHz 8.015 dBm	
Occupied Bandwidth 1.0733 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB	
Transmit Freq Error -4.806 kHz x dB Bandwidth 642.778 kHz	

Test Model	DTS (6dB) Bandwidth	
	BluetoothV4.2 DTS	
	Channel 19: 2440MHz	GFSK modulation

Agilent 17:40:01 Jul 26, 2020		Freq/Channel
Ch Freq 2.44 GHz Trig Free		Center Freq 2.44000000 GHz
Occupied Bandwidth		Start Freq 2.43850000 GHz
Center 2.440000000 GHz		Stop Freq 2.44150000 GHz
		CF Step 300.000000 kHz Auto Man
		Freq Offset 0.00000000 Hz
		Signal Track On Off
		Scale Type Log Lin

Ref 15 dBm #Atten 20 dB Mkr1 2.4399925 GHz 8.302 dBm	
Occupied Bandwidth 1.0706 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB	
Transmit Freq Error -4.586 kHz x dB Bandwidth 632.911 kHz	

Center 2.440000000 GHz

Ref 15 dBm

#Atten 20 dB

Mkr1 2.4399925 GHz

8.302 dBm

#Peak

Log

10

dB/

Offst

10

dB

Center 2.44 GHz

#Res BW 100 kHz

#VBW 300 kHz

Span 3 MHz

Sweep 5 ms (401 pts)

Occupied Bandwidth

1.0706 MHz

Occ BW % Pwr

99.00 %

x dB


-6.00 dB

Transmit Freq Error

-4.586 kHz

x dB Bandwidth

632.911 kHz



8.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER

8.2.1 Applicable Standard

According to FCC Part 15.247(b)(3) and KDB 558074 D01 15.247 Meas Guidance v05r02

8.2.2 Conformance Limit

The maximum peak conducted output power of the intentional radiator for systems using digital modulation in the 2400 - 2483.5 MHz bands shall not exceed: 1 Watt (30dBm).

8.2.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.2.4 Test Procedure

■ According to FCC Part15.247(b)(3)

As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. For smart system, Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Set the RBW $\geq$ DTS bandwidth(about 1MHz).

Set VBW $\approx$ 3*RBW(about 3MHz)

Set the span $\geq$ 3*RBW

Set Sweep time = auto couple.

Set Detector = peak.

Set Trace mode = max hold.

Allow trace to fully stabilize. Use peak marker function to determine the peak amplitude level.


■ According to FCC Part 15.247(b)(4):


Conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Test Results

Temperature:	24.5° C
Relative Humidity:	55%
ATM Pressure:	1011 mbar

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Level (dBm)	Limit (dBm)	Verdict
Bluetooth V4.2 DTS	0	2402	8.10	30	PASS
	19	2440	8.45	30	PASS
	39	2480	8.38	30	PASS





8.3 MAXIMUM POWER SPECTRAL DENSITY

8.3.1 Applicable Standard

According to FCC Part 15.247(e) and KDB 558074 D01 15.247 Meas Guidance v05r02

8.3.2 Conformance Limit

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

8.3.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.3.4 Test Procedure

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance

The transmitter output (antenna port) was connected to the spectrum analyzer

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: 3 kHz

Set the VBW to: 10 kHz.

Set Detector = peak.

Set Sweep time = auto couple.

Set Trace mode = max hold.


Allow trace to fully stabilize.


Use the peak marker function to determine the maximum amplitude level within the RBW.

8.3.5 Test Results

Temperature:	24.5° C
Relative Humidity:	55%
ATM Pressure:	1011 mbar

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Level (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
Bluetooth V4.2 DTS	0	2402	-6.71	<8	PASS
	19	2440	-6.26	<8	PASS
	39	2480	-5.21	<8	PASS
Note: N/A					





8.4 UNWANTED EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS

8.4.1 Applicable Standard

According to FCC Part 15.247(d) and KDB 558074 D01 15.247 Meas Guidance v05r02

8.4.2 Conformance Limit

According to FCC Part 15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

8.4.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.4.4 Test Procedure

The transmitter output (antenna port) was connected to the spectrum analyzer

■ Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to = 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Set Detector = peak.

Set Sweep time = auto couple.

Set Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

■ Emission level measurement

Set the center frequency and span to encompass frequency range to be measured.

Set the RBW = 100 kHz.

Set the VBW = 300 kHz.

Set Detector = peak

Sweep time = auto couple.

Trace mode = max hold.


Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements. Report the three highest emissions relative to the limit.

8.4.5 Test Results

Temperature:	24.5° C
Relative Humidity:	55%
ATM Pressure:	1011 mbar



Agilent 19:08:28 Jul 26, 2020

Ref 15 dBm #Atten 20 dB Mkr1 24.451 GHz -45.66 dBm

Peak Log 10 dB/Offst 10 dB

M1 S2 S3 FC AA

Start 30.00000000 MHz

Start 30 MHz #Res BW 100 kHz #VBW 300 kHz Stop 25 GHz Sweep 2.587 s (8192 pts)

Freq/Channel

Center Freq
12.51500000 GHz

Start Freq
30.00000000 MHz


Stop Freq
25.00000000 GHz


CF Step
2.49700000 GHz
Auto Man


Freq Offset
0.00000000 Hz

Signal Track
On Off

Scale Type
Log Lin







8.5 RADIATED SPURIOUS EMISSION

8.5.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and KDB 558074 D01 15.247 Meas Guidance v05r02

8.5.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part 15.209, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log (uV/m)	300
0.490-1.705	24000/F(KHz)	20 log (uV/m)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

8.5.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

8.5.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz(1GHz to 25GHz), 100 kHz for $f < 1$ GHz(30MHz to 1GHz)

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

8.5.5 Test Results

Temperature:	24.5° C
Relative Humidity:	55%
ATM Pressure:	1011 mbar

■ Spurious Emission below 30MHz (9KHz to 30MHz)

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40\log(\text{Specific distance}/\text{test distance})$ (dB);

Limit line = Specific limits(dBuV) + distance extrapolation factor

■ Spurious Emission Above 1GHz (1GHz to 25GHz)

Bluetooth V4.2 DTS mode have been tested, and the worst result was report as below:

Antenna 1:

Test mode: BLE Frequency: Channel 0: 2402MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4405.09	V	52.18	41.32	74.00	54.00	-21.82	-12.68
9099.72	V	52.97	42.85	74.00	54.00	-21.03	-11.15
13288.28	V	56.54	46.21	74.00	54.00	-17.46	-7.79
4392.38	H	52.77	42.31	74.00	54.00	-21.23	-11.69
7454.43	H	52.90	41.62	74.00	54.00	-21.10	-12.38
11368.0	H	55.42	44.36	74.00	54.00	-17.06	-8.03

Test mode: BLE Frequency: Channel 19: 2440MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
3347.37	V	45.64	36.30	74.00	54.00	-28.36	-17.70
6679.04	V	52.93	41.63	74.00	54.00	-21.07	-12.37
13097.62	V	54.76	43.87	74.00	54.00	-19.24	-10.13
4405.09	H	51.67	41.52	74.00	54.00	-22.33	-12.48
6583.21	H	53.65	42.95	74.00	54.00	-20.35	-11.05
10333.80	H	56.02	43.68	74.00	54.00	-17.98	-10.32

Test mode: BLE Frequency: Channel 39: 2480MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4790.24	V	51.07	41.25	74.00	54.00	-22.93	-12.75
7200.31	V	54.40	43.56	74.00	54.00	-19.60	-10.44
11368.00	V	56.59	44.78	74.00	54.00	-17.41	-9.22
7474.0	H	53.10	42.36	74.00	54.00	-20.90	-11.64
11076.1	H	55.11	44.85	74.00	54.00	-18.89	-9.15
13677.96	H	55.29	43.57	74.00	54.00	-18.71	-10.43

Note: (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).

(2) Emission Level= Reading Level+Correct Factor.

(3) Correct Factor= Ant_F + Cab_L - Preamp

(4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Antenna 2:

Test mode: BLE Frequency: Channel 0: 2402MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4158.26	V	43.94	28.60	74.00	54.00	-30.06	-25.40
7179.52	V	52.24	36.40	74.00	54.00	-21.76	-17.60
14739.08	V	58.26	41.20	74.00	54.00	-15.74	-12.80
2865.30	H	42.27	30.70	74.00	54.00	-31.73	-23.30
5402.27	H	47.76	33.20	74.00	54.00	-26.24	-20.80
13057.93	H	56.31	38.10	74.00	54.00	-17.69	-15.90

Test mode: BLE Frequency: Channel 19: 2440MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
2871.51	V	43.54	27.90	74.00	54.00	-30.46	-26.10
6441.10	V	49.96	34.50	74.00	54.00	-24.04	-19.50
12971.41	V	56.28	37.80	74.00	54.00	-17.72	-16.20
2842.61	H	43.71	27.40	74.00	54.00	-30.29	-26.60
7883.22	H	52.03	36.30	74.00	54.00	-21.97	-17.70
15215.22	H	56.77	38.30	74.00	54.00	-17.23	-15.70

Test mode: BLE Frequency: Channel 39: 2480MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
2847.55	V	44.03	28.10	74.00	54.00	-29.97	-25.90
7104.18	V	50.50	34.20	74.00	54.00	-23.5	-19.80
12260.53	V	56.26	38.60	74.00	54.00	-17.74	-15.40
2901.55	H	43.57	27.60	74.00	54.00	-30.43	-26.40
4959.30	H	47.91	33.60	74.00	54.00	-26.09	-20.40
14510.81	H	57.75	38.70	74.00	54.00	-16.25	-15.30

- Note:**
- (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).
 - (2) Emission Level= Reading Level+Correct Factor.
 - (3) Correct Factor= Ant_F + Cab_L - Preamp
 - (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

Antenna 1:


Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2337.91	H	44.39	74.00	34.30	54.00
2345.58	V	43.83	74.00	32.90	54.00

Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2489.46	H	43.20	74.00	33.30	54.00
2485.49	V	42.34	74.00	32.50	54.00


- Note:**
- (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).
 - (2) Emission Level= Reading Level+Correct Factor.
 - (3) Correct Factor= Ant_F + Cab_L - Preamp
 - (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

All the modulation modes were tested, the data of the worst mode are described in the following table


Test Model	Spurious Emission in Restricted Band 2310-2390MHz		
	Bluetooth V4.2 DTS		
	Channel 0: 2402MHz		H




Test Model	Spurious Emission in Restricted Band 2310-2390MHz		
	Bluetooth V4.2 DTS		
	Channel 0: 2402MHz		V



Test Model	Spurious Emission in Restricted Band 2483.5-2500MHz		
	Bluetooth V4.2 DTS		
	Channel 39: 2480MHz		H



Test Model	Spurious Emission in Restricted Band 2483.5-2500MHz		
	Bluetooth V4.2 DTS		
	Channel 39: 2480MHz		V



Antenna 2:


Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2384.57	H	52.04	74.00	35.40	54.00
2389.11	V	52.52	74.00	36.10	54.00

Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2483.67	H	54.27	74.00	36.30	54.00
2483.76	V	53.59	74.00	36.40	54.00


- Note:** (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).
(2) Emission Level= Reading Level+Correct Factor.
(3) Correct Factor= Ant_F + Cab_L - Preamp
(4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

All the modulation modes were tested, the data of the worst mode are described in the following table

Test Model	Spurious Emission in Restricted Band 2310-2390MHz		
	Bluetooth V4.2 DTS		
	Channel 0: 2402MHz		H




Test Model	Spurious Emission in Restricted Band 2310-2390MHz		
	Bluetooth V4.2 DTS		
	Channel 0: 2402MHz		V



Test Model

Spurious Emission in Restricted Band 2483.5-2500MHz
Bluetooth V4.2 DTS
Channel 39: 2480MHz

H



Site 3m Chamber #1

Polarization: **Horizontal**

Temperature: 29.5 C

Limit: (RE)FCC PART 15 CLASS B


Power: DC 3.3V

Humidity: 48 %

Test Model

Spurious Emission in Restricted Band 2483.5-2500MHz
Bluetooth V4.2 DTS
Channel 39: 2480MHz

V



Site 3m Chamber #1

Polarization: **Vertical**

Temperature: 29.5 C

Limit: (RE)FCC PART 15 CLASS B


Power: DC 3.3V

Humidity: 48 %


■ Spurious Emission below 1GHz (30MHz to 1GHz)

All modes have been tested, and the worst result recorded was report as below:

Antenna 1:



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		155.9101	57.71	-27.01	30.70	43.50	-12.80	QP		
2		191.7450	58.88	-23.38	35.50	43.50	-8.00	QP		
3	*	227.6906	62.42	-22.92	39.50	46.00	-6.50	QP		
4		300.3672	57.49	-20.19	37.30	46.00	-8.70	QP		
5		312.1794	57.29	-19.89	37.40	46.00	-8.60	QP		
6		348.0274	54.03	-19.43	34.60	46.00	-11.40	QP		



Site Radiated Emission 3m #1

Limit: FCC Part15.209

Mode: BLE 2402MHz

Note:


Polarization: **Vertical**

Power: DC 3.3V


Temperature: 24

Humidity: 55 %


No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		191.7450	48.08	-23.38	24.70	43.50	-18.80	QP		
2		216.0240	49.23	-23.83	25.40	46.00	-20.60	QP		
3		227.6906	50.12	-22.92	27.20	46.00	-18.80	QP		
4		239.9874	49.55	-22.95	26.60	46.00	-19.40	QP		
5		324.4561	45.73	-19.33	26.40	46.00	-19.60	QP		
6	*	887.6099	36.08	-8.68	27.40	46.00	-18.60	QP		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		192.4186	55.41	-23.31	32.10	43.50	-11.40	QP		
2		234.1684	59.27	-22.57	36.70	46.00	-9.30	QP		
3	*	287.9904	60.07	-20.57	39.50	46.00	-6.50	QP		
4		300.3672	57.29	-20.19	37.10	46.00	-8.90	QP		
5		336.0352	55.44	-19.04	36.40	46.00	-9.60	QP		
6		801.7863	36.66	-10.16	26.50	46.00	-19.50	QP		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		227.6906	46.82	-22.92	23.90	46.00	-22.10	QP		
2		239.9873	46.05	-22.95	23.10	46.00	-22.90	QP		
3	*	499.4246	42.00	-16.40	25.60	46.00	-20.40	QP		
4		801.7863	33.26	-10.16	23.10	46.00	-22.90	QP		
5		878.3214	33.83	-8.83	25.00	46.00	-21.00	QP		
6		938.8326	33.09	-8.89	24.20	46.00	-21.80	QP		



Site Radiated Emission 3m #1

Polarization: **Horizontal**

Temperature: 24

Limit: FCC Part15.209


Power: DC 3.3V

Humidity: 55 %

Mode: BLE 2480MHz


Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		131.7577	53.93	-26.83	27.10	43.50	-16.40	QP		
2	*	155.9101	66.51	-27.01	39.50	43.50	-4.00	QP		
3		191.7450	57.98	-23.38	34.60	43.50	-8.90	QP		
4		228.4904	60.81	-22.81	38.00	46.00	-8.00	QP		
5		252.0627	57.15	-22.75	34.40	46.00	-11.60	QP		
6		312.1794	54.49	-19.89	34.60	46.00	-11.40	QP		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		35.6239	39.65	-23.95	15.70	40.00	-24.30	QP		
2		37.0248	38.42	-23.32	15.10	40.00	-24.90	QP		
3		744.8660	31.87	-10.37	21.50	46.00	-24.50	QP		
4	*	878.3214	30.63	-8.83	21.80	46.00	-24.20	QP		
5		909.6666	28.85	-7.65	21.20	46.00	-24.80	QP		
6		958.7943	29.66	-8.16	21.50	46.00	-24.50	QP		

Antenna 2:



Site 3m Chamber #1

Polarization: **Vertical**

Temperature: 29.5 C

Limit: (RE)FCC PART 15 CLASS B


Power: DC 3.3V

Humidity: 48 %


Mode: BLE 2402MHZ

Note:


No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		42.9938	43.48	-12.76	30.72	40.00	-9.28	QP		
2	!	119.4360	51.99	-14.33	37.66	43.50	-5.84	QP		
3	!	156.1836	52.49	-13.91	38.58	43.50	-4.92	QP		
4		379.4150	43.03	-7.13	35.90	46.00	-10.10	QP		
5		609.3872	39.19	-2.73	36.46	46.00	-9.54	QP		
6	*	834.7794	38.66	2.64	41.30	46.00	-4.70	QP		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree degree	Comment
1		72.0843	39.08	-13.59	25.49	40.00	-14.51	QP			
2		119.9607	45.91	-14.35	31.56	43.50	-11.94	QP			
3		143.8925	51.49	-14.25	37.24	43.50	-6.26	QP			
4	*	180.1743	53.41	-14.06	39.35	43.50	-4.15	QP			
5		252.6157	50.12	-11.18	38.94	46.00	-7.06	QP			
6	!	761.7045	39.92	0.59	40.51	46.00	-5.49	QP			




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		43.0127	43.32	-12.76	30.56	40.00	-9.44	QP		
2		117.7725	51.49	-14.29	37.20	43.50	-6.30	QP		
3		180.8865	50.37	-14.00	36.37	43.50	-7.13	QP		
4		264.2820	46.07	-10.81	35.26	46.00	-10.74	QP		
5		606.9880	40.34	-2.75	37.59	46.00	-8.41	QP		
6	*	758.7056	41.18	0.48	41.66	46.00	-4.34	QP		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		71.6747	37.97	-13.50	24.47	40.00	-15.53	QP		
2		120.2766	47.68	-14.36	33.32	43.50	-10.18	QP		
3		143.9556	51.62	-14.25	37.37	43.50	-6.13	QP		
4		216.0240	51.78	-13.27	38.51	46.00	-7.49	QP		
5		287.9904	47.86	-9.66	38.20	46.00	-7.80	QP		
6	*	761.7045	40.48	0.59	41.07	46.00	-4.93	QP		



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		30.9482	46.41	-14.52	31.89	40.00	-8.11	QP		
2		117.8758	48.68	-14.30	34.38	43.50	-9.12	QP		
3	*	192.0815	52.77	-13.72	39.05	43.50	-4.45	QP		
4		276.7293	46.38	-10.06	36.32	46.00	-9.68	QP		
5		379.4150	42.33	-7.13	35.20	46.00	-10.80	QP		
6	!	761.7045	39.87	0.59	40.46	46.00	-5.54	QP		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		31.8706	33.78	-14.47	19.31	40.00	-20.69	QP		
2		71.6747	37.57	-13.50	24.07	40.00	-15.93	QP		
3	!	156.0468	51.58	-13.91	37.67	43.50	-5.83	QP		
4	*	191.9973	51.76	-13.73	38.03	43.50	-5.47	QP		
5		299.8410	48.73	-8.97	39.76	46.00	-6.24	QP		
6		800.0310	35.49	1.97	37.46	46.00	-8.54	QP		

8.6 CONDUCTED EMISSIONS TEST

8.6.1 Applicable Standard

According to FCC Part 15.207(a)

8.6.2 Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

8.6.3 Test Configuration

Test according to clause 7.3 conducted emission test setup

8.6.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.
Maximum procedure was performed on the highest emissions to ensure EUT compliance.
Repeat above procedures until all frequency measured were complete.

8.6.5 Test Results

N/A

8.7 ANTENNA APPLICATION

8.7.1 Antenna Requirement

Standard	Requirement
FCC CRF Part 15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

8.7.2 Result

PASS.

The EUT has 2 antennas: One PCB antenna, one IPEX connector antenna; their antenna gains are both 2.0 dBi;

Note: ☒ Antenna use a permanently attached antenna which is not replaceable.
☒ Not using a standard antenna jack or electrical connector for antenna replacement
☐ The antenna has to be professionally installed (please provide method of installation)

which in accordance to section 15.203, please refer to the internal photos.

*** End of Report ***

声 明 Statement

1. 本报告无授权批准人签字及“检验报告专用章”无效;

This report will be void without authorized signature or special seal for testing report.

2. 未经许可本报告不得部分复制;

This report shall not be copied partly without authorization.

3. 本报告的检测结果仅对送测样品有效, 委托方对样品的代表性和资料的真实性负责;

The test results or observations are applicable only to tested sample. Client shall be responsible for representativeness of the sample and authenticity of the material.

4. 本检测报告中检测项目标注有特殊符号则该项目不在资质认定范围内, 仅作为客户委托、科研、教学或内部质量控制等目的使用;

The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.

5. 本检测报告以实测值进行符合性判定, 未考虑不确定度所带来的风险, 本实验室不承担相关责任, 特别约定、标准或规范中有明确规定的除外;

The test results or observations are provided in accordance with measured value, without taking risks caused by uncertainty into account. Without explicit stipulation in special agreements, standards or regulations, EMTEK shall not assume any responsibility.

6. 对本检测报告若有异议, 请于收到报告之日起 20 日内提出;

Objections shall be raised within 20 days from the date receiving the report.