



Report No.SH16020016W01

FCC RF TEST REPORT

Issued to

Shanghai MXCHIP Information Technology Co., Ltd

For

Embedded WiFi module

Model Name : EMW3081-E, EMW3081-P
Trade Name : MXCHIP
Brand Name : MXCHIP
Standard : 47 CFR Part 15, Subpart C
ANSI C63.10-2013
FCC ID : P53-EMW3081
Test date : Feb.24,2016 to Mar.10,2016
Issue date : Mar.11,2016

Shanghai MORLAB Communication Technology Co., Ltd.



Tested by Wu Hongfei

Approved by [Signature]

Review by Pangmin

CTIA Authorized Test Lab
LAB CODE 20081223-00
IEEE 1725

OFTA
電訊管理局



TAF
Testing Laboratory
2030

GCF
Official Observer of
Global Certification Forum

Bluetooth
BQTF

FCC
Reg.
No.741109

The report refers only to the sample tested and does not apply to the bulk. This report is issued in confidence to the client and it will be strictly treated as such by the Shanghai MORLAB Communication Technology Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it or a certified copy thereof prepared by the Shanghai MORLAB Communication Technology Co., Ltd to his customer. Supplier or others persons directly concerned. Shanghai MORLAB Communication Technology Co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report. In the event of the improper use of the report, Shanghai MORLAB Communication Technology Co., Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

DIRECTORY

1.	General Information	4
1.1	Applicant	4
1.2	Manufacturer	4
1.3	Description of EUT	4
2.	Facilities and Accreditations	5
2.1	Test Facility	5
2.2	Environmental Conditions	5
2.3	Measurement Uncertainty	5
2.4	List of Equipments Used	6
3.	Test Standards and Results	7
4.	47 CFR Part 15C	8
4.1	Antenna requirement	8
5.	Test Result.....	9
5.1	Peak Output Power.....	9
5.2	6dB & 20dB Bandwidth.....	11
5.3	Conducted Spurious Emissions.....	25
5.4	Power Spectral Density (PSD)	33
5.5	Band Edge	41
5.6	Conducted Emission	51
5.7	Radiated Emission.....	54
Annex A	Photos of the EUT	56
Annex B	Photos of Setup	58

Change History

Issue	Date	Reason for change
1.0	Mar.11,2016	First edition

1. General Information

1.1 Applicant

Shanghai MXCHIP Information Technology Co., Ltd

9thFloor,No.5,Lane2145JinshaJiangRoad,Putuo District,ShangHai (200333)

1.2 Manufacturer

Shanghai MXCHIP Information Technology Co., Ltd

9thFloor,No.5,Lane2145JinshaJiangRoad,Putuo District,ShangHai (200333)

1.3 Description of EUT

EUT Name.....: Embedded WiFi module
Model Name.....: EMW3081-E, EMW3081-P
Brand Name.....: MXCHIP
Trade Name.....: MXCHIP
Hardware Version.....: EMW3081 V10
Software Version.....: 0000.0000.AT10
Modulation Type.....: DSSS (802.11b), OFDM (802.11g/n)
Frequency Range.....: 2.412GHz - 2.462GHz (at interval of 5 MHz)
Channel Number.....: 11
Antenna Type.....: PCB / External Antenna
Antenna Gain.....: 2 dBi

NOTE 1:

*The EUT contains WIFI Module operating at 2.4GHz ISM band; it supports 802.11b, 802.11g, 802.11n and they are all tested in this report. The frequencies allocated is $F \text{ (MHz)} = 2412 + 5 * (n - 1)$ ($1 \leq n \leq 11$). The lowest, middle, highest channel numbers of the EUT used and tested in this report are separately 1 (2412MHz), 6 (2437MHz) and 11 (2462MHz).*

For 802.11n-40MHz, the lowest, middle, highest channel numbers of the EUT used and tested in this report are separately 3 (2422MHz), 6 (2437MHz) and 9 (2452MHz).

NOTE 2:

For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacture.

2. Facilities and Accreditations

2.1 Test Facility

Shanghai Morlab Communications Technology Co., Ltd. Morlab Laboratory is a third party testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L6644. A 9*6*6(m) full/semi-anechoic chamber was used for the radiated emissions test.

2.2 Environmental Conditions

Ambient temperature: 15~35°C

Relative humidity: 30~60%

Atmosphere pressure: 86-106kPa

2.3 Measurement Uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

Uncertainty of Conducted Emission: $\pm 1.76\text{dB}$

Uncertainty of Radiated Emission: $\pm 3.16\text{dB}$

2.4 List of Equipments Used

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Service Simulator	Anritsu	MT8852A	6K00002788	2015.9.22	1 year
Spectrum Analyzer	R&S	FSU26	200880	2015.2.25	1 year
Power Splitter	Weinschel	1506A	NW521	(n.a.)	(n.a.)
Power Splitter	Mini-Circuits	ZFRSC-183-S+	76500F1016	(n.a.)	(n.a.)
Attenuator 1	Resnet	10dB	(n.a.)	(n.a.)	(n.a.)
Attenuator 2	Resnet	3dB	(n.a.)	(n.a.)	(n.a.)
Full/Semi-Anechoic Chamber	Albatross	9m*6m*6m	(n.a.)	2015.9.14	3 year
EMI Test Receiver	R&S	ESCI	101351	2015.8.5	1 year
Antenna	Schwarzbeck	BBHA 9120C	9120C-384	2015.7.25	1 year
Antenna	R&S	HL562	100385	2015.6.17	1 year
Antenna	R&S	HF906	100565	2015.6.17	1 year
LISN	Rohde&Schwarz	ENV216	812744	2015.9.22	1 year
Personal Computer	HP	(n.a.)	(n.a.)	(n.a.)	(n.a.)
Test Antenna-Horn	Schwarzbeck	BBHA9170	BBHA91970171	2015.9.22	1 year
Test Antenna-Log	Schwarzbeck	VULB 9163	9163-561	2015.9.25	1 year
Test Antenna-Loop	Rohde&Schwarz	HFH2-Z2	860004/001	2015.9.22	1 year
Test Antenna-Horn	Schwarzbeck	BBHA 9120D	9120D-1033	2014.7.24	3 year
EPM Series Power Meter	Agilent	E4418B	GB43318055	2015.5.24	1 year
Power Sensor	Agilent	8482A	MY41091706	2015.5.24	1 year
Temporary Antenna Connector	Farpu	SMA-K	(n.a.)	(n.a.)	(n.a.)
RF Cable	(n.a.)	(n.a.)	(n.a.)	(n.a.)	(n.a.)
Power Supplier	NF	ES2000S	9087735	2015.09.25	1 year
Laptop	ACER	Aspire 4376ZG	LXPFY0C004 935291221601	(n.a.)	(n.a.)
Laptop Adapter	LITEON	PA-1650-22	9801016502	(n.a.)	(n.a.)
USB Data Cable	(n.a.)	(n.a.)	(n.a.)	(n.a.)	(n.a.)

NOTE:

Equipments listed above have been calibrated and are in the period of validation.

3. Test Standards and Results

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

FCC Part 15 Subpart C §15.247

ANSI C63.10-2013

June 2015 KDB558074

NOTE:

(1)All test items were verified and recorded according to the standards and without any deviation during the test.

(2)This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart C (WIFI, 2.4GHz ISM band radiators),recorded in a separate test report.

Test items and the results are as bellow:

No.	FCC Rules	Description	Result
1	15.203	Antenna Requirement	Pass
2	15.247(b)	Peak Output power	Pass
3	15.247(a)	20dB Bandwidth	Pass
4	15.247(d)	Conducted Spurious Emission	Pass
5	15.247(d)	Band Edge	Pass
6	15.207	Conducted Emission	Pass
7	15.247(d) 15.209	Radiated Emission	Pass
8	15.247(e)	Power Spectral Density (PSD)	Pass

4. 47 CFR Part 15C

4.1 Antenna requirement

4.1.1 Applicable standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

4.1.2 Result: Compliant

For EUT with PCB antenna, it has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

For EUT with external antenna, has no standard external antenna jack or electrical connector, only professional users can access to and obtain materials and equipments to install of an external antenna. Please refer to User Manual.

5. Test Result

5.1 Peak Output Power


5.1.1 Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

5.1.2 Test Description

The measured output power was calculated by the reading of the spectrum analyzer and calibration.

A. Test Setup:



The EUT (Equipment under the test) is coupled to the Power Meter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading, all test result in power meter.

5.1.3 Test Result

The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.(Duty cycle > 98%)

A. Test Verdict:


Mode	Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
			dBm	W	dBm	W	
802.11b	1	2412	15.93	0.03917	30	1	Pass
	6	2437	15.22	0.03327			Pass
	11	2462	14.28	0.02679			Pass
802.11g	1	2412	15.20	0.03311			Pass
	6	2437	14.82	0.03034			Pass
	11	2462	13.93	0.02472			Pass
802.11n (20MHz)	1	2412	15.17	0.03289			Pass
	6	2437	13.66	0.02323			Pass
	11	2462	13.58	0.02280			Pass
802.11n (40MHz)	3	2422	14.32	0.02704			Pass
	6	2437	14.04	0.02535			Pass
	9	2452	13.36	0.02168			Pass

5.2 6dB & 20dB Bandwidth

5.2.1 Requirement

According to FCC section 15.247(a) (2), Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

5.2.2 Test Description



5.2.3 Test Result

The lowest, middle and highest channels are selected to perform testing to record the 6 dB bandwidth of the Module.

A. Test Verdict:

802.11b Test mode

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Refer to plot	20dB Bandwidth (MHz)	Refer to plot	Limit (KHz)	Result
1	2412	8.133	Plot A1	15.144	Plot A2	≥ 500	Pass
6	2437	9.054	Plot B1	15.184	Plot B2	≥ 500	Pass
11	2462	8.605	Plot C1	15.136	Plot C2	≥ 500	Pass

802.11g Test mode

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Refer to plot	20dB Bandwidth (MHz)	Refer to plot	Limit (KHz)	Result
1	2412	16.466	Plot D1	17.387	Plot D2	≥ 500	Pass
6	2437	16.506	Plot E1	17.708	Plot E2	≥ 500	Pass
11	2462	16.458	Plot F1	17.219	Plot F2	≥ 500	Pass


802.11n (20MHz) Test mode

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Refer to plot	20dB Bandwidth (MHz)	Refer to plot	Limit (KHz)	Result
1	2412	17.668	Plot G1	18.429	Plot G2	≥ 500	Pass
6	2437	17.668	Plot H1	18.549	Plot H2	≥ 500	Pass
11	2462	17.740	Plot I1	18.621	Plot I2	≥ 500	Pass

802.11n (40MHz) Test mode


Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Refer to plot	20dB Bandwidth (MHz)	Refer to plot	Limit (KHz)	Result
3	2422	36.506	Plot J1	37.628	Plot J2	≥ 500	Pass
6	2437	36.602	Plot K1	37.163	Plot K2	≥ 500	Pass
9	2452	36.538	Plot L1	37.660	Plot L2	≥ 500	Pass

B. Test Plots:




Date: 24.FEB.2016 13:23:24

Plot A1




Date: 24.FEB.2016 13:25:42

Plot A2




Date: 24.FEB.2016 13:36:52

Plot B1




Date: 24.FEB.2016 13:37:43

Plot B2




Date: 24.FEB.2016 13:39:29

Plot C1




Date: 24.FEB.2016 13:40:25

Plot C2




Date: 24.FEB.2016 13:27:36

Plot D1




Date: 24.FEB.2016 13:28:30

Plot D2




Date: 24.FEB.2016 13:34:18

Plot E1




Date: 24.FEB.2016 13:35:32

Plot E2




Date: 24.FEB.2016 13:41:35

Plot F1




Date: 24.FEB.2016 13:42:41

Plot F2




Date: 24.FEB.2016 13:30:55

Plot G1




Date: 24.FEB.2016 13:30:17

Plot G2




Date: 24.FEB.2016 13:32:28

Plot H1




Date: 24.FEB.2016 13:33:04

Plot H2




Date: 24.FEB.2016 13:44:21

Plot I1




Date: 24.FEB.2016 13:43:38

Plot I2




Date: 9.MAR.2016 16:05:42

Plot J1




Date: 9.MAR.2016 16:06:15

Plot J2




Date: 9.MAR.2016 16:04:36

Plot K1




Date: 9.MAR.2016 16:03:51

Plot K2



Date: 9.MAR.2016 16:01:13

Plot L1



Date: 9.MAR.2016 16:02:26


Plot L2

5.3 Conducted Spurious Emissions

5.3.1 Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.3.2 Test Description



5.3.3 Test Result

The Wifi Module operates at hopping-off test mode. The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions.

A. Test Verdict:

802.11b Test mode

Channel	Frequency (MHz)	Measured max out of band emission(dBm)	Refer to plot	Limit(dBm)		Result
				Carrier level	Calculated 20dBc limit	
1	2412	-47.24	Plot A	5.97	-14.03	Pass
6	2437	-48.42	Plot B	3.80	-16.20	Pass
11	2462	-45.34	Plot C	8.18	-11.82	Pass

802.11g Test mode

Channel	Frequency (MHz)	Measured max out of band emission(dBm)	Refer to plot	Limit(dBm)		Result
				Carrier level	Calculated 20dBc limit	
1	2412	-48.85	Plot D	2.34	-17.66	Pass
6	2437	-48.80	Plot E	-0.40	-20.40	Pass
11	2462	-49.09	Plot F	1.47	-18.53	Pass


802.11n (20MHz) Test mode

Channel	Frequency (MHz)	Measured max out of band emission(dBm)	Refer to plot	Limit(dBm)		Result
				Carrier level	Calculated 20dBc limit	
1	2412	-48.95	Plot G	-1.00	-21.00	Pass
6	2437	-49.21	Plot H	-0.93	-20.93	Pass
11	2462	-48.82	Plot I	-1.71	-21.71	Pass

802.11n (40MHz) Test mode


Channel	Frequency (MHz)	Measured max out of band emission(dBm)	Refer to plot	Limit(dBm)		Result
				Carrier level	Calculated 20dBc limit	
3	2422	-48.76	Plot J	-2.99	-22.99	Pass
6	2437	-49.22	Plot K	-3.73	-23.73	Pass
9	2452	-49.30	Plot L	-4.73	-24.73	Pass

B. Test Plot:




Date: 24.FEB.2016 15:54:28

Plot A




Date: 24.FEB.2016 15:58:24

Plot B




Date: 24.FEB.2016 15:59:10

Plot C




Date: 24.FEB.2016 15:55:31

Plot D




Date: 24.FEB.2016 15:57:46

Plot E




Date: 24.FEB.2016 15:59:46

Plot F




Date: 24.FEB.2016 15:56:15

Plot G




Date: 24.FEB.2016 15:57:11

Plot H




Date: 24.FEB.2016 16:00:20

Plot I




Date: 9.MAR.2016 16:09:48

Plot J



Date: 9.MAR.2016 16:10:34

Plot K



Date: 9.MAR.2016 16:11:16


Plot L

5.4 Power Spectral Density (PSD)

5.4.1 Requirement

According to FCC section 15.247(e), the same method of determining the conducted output power shall be used to determine the power spectral density. If a peak output power is measured, then a peak power spectral density measurement is required. If an average output power is measured, then an average power spectral density measurement should be used

5.4.2 Test Description



5.4.3 Test Result

A. Test Verdict

802.11b Test mode

Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Refer to plot	Limit (dBm/3kHz)	Result
1	2412	-6.07	Plot A	8	Pass
6	2437	-10.18	Plot B	8	Pass
11	2462	-6.37	Plot C	8	Pass

802.11g Test mode

Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Refer to plot	Limit (dBm/3kHz)	Result
1	2412	-11.48	Plot D	8	Pass
6	2437	-11.77	Plot E	8	Pass
11	2462	-13.57	Plot F	8	Pass


802.11n (20MHz) Test mode

Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Refer to plot	Limit (dBm/3kHz)	Result
1	2412	-12.41	Plot G	8	Pass
6	2437	-12.96	Plot H	8	Pass
11	2462	-15.42	Plot I	8	Pass

802.11n (40MHz) Test mode


Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Refer to plot	Limit (dBm/3kHz)	Result
3	2422	-15.81	Plot J	8	Pass
6	2437	-16.87	Plot K	8	Pass
9	2452	-17.52	Plot L	8	Pass

B. Test Plot




Date: 24.FEB.2016 16:12:00

Plot A




Date: 24.FEB.2016 16:15:20

Plot B




Date: 24.FEB.2016 16:16:23

Plot C




Date: 24.FEB.2016 16:12:33

Plot D




Date: 24.FEB.2016 16:13:54

Plot E




Date: 24.FEB.2016 16:17:12

Plot F




Date: 24.FEB.2016 16:13:04

Plot G




Date: 24.FEB.2016 16:13:28

Plot H




Date: 24.FEB.2016 16:17:43

Plot I




Date: 9.MAR.2016 16:14:53

Plot J



Date: 9.MAR.2016 16:14:14

Plot K



Date: 9.MAR.2016 16:13:33


Plot L

5.5 Band Edge

5.5.1 Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, , In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

5.5.2 Test Description



The Module is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

5.5.3 Test Result

The lowest and highest channels are tested to verify the Restricted Frequency Bands.

The measurement results are obtained as below:

$$E \text{ [dBV/m]} = UR + AT + A\text{Factor [dB]}; AT = LCable \text{ loss [dB]} - G\text{preamp [dB]}$$

AT: Total correction Factor except Antenna

UR: Receiver Reading

Gpreamp: Preamplifier Gain

AFactor: Antenna Factor at 3m

Note: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (vertical) was recorded in this test report.

The lowest and highest channels are tested to verify the Restricted Frequency Bands

A. Test Verdict

802.11b Test mode

Ch	Frequency (MHz)	Detector PK/AV	Receiver Reading UR (dBuV/m)	AT (dB)	Afactor (dB@3m)	Max. Emission (dBuV/m)	Limit (dBuV/m)	Result
1	2361.20	PK	43.59	-32.2	32.56	43.95	74	Pass
1	2345.23	AV	38.48	-32.2	32.56	38.84	54	Pass
11	2489.58	PK	43.22	-30.7	32.50	45.02	74	Pass
11	2494.88	AV	38.24	-30.7	32.50	40.04	54	Pass

802.11g Test mode

Ch	Frequency (MHz)	Detector PK/AV	Receiver Reading UR (dBuV/m)	AT (dB)	Afactor (dB@3m)	Max. Emission (dBuV/m)	Limit (dBuV/m)	Result
1	2360.66	PK	42.59	-32.2	32.56	42.95	74	Pass
1	2374.84	AV	39.06	-32.2	32.56	39.42	54	Pass
11	2484.53	PK	43.25	-30.7	32.50	45.05	74	Pass
11	2491.59	AV	38.24	-30.7	32.50	40.04	54	Pass


802.11n (20MHz) Test mode

Ch	Frequency (MHz)	Detector PK/AV	Receiver Reading UR (dBuV/m)	AT (dB)	Afactor (dB@3m)	Max. Emission (dBuV/m)	Limit (dBuV/m)	Result
1	2357.97	PK	42.15	-32.2	32.56	42.51	74	Pass
1	2374.84	AV	38.14	-32.2	32.56	38.50	54	Pass
11	2490.56	PK	43.52	-30.7	32.50	45.32	74	Pass
11	2489.40	AV	37.58	-30.7	32.50	39.38	54	Pass

802.11n (40MHz) Test mode


Ch	Frequency (MHz)	Detector PK/AV	Receiver Reading UR (dBuV/m)	AT (dB)	Afactor (dB@3m)	Max. Emission (dBuV/m)	Limit (dBuV/m)	Result
3	2368.82	PK	42.42	-32.2	32.56	42.78	74	Pass
3	2363.34	AV	37.68	-32.2	32.56	38.04	54	Pass
9	2486.23	PK	44.36	-30.7	32.50	46.16	74	Pass
9	2487.23	AV	37.85	-30.7	32.50	39.65	54	Pass

B. Test Plot




Date: 24.FEB.2016 17:02:51

(802.11b Channel = 1 PK)




Date: 24.FEB.2016 17:01:18

(802.11b Channel = 1 AV)




Date: 24.FEB.2016 16:56:28

(802.11b Channel = 11 PK)




Date: 24.FEB.2016 16:57:13

(802.11b Channel = 11 AV)




Date: 10.MAR.2016 11:38:22

(802.11g Channel = 1 PK)




Date: 10.MAR.2016 11:40:17

(802.11g Channel = 1 AV)




Date: 24.FEB.2016 16:58:26

(802.11g Channel = 11 PK)




Date: 24.FEB.2016 16:57:53

(802.11g Channel = 11 AV)




Date: 10.MAR.2016 11:42:27

(802.11n-20MHz Channel = 1 PK)




Date: 10.MAR.2016 11:41:57

(802.11n-20MHz Channel = 1 AV)




Date: 24.FEB.2016 16:59:06

(802.11n-20MHz Channel = 11 PK)




Date: 24.FEB.2016 16:59:32

(802.11n-20MHz Channel = 11 AV)




Date: 10.MAR.2016 11:46:41

(802.11n-40MHz Channel = 1 PK)




Date: 10.MAR.2016 11:47:32

(802.11n-40MHz Channel = 1 AV)



Date: 10.MAR.2016 11:50:07

(802.11n-40MHz Channel = 11 PK)



Date: 10.MAR.2016 11:50:32

(802.11n-40MHz Channel = 11 AV)

5.6 Conducted Emission

5.6.1 Requirement


According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network(LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

5.6.2 Test Description



The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT connected to Class B Computer/Laptop via USB data cable. The Computer/Laptop installed by US power 120V/60Hz, through a Line Impedance Stabilization Network (LISN), which was supplied power source and was grounded to the ground plane.

. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10-2013


5.6.3 Test result

Test Verdict Recorded for Suspicious Points:


Line	Freq MHz	Result dBuV	Limit dBuV	Margin dB
QP	0.16	54.96	65.30	10.34
Average	0.17	43.68	55.08	11.40
Average	0.20	35.83	53.80	17.97
QP	0.20	48.06	63.80	15.74
QP	0.22	41.30	62.92	21.62
Average	0.25	31.23	51.78	20.55
Average	0.85	29.38	46.00	16.62
QP	1.09	33.36	56.00	22.64
Average	1.11	28.94	46.00	17.06
Average	1.51	30.04	46.00	15.96
QP	1.57	35.15	56.00	20.85
QP	1.92	35.68	56.00	20.32

Neutral	Freq MHz	Result dBuV	Limit dBuV	Margin dB
QP	0.16	55.07	65.30	10.23
Average	0.17	42.52	55.08	12.56
Average	0.19	34.23	54.20	19.97
QP	0.19	47.44	64.02	16.58
QP	0.21	41.88	63.10	21.22
QP	0.53	33.49	56.00	22.51
Average	0.54	27.87	46.00	18.13
Average	1.06	26.22	46.00	19.78
QP	1.08	32.00	56.00	24.00
Average	1.25	25.97	46.00	20.03
QP	1.85	32.03	56.00	23.97
Average	1.89	27.70	46.00	18.30

Test Plot:



(Plot A: L Phase)



(Plot B: N Phase)

5.7 Radiated Emission

5.7.1 Requirement


According to FCC section 15.247(c), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table


Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)	Limit($\text{dB}\mu\text{V/m}$)	Detector
0.009-0.490	2400/F(kHz)	300	/	/
0.490-1.705	24000/F(kHz)	30	/	/
1.705-30	30	30	/	/
30 - 88	100	3	40	QP
88 - 216	150	3	43.5	QP
216 - 960	200	3	46	QP
960 - 1000	500	3	54	QP
Above 1000	500	3	54	AV

In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table)


5.7.2 Test setup



Radiated Emissions Below 30MHz



Radiated Emissions 30-1000MHz



Radiated Emissions above 1000MHz

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.10-2013. Below 1GHz, the EUT was set-up on insulator 80cm above the Ground Plane. Above 1GHz, the EUT was set-up on insulator 150cm above the Ground Plane. The set-up and test methods were according to ANSI C63.10

The Wifi Module is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading. During the measurement, the Wifi Module is activated and controlled by the Wifi Service Supplier (SS) via a Common Antenna, and is set to

operate under transmitting at maximum power.

For the Test Antenna: In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength, the azimuth range of turntable was 0o to 360o, the receive antenna has two polarizations horizontal and vertical. When doing measurements above 1GHz, the EUT was placed within the 3dB beam width range of the horn antenna, and the EUT was tested in 3 orthogonal positions as recommended in ANSI C63.10 for Radiated Emissions and the worst-case data was presented.

5.7.3 Test Result

A. Test Result for 9kHz~30MHz

Frequency (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
--	--	10	--	See Note

Note:

- The amplitude of spurious emissions that are attenuated by more than 10dB below the permissible value has no need to be reported.
- Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);
- Limit line = specific limits (dBuV) + distance extrapolation factor.



B. Test Result for above 30MHz ~ 10th Harmonic

Frequency (MHz)	Level (dBuV)	Limit Line (dBuV)	Margin (dB)	Antenna Polarization	Result
73.10	34.60	40.00	5.40	Horizontal	PASS
161.47	30.74	43.50	12.76	Horizontal	PASS
212.27	40.26	43.50	3.24	Horizontal	PASS
359.19	34.22	46.00	11.78	Horizontal	PASS
4830.53	31.60	54.00	22.40	Horizontal	PASS
7243.89	30.94	54.00	19.06	Horizontal	PASS
9654.56	32.76	54.00	21.24	Horizontal	PASS
73.10	29.40	40.00	10.60	Vertical	PASS
93.44	29.99	43.50	13.51	Vertical	PASS
214.51	31.14	43.50	12.36	Vertical	PASS
361.71	31.73	46.00	14.27	Vertical	PASS
4830.53	34.95	54.00	19.05	Vertical	PASS
7243.89	32.69	54.00	21.31	Vertical	PASS
9654.56	34.67	54.00	19.336	Vertical	PASS

Note:


- The worst case (802.11b Channel 1:2412MHz) is recorded in the report.
- Both PCB antenna and External antenna were tested, the worst case (External antenna) is recorded in the report.

Annex A Photos of the EUT



Annex B Photos of Setup

1. RF





2. Conducted Emission



3. Radiated Emission





** END OF REPORT **