

Statement of compliance to Maximum Permissible Exposure (MPE)

Equipment : Wi-Fi Module
Type/Model : EMW3280
Applicant : MXchip Information Technology (Shanghai) Co., Ltd.
Floor 2, Building 9, Lane 271, Qianyang Rd, Shanghai,
China

Power density (S) is calculated according to the formula:

$$S = PG / (4\pi R^2)$$

Where S = power density in mW/cm²

P = transmit power in mW

G = numeric gain of transmit antenna

R = distance (cm)

As we can see from the test report SH12080219-001:

The maximum conducted power P = 24.15dBm = 260.02mW

Max. Gain of external antenna = 3.50dBi = 2.239


Here R is chosen to be 20cm,

$$S = PG / (4\pi R^2) = 260.02 * 2.239 / (4 * 3.14 * 20 * 20) = 0.12\text{mW/cm}^2$$

This level is below the 1 mW/cm² MPE for General Population / Uncontrolled Exposure as stated in OET BULLETIN 65 Edition 97-01.

Date of issue: Sep 29, 2012

Prepared by:


Wakeyou Wang (Project Engineer)

Reviewed by:


Daniel Zhao (Reviewer)



FCC ID: P53-EMW3280

Appendix I

Definition below must be outlined in the User Manual:

To satisfy FCC RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation. To ensure compliance, operations at closer than this distance is not recommended.