



FCC RF Test Report

APPLICANT : VERTU Corporation Limited
EQUIPMENT : Cellular Telephone
BRAND NAME : VERTU
MODEL NAME : SIGNATURE TOUCH
TYPE NAME : VM-03
FCC ID : P7QVM-03
STANDARD : FCC Part 15 Subpart E §15.407
CLASSIFICATION : (NII) Unlicensed National Information Infrastructure

The product was received on Jul. 02, 2015 and testing was completed on Aug. 16, 2015. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Feature of Equipment Under Test	5
1.4 Product Specification of Equipment Under Test	6
1.5 Modification of EUT	6
1.6 Testing Location	7
1.7 Applicable Standards	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Carrier Frequency and Channel	8
2.2 Pre-Scanned RF Power	9
2.3 Test Mode	10
2.4 Connection Diagram of Test System	11
2.5 Support Unit used in test configuration and system	12
2.6 EUT Operation Test Setup	12
2.7 Measurement Results Explanation Example	12
3 TEST RESULT	13
3.1 6dB Bandwidth Measurement	13
3.2 Maximum Conducted Output Power Measurement	15
3.3 Power Spectral Density Measurement	16
3.4 Unwanted Emissions Measurement	19
3.5 AC Conducted Emission Measurement	24
3.6 Frequency Stability Measurement	30
3.7 Automatically Discontinue Transmission	31
3.8 Antenna Requirements	32
4 LIST OF MEASURING EQUIPMENT	33
5 UNCERTAINTY OF EVALUATION	34
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. RADIATED TEST RESULTS	
APPENDIX C. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR570205F	Rev. 01	Initial issue of report	Aug. 26, 2015
FR570205F	Rev. 02	Revising Bluetooth version in section 1.3.	Sep. 07, 2015

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.403(i)	6dB Bandwidth	> 500kHz	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	≤ 30 dBm	Pass	-
3.3	15.407(a)	Power Spectral Density	≤ 30 dBm/500kHz	Pass	-
3.4	15.407(b)	Unwanted Emissions	$\leq -17, -27$ dBm/MHz & 15.209(a)	Pass	Under limit 7.90 dB at 5714.840 MHz
3.5	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 8.90 dB at 13.558 MHz
3.6	15.407(g)	Frequency Stability	Within Operation Band	Pass	-
3.7	15.407(c)	Automatically Discontinue Transmission	Discontinue Transmission	Pass	-
3.8	15.203 & 15.407(a)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

VERTU Corporation Limited

Beacon Hill Road, Church Crookham, Hampshire GU52 8DY, United Kingdom

1.2 Manufacturer

VERTU Corporation Limited

Beacon Hill Road, Church Crookham, Hampshire GU52 8DY, United Kingdom

1.3 Feature of Equipment Under Test

Product Feature	
Equipment	Cellular Telephone
Brand Name	VERTU
Model Name	SIGNATURE TOUCH
Type Name	VM-03
FCC ID	P7QVM-03
EUT supports Radios application	GSM/EGPRS/WCDMA/HSPA/LTE/NFC WLAN 11a/b/g/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth v4.1 EDR/LE
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Specification of Accessory		
AC Adapter	Brand Name	VERTU
	Model Name	AC-32V
Car Charger	Brand Name	VERTU
	Model Name	DC-30V
Battery	Brand Name	VERTU
	Model Name	VBL-02
Portable Power Charger	Brand Name	VERTU
	Model Name	DC-15V
Earphone 1	Brand Name	VERTU
	Model Name	WH-4V
Earphone 2	Brand Name	VERTU
	Model Name	WH-5V
Earphone 3	Brand Name	VERTU
	Model Name	HP-1V
USB Cable	Brand Name	VERTU
	Model Name	CA-225DV
Wireless Charger	Brand Name	VERTU
	Model Name	AC-35V
Wireless Speaker	Brand Name	VERTU
	Model Name	SP-1V

1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx/Rx Channel Frequency Range	5725 MHz ~ 5850 MHz
Maximum Output Power	802.11a : 10.93 dBm / 0.0124 W 802.11n HT20 : 10.71 dBm / 0.0118 W 802.11n HT40 : 10.77 dBm / 0.0119 W 802.11ac VHT20: 8.00 dBm / 0.0063 W 802.11ac VHT40: 7.96 dBm / 0.0063 W 802.11ac VHT80: 7.68 dBm / 0.0059 W
Type of Modulation	802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)
Antenna Type	PIFA Antenna
Antenna Gain	-0.40 dBi

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH02-HY	CO05-HY

Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-3273456 / FAX: +886-3-3284978	
Test Site No.	Sporton Site No.	
	03CH11-HY	

Note: The test site complies with ANSI C63.4 2009 requirement.

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart E
- FCC KDB 789033 D02 General UNII Test Procedures New Rules v01
- ANSI C63.10-2009

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. FCC permits the use of the 1.5 meter table as an alternative in C63.10-2013 through inquiry tracking number 961829.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.

The final configuration from all the combinations and the worst-case data rates were investigated by measuring the maximum power across all the data rates and modulation modes under section 2.2.

Based on the worst configuration found above, the RF power setting is set individually to meet FCC compliance limit for the final conducted and radiated tests shown in section 2.3.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5725-5850 MHz Band 4 (U-NII-3)	149	5745	157	5785
	151	5755	159	5795
	153	5765	161	5805
	155	5775	165	5825

Note: The above Frequency and Channel in boldface were 802.11n HT40.



2.2 Pre-Scanned RF Power

Preliminary tests were performed in different data rate and data rate associated with the highest power were chosen for full test in the following tables. Final Output Power equals to Measured Output Power adds the duty factor.

5GHz 802.11a mode								
Data Rate (MHz)	6M bps	9M bps	12M bps	18M bps	24M bps	36M bps	48M bps	54M bps
Average Power (dBm)	10.93	10.85	10.92	10.84	10.84	10.92	10.86	10.88

5GHz 802.11n HT20 mode								
Data Rate (MHz)	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
Average Power (dBm)	10.71	10.51	10.64	10.66	10.68	10.69	10.60	10.69

5GHz 802.11n HT40 mode								
Data Rate (MHz)	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
Average Power (dBm)	10.77	10.75	10.60	10.64	10.72	10.56	10.58	10.64

5GHz 802.11ac VHT20 mode									
Data Rate (MHz)	MCS 0	MCS 1	MCS 2	MCS 3	MCS 4	MCS 5	MCS 6	MCS 7	MCS 8
Average Power (dBm)	8.00	7.98	7.86	7.92	7.95	7.91	7.79	7.75	7.91

5GHz 802.11ac VHT40 mode										
Data Rate (MHz)	MCS 0	MCS 1	MCS 2	MCS 3	MCS 4	MCS 5	MCS 6	MCS 7	MCS 8	MCS 9
Average Power (dBm)	7.96	7.85	7.80	7.89	7.89	7.54	7.65	7.63	7.76	7.78

5GHz 802.11ac VHT80 mode										
Data Rate (MHz)	MCS 0	MCS 1	MCS 2	MCS 3	MCS 4	MCS 5	MCS 6	MCS 7	MCS 8	MCS 9
Average Power (dBm)	7.68	7.61	7.61	7.67	7.58	7.62	7.66	7.55	7.48	7.63

2.3 Test Mode

Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates from the power table described in section 2.2.

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0
802.11ac VHT80	MCS0


AC Conducted Emission	Mode 1 : LTE Band 7 Idle + WLAN Link + Bluetooth Link + NFC Link + Earphone 2 + Battery + USB Cable (Charging from Adapter)
------------------------------	---

Ch. #		Band IV : 5725-5850 MHz		
		802.11a	802.11n HT20	802.11n HT40
L	Low	149	149	151
M	Middle	157	157	-
H	High	165	165	159


Ch. #		Band IV : 5725-5850 MHz		
		802.11ac VHT20	802.11ac VHT40	802.11ac VHT80
L	Low	149	151	-
M	Middle	157	-	155
H	High	165	159	-

2.4 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emissions>



2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	D-Link	DIR-628	KA2DIR628A2	N/A	Unshielded, 1.8 m
3.	iPod	Apple	A1285	FCC DoC	Shielded, 1.0 m	N/A
4.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	NFC Card	Metro Taipei	Easy Card	N/A	N/A	N/A

2.6 EUT Operation Test Setup

For WLAN function, programmed RF utility, "Tera Term" installed in the notebook make the EUT provide functions like channel selection and power level for continuous transmitting and receiving signals.

2.7 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\
 &= 4.2 + 10 = 14.2 \text{ (dB)}
 \end{aligned}$$

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Description of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01.
Section C) Emission bandwidth for the band 5.725-5.85GHz
2. Set RBW = 100kHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
7. Measure and record the results in the test report.


3.1.4 Test Setup





3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.2.3 Test Procedures

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v01.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor, $10 \log(1/x)$, where x is the duty cycle.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01.
Section F) Maximum power spectral density.


Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

1. The testing follows Method SA-2 of FCC KDB 789033 D01 General UNII Test Procedures v01r03.
 - Measure the duty cycle.
 - Set span to encompass the entire emission bandwidth (EBW) of the signal.
 - Set RBW = 300 kHz.
 - Set VBW $\geq$ 1 MHz.
 - Number of points in sweep $\geq$ 2 Span / RBW.
 - Sweep time = auto.
 - Detector = RMS
 - Trace average at least 100 traces in power averaging mode.
 - Add $10 \log(500\text{kHz}/\text{RBW})$ to the test result.
 - Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.

2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.


3.3.4 Test Setup





3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Unwanted Emissions Measurement

This section as specified in FCC Part 15.407(b) is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement. The unwanted emissions shall comply with 15.407(b)(1) to (6), and restricted bands per FCC Part 15.205.

3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5725-5850 MHz band: all emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an EIRP of -17 dBm/MHz (78.3dBμV/m); for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an EIRP of -27 dBm/MHz (68.3dBμV/m).
- (2) Unwanted spurious emissions fallen in restricted bands per FCC Part 15.205 shall comply with the general field strength limits set forth in § 15.209 as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts)}$$

EIRP (dBm)	Field Strength at 3m (dBμV/m)
-17	78.3
- 27	68.3

- (3) KDB789033 v01r03 H)2)c)(i) As specified in 15.407(b), emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz (or -17 dBm/MHz as specified in 15.407(b)(4)). However, an out-of-band emission that complies with both the average and peak limits of 15.209 is not required to satisfy the -27 dBm/MHz or -17 dBm/MHz peak emission limit.

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01.

Section G) Unwanted emissions measurement.

(1) Procedure for Unwanted Emissions Measurements Below 1000MHz

- RBW = 120 kHz
- VBW = 300 kHz
- Detector = Peak
- Trace mode = max hold

(2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz

- RBW = 1 MHz
- VBW $\geq$ 3 MHz
- Detector = Peak
- Sweep time = auto
- Trace mode = max hold

(3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz

- RBW = 1 MHz
- VBW = 10 Hz, when duty cycle is no less than 98 percent.
- VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


Antenna	Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
1	802.11a	95.22	2075.32	0.48	1kHz
1	5GHz 802.11n HT20	94.50	1927.89	0.52	1kHz
1	5GHz 802.11n HT40	90.17	951.92	1.05	3kHz
1	5GHz 802.11n VHT20	95.41	1931.09	0.52	1kHz
1	5GHz 802.11n VHT40	90.14	951.92	1.05	3kHz
1	5GHz 802.11n VHT80	82.81	461.14	2.17	3kHz




2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.4.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.4.6 Test Result of Radiated Band Edges

Please refer to Appendix A.

3.4.7 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix A.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.


3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

<Original Test Result>

Test Mode :	Mode 1	Temperature :	23~25℃
Test Engineer :	Eric Jeng	Relative Humidity :	48~52%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	LTE Band 7 Idle + WLAN Link + Bluetooth Link + NFC Link + Earphone 2 + Battery + USB Cable (Charging from Adapter)		




Final Result : QuasiPeak

Frequency (MHz)	QuasiPeak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.430000	33.4	Off	L1	19.5	23.9	57.3
0.502000	34.6	Off	L1	19.4	21.4	56.0
0.654000	34.6	Off	L1	19.5	21.4	56.0
0.862000	31.8	Off	L1	19.5	24.2	56.0
1.110000	33.9	Off	L1	19.5	22.1	56.0
13.558000	58.8	Off	L1	19.9	1.2	60.0
18.854000	36.1	Off	L1	20.0	23.9	60.0

Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.430000	25.1	Off	L1	19.5	22.2	47.3
0.502000	27.3	Off	L1	19.4	18.7	46.0
0.654000	24.5	Off	L1	19.5	21.5	46.0
0.862000	20.6	Off	L1	19.5	25.4	46.0
1.110000	21.0	Off	L1	19.5	25.0	46.0
13.558000	55.4	Off	L1	19.9	-5.4	50.0
18.854000	21.6	Off	L1	20.0	28.4	50.0

Test Mode :	Mode 1	Temperature :	23~25°C
Test Engineer :	Eric Jeng	Relative Humidity :	48~52%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	LTE Band 7 Idle + WLAN Link + Bluetooth Link + NFC Link + Earphone 2 + Battery + USB Cable (Charging from Adapter)		


Final Result : QuasiPeak


Frequency (MHz)	QuasiPeak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.438000	30.9	Off	N	19.5	26.2	57.1
0.582000	32.0	Off	N	19.4	24.0	56.0
1.070000	31.8	Off	N	19.6	24.2	56.0
1.670000	28.7	Off	N	19.6	27.3	56.0
13.558000	59.9	Off	N	19.9	0.1	60.0
16.574000	30.5	Off	N	20.0	29.5	60.0

Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.438000	19.8	Off	N	19.5	27.3	47.1
0.582000	29.4	Off	N	19.4	16.6	46.0
1.070000	20.2	Off	N	19.6	25.8	46.0
1.670000	16.7	Off	N	19.6	29.3	46.0
13.558000	56.7	Off	N	19.9	-6.7	50.0
16.574000	17.9	Off	N	20.0	32.1	50.0

<Terminal Test Result>

Test Mode :	Mode 1	Temperature :	23~25°C
Test Engineer :	Eric Jeng	Relative Humidity :	48~52%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	LTE Band 7 Idle + WLAN Link + Bluetooth Link + NFC Link + Earphone 2 + Battery + USB Cable (Charging from Adapter)		


Final Result : QuasiPeak


Frequency (MHz)	QuasiPeak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
13.558000	50.4	Off	L1	19.9	9.6	60.0

Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
13.558000	41.1	Off	L1	19.9	8.9	50.0



Test Mode :	Mode 1	Temperature :	23~25°C
Test Engineer :	Eric Jeng	Relative Humidity :	48~52%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	LTE Band 7 Idle + WLAN Link + Bluetooth Link + NFC Link + Earphone 2 + Battery + USB Cable (Charging from Adapter)		

**Final Result : QuasiPeak**

Frequency (MHz)	QuasiPeak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
13.558000	42.3	Off	N	20.0	17.7	60.0

Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
13.558000	37.0	Off	N	20.0	13.0	50.0

3.6 Frequency Stability Measurement

3.6.1 Limit of Frequency Stability

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. To ensure emission at the band edge is maintained within the authorized band, those values shall be measured by radiation emissions at upper and lower frequency points, and finally compensated by frequency deviation as procedures below.
2. The EUT was operated at the maximum output power, and connected to the spectrum analyzer, which is set to maximum hold function and peak detector. The peak value of the power envelope was measured and noted. The upper and lower frequency points were respectively measured relatively 10dB lower than the measured peak value.
3. The frequency deviation was calculated by adding the upper frequency point and the lower frequency point divided by two. Those detailed values of frequency deviation are provided in table below.

3.6.4 Test Setup



3.6.5 Test Result of Frequency Stability

Please refer to Appendix A.



3.7 Automatically Discontinue Transmission

3.7.1 Limit of Automatically Discontinue Transmission

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Result of Automatically Discontinue Transmission

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.



3.8 Antenna Requirements

3.8.1 Standard Applicable

According to FCC 47 CFR Section 15.407(a)(1)(2), if transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.8.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.8.3 Antenna Gain

The antenna gain is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	Testo	608-H1	34897199	N/A	May. 04, 2015	Jul. 30, 2015 ~ Aug. 01, 2015	May. 03, 2016	Conducted (TH02-HY)
Power Meter	Anritsu	ML2495A	1036004	300MHz~40GHz	Jul. 29, 2015	Jul. 30, 2015 ~ Aug. 01, 2015	Jul. 28, 2016	Conducted (TH02-HY)
Power Sensor	Anritsu	MA2411B	1027253	300MHz~40GHz	Jul. 29, 2015	Jul. 30, 2015 ~ Aug. 01, 2015	Jul. 28, 2016	Conducted (TH02-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz~40GHz	Jun. 18, 2015	Jul. 30, 2015 ~ Aug. 01, 2015	Jun. 17, 2016	Conducted (TH02-HY)
Thermal Chamber	Ten Billion	TTH-D3SP	TBN-930701	N/A	Jul. 16, 2015	Jul. 30, 2015 ~ Aug. 01, 2015	Jul. 15, 2016	Conducted (TH02-HY)
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170584	18GHz- 40GHz	Nov. 03, 2014	Aug. 05, 2015 ~ Aug. 16, 2015	Nov. 02, 2015	Radiation (03CH11-HY)
Loop Antenna	TESEQ	HLA 6120	31244	9kHz~30MHz	Feb. 02, 2015	Aug. 05, 2015 ~ Aug. 16, 2015	Feb. 01, 2016	Radiation (03CH11-HY)
Amplifier	SONOMA	310N	187312	9kHz~1GHz	Nov. 24, 2014	Aug. 05, 2015 ~ Aug. 16, 2015	Nov. 23, 2015	Radiation (03CH11-HY)
Bilog Antenna	TESEQ	CBL 6111D	35414	30MHz~1GHz	Oct. 24, 2014	Aug. 05, 2015 ~ Aug. 16, 2015	Oct. 23, 2015	Radiation (03CH11-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1326	1GHz ~ 18GHz	Oct. 03, 2014	Aug. 05, 2015 ~ Aug. 16, 2015	Oct. 02, 2015	Radiation (03CH11-HY)
Hygrometer	TECPEL	DTN-303B	TP140325	N/A	Nov. 19, 2014	Aug. 05, 2015 ~ Aug. 16, 2015	Nov. 18, 2015	Radiation (03CH11-HY)
Preamplifier	Keysight	83017A	MY53270080	1GHz~26.5GHz	Nov. 20, 2014	Aug. 05, 2015 ~ Aug. 16, 2015	Nov. 19, 2015	Radiation (03CH11-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1902247	1GHz~18GHz	Jul. 01, 2015	Aug. 05, 2015 ~ Aug. 16, 2015	Jun. 30, 2016	Radiation (03CH11-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200486	10Hz ~ 44GHz	Sep. 24, 2014	Aug. 05, 2015 ~ Aug. 16, 2015	Sep. 23, 2015	Radiation (03CH11-HY)
Controller	EMEC	EM 1000	N/A	Control Turn table & Ant Mast	N/A	Aug. 05, 2015 ~ Aug. 16, 2015	N/A	Radiation (03CH11-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	Aug. 05, 2015 ~ Aug. 16, 2015	N/A	Radiation (03CH11-HY)
Turn Table	EMEC	TT 2000	N/A	0-360 degree	N/A	Aug. 05, 2015 ~ Aug. 16, 2015	N/A	Radiation (03CH11-HY)
EMI Test Receiver	Agilent	N9038A	MY53290053	20Hz to 26.5GHz	Feb. 02, 2015	Aug. 05, 2015 ~ Aug. 16, 2015	Feb. 01, 2016	Radiation (03CH11-HY)
Preamplifier	MITEQ	JS44-1800400 0-33-8P	1840917	18GHz ~ 40GHz	Jun. 02, 2015	Aug. 05, 2015 ~ Aug. 16, 2015	Jun. 01, 2016	Radiation (03CH11-HY)
EMI Test Receiver	Rohde & Schwarz	ESCS 30	100356	9kHz ~ 2.75GHz	Dec. 01, 2014	Aug. 07, 2015 ~ Aug. 11, 2015	Nov. 30, 2015	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Apr. 20, 2015	Aug. 07, 2015 ~ Aug. 11, 2015	Apr. 19, 2016	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 02, 2014	Aug. 07, 2015 ~ Aug. 11, 2015	Dec. 01, 2015	Conduction (CO05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Aug. 07, 2015 ~ Aug. 11, 2015	N/A	Conduction (CO05-HY)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.26
---	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.90
---	------



Appendix A. Conducted Test Results

Test Engineer:	AC Chang	Temperature:	21~25	°C
Test Date:	2015/7/30~2015/8/1	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% OBW

Band IV							
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	6 dB Bandwidth (MHz)	FCC 6dB Bandwidth Limit (MHz)	Pass/Fail
11a	6M bps	1	149	5745	15.32	0.5	Pass
11a	6Mbps	1	157	5785	15.34	0.5	Pass
11a	6Mbps	1	165	5825	15.32	0.5	Pass
HT20	MCS 0	1	149	5745	15.32	0.5	Pass
HT20	MCS 0	1	157	5785	15.12	0.5	Pass
HT20	MCS 0	1	165	5825	15.32	0.5	Pass
HT40	MCS 0	1	151	5755	35.12	0.5	Pass
HT40	MCS 0	1	159	5795	35.12	0.5	Pass
VHT20	MCS 0	1	149	5745	15.12	0.5	Pass
VHT20	MCS 0	1	157	5785	15.12	0.5	Pass
VHT20	MCS 0	1	165	5825	15.12	0.5	Pass
VHT40	MCS 0	1	151	5755	35.12	0.5	Pass
VHT40	MCS 0	1	159	5795	35.12	0.5	Pass
VHT80	MCS 0	1	155	5775	75.04	0.5	Pass

TEST RESULTS DATA
Average Power Table

Band IV										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)		Pass/Fail
11a	6M bps	1	149	5745	0.21	10.93	30.00	-0.40		Pass
11a	6Mbps	1	157	5785	0.21	10.60	30.00	-0.40		Pass
11a	6Mbps	1	165	5825	0.21	10.85	30.00	-0.40		Pass
HT20	MCS 0	1	149	5745	0.25	10.71	30.00	-0.40		Pass
HT20	MCS 0	1	157	5785	0.25	10.57	30.00	-0.40		Pass
HT20	MCS 0	1	165	5825	0.25	10.65	30.00	-0.40		Pass
HT40	MCS 0	1	151	5755	0.45	10.77	30.00	-0.40		Pass
HT40	MCS 0	1	159	5795	0.45	10.58	30.00	-0.40		Pass
VHT20	MCS 0	1	149	5745	0.20	8.00	30.00	-0.40		Pass
VHT20	MCS 0	1	157	5785	0.20	7.72	30.00	-0.40		Pass
VHT20	MCS 0	1	165	5825	0.20	7.91	30.00	-0.40		Pass
VHT40	MCS 0	1	151	5755	0.45	7.96	30.00	-0.40		Pass
VHT40	MCS 0	1	159	5795	0.45	7.94	30.00	-0.40		Pass
VHT80	MCS 0	1	155	5775	0.82	7.68	30.00	-0.40		Pass

TEST RESULTS DATA
Power Spectral Density

Band IV										
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)	10log (500kHz /RBW) Factor (dB)	Average Power Density (dBm/500kHz)	Average PSD Limit (dBm/500kHz)	DG (dBi)	Pass/Fail
11a	6M bps	1	149	5745	0.21	2.22	-2.70	30.00	-0.40	Pass
11a	6Mbps	1	157	5785	0.21	2.22	-2.64	30.00	-0.40	Pass
11a	6Mbps	1	165	5825	0.21	2.22	-2.60	30.00	-0.40	Pass
HT20	MCS 0	1	149	5745	0.25	2.22	-2.73	30.00	-0.40	Pass
HT20	MCS 0	1	157	5785	0.25	2.22	-2.62	30.00	-0.40	Pass
HT20	MCS 0	1	165	5825	0.25	2.22	-2.43	30.00	-0.40	Pass
HT40	MCS 0	1	151	5755	0.45	2.22	-6.12	30.00	-0.40	Pass
HT40	MCS 0	1	159	5795	0.45	2.22	-6.09	30.00	-0.40	Pass
VHT20	MCS 0	1	149	5745	0.20	2.22	-5.82	30.00	-0.40	Pass
VHT20	MCS 0	1	157	5785	0.20	2.22	-6.23	30.00	-0.40	Pass
VHT20	MCS 0	1	165	5825	0.20	2.22	-6.19	30.00	-0.40	Pass
VHT40	MCS 0	1	151	5755	0.45	2.22	-8.74	30.00	-0.40	Pass
VHT40	MCS 0	1	159	5795	0.45	2.22	-8.98	30.00	-0.40	Pass
VHT80	MCS 0	1	155	5775	0.82	2.22	-7.13	30.00	-0.40	Pass

TEST RESULTS DATA
Frequency Stability

Band IV										
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Center Frequency (MHz)	Frequency Deviation (MHz)	Frequency Stability (ppm)	Temperature (°C)	Voltage (V)	Note
11a	6M bps	1	149	5745	5745.050	0.050	8.70	20	3.5	
11a	6M bps	1	149	5745	5745.050	0.050	8.70	20	4.35	
11a	6M bps	1	149	5745	5745.050	0.050	8.70	20	4	
11a	6M bps	1	149	5745	5745.050	0.050	8.70	-30	4	
11a	6M bps	1	149	5745	5745.100	0.100	17.41	50	4	



Appendix B. Radiated Spurious Emission

Test Engineer :	Nick Yu and Jesse Wang	Temperature :	21~23°C
		Relative Humidity :	56~59%

15E Band 4 - 5725~5850MHz

WIFI 802.11a (Band Edge @ 3m)

<EUT with AC Adapter>

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 149 5745MHz		5694.44	48.98	-25.02	74	40.95	32.27	9.39	33.63	100	103	P	H
		5724.44	49.6	-28.7	78.3	41.49	32.31	9.44	33.64	100	103	P	H
		5690.68	40.44	-13.56	54	32.41	32.27	9.39	33.63	100	103	A	H
	*	5745	95.58	-	-	87.45	32.34	9.44	33.65	100	103	P	H
	*	5745	88.31	-	-	80.18	32.34	9.44	33.65	100	103	A	H
													H
													H
													H
		5709.8	51.47	-22.53	74	43.43	32.29	9.39	33.64	125	114	P	V
		5724.6	52.96	-25.34	78.3	44.85	32.31	9.44	33.64	125	114	P	V
		5713.32	42.04	-11.96	54	34	32.29	9.39	33.64	125	114	A	V
	*	5745	101.21	-	-	93.08	32.34	9.44	33.65	125	114	P	V
	*	5745	93.23	-	-	85.1	32.34	9.44	33.65	125	114	A	V
													V
													V
													V



WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 157 5785MHz		5700.76	48.42	-25.58	74	40.37	32.29	9.39	33.63	100	125	P	H
		5723.8	47.85	-30.45	78.3	39.74	32.31	9.44	33.64	100	125	P	H
		5713.16	40.04	-13.96	54	32	32.29	9.39	33.64	100	125	A	H
	*	5785	94.97	-	-	86.75	32.39	9.49	33.66	100	125	P	H
	*	5785	87.95	-	-	79.73	32.39	9.49	33.66	100	125	A	H
		5856.64	48.47	-29.83	78.3	40.1	32.51	9.54	33.68	100	125	P	H
		5887.6	50.47	-23.53	74	42.04	32.56	9.57	33.7	100	125	P	H
		5872.48	40.52	-13.48	54	32.14	32.53	9.54	33.69	100	125	A	H
		5703.72	48.48	-25.52	74	40.43	32.29	9.39	33.63	130	114	P	V
		5719.32	48.65	-29.65	78.3	40.59	32.31	9.39	33.64	130	114	P	V
		5711.16	40.23	-13.77	54	32.19	32.29	9.39	33.64	130	114	A	V
	*	5785	99.74	-	-	91.52	32.39	9.49	33.66	130	114	P	V
	*	5785	91.97	-	-	83.75	32.39	9.49	33.66	130	114	A	V
		5858.4	48.86	-29.44	78.3	40.5	32.51	9.54	33.69	130	114	P	V
		5868.72	49.3	-24.7	74	40.94	32.51	9.54	33.69	130	114	P	V
		5881.44	40.55	-13.45	54	32.14	32.53	9.57	33.69	130	114	A	V



WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 165 5825MHz	*	5825	96.06	-	-	87.75	32.46	9.52	33.67	100	102	P	H
	*	5825	88.38	-	-	80.07	32.46	9.52	33.67	100	102	A	H
		5854.96	48.64	-29.66	78.3	40.27	32.51	9.54	33.68	100	102	P	H
		5878.8	50.31	-23.69	74	41.93	32.53	9.54	33.69	100	102	P	H
		5860.24	40.7	-13.3	54	32.34	32.51	9.54	33.69	100	102	A	H
													H
													H
													H
	*	5825	99.88	-	-	91.57	32.46	9.52	33.67	114	114	P	V
	*	5825	92.11	-	-	83.8	32.46	9.52	33.67	114	114	A	V
		5853.6	49.36	-28.94	78.3	40.99	32.51	9.54	33.68	114	114	P	V
		5862.88	49.37	-24.63	74	41.01	32.51	9.54	33.69	114	114	P	V
		5867.2	40.85	-13.15	54	32.49	32.51	9.54	33.69	114	114	A	V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15E Band 4 5725~5850MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 149 5745MHz		11490	44.71	-29.29	74	56.49	40.01	13.95	65.74	100	0	P	H
		17232	45.84	-28.16	74	51.58	41.41	16.93	64.08	100	0	P	H
													H
													H
		11490	45.69	-28.31	74	57.47	40.01	13.95	65.74	100	0	P	V
		17232	46.29	-27.71	74	52.03	41.41	16.93	64.08	100	0	P	V
													V
													V
802.11a CH 157 5785MHz		11570	44.73	-29.27	74	56.5	39.89	14	65.66	100	0	P	H
		17352	46.21	-27.79	74	51.76	41.67	17	64.22	100	0	P	H
													H
													H
		11570	44.85	-29.15	74	56.62	39.89	14	65.66	100	0	P	V
		17352	45.94	-28.06	74	51.49	41.67	17	64.22	100	0	P	V
													V
													V
802.11a CH 165 5825MHz		11650	43.92	-30.08	74	55.71	39.78	14.05	65.62	100	0	P	H
		17472	45.27	-28.73	74	50.62	41.93	17.08	64.36	100	0	P	H
													H
													H
		11650	45.25	-28.75	74	57.04	39.78	14.05	65.62	100	0	P	V
		17472	45.35	-28.65	74	50.7	41.93	17.08	64.36	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

**15E Band 4 5725~5850MHz****WIFI 802.11n HT20 (Band Edge @ 3m)**

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 149 5745MHz		5710.44	49.63	-24.37	74	41.59	32.29	9.39	33.64	100	103	P	H
		5721.56	49.3	-29	78.3	41.19	32.31	9.44	33.64	100	103	P	H
		5711.96	40.46	-13.54	54	32.42	32.29	9.39	33.64	100	103	A	H
	*	5745	94.43	-	-	86.3	32.34	9.44	33.65	100	103	P	H
	*	5745	87.36	-	-	79.23	32.34	9.44	33.65	100	103	A	H
													H
													H
													H
		5705.56	50.31	-23.69	74	42.27	32.29	9.39	33.64	100	115	P	V
		5724.52	53.07	-25.23	78.3	44.96	32.31	9.44	33.64	100	115	P	V
		5713.48	42.18	-11.82	54	34.14	32.29	9.39	33.64	100	115	A	V
	*	5745	101.66	-	-	93.53	32.34	9.44	33.65	100	115	P	V
	*	5745	93.5	-	-	85.37	32.34	9.44	33.65	100	115	A	V
													V
													V
													V



WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 157 5785MHz		5686.76	49.88	-24.12	74	41.85	32.27	9.39	33.63	100	126	P	H
		5715	48.56	-25.44	74	40.52	32.29	9.39	33.64	100	126	P	H
		5708.6	40.06	-13.94	54	32.02	32.29	9.39	33.64	100	126	A	H
	*	5785	95.63	-	-	87.41	32.39	9.49	33.66	100	126	P	H
	*	5785	88.33	-	-	80.11	32.39	9.49	33.66	100	126	A	H
		5856.72	49.63	-28.67	78.3	41.26	32.51	9.54	33.68	100	126	P	H
		5861.04	49.26	-24.74	74	40.9	32.51	9.54	33.69	100	126	P	H
		5863.76	40.6	-13.4	54	32.24	32.51	9.54	33.69	100	126	A	H
		5713.48	49.55	-24.45	74	41.51	32.29	9.39	33.64	100	114	P	V
		5718.52	48.29	-30.01	78.3	40.23	32.31	9.39	33.64	100	114	P	V
		5714.76	40.4	-13.6	54	32.36	32.29	9.39	33.64	100	114	A	V
	*	5785	100.43	-	-	92.21	32.39	9.49	33.66	100	114	P	V
	*	5785	92.69	-	-	84.47	32.39	9.49	33.66	100	114	A	V
		5854	49.42	-28.88	78.3	41.05	32.51	9.54	33.68	100	114	P	V
		5881.12	49.14	-24.86	74	40.76	32.53	9.54	33.69	100	114	P	V
		5870.16	40.55	-13.45	54	32.19	32.51	9.54	33.69	100	114	A	V



WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 165 5825MHz	*	5825	95.6	-	-	87.29	32.46	9.52	33.67	100	129	P	H
	*	5825	88.9	-	-	80.59	32.46	9.52	33.67	100	129	A	H
		5851.28	48.88	-29.42	78.3	40.54	32.48	9.54	33.68	100	129	P	H
		5873.6	49.2	-24.8	74	40.82	32.53	9.54	33.69	100	129	P	H
		5862.96	40.78	-13.22	54	32.42	32.51	9.54	33.69	100	129	A	H
													H
													H
													H
	*	5825	101.01	-	-	92.7	32.46	9.52	33.67	107	115	P	V
	*	5825	92.68	-	-	84.37	32.46	9.52	33.67	107	115	A	V
		5850.32	50	-28.3	78.3	41.66	32.48	9.54	33.68	107	115	P	V
		5866.72	49.51	-24.49	74	41.15	32.51	9.54	33.69	107	115	P	V
		5868.4	40.94	-13.06	54	32.58	32.51	9.54	33.69	107	115	A	V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15E Band 4 5725~5850MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 149 5745MHz		11490	45.32	-28.68	74	57.1	40.01	13.95	65.74	100	0	P	H
		17232	46.13	-27.87	74	51.87	41.41	16.93	64.08	100	0	P	H
													H
													H
		11490	44.9	-29.1	74	56.68	40.01	13.95	65.74	100	0	P	V
		17232	46	-28	74	51.74	41.41	16.93	64.08	100	0	P	V
													V
													V
802.11n HT20 CH 157 5785MHz		11570	45.41	-28.59	74	57.18	39.89	14	65.66	100	0	P	H
		17352	47.1	-26.9	74	52.65	41.67	17	64.22	100	0	P	H
													H
													H
		11570	45.44	-28.56	74	57.21	39.89	14	65.66	100	0	P	V
		17352	46.04	-27.96	74	51.59	41.67	17	64.22	100	0	P	V
													V
													V
802.11n HT20 CH 165 5825MHz		11650	44.71	-29.29	74	56.5	39.78	14.05	65.62	100	0	P	H
		17472	45.51	-28.49	74	50.86	41.93	17.08	64.36	100	0	P	H
													H
													H
		11650	44.26	-29.74	74	56.05	39.78	14.05	65.62	100	0	P	V
		17472	44.72	-29.28	74	50.07	41.93	17.08	64.36	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15E Band 4 5725~5850MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT40 CH 151 5755MHz		5697.32	50.88	-23.12	74	42.85	32.27	9.39	33.63	100	120	P	H
		5717.24	54.08	-24.22	78.3	46.04	32.29	9.39	33.64	100	120	P	H
		5715	42.03	-11.97	54	33.99	32.29	9.39	33.64	100	120	A	H
	*	5755	91.93	-	-	83.78	32.36	9.44	33.65	100	120	P	H
	*	5755	85.2	-	-	77.05	32.36	9.44	33.65	100	120	A	H
		5852.24	48.89	-29.41	78.3	40.55	32.48	9.54	33.68	100	120	P	H
		5866	48.86	-25.14	74	40.5	32.51	9.54	33.69	100	120	P	H
		5871.04	40.7	-13.3	54	32.32	32.53	9.54	33.69	100	120	A	H
		5713.72	52.91	-21.09	74	44.87	32.29	9.39	33.64	102	115	P	V
		5722.2	57.46	-20.84	78.3	49.35	32.31	9.44	33.64	102	115	P	V
		5714.84	46.1	-7.9	54	38.06	32.29	9.39	33.64	102	115	A	V
	*	5755	98.07	-	-	89.92	32.36	9.44	33.65	102	115	P	V
	*	5755	90.67	-	-	82.52	32.36	9.44	33.65	102	115	A	V
		5856.24	49.55	-28.75	78.3	41.18	32.51	9.54	33.68	102	115	P	V
		5886.32	49.12	-24.88	74	40.72	32.53	9.57	33.7	102	115	P	V
		5888.24	40.73	-13.27	54	32.3	32.56	9.57	33.7	102	115	A	V



WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT40 CH 159 5795MHz		5687.56	48.32	-25.68	74	40.29	32.27	9.39	33.63	100	120	P	H
		5715.72	48.1	-30.2	78.3	40.06	32.29	9.39	33.64	100	120	P	H
		5699.32	40.23	-13.77	54	32.2	32.27	9.39	33.63	100	120	A	H
	*	5795	93.11	-	-	84.87	32.41	9.49	33.66	100	120	P	H
	*	5795	85.13	-	-	76.89	32.41	9.49	33.66	100	120	A	H
		5851.12	49.43	-28.87	78.3	41.09	32.48	9.54	33.68	100	120	P	H
		5869.12	49.97	-24.03	74	41.61	32.51	9.54	33.69	100	120	P	H
		5884.56	40.99	-13.01	54	32.59	32.53	9.57	33.7	100	120	A	H
		5697.48	50.69	-23.31	74	42.66	32.27	9.39	33.63	109	114	P	V
		5717.72	48.61	-29.69	78.3	40.55	32.31	9.39	33.64	109	114	P	V
		5714.28	40.78	-13.22	54	32.74	32.29	9.39	33.64	109	114	A	V
	*	5795	97.36	-	-	89.12	32.41	9.49	33.66	109	114	P	V
	*	5795	90.09	-	-	81.85	32.41	9.49	33.66	109	114	A	V
		5857.92	54.71	-23.59	78.3	46.35	32.51	9.54	33.69	109	114	P	V
		5868.48	51.26	-22.74	74	42.9	32.51	9.54	33.69	109	114	P	V
		5860.48	41.26	-12.74	54	32.9	32.51	9.54	33.69	109	114	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15E Band 4 5725~5850MHz

WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT40 CH 151 5755MHz		11510	44.93	-29.07	74	56.68	40	13.95	65.7	100	0	P	H
		17268	44.71	-29.29	74	50.39	41.49	16.95	64.12	100	0	P	H
													H
													H
		11510	45.55	-28.45	74	57.3	40	13.95	65.7	100	0	P	V
		17268	45.74	-28.26	74	51.42	41.49	16.95	64.12	100	0	P	V
													V
													V
802.11n HT40 CH 159 5795MHz		11590	45.83	-28.17	74	57.62	39.86	14	65.65	100	0	P	H
		17388	45.22	-28.78	74	50.71	41.74	17.03	64.26	100	0	P	H
													H
													H
		11590	45.46	-28.54	74	57.25	39.86	14	65.65	100	0	P	V
		17388	46.48	-27.52	74	51.97	41.74	17.03	64.26	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15E Band 4 5725~5850MHz

WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11ac VHT80 CH 155 5775MHz		5704.92	50.32	-23.68	74	42.28	32.29	9.39	33.64	100	120	P	H
		5719.8	51.93	-26.37	78.3	43.87	32.31	9.39	33.64	100	120	P	H
		5710.12	42.27	-11.73	54	34.23	32.29	9.39	33.64	100	120	A	H
	*	5775	87.32	-	-	79.09	32.39	9.49	33.65	100	120	P	H
	*	5775	79.64	-	-	71.41	32.39	9.49	33.65	100	120	A	H
		5850.4	48.89	-29.41	78.3	40.55	32.48	9.54	33.68	100	120	P	H
		5864.32	49.38	-24.62	74	41.02	32.51	9.54	33.69	100	120	P	H
		5860.64	41.76	-12.24	54	33.4	32.51	9.54	33.69	100	120	A	H
		5705	54.39	-19.61	74	46.35	32.29	9.39	33.64	100	114	P	V
		5722.84	54.4	-23.9	78.3	46.29	32.31	9.44	33.64	100	114	P	V
		5712.12	45.35	-8.65	54	37.31	32.29	9.39	33.64	100	114	A	V
	*	5775	92.35	-	-	84.12	32.39	9.49	33.65	100	114	P	V
	*	5775	84.92	-	-	76.69	32.39	9.49	33.65	100	114	A	V
		5853.12	49.07	-29.23	78.3	40.73	32.48	9.54	33.68	100	114	P	V
		5866.64	49.74	-24.26	74	41.38	32.51	9.54	33.69	100	114	P	V
		5860.24	42.14	-11.86	54	33.78	32.51	9.54	33.69	100	114	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15E Band 4 5725~5850MHz

WIFI 802.11ac VHT80 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11ac VHT80 CH 155 5775MHz		11550	45.52	-28.48	74	57.3	39.92	13.97	65.67	100	0	P	H
		17328	46.01	-27.99	74	51.59	41.6	17	64.18	100	0	P	H
													H
													H
		11550	45.6	-28.4	74	57.38	39.92	13.97	65.67	100	0	P	V
		17328	46.09	-27.91	74	51.67	41.6	17	64.18	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15E Emission below 1GHz

5GHz WIFI 802. 11ac VHT80 (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
5GHz 802.11ac VHT80 LF		133.95	29.2	-14.3	43.5	48.24	11.28	1.46	31.78			P	H
		188.76	32.21	-11.29	43.5	54.17	8.18	1.64	31.78	109	124	P	H
		233.31	28.4	-17.6	46	48.48	9.9	1.79	31.77			P	H
		374.2	24.12	-21.88	46	38.75	14.84	2.32	31.79			P	H
		647.9	22.55	-23.45	46	32.47	19.1	3.02	32.04			P	H
		952.4	22.68	-23.32	46	29.47	20.55	3.68	31.02			P	H
													H
													H
													H
													H
													H
													H
		41.07	30.36	-9.64	40	49.45	12.06	0.67	31.82	115	223	P	V
		72.93	23.24	-16.76	40	48.5	5.49	1.04	31.79			P	V
		200.64	25.31	-18.19	43.5	46.88	8.57	1.64	31.78			P	V
		379.1	18.91	-27.09	46	33.49	14.89	2.32	31.79			P	V
		771.8	23.19	-22.81	46	32.09	19.7	3.35	31.95			P	V
		967.8	23.57	-30.43	54	30.2	20.48	3.78	30.89			P	V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency per 15.209(c).
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



15E Band 4 5725~5850MHz

WIFI 802.11ac VHT80 (Band Edge @ 3m)

<EUT with WPC Charger>

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11ac VHT80 CH 155 5775MHz		5697.72	50.43	-23.57	74	42.4	32.27	9.39	33.63	367	299	P	H
		5724.52	51.61	-26.69	78.3	43.5	32.31	9.44	33.64	367	299	P	H
		5709.96	42.72	-11.28	54	34.68	32.29	9.39	33.64	367	299	A	H
	*	5775	89.05	-	-	80.82	32.39	9.49	33.65	367	299	P	H
	*	5775	82.08	-	-	73.85	32.39	9.49	33.65	367	299	A	H
		5854.64	49.49	-28.81	78.3	41.12	32.51	9.54	33.68	367	299	P	H
		5863.92	49.84	-24.16	74	41.48	32.51	9.54	33.69	367	299	P	H
		5874.96	41.37	-12.63	54	32.99	32.53	9.54	33.69	367	299	A	H
		5706.6	50.5	-23.5	74	42.46	32.29	9.39	33.64	279	192	P	V
		5721.08	51.35	-26.95	78.3	43.29	32.31	9.39	33.64	279	192	P	V
		5705.4	42.67	-11.33	54	34.63	32.29	9.39	33.64	279	192	A	V
	*	5775	90.29	-	-	82.06	32.39	9.49	33.65	279	192	P	V
	*	5775	82.43	-	-	74.2	32.39	9.49	33.65	279	192	A	V
		5852.88	49.2	-29.1	78.3	40.86	32.48	9.54	33.68	279	192	P	V
		5876.8	49.85	-24.15	74	41.47	32.53	9.54	33.69	279	192	P	V
		5862	41.82	-12.18	54	33.46	32.51	9.54	33.69	279	192	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

**15E Band 4 5725~5850MHz****WIFI 802.11ac VHT80 (Harmonic @ 3m)**

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11ac VHT80 CH 155 5775MHz		11550	45.37	-28.63	74	57.15	39.92	13.97	65.67	100	0	P	H
		17328	47	-27	74	52.58	41.6	17	64.18	100	0	P	H
													H
													H
		11550	44.64	-29.36	74	56.42	39.92	13.97	65.67	100	0	P	V
		17328	45.91	-28.09	74	51.49	41.6	17	64.18	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15E Emission below 1GHz

5GHz WIFI 802.11ac VHT80 (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
5GHz 802.11ac VHT80 LF		87.24	26.87	-13.13	40	49.33	8.05	1.28	31.79			P	H
		122.61	30.14	-13.36	43.5	49.19	11.45	1.28	31.78			P	H
		191.73	32.12	-11.38	43.5	53.96	8.3	1.64	31.78	102	124	P	H
		307	23.55	-22.45	46	39.92	13.28	2.11	31.76			P	H
		729.1	24.11	-21.89	46	33.1	19.77	3.25	32.01			P	H
		948.9	25.05	-20.95	46	31.82	20.59	3.68	31.04			P	H
													H
													H
													H
													H
													H
													H
		53.22	26.79	-13.21	40	50.98	6.57	1.04	31.8	121	236	P	V
		122.88	29.8	-13.7	43.5	48.84	11.46	1.28	31.78			P	V
		199.83	23.87	-19.63	43.5	45.41	8.6	1.64	31.78			P	V
		397.3	22.85	-23.15	46	36.77	15.56	2.32	31.8			P	V
		841.8	22.18	-23.82	46	30.29	20.2	3.4	31.71			P	V
		986	22.82	-31.18	54	29.37	20.42	3.78	30.75			P	V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency per 15.209(c).
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

3. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

4. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

3. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

4. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

3. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

4. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.